

Energy and Ancillary Service Co-Optimization Formulation

Keyur Patel, Senior Lead, Market Design Specialist

Angelo Marcino, Senior Lead, Market Design Specialist

PJM Interconnection June 1, 2022

For Public Use



This page is intentionally left blank



Table of Contents

	•	hms
l.		duction
II.	Secu	rity Constraint Economic Dispatch (SCED) Objective Function
I. III.	A.	Resource Energy Costs
	B.	Price Responsive Demand Value
	C.	Import Transaction Costs
	D.	Export Transaction Value
	E.	Regulation Reserve Costs
	F.	Synchronized Reserve Costs
	G.	Non-Synchronized Reserve Costs
	О. Н.	Secondary Reserve Costs
) Constraints
III.		
	Α.	Power Balance Constraint
III.	B.	Transmission Constraints
	C.	Resource Capacity Constraints
		Resource's Economic Maximum Constraint Limit
		Resource's Economic Minimum Constraint Limit
		3. Resource's Reserve Capability Constraints
	D.	Resource's Ramp Rate Constraints
		1. Resource's Ramp-Up Constraints
		2. Resource's Ramp-Down Constraints
	E.	Reserve Requirement Constraints
		Synchronized Reserve Requirement Constraints
		Primary Reserve Requirement Constraints
		30-minute Reserve Requirement Constraints
IV.	LMP	and Reserve Clearing Price Calculations
		Reserve Clearing Price



I. Introduction

This document provides a high-level mathematical formulation and explanation of the objective function used in the clearing of the Energy and Ancillary Service Markets. The intent of this document is to provide a better understanding of the mechanics.

Due to the approaching implementation of Reserve Price Formation, the paper provides details on the Secondary Reserve market. Such costs and constraints will not be considered until the implementation, scheduled for 10/1/2022.

II. Security Constraint Economic Dispatch (SCED) Objective Function

SCED is a mathematical model that generates the most economic resource dispatch during Real-time operations while considering key system operating constraints, such as power balance, reserve requirements, transmission congestion, as well as resource parameters, such as ramp rates, minimum and maximum output capability. The overall objective function of the SCED algorithm is to minimize the total system product cost over the study interval(s).

MINIMIZE {Resource Energy Costs

- Price Responsive Demand Value
- + Import Transaction Cost
- Export Transaction Value
- + Regulation Reserve Costs
- + Synchronized Reserve Costs
- + Non-Synchronized Reserve Costs
- + Secondary Reserve Costs
- + Various Applicable Violation Penalties*}

*Note: Includes transmission constraint violation penalties, energy surplus and deficit penalties, regulation and reserves violation penalties, etc.

The objective function cost terms are described below. For purposes of the following equations, the parameters are defined as:

- n = Number of Resources
- PRD = Price Responsive Demand
- ImportTran. = Number of import transactions
- ExportTran. = Number of export transactions
- RegResource = Number of Regulation eligible resources
- SRResource = Number of eligible Synchronized Reserve resources
- NSRResource = number of resources eligible for Non-Synchronized Reserve and not committed for energy



- SecRResource = Number or resources eligible for Secondary Reserve
- LS = Loss Sensitivities

A. Resource Energy Costs

Resource energy costs apply only to generation resources and Economic Load Response resources. Energy costs are expressed mathematically in the SCED objective function as follows:

Resource Energy Costs

$$\sum_{i=1}^{n} Energy_MW(i) * EnergyOfferCurve(i) \quad for \forall i \in n \text{ number of resources}$$

B. Price Responsive Demand Value

Price Responsive Demand value is expressed mathematically in the SCED objective function as follows:

Price Responsive Demand Value

$$\sum_{i=1}^{PRD} PRD_MW(i) * EnergyOfferCurve(i) for \forall i \in PRD resources$$

C. Import Transaction Costs

Import transaction cost is expressed mathematically in the SCED objective function as follows:

Import Transaction Cost

ImportTran.

$$\sum_{i=1} Import_Transaction_MW(i) * Import\ Transaction\ offer\ Curve(i) \quad for\ \forall\ i$$

$$\in ImportTran.$$

D. Export Transaction Value

Export value is expressed mathematically in the SCED objective function as follows:

Export Transaction Value

ExportTran.

$$\sum_{i=1}^{port_Transaction_MW(i) * Export_Transaction_Bid_Curve(i)} for \forall i$$
 $\in Export_Transaction_MW(i) * Export_Transaction_Bid_Curve(i)$



E. Regulation Reserve Costs

Regulating reserve costs apply only to regulation-eligible resources. Regulating reserve costs are expressed mathematically in the SCED objective function as follows:

$$\sum_{i=1}^{RegResource} Reg_MW(i) * RegOffer(i) for \forall i \in RegResource$$

F. Synchronized Reserve Costs

Synchronized Reserve costs apply to all synchronized reserve eligible resources. Synchronized Reserve costs are expressed mathematically in the SCED objective function as follows:

$$\sum_{i=1}^{SRResource} SR_MW(i) * SRofferCurve(i) \quad for \ \forall \ i \in SRResource$$

G. Non-Synchronized Reserve Costs

Non-Synchronized Reserve costs apply to all non-synchronized reserve eligible resources. Non-Synchronized Reserve costs are expressed mathematically in the SCED objective function as follows:

$$\sum_{i=1}^{NSRResource} NSR_MW(i) * NSRofferCurve(i) \quad for \ \forall \ i \ \in NSRResource$$

H. Secondary Reserve Costs

Secondary Reserve costs apply to all synchronized reserve eligible resource. Secondary Reserve costs are expressed mathematically in the SCED objective function as follows:

$$\sum_{i=1}^{SecRResource} SecR_MW(i) * SecRofferCurve(i) \quad for \ \forall \ i \ \in SecRResource$$



III. SCED Constraints

The objective function of SCED is minimized subject to the following constraints in optimizations.

A. Power Balance Constraint

The power balance constraint in SCED ensures that all energy injected into the PJM system during the dispatch interval balances with all energy withdrawal including losses in the system.

$$\begin{split} & \sum_{i=1}^{n} \left(1 - LS(i)\right) * Energy_{MW(i)} + \sum_{i=1}^{importTran.} \left(1 - LS(i)\right) * Import_{Transaction_{MW(i)}} - \\ & \sum_{i=1}^{ExportTran.} \left(1 - LS(i)\right) * Export_{Transaction_{MW(i)}} - \sum_{i=1}^{PRD} \left(1 - LS(i)\right) * PRD \quad MW(i) = \\ & Load \; Forecast \end{split}$$

B. Transmission Constraints

The transmission constraints in SCED ensure that the flows over the monitored transmission constraints are within the applicable limits of transmission lines.

$$\sum_{i=1}^{n} Energy_MW(i) * DFax(i,k) + \sum_{i=1}^{importTran.} Import_Transaction_MW(i) * DFax(i,k) \\ - \sum_{i=1}^{ExportTran.} Export_Transaction_MW(i) * DFax(i,k) - \sum_{i=1}^{PRD} PRD_MW(i) \\ * DFax(i,k) \leq Line\ Limit\ ; for\ \forall\ k\ \in\ active\ Transmission\ constraints$$

C. Resource Capacity Constraints

1. Resource's Economic Maximum Constraint Limit

$$\sum_{i=1}^{n} Energy_MW(i) + SR_MW(i) + SecR_MW(i) + Reg_MW(i) \le EcoMax(i) \; ; \; for \; \forall \; i$$

$$\in n. where \; n \; \in committed \; resources$$

2. Resource's Economic Minimum Constraint Limit

$$\sum_{i=1}^{n} Energy_MW(i) + Reg_MW(i) \ge EcoMin(i) \; ; \quad for \, \forall \, i \in n \, , where \, n$$

$$\in committed \, resources$$



3. Resource's Reserve Capability Constraints

Resource's Synchronized Reserve Capability Constraints

$$\sum_{i=1}^{n} SR_MW(i) \le RampRate(i) * 10 \; ; \; for \forall i \in n, where n \in committed resources$$

Resource's Non-Synchronized Reserve Capability Constraints

$$\sum_{i=1}^{n} NSR_MW(i) \le EcoMin(i) + (10 - startup plus notification time) * RampRate(i) ; for \forall i$$

$$\in n, where n \in eligible NSR resources$$

Resource's Online Secondary Reserve Capability Constraints

$$\sum_{i=1}^{n} SecR_{MW(i)} \leq RampRate(i) * 20 \; ; \; for \, \forall \, i \, \in n \, , where \, n \, \in \, committed \, resources$$

Resource's Offline Secondary Reserve Capability Constraints

$$\sum_{i=1}^{n} SecR_MW(i) \le RampRate(i) * 20 \; ; \; for \, \forall \, i \in n \, , where \, n$$

$$\in offline \, resources \, with \, startup \, plus \, notification \, time \leq 10 \, minutes$$

$$\sum_{i=1}^{n} SecR_MW(i) \leq EcoMin(i) + (30 - startup\ plus\ notificatin\ time) * RampRate(i) ; for\ \forall\ i$$

$$\in n\ , where\ n \in offline\ resources\ with\ startup\ plus\ notification\ time$$

$$\geq 10\ minutes\ and \leq 30\ minutes$$



Resource's Regulation Capability Constraints

$$\sum_{i=1}^{n} Reg_MW(i) \le Min[0.5 * (RegMax(i) - RegMin(i)), RegOfferMW(i)]; for \forall i$$

$$\in n, where n \in Regulation Eligible resources$$

D. Resource's Ramp Rate Constraints

1. Resource's Ramp-Up Constraints

$$\sum_{i=1}^{n} Energy_MW(i) \le Initial_MW(i) + RampRate(i) * 5 ; for \forall i \in n, where n \in committed resources$$

2. Resource's Ramp-Down Constraints

$$\sum_{i=1}^{n} Initial_MW(i) - Energy_MW(i) \ge RampRate(i) * 5; for \forall i \in n,$$

$$where n \in committed resources$$

E. Reserve Requirement Constraints

1. Synchronized Reserve Requirement Constraints

For RTO reserve requirement:

$$\sum_{i=1}^{n} SR_MW(i) \ge RTO_SR_Reserve_Requirement \quad ; for \ \forall \ i \ \in n \ no. \ of \ resources;$$

For each sub-zone z:

$$\sum_{i=1}^{n} SR_MW(i) \ge Subzone_SR_Reserve_Requirement \quad ; for \ \forall \ i \ \in n \ no. \ of \ resources, n$$

$$\in subzone \ z;$$



2. Primary Reserve Requirement Constraints

For RTO Primary Reserve Requirement:

$$\sum_{i=1}^{n} SR_MW(i) + NSR_MW(i) \ge RTO_NSR_Reserve_Requirement \quad ; for \forall i$$

$$\in n \ no. \ of \ resources;$$

For each sub-zone z:

$$\sum_{i=1}^{n} SR_MW(i) + NSR_MW(i) \ge Subzone_NSR_Reserve_Requirement \quad ; for \ \forall \ i$$

$$\in n \ no. \ of \ resources, n \in subzone \ z;$$

3. 30-minute Reserve Requirement Constraints

The RTO 30-minute Reserve Requirement is calculated as:

$$\sum_{i=1}^{n} SR_MW(i) + NSR_MW(i) + SecR_MW(i) \ge RTO_SecR_Reserve_Requirement \quad ; for \ \forall \ i \\ \in n \ no. \ of \ resources;$$

For each sub-zone z:

$$\sum_{i=1}^{n} SR_MW(i) + NSR_MW(i) + SecR_MW(i) \ge Subzone_SecR_Reserve_Requirement \quad ; for \ \forall \ i \\ \in n \ no. \ of \ resources, n \ \in subzone \ z;$$



IV. LMP and Reserve Clearing Price Calculations

Each Pnode LMP is calculated as:

 $LMP(i) = Energy\ Price - Loss\ Price(i) + Congestion\ Price(i)$ For for $\forall\ i \in no.\ of\ pnodes$

where,

 ${\it Energy Price} = {\it Shadow Price of Power Balance Constraint}$

Loss Price (i) = LS(i) * Energy Price

Congestion Price(i) =

 $\sum_{k=1}^{n} Shadow\ Price(k) * DFax(i,k)$ For $\forall\ k \in active\ transmission\ constraints$

A. Reserve Clearing Price

- Secondary Reserve Clearing Price = SP30
- Non-Synchronized Reserve Clearing Price = SPPR + SP30
- Synchronized Reserve Clearing Price = SPSR + SPPR + SP30

Where,

SP30 = Shadow Price of 30-minute Reserve Requirement

SPPR = Shadow Price of Primary Reserve Requirement

SPSR = Shadow Price of Synchronized Reserve Requirement