


- This metric shows the monthly maximum net load ramps for various time frames (1, 3 and 8 hours) for both ramp up and ramp down.
- Metered Load = Total Electric Distribution Company demand, calculated from real-time telemetry
- Gross Load = Metered Load + BTM Solar
- Net Load = Gross Load – FTM & BTM Solar – FTM Wind

(BTM = Behind-the-meter, FTM = Front-of-the-meter)

1) Monthly Maximum Net Load Ramp


Ramp (MW)



- This metric shows the hourly maximum percent of metered load served by the total of three different renewables in PJM for each month: wind (FTM), solar (FTM) and hydro, run of river.
- Metered Load = Total Electric Distribution Company demand, calculated from real-time telemetry


(FTM = Front-of-the-meter)

2) Hourly Maximum Percent of Metered Load Served by Renewables




- This metric shows the percentage of bus-intervals across a month having a negative real-time total LMP. A qualified bus may be a generator, load, or other type of pricing node as defined by PJM Settlements.

3a) Monthly Percent of Negative Pricing Interval-Busses




- This metric shows the percentage of bus-intervals year-to-date (YTD) (through December 2024) having a negative real-time total LMP by location. A qualified bus may be a generator, load, or other type of pricing node as defined by PJM Settlements.
- Mapped to DIMA station longitude and latitude
- Rasterized to five square mile blocks

3b) YTD Percent of Negative Pricing Interval-Busses by Location




- This metric shows the gross load and net load during the hour of each day with the largest difference between the two.
 - Metered Load = Total Electric Distribution Company demand, calculated from real-time telemetry
 - Gross Load = Metered Load + BTM Solar
 - Net Load = Gross Load – FTM & BTM Solar – FTM Wind
- (BTM = Behind-the-meter, FTM = Front-of-the-meter)

4) Maximum Daily Difference Between Gross Load and Net Load




- This metric shows the offline/unscheduled generation that is capable of being scheduled and coming online in a future interval.
- For each hourly interval, it shows the calculated potential generator scheduling reserve available in a 2-hour-forward horizon.
- Measured at the RTO level
- The metric includes the following unit types: Coal, Hydro, Hydro Pumped Storage, Landfill, Natural Gas, Oil, Waste

Scheduling Reserve (MW)



- This metric shows the amount of currently online generation that can shut down and return in a forward horizon
 - Complement to scheduling reserve
- For each hourly interval, it shows the calculated potential generator cycling reserve available in 2-hour, 4-hour, 8-hour and 12-hour-forward horizons (values are inclusive and not additive, i.e. 2-hour values are included in the 4-hour, 8-hour and 12-hour values).
- Measured at the RTO level
- The metric includes the following unit types: Coal, Hydro, Hydro Pumped Storage, Landfill, Natural Gas, Oil, Waste

Cycling Reserve (MW)



SME:
Scott Benner
Scott.Benner@pjm.com



Member Hotline

(610) 666 – 8980


(866) 400 – 8980

custsvc@pjm.com

**PROTECT THE
POWER GRID**
**THINK BEFORE
YOU CLICK!**



**BE ALERT TO
MALICIOUS PHISHING
EMAILS**



Report suspicious email activity to PJM.
Call (610) 666-2244 or email it_ops_ctr_shift@pjm.com