Trainer (PECO) - Delco Tap (PECO) - Mickleton (ACE)

General Information

Proposing entity name PE

Does the entity who is submitting this proposal intend to be the Designated Entity for this proposed project?

Yes

Company proposal ID

PJM Proposal ID 125

Project title Trainer (PECO) - Delco Tap (PECO) - Mickleton (ACE)

Project description Reconductor 2301 / 220-38 line Trainer - Delco - Mickleton to increase ratings of facility to minimum

1094 MVA rating. Replace substation terminal equipment to achieve minimum rating. Replace structures with 500/230KV double-circuit poles for future potential 500KV expansion (ACE only).

Email Proprietary Information

Project in-service date 06/2032

Tie-line impact Yes

Interregional project No

Is the proposer offering a binding cap on capital costs?

Additional benefits New structures to be built to 500KV standards, along with 500KV double circuit poles, for potential

future expansion supports vision for future potential load growth in region. Perspective load growth

in this corridor would likely require a 500kV path.

Project Components

1. Trainer - Delco Tap - Mickleton Rebuild (PECO Portion)

- 2. Delco Tap Mickleton Rebuild (ACE Portion)
- 3. Mickleton Substation Upgrades (ACE)

2025-W1-125

4. Trainer and Delco Tap Substation Upgrades (PECO)

Transmission Line Upgrade Component

Component title Trainer - Delco Tap - Mickleton Rebuild (PECO Portion)

Project description Reconductor line segments between Trainer - Delco Tap, and Delco Tap to first structure after river

crossing. Reconductoring past that point will be constructed by ACE. Reinforcement of transmission

structures.

Impacted transmission line 230KV 220-34 Trainer - Delco Tap, 230KV 220-34/2301 Delco Tap - Mickleton

Point A Trainer

Point B Delco Tap

Point C 2301 River Crossing point

Terrain description 220-34 Trainer - Delco Tap runs along freight rail ROW. 220-34 Delco Tap - Mickleton crosses

Delaware River at existing river crossing ROW.

Existing Line Physical Characteristics

Operating voltage 230

Conductor size and type 900 kcmil 20/7 ACSR (CANARY), 1113 kcmil 28/19 ACSS/TW (Del River Crossing)

Hardware plan description Install standard connection hardware.

Tower line characteristics 8 steel structures on 220-38 Trainer - Delco tap, 2 river tower structures on segment Delco Tap -

Mickleton

Proposed Line Characteristics

Designed Operating

Voltage (kV) 230.000000 230.000000

Normal ratings Emergency ratings

Summer (MVA) 1083.000000 1228.000000

Winter (MVA)	1138.000000	1282.000000
Conductor size and type	1467.8 kcmil ACSS/TW (St. Croix), new conduction.	ctor being developed by Southwire for river crossing
Shield wire size and type	Install 0.638" OPGW on section between Delco Tap and point C (first tower in NJ) Existing shield wire will remain between Trainer - Delco Tap.	
Rebuild line length	1.9 miles	
Rebuild portion description		section, reconductor 220-38 Delco Tap - Mickleton e of Delaware River. Reinforce 8 steel structures ossing towers.
Right of way	Existing ROW will be utilized.	
Construction responsibility	PECO	
Benefits/Comments	IDV provided	
Component Cost Details - In Current Year \$		
Engineering & design	detailed cost	
Permitting / routing / siting	detailed cost	
ROW / land acquisition	detailed cost	
Materials & equipment	detailed cost	
Construction & commissioning	detailed cost	
Construction management	detailed cost	
Overheads & miscellaneous costs	detailed cost	
Contingency	detailed cost	
Total component cost	\$5,629,218.58	
Component cost (in-service year)	\$6,533,729.41	

Transmission Line Upgrade Component

Component title Delco Tap - Mickleton Rebuild (ACE Portion)

Project description Reconductor line segments between Mickleton and the first transmission structure in New Jersey on

the 2301 line Delco Tap - Mickleton. Reconductoring past that point will be constructed by PECO.

Replacement of tower structures.

Impacted transmission line 2301 Delco Tap - Mickleton

Point A First transmission structure before Delaware river

Point B Mickleton

Point C

Terrain description Flat, rural

Existing Line Physical Characteristics

Operating voltage 230

Conductor size and type 946.7 kcmil 35/7 ACSS/TW (Fraser), 1113 kcmil 30/7 ACSS/TW (Blue Jay)

Hardware plan description Install standard connection hardware and insulators.

Tower line characteristics 43 steel lattice tower structures to be removed and replaced by 27 DC Tangent – 500kV/230kV

towers and 16 DC Deadend – 500kV/230kV towers.

Proposed Line Characteristics

Designed Operating

Voltage (kV) 230.000000 230.000000

Normal ratings Emergency ratings

Summer (MVA) 998.000000 1195.000000

Winter (MVA) 1195.000000 1195.000000

Conductor size and type Double-bundled 959.6 kcmil 26/7 ACSS/TW (Suwanee)

Shield wire size and type Install 0.638" OPGW along full length of line. Rebuild line length 7.5 miles Rebuild portion description Reconductor entire section between Mickleton substation and the last transmission tower in New Jersey before the Delaware River Crossing. Replacement of all transmission towers. Existing ROW will be utilized. Right of way Construction responsibility ACE Benefits/Comments Transmission structures to utilize dual 500KV/230KV design for future potential 500KV line (500KV arms will not be included / part of scope) Component Cost Details - In Current Year \$ Engineering & design detailed cost Permitting / routing / siting detailed cost ROW / land acquisition detailed cost Materials & equipment detailed cost Construction & commissioning detailed cost Construction management detailed cost Overheads & miscellaneous costs detailed cost Contingency detailed cost Total component cost \$58,263,723.04 Component cost (in-service year) \$67,342,724.64 **Substation Upgrade Component** Component title Mickleton Substation Upgrades (ACE)

Project description

2025-W1-125

Replacement of substation equipment at Mickleton substation to achieve minimum 2301 Delco Tap

- Mickleton line summer emergency rating of 1094 MVA.

Substation name Mickleton ACE Substation zone Substation upgrade scope Replacement of (1) 2000A circuit switcher with 3000A MOD, (1) 3000A relay, (1) circuit breaker, conduit, takeoff structures, and associated CCVTs. **Transformer Information** None New equipment description 3000A MOD, relays, and circuit breaker. Equipment replacements to achieve minimum 1094 MVA Summer emergency rating. Substation assumptions Assumptions made that existing equipment foundations in yard are adequate for replacements. Assumptions made that future load growth will not be grow more than currently forecasted for the Mickleton 230KV yard. Real-estate description Construction responsibility ACE Benefits/Comments New equipment to be built to 500KV standards Component Cost Details - In Current Year \$ Engineering & design detailed cost Permitting / routing / siting detailed cost ROW / land acquisition detailed cost Materials & equipment detailed cost Construction & commissioning detailed cost Construction management detailed cost Overheads & miscellaneous costs detailed cost

detailed cost

\$2,773,036.12

Contingency

Total component cost

Component cost (in-service year)	\$3,223,971.57
Substation Upgrade Component	
Component title	Trainer and Delco Tap Substation Upgrades (PECO)
Project description	Replacement of substation equipment at Trainer and Delco Tap to achieve 1094 MVA summer emergency rating (breaker, circuit switcher, and relays).
Substation name	Trainer, Delco Tap
Substation zone	PECO
Substation upgrade scope	Replacement of (1) circuit breaker and associated CTs, (2) circuit switchers, and (2) relays.
Transformer Information	
None	
New equipment description	Replace oil filled circuit breaker with higher rated breaker. Replacement of circuit switcher with higher rated circuit breaker. Equipment replacements to achieve minimum 1094 MVA Summer emergency rating.
Substation assumptions	Assumptions made that replacement breakers fit footprint of existing equipment with adequate foundation. Assumptions made that existing control house has space for new relaying. Assumptions made that river crossing cofferdam tower islands are adequate and do not require additional improvements.
Real-estate description	
Construction responsibility	PECO
Benefits/Comments	
Component Cost Details - In Current Year \$	
Engineering & design	detailed cost
Permitting / routing / siting	detailed cost
ROW / land acquisition	detailed cost
Materials & equipment	detailed cost

Construction & commissioning detailed cost

Construction management detailed cost

Overheads & miscellaneous costs detailed cost

Contingency detailed cost

Total component cost \$916,384.42

Component cost (in-service year) \$1,063,630.37

Congestion Drivers

None

Existing Flowgates

None

New Flowgates

None

Financial Information

Capital spend start date 01/2026

Construction start date 09/2031

Project Duration (In Months) 77

Additional Comments

None

2025-W1-125