Harrison-Obetz-Marion Road 138kV Line Rebuild

General Information

Proposing entity name AEPSCT

Does the entity who is submitting this proposal intend to be the Designated Entity for this proposed project?

Company proposal ID AEP_Q

PJM Proposal ID 515

Project title Harrison-Obetz-Marion Road 138kV Line Rebuild

Yes

Rebuild 7.28 miles on the Harrison Extension 138kV line asset part of the Harrison-Obetz-Marion Road 138kV Circuit. Reconductor approximately 3.2 miles of 636 ACSR 26/7 conductor on the Bixby-Marion Road 138kV line asset also part of the Harrison-Obetz-Marion Road 138kV circuit.

Replace 795 KCM ACSR station conductors at Obetz 138kV Station

Email jmperez@aep.com

Project in-service date 11/2029

Tie-line impact No

Interregional project No

Is the proposer offering a binding cap on capital costs?

Additional benefits

Project description

Project Components

- 1. Harrison-Obetz 138kV Circuit
- 2. Obetz-Marion Road 138kV Circuit
- 3. Obetz Station

Transmission Line Upgrade Component

Component title Harrison-Obetz 138kV Circuit

Project description Rebuild approximately 4.5 miles from Harrison station to Obetz station.

Impacted transmission line Harrison-Obetz-Marion 138kV Line

Point A Harrison Station

Point B Obetz Station

Point C

Terrain description Flat and urban with some industrial areas

Existing Line Physical Characteristics

Operating voltage 138

Conductor size and type 636 ACSR 26/7 Grossbeak

Hardware plan description

Hardware will be replaced along the way

Tower line characteristics

The section from Harrison to Obetz consists mostly of wood H frame structures originally installed in

1950.

Proposed Line Characteristics

Designed Operating

Voltage (kV) 138.000000 138.000000

Normal ratings Emergency ratings

Summer (MVA) 257.000000 360.000000

Winter (MVA) 325.000000 404.000000

Conductor size and type 795 ACSR Drake

Shield wire size and type 7#8 Alumoweld AW7 Shield Wire & OPGW

2025-W1-515 2

Rebuild line length 4.5 miles Rebuild portion description Approximately 4.5 miles will be rebuilt under this component from Harrison station all the way to Obetz station. Right of way Plan includes supplementing/augmenting approximately 50% of our existing easements. Construction responsibility AEP Benefits/Comments This proposal rebuilds an aging asset with 1950's wood structures with a modern and resilient steel design. Component Cost Details - In Current Year \$ Engineering & design Detailed cost breakdown Permitting / routing / siting Detailed cost breakdown ROW / land acquisition Detailed cost breakdown Materials & equipment Detailed cost breakdown Construction & commissioning Detailed cost breakdown Construction management Detailed cost breakdown Overheads & miscellaneous costs Detailed cost breakdown Detailed cost breakdown Contingency \$14,202,481.29 Total component cost Component cost (in-service year) \$14,202,481.29 Transmission Line Upgrade Component

Component title Obetz-Marion Road 138kV Circuit

Project description Rebuild approximately 2.8 miles from Obetz station to structure 21 of the Bixby-Marion Road 138kV Line asset. Reconductor approximately 3.2 miles from structure 21 of the Bixby-Marion Road 138kV

Line asset to Marion Road.

Harrison-Obetz-Marion Road 138kV Impacted transmission line

Point A Obetz Station Structure 21 of the Bixby-Marion Road 138kV Line Asset Point B Point C Marion Road Station Terrain description Flat and urban with some industrial areas. **Existing Line Physical Characteristics** Operating voltage 138 Conductor size and type 636 ACSR 26/7 Hardware plan description Hardware will be replaced as necessary to accommodate new conductor. Tower line characteristics The portion of the circuit from Obetz to structure 21 of the Bixby-Marion Road 138kV line asset consists of mostly wood H frames installed in 1950. From structure 21 to Marion Road station it is a mix of double circuit lattice structures and steel poles originally constructed in 1976. **Proposed Line Characteristics** Designed Operating Voltage (kV) 138.000000 138.000000 Normal ratings **Emergency ratings** Summer (MVA) 291.000000 353.000000 Winter (MVA) 368.000000 373.000000 Conductor size and type 477 ACSS Hawk Shield wire size and type 7#8 Alumoweld AW 7 & OPGW Rebuild line length 6 miles (see breakdown below) Of the total 6 miles, 2.8 miles will be fully rebuilt while 3.2 miles will be reconductored. Rebuild portion description Right of way Proposal includes augmenting/supplementing 50% of our existing easements.

Construction responsibility AEP

Benefits/Comments

This proposal rebuilds an aging asset with 1950's wood structures with a modern and resilient steel

design.

Component Cost Details - In Current Year \$

Engineering & design Detailed cost breakdown

Permitting / routing / siting Detailed cost breakdown

ROW / land acquisition Detailed cost breakdown

Materials & equipment Detailed cost breakdown

Construction & commissioning Detailed cost breakdown

Construction management Detailed cost breakdown

Overheads & miscellaneous costs Detailed cost breakdown

Contingency Detailed cost breakdown

Total component cost \$21,303,721.93

Component cost (in-service year) \$21,303,721.93

Substation Upgrade Component

Component title Obetz Station

Project description Replace 795 KCM ACSR Bus Conductors at Obetz Station

Substation name Obetz Station

Substation zone 205

Substation upgrade scope Replace 795 KCM ACSR Bus Conductors at Obetz Station

Transformer Information

None

2025-W1-515 5

New equipment description 1272 KCM AAC 61 Str Bus conductors

Substation assumptions

The station structures are adequate and only replacing the bus conductor will be needed.

Real-estate description N/A

Construction responsibility AEP

Benefits/Comments

Component Cost Details - In Current Year \$

Engineering & design Detailed cost breakdown

Permitting / routing / siting Detailed cost breakdown

ROW / land acquisition Detailed cost breakdown

Materials & equipment Detailed cost breakdown

Construction & commissioning Detailed cost breakdown

Construction management Detailed cost breakdown

Overheads & miscellaneous costs Detailed cost breakdown

Contingency Detailed cost breakdown

Total component cost \$238,304.70

Component cost (in-service year) \$238,304.70

Congestion Drivers

None

Existing Flowgates

FG#	Fr Bus No.	From Bus Name	To Bus No.	To Bus Name	CKT	Voltage	TO Zone	Analysis type	Status
2025W1-GD-S190	243522	05HARRISON	243550	05OBETZ	1	138	205	Generation Deliverability	Included

FG#	Fr Bus No.	From Bus Name	To Bus No.	To Bus Name	СКТ	Voltage	TO Zone	Analysis type	Status
2025W1-IPD-S187	243522	05HARRISON	243550	05OBETZ	1	138	205	Individual Plant Deliverability	Included
2025W1-GD-S229	243550	05OBETZ	243539	05MARION RD	1	138	205	Generation Deliverability	Included
2025W1-GD-S207	243550	05OBETZ	243539	05MARION RD	1	138	205	Generation Deliverability	Included
2025W1-GD-S183	243522	05HARRISON	243550	05OBETZ	1	138	205	Generation Deliverability	Included
2025W1-IPD-S169	243522	05HARRISON	243550	05OBETZ	1	138	205	Individual Plant Deliverability	Included
2025W1-GD-S406	243522	05HARRISON	243550	05OBETZ	1	138	205	Generation Deliverability	Included
2025W1-GD-S205	243522	05HARRISON	243550	05OBETZ	1	138	205	Generation Deliverability	Included

New Flowgates

None

Financial Information

Capital spend start date 03/2026

Construction start date 10/2028

Project Duration (In Months) 44

Additional Comments

None

2025-W1-515 7