



# System Restoration: Getting Started with Restoration

Restoration Strategies

*Student Guide*

Prepared by:  
State & Member Training  
PJM©2025

# Table of Contents


<b>Course Overview</b>	<b>2</b>
Objectives	3
<b>Methods of Restoration</b>	<b>3</b>
Methods of Restoration	4
Choosing a Restoration Method Exercise	15
<b>Switching Strategies</b>	<b>15</b>
Switching Strategies	16
<b>Restoring Power to Critical Facilities</b>	<b>19</b>
Restoring Power to Critical Facilities	20
<b>Black Start Generating Units</b>	<b>24</b>
Black Start Generating Units	25
<b>Cross Zonal Coordination</b>	<b>31</b>
Cross Zonal Coordination	32
<b>Status Reports</b>	<b>35</b>
Status Reports	36
<b>Summary</b>	<b>37</b>
Summary	38

# Objectives

At the end of this module, the Learner will be able to:

- Describe strategies for system restoration
- Define cranking paths, critical loads and priority loads
- Describe the black start generation requirements
- Describe reporting requirements for PJM

# Methods of Restoration



## Methods of System Restoration

www.pjm.com | Public

PJM©2025

### Bottom-Up Approach

The Bottom-Up approach to restoration:

- Form islands from black-start generation
- Several variations
- Only method available in a full shutdown with no outside assistance available
- Should be the basis for company restoration plans




## Bottom-Up Approach

The bottom-up restoration strategy includes:

1. Select units to black start
2. Start and stabilize black start units
3. Determine restoration transmission path
4. Begin expanding island(s) by restoring transmission and load
5. Synchronize island(s) when appropriate

3

## Bottom-Up Approach: Multiple Island Method



4

## Bottom-up Approach: Multiple Island Method

- **Advantages:**

- Multiple areas of the system being restored at the same time
- Faster restart of specific generation
- If one area blacks out, the other areas are in service
- Allows for critical load pick-up
- High series reactance; high voltage drop



5

## Bottom-up Approach: Multiple Island Method


- **Disadvantages:**

- More complex
- Less stability due to smaller islands (larger frequency deviations)
- Frequency control is area specific (controlled by individual generators)
- Overall restoration time is longer
- Reduced fault current for relay operation



6

## Bottom-up Approach: Core Island Method



7

## Bottom-up Approach: Core Island Method

- **Advantages:**

- Larger, more stable island with more generation
- Focused control and switching
- Allows for quicker load restoration (based on amount of generation)
- Quicker interconnection based on stability
- Overall restoration time is shorter
- Faster clearing time based on available fault current



8

## Bottom-up Approach: Core Island Method


- **Disadvantages:**

- Process starts over if island blacks out
- Critical load restoration may be delayed if located outside of core island
- DC power may be expended at stations outside of the core island



9

## Bottom-up Approach: Backbone Island Method



10



## Bottom-up Approach: Backbone Island Method

- **Advantages:**

- Critical load restoration to generating and substation facilities
- Focused control and switching
- Allows for outside assistance



11

## Bottom-up Approach: Backbone Island Method

- **Disadvantages:**

- Over-voltage conditions due to excess line charging
- Instability issues due to limited generation and less transmission networking
- Delay in critical load restoration



12

## Top-Down Approach


The top-down restoration strategy includes:

1. Restore backbone transmission system, usually from outside assistance
2. Restore critical generating station and substation load
3. Bring on more generation
4. Restore underlying transmission system
5. Continue restoring load



13

## Top-Down Approach



14

## Top-Down Approach

- **Advantages:**

- Quicker critical load restoration
- Parallel restoration of areas within the system
- Stability
- Synchronization not required



15

## Top-Down Approach

- **Disadvantages:**

- Over-voltage conditions due to excess line charging
- Reliant on neighboring entities
- Transmission constraints




16

## Combination Approach


Combines the **Bottom-up** and **Top-down** Approach

- Includes:
  - Restoring transmission from an outside source, at the same time as building "islands" of generation
  - Interconnecting "islands" with each other or outside source when able



17

## Combination Approach



18

## Combination Approach

- **Advantages:**

- Quickest timeframe for restoring power to critical loads
- Parallel restoration of areas within the system
- Stability based on load connected outside of area



19

## Combination Approach

- **Disadvantages:**


- Over-voltages due to excess line charging
- Reliant on neighboring entities
- Requires synchronization of multiple areas
- Complex control and switching



20

## Selection of a Restoration Method

- Restoration method chosen depends on:
  - Extent of blackout
  - Availability of outside assistance
  - Availability of internal black-start generation
- Company restoration plans are based on worst case scenario and must be approved by PJM

 When *deviating* from approved restoration plan, **communication must occur** between the TO and PJM

# Choosing a Restoration Method Exercise

1. Your system has suffered a disturbance involving multiple transmission trippings. The disturbance has left several blacked out “pockets” or “holes” in your system. Each pocket contains a large steam generation unit, but no CTs or hydro units. Though your system suffered a loss of load during this event, the portion of the system remaining is very stable.

Which is the best restoration strategy to be applied? \_\_\_\_\_

2. Your system has suffered a complete blackout. You receive information that your neighboring systems are also blacked out. Your system consists of several large load centers with black-start capable CTs available in each load center. These load centers are connected to each other by very long transmission lines.

Which is the best restoration strategy to be applied? \_\_\_\_\_

3. Your system has suffered a complete blackout. You receive information that your neighboring systems are unaffected and still connected to the Eastern Interconnection. You have a very large system with a critical load center including a nuclear plant in the electrical center of your system. You have black-start capable generation strategically placed throughout your system.

Which is the best restoration strategy to be applied? \_\_\_\_\_

4. Your system has suffered a complete blackout. You receive information that your neighboring systems are also blacked out. Your system consists of a large load center in the electrical center of the system with small pockets of rural load covering a large physical area. Most of your generating resources are located in the large load center.

Which is the best restoration strategy to be applied? \_\_\_\_\_

# Switching Strategies



## Switching Strategies

www.pjm.com | Public

PJM©2025

### All Open Approach

All Open Approach to Switching:

- All circuit breakers at blacked-out substations are opened prior to restoration process



23



## All Open Approach

- **Advantages:**

- Simpler and safer configuration to re-energize
  - Inadvertent load pick-up less likely
  - Only breakers involved in restoration process need to be closed



24

## All Open Approach

- **Disadvantages:**

- Longer restoration time
- More stored energy required for greater number of breaker operations
  - Compressed air or gas, springs, station battery
  - Breakers should be capable of one open-close-open operation without AC station service



25

## Controlled Open Approach

### Controlled Operation Approach to Switching:

- Only those circuit breakers necessary to allow system restoration to proceed are opened



26

## Controlled Open Approach

- **Advantages:**
  - Less stored energy requirements
    - Breakers not involved in the initial sectionalization and restoration remain closed
    - Some breaker operations may not be needed until after station service is re-established



27

## Controlled Open Approach

- **Disadvantages:**

- Dispatcher must be continually aware of boundary between restored and de-energized systems
  - Switching process becomes more complex
  - Possibility of system shutdown due to inadvertent load pickup is increased



28

## System Sectionalizing

- **System Sectionalizing**

- Disconnect load and capacitors from system prior to energization
- Use reactors to prevent high voltage
- Review transformer tap positions prior to energization
- Generator voltage regulators should be in service
- Protective relaying on all equipment should be in service

29

# Restoring Power to Critical Facilities



## Restoring Power to Critical Facilities

www.pjm.com | Public

PJM©2025

### Cranking Paths

**Cranking Path:** a transmission path from a black start unit to another generator with the intent to facilitate startup of that generator to aid in the restoration process



31

## Cranking Paths

- Types of cranking paths:
  - Critical Restoration Paths
    - *Nuclear*: provides off-site power to a nuclear plant's auxiliary equipment to allow the nuclear plant to maintain a safe shutdown
    - *Load*: restores load that is identified as critical
  - Non-Critical Restoration Paths
    - Restores non-critical, or priority loads or facilities, as identified within the restoration plan

32

## Critical Load Restoration

- Critical loads are defined by PJM
- Minimum Critical Load Requirements for each transmission zone consists of:
  - Cranking power load to units with a **"hot" start-up time of 4 hours or less**
  - Off-site nuclear station light and power
    - Including units off-line prior to disturbance to maintain a safe shutdown
    - One feed into each facility
  - Critical gas infrastructure
    - Key in quick restoration of critical steam units

33

## Priority Load Restoration

- Priority load provided by black start or other generation
  - Nuclear Station Auxiliary Power (2nd feed)
  - Cranking power to generation with a start time greater than 4 hours
  - Power to electric infrastructure
    - Light and power to substations
    - Pumping plants for underground cable systems
  - Communication equipment
  - Command and control facilities
  - Under-frequency load shed circuits

34

## Load Restoration

### Nuclear Station Auxiliary Power (Priority Load)

- Emergency on-site generators provide for safe shutdown, only
- To facilitate a restart:
  - Two independent off-site power sources
  - Stable voltages and frequency
  - No damage to unit



35

## Load Restoration

Substation light & power required for:

***SF6 Circuit Breakers (heaters & compressor)***



***Battery Chargers***




36

## Load Restoration

### Pipe-Type Cable Installations

- With no power at pumping plants, there is risk of immediate electrical failure or damage to cable upon re-energization
- Locations of pipe-type cable installations and pumping plants should be known by dispatchers
- Pressures should be verified prior to re-energization if cable and pumping plants have been off



Cross-Sectional View of  
345kV Pipe-Type Cable

37

## Load Restoration


### Priority Customer Load

- Circuits with load identified by company
  - Governmental, military facilities
  - Medical facilities
  - Public health (water, sewage pumping stations)
  - Public communications (TV, radio)
  - Communication facilities (phone)
  - Law enforcement (police, fire)





# Black Start Generating Units



## Black Start Generating Units

**Black Start Unit:** a generating unit that has equipment enabling it to start without an outside electrical supply or a unit with the demonstrated ability to automatically remain operating, at reduced levels, when disconnected from the grid

## NERC Requirements for Critical Black Start (EOP-005)

- Each GOP:
  - Shall participate in the RC's restoration drills, exercises, or simulations as requested by the Reliability Coordinator
  - With a black start resource shall:
    - Have documented procedures for starting each one and energizing a bus
    - Notify its TOP of any known changes to the capabilities of that black start resource affecting the ability to meet the TOP's restoration plan within 24 hours following such change
    - Provide a minimum of two hours of training every two calendar years to each of its operating personnel responsible for the startup of its black start resource
      - Training shall include a review of the applicable restoration plan and coordination with the TOP
    - Test the capability of the resource to perform

41

## NERC Requirements for Critical Black Start (EOP-005)

- Each TOP:
  - Shall have a restoration plan, approved by its RC, that identifies each black start resource, their characteristics, and associated cranking paths/switching requirements
  - Shall have black start resource testing requirements to verify that each black start resource is capable of meeting the requirements of its restoration plan

42

## PJM Requirements for Black Start

- Must be tested annually
  - Unit can self-start when requested from a "blackout" state without any outside source of power
  - Personnel are familiar with up-to-date procedures
  - Close unit onto a dead bus within 3 hours of the request
  - Run for 16 hours, or as defined by TO restoration plan
    - GOs must notify PJM and the TO if a critical black start fuel resource at max output falls below 10 hours
  - Maintain frequency and voltage under varying load

43

## PJM Requirements for Black Start

- Exceptions or additions to the PJM black start requirements will be allowed, with PJM approval:
  - Coping power needs for steam units that cannot be supplied by resources other than black start
  - Exceptions to critical cranking power are made for intermittent generation (i.e., wind, solar)
  - Exception to critical cranking power will be considered on a case by case basis for:
    - Complex cranking paths for minimum ICAP gain
    - Non-dispatchable unit or units with very high minimum limits

44

## Amount of Black Start Required

**Required Black Start = 110%  
(Critical Load requirement) on a  
locational basis**

- At least 2 black start resources per transmission zone
  - PJM allocated
  - Cross zonal coordination is possible

45

## Fuel Assured Black Start Units

### Fuel Assured Black Start Units

Fuel Storage of 16+ hours

Multiple interstate pipeline connections

Gas supply basin / Gathering system ahead of interstate pipeline

46

## Fuel Assured Black Start Units


### Hydro/Intermittent/Hybrid Resources

#### 16 hours at a 90% confidence MW output

- Calculate the MWh for each hour of the day
- Sum the hours with MWh  $\geq$  assumed black start MW for each day
- Each day with the sum  $\geq 16$  is a 1; less than 16 is a 0
- Yearly confidence level is:
  - A simple average
  - Calculated using ELCC weather-weighted average to find unit specific confidence levels

47

## Fuel Assured Black Start Units



48

## Black Start Unit Procurement - PJM Responsibilities

- In its roles as Transmission Operator (TOP), PJM is responsible for selecting the black start resources for a system restoration plan
- Would work closely with the TOs to identify these units based on:
  - Critical Load requirements
  - Available black start resources
  - Minimum number of black start resources allocated to a zone
  - Possible cross zonal opportunities

49

## Black Start Unit Procurement - PJM Responsibilities

- Utilize the start time parameters and test data to evaluate the black start resources and whether these resources will meet the requirements of the restoration plans
  - May require some black start resources to adhere to less than a 3-hour start time given critical load restoration timing requirements
    - These units will be notified of this timing requirement and tests to it during annual black start testing
  - Recognizes that black start resources with 3-hour start times may not be appropriate to meet nuclear power off-site safe-shutdown load restoration requirements
    - The target restoration time for off-site power to nuclear stations is 4 hours

50

## **Black Start Unit Procurement - PJM Responsibilities**

- In collaboration with the TOs, will select black start units to meet critical load requirements during the 5-year black start selection process described in PJM Manual 14D: Generator Operational Requirements
- Will utilize the black start replacement process, as described in M-14D, for changes to black start availability or critical load requirements that occur within the 5-year period

51

## **Black Start Unit Procurement - Member Responsibilities**

- Adjust their system restoration plan based on the black start units allocated to it from this selection process
- Has the option of procuring additional black start resources
  - Cost will be on the TO
- Under frequency islanding schemes and load rejection schemes
  - Can be used in conjunction with black start
- Disputes or disagreements
  - SOS-T consultation → Dispute Resolution Process

52




- Reliability Requirements:
  - Critical load
  - Restoration timing
  - Redundancy
- Efficiency Opportunities:
  - Speed of restoration
  - Cost savings




## Cross-Zonal Coordination

### Level One Cross-Zonal Coordination




## Cross-Zonal Coordination

### Level Two Cross-Zonal Coordination



## Cross-Zonal Coordination

### Level Three Cross-Zonal Coordination



## Cross Zonal Coordination

- Technical Feasibility Requirements:
  - Maintaining voltages within limits
  - Maintaining MW flows within thermal limits
  - Maintaining dynamic stability of generation
  - Timing requirements of serving critical load
  - Test history and performance history of each black start resource

## Cross Zonal Coordination

- Complexity Considerations:
  - Amount of switching to establish each cranking path
    - Characteristics of cranking path (length, geography, travel time, number of substations, voltage level)
    - Staffing availability (field/control room) to support building cranking path to neighboring area

59

## Cross Zonal Coordination

- SCADA versus Manual control:
  - Logistical coordination
    - Adjacent TO zones only (do not cross 3 or more zones)
    - Type of load restored in each TO zone
    - Potential additional TO costs incurred to enable cross zonal coordination
    - Number of TO zones in coordination with a single TO zone
- TO/State relationship considerations
  - Restoration priority to remain local

60

# Status Reports



## Status Reports

www.pjm.com | Public


PJM©2025

Company Hourly Restoration Report *					
Date:			Time:		
Reporting Company:					
Transmission Zone:					
Company Contact:			Estimated Time to Complete Total Restoration:		
			Date: Time:		
During drills, submit forms to <a href="mailto:RestorationDrillGeneration@pjm.com">RestorationDrillGeneration@pjm.com</a> . If no changes since last report submitted, report is not required.					
GENERATION REPORT:		MW	LOAD RESTORATION REPORT:		MW
Generation: Capacity on Line			Total Customer Load Restored		
Generation: Energy on Line			# Of Customers Restored (000)		
# Of Generators on Line			% Customers Restored		
# Of Subsystems (Islands)			% Customers Restored Last Hour		
CAPACITY DUE IN:					
Generation in One Hour (1)					
Generation in Three Hours (3)					
Generation in six Hours (6)					
UNITS ON LINE SINCE LAST REPORT					
Station	Unit	MW	Station	Unit	MW
UNITS EXPECTED DURING NEXT HOUR					
Station	Unit	MW	Station	Unit	MW
Damage detected since last report / comments:					
CRANKING POWER					
From Company to Station	kV	Time	From Company to Station	kV	Time



# Summary

Summary



In this presentation, we:

- Described strategies for system restoration
- Defined cranking paths, critical loads, and priority loads
- Described the black start generation requirements
- Described reporting requirements for PJM

65

## Questions?

PJM Client Management & Services	
Telephone:	(610) 666-8980
Toll Free Telephone:	(866) 400-8980
Website:	www.PJM.com
Email:	trainingsupport@pjm.com



The Member Community is PJM's self-service portal for members to search for answers to their questions or to track and/or open cases with Client Management & Services

