

PJM Interconnection, L.L.C., Intra-PJM Tariffs  
Filing Category: Normal Filing Date: 06/28/2013  
FERC Docket: ER13-01859-000 FERC Action: Accept  
FERC Order: Delegated Letter Order Order Date:  
08/05/2013  
Effective Date: 07/01/2013 Status: Effective  
ATTACHMENT DD.5.10, OATT ATTACHMENT DD.5.10 Auction Clearing Requirements, 14.0.0

## 5.10 Auction Clearing Requirements

The Office of the Interconnection shall clear each Base Residual Auction and Incremental Auction for a Delivery Year in accordance with the following:

a) Variable Resource Requirement Curve

The Office of the Interconnection shall determine Variable Resource Requirement Curves for the PJM Region and for such Locational Deliverability Areas as determined appropriate in accordance with subsection (a)(iii) for such Delivery Year to establish the level of Capacity Resources that will provide an acceptable level of reliability consistent with the Reliability Principles and Standards. It is recognized that the variable resource requirement reflected in the Variable Resource Requirement Curve can result in an optimized auction clearing in which the level of Capacity Resources committed for a Delivery Year exceeds the PJM Region Reliability Requirement (less the Short-Term Resource Procurement Target) or Locational Deliverability Area Reliability Requirement (less the Short-Term Resource Procurement Target for the Zones associated with such LDA) for such Delivery Year. For any auction, the Updated Forecast Peak Load, and Short-Term Resource Procurement Target applicable to such auction, shall be used, and Price Responsive Demand from any applicable approved PRD Plan, including any associated PRD Reservation Prices, shall be reflected in the derivation of the Variable Resource Requirement Curves, in accordance with the methodology specified in the PJM Manuals.

i) Methodology to Establish the Variable Resource Requirement Curve

Prior to the Base Residual Auction, in accordance with the schedule in the PJM Manuals, the Office of the Interconnection shall establish the Variable Resource Requirement Curve for the PJM Region as follows:

- Each Variable Resource Requirement Curve shall be plotted on a graph on which Unforced Capacity is on the x-axis and price is on the y-axis;
- The Variable Resource Requirement Curve for the PJM Region shall be plotted by first combining (i) a horizontal line from the y-axis to point (1), (ii) a straight line connecting points (1) and (2), (iii) a straight line connecting points (2) and (3), and (iv) a vertical line from point (3) to the x-axis, where:
  - For point (1), price equals: {the greater of [the Cost of New Entry] or [1.5 times (the Cost of New Entry minus the Net Energy and Ancillary Service Revenue Offset)]} divided by (one minus the

pool-wide average EFORd) and Unforced Capacity equals: [the PJM Region Reliability Requirement multiplied by (100% plus the approved PJM Region Installed Reserve Margin (“IRM”)% minus 3%) divided by (100% plus IRM%)] minus the Short-Term Resource Procurement Target;

- For point (2), price equals: (the Cost of New Entry minus the Net Energy and Ancillary Service Revenue Offset) divided by (one minus the pool-wide average EFORd) and Unforced Capacity equals: [the PJM Region Reliability Requirement multiplied by (100% plus IRM% plus 1%) divided by (100% plus IRM%)] minus the Short-Term Resource Procurement Target; and
- For point (3), price equals [0.2 times (the Cost of New Entry minus the Net Energy and Ancillary Service Revenue Offset)] divided by (one minus the pool-wide average EFORd) and Unforced Capacity equals: [the PJM Region Reliability Requirement multiplied by (100% plus IRM% plus 5%) divided by (100% plus IRM%)] minus the Short-Term Resource Procurement Target;

ii) For any Delivery Year, the Office of the Interconnection shall establish a separate Variable Resource Requirement Curve for each LDA for which:

- A. the Capacity Emergency Transfer Limit is less than 1.15 times the Capacity Emergency Transfer Objective, as determined by the Office of the Interconnection in accordance with NERC and Applicable Regional Entity guidelines; or
- B. such LDA had a Locational Price Adder in any one or more of the three immediately preceding Base Residual Auctions; or
- C. such LDA is determined in a preliminary analysis by the Office of the Interconnection to be likely to have a Locational Price Adder, based on historic offer price levels; provided however that for the Base Residual Auction conducted for the Delivery Year commencing on June 1, 2012, the Eastern Mid-Atlantic Region (“EMAR”), Southwest Mid-Atlantic Region (“SWMAR”), and Mid-Atlantic Region (“MAR”) LDAs shall employ separate Variable Resource Requirement Curves regardless of the outcome of the above three tests; and provided further that the Office of the Interconnection may establish a separate Variable Resource Requirement Curve for an LDA not otherwise qualifying under the above three tests if it finds that such is required to achieve an acceptable level of reliability consistent with the Reliability Principles and Standards, in which case the Office of the Interconnection shall post such finding, such LDA, and such Variable Resource Requirement Curve on its internet site no later than the March 31 last preceding the Base Residual Auction for such Delivery Year.

The same process as set forth in subsection (a)(i) shall be used to establish the Variable Resource Requirement Curve for any such LDA, except that the Locational Deliverability Area Reliability Requirement for such LDA shall be substituted for the PJM Region Reliability Requirement and the LDA Short-Term Resource Procurement Target shall be substituted for the PJM Region Short-Term Resource Procurement Target. For purposes of calculating the Capacity Emergency Transfer Limit under this section, all generation resources located in the PJM Region that are, or that qualify to become, Capacity Resources, shall be modeled at their full capacity rating, regardless of the amount of capacity cleared from such resource for the immediately preceding Delivery Year.

iii) Procedure for ongoing review of Variable Resource Requirement Curve shape.

Beginning with the Delivery Year that commences June 1, 2018, and continuing no later than for every fourth Delivery Year thereafter, the Office of the Interconnection shall perform a review of the shape of the Variable Resource Requirement Curve, as established by the requirements of the foregoing subsection. Such analysis shall be based on simulation of market conditions to quantify the ability of the market to invest in new Capacity Resources and to meet the applicable reliability requirements on a probabilistic basis. Based on the results of such review, PJM shall prepare a recommendation to either modify or retain the existing Variable Resource Requirement Curve shape. The Office of the Interconnection shall post the recommendation and shall review the recommendation through the stakeholder process to solicit stakeholder input. If a modification of the Variable Resource Requirement Curve shape is recommended, the following process shall be followed:

- A) If the Office of the Interconnection determines that the Variable Resource Requirement Curve shape should be modified, Staff of the Office of the Interconnection shall propose a new Variable Resource Requirement Curve shape on or before July 15, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new values would be applied.
- B) The PJM Members shall review the proposed modification to the Variable Resource Requirement Curve shape.
- C) The PJM Members shall either vote to (i) endorse the proposed modification, (ii) propose alternate modifications or (iii) recommend no modification, by October 31, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new values would be applied.
- D) The PJM Board of Managers shall consider a proposed modification to the Variable Resource Requirement Curve shape, and the Office of the Interconnection shall file any approved modified Variable

Resource Requirement Curve shape with the FERC by December 1, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new values would be applied.

iv) Cost of New Entry

- A) For the Delivery Year commencing on June 1, 2015, and continuing thereafter unless and until changed pursuant to subsection (B) below, the Cost of New Entry for the PJM Region shall be \$128,000 per MW-year. The Cost of New Entry for each LDA shall be determined based upon the Transmission Owner zones that comprise such LDA, as provided in the table below. If an LDA combines transmission zones with differing Cost of New Entry values, the lowest such value shall be used.

<b>Geographic Location Within the PJM Region Encompassing These Zones</b>	<b>Cost of New Entry in \$/MW-Year</b>
PS, JCP&L, AE, PECO, DPL, RECO (“CONE Area 1”)	140,000
BGE, PEPCO (“CONE Area 2”)	130,600
AEP, Dayton, ComEd, APS, DQL, ATSI, DEOK, EKPC (“CONE Area 3”)	127,500
PPL, MetEd, Penelec (“CONE Area 4”)	134,500
Dominion (“CONE Area 5”)	114,500

- B) Beginning with the 2016-2017 Delivery Year, the CONE shall be adjusted to reflect changes in generating plant construction costs based on changes in the Applicable H-W Index, in accordance with the following:

(1) The Applicable H-W Index for any Delivery Year shall be the most recently published twelve-month change, at the time CONE values are required to be posted for the Base Residual Auction for such Delivery Year, in the Total Other Production Plant Index shown in the Handy-Whitman Index of Public Utility Construction Costs for the North Atlantic Region for purposes of CONE Areas 1, 2, and 4, for the North Central Region for purposes of CONE Area 3, and for the South Atlantic Region for purposes of CONE Area 5.

(2) The CONE in a CONE Area shall be adjusted prior to the Base Residual Auction for each Delivery Year by applying the Applicable H-W Index for such CONE Area to the Benchmark CONE for such CONE Area.

(3) The Benchmark CONE for a CONE Area shall be the CONE used for such CONE Area in the Base Residual Auction for the prior Delivery Year (provided, however that the Gross CONE values stated in subsection (a)(iv)(A) above shall be the Benchmark CONE values for the 2015-2016 Delivery Year to which the Applicable H-W Index shall be applied to

determine the CONE for subsequent Delivery Years).

(4) Notwithstanding the foregoing, CONE values for any CONE Area for any Delivery Year shall be subject to amendment pursuant to appropriate filings with FERC under the Federal Power Act, including, without limitation, any filings resulting from the process described in section 5.10(a)(vii)(C) or any filing to establish new or revised CONE Areas.

v) Net Energy and Ancillary Services Revenue Offset

A) The Office of the Interconnection shall determine the Net Energy and Ancillary Services Revenue Offset each year for the PJM Region as (A) the annual average of the revenues that would have been received by the Reference Resource from the PJM energy markets during a period of three consecutive calendar years preceding the time of the determination, based on (1) the heat rate and other characteristics of such Reference Resource; (2) fuel prices reported during such period at an appropriate pricing point for the PJM Region with a fuel transmission adder appropriate for such region, as set forth in the PJM Manuals, assumed variable operation and maintenance expenses for such resource of \$6.47 per MWh, and actual PJM hourly average Locational Marginal Prices recorded in the PJM Region during such period; and (3) an assumption that the Reference Resource would be dispatched for both the Day-Ahead and Real-Time Energy Markets on a Peak-Hour Dispatch basis; plus (B) ancillary service revenues of \$2,199 per MW-year.

B) The Office of the Interconnection also shall determine a Net Energy and Ancillary Service Revenue Offset each year for each sub-region of the PJM Region for which the Cost of New Entry is determined as identified above, using the same procedures and methods as set forth in the previous subsection; provided, however, that: (1) the average hourly LMPs for the Zone in which the Reference Resource was assumed to be installed for purposes of the CONE estimate (as specified in the PJM Manuals) shall be used in place of the PJM Region average hourly LMPs; (2) if such sub-region was not integrated into the PJM Region for the entire applicable period, then the offset shall be calculated using only those whole calendar years during which the sub-region was integrated; and (3) a posted fuel pricing point in such sub-region, if available, and (if such pricing point is not available) a fuel transmission adder appropriate to each assumed Cost of New Entry location from an appropriate PJM Region pricing point shall be used for each such sub-region.

vi) Process for Establishing Parameters of Variable Resource Requirement

Curve

- A) The parameters of the Variable Resource Requirement Curve will be established prior to the conduct of the Base Residual Auction for a Delivery Year and will be used for such Base Residual Auction.
- B) The Office of the Interconnection shall determine the PJM Region Reliability Requirement and the Locational Deliverability Area Reliability Requirement for each Locational Deliverability Area for which a Variable Resource Requirement Curve has been established for such Base Residual Auction on or before February 1, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new values will be applied, in accordance with the Reliability Assurance Agreement.
- C) Beginning with the Delivery Year that commences June 1, 2018, and continuing no later than for every fourth Delivery Year thereafter, the Office of the Interconnection shall review the calculation of the Cost of New Entry for each CONE Area.
  - 1) If the Office of the Interconnection determines that the Cost of New Entry values should be modified, the Staff of the Office of the Interconnection shall propose new Cost of New Entry values on or before July 15, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new values would be applied.
  - 2) The PJM Members shall review the proposed values.
  - 3) The PJM Members shall either vote to (i) endorse the proposed values, (ii) propose alternate values or (iii) recommend no modification, by October 31, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new values would be applied.
  - 4) The PJM Board of Managers shall consider Cost of New Entry values, and the Office of the Interconnection shall file any approved modified Cost of New Entry values with the FERC by December 1, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new values would be applied.
- D) Beginning with the Delivery Year that commences June 1, 2018, and continuing no later than for every fourth Delivery Year thereafter, the Office of the Interconnection shall review the methodology set forth in this Attachment for determining the Net Energy and Ancillary Services Revenue Offset for the PJM Region

and for each Zone.

- 1) If the Office of the Interconnection determines that the Net Energy and Ancillary Services Revenue Offset methodology should be modified, Staff of the Office of the Interconnection shall propose a new Net Energy and Ancillary Services Revenue Offset methodology on or before July 15, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new methodology would be applied.
- 2) The PJM Members shall review the proposed methodology.
- 3) The PJM Members shall either vote to (i) endorse the proposed methodology, (ii) propose an alternate methodology or (iii) recommend no modification, by October 31, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new methodology would be applied.
- 4) The PJM Board of Managers shall consider the Net Revenue Offset methodology, and the Office of the Interconnection shall file any approved modified Net Energy and Ancillary Services Revenue Offset values with the FERC by December 1, prior to the conduct of the Base Residual Auction for the first Delivery Year in which the new values would be applied.

b) Locational Requirements

The Office of Interconnection shall establish locational requirements prior to the Base Residual Auction to quantify the amount of Unforced Capacity that must be committed in each Locational Deliverability Area, in accordance with the PJM Reliability Assurance Agreement.

c) ~~Minimum Annual~~ Resource Requirements and Constraints

Prior to the Base Residual Auction and each Incremental Auction for ~~the each~~ Delivery Years, ~~beginning with the Delivery Year that starts on~~ starting June 1, 2014 ~~and ending May 31, 2017~~, the Office of the Interconnection shall establish the Minimum Annual Resource Requirement and the Minimum Extended Summer Resource Requirement for the PJM Region and for each Locational Deliverability Area for which the Office of the Interconnection is required under section 5.10(a) of this Attachment DD to establish a separate VRR Curve for such Delivery Year.

Prior to the Base Residual Auction and Incremental Auctions for each Delivery Year beginning with the Delivery Year that commences June 1, 2017, the Office of the Interconnection shall establish the Limited Resource Constraints and the Sub-Annual Resource Constraints for the PJM Region and for each Locational Deliverability Area for which the Office of the Interconnection is

Formatted: Not Highlight

Formatted: Not Highlight

Formatted: Not Highlight

required under section 5.10(a) of this Attachment DD to establish a separate VRR Curve for such Delivery Year.

d) Preliminary PJM Region Peak Load Forecast for the Delivery Year

The Office of the Interconnection shall establish the Preliminary PJM Region Load Forecast for the Delivery Year in accordance with the PJM Manuals by February 1, prior to the conduct of the Base Residual Auction for such Delivery Year.

e) Updated PJM Region Peak Load Forecasts for Incremental Auctions

The Office of the Interconnection shall establish the updated PJM Region Peak Load Forecast for a Delivery Year in accordance with the PJM Manuals by February 1, prior to the conduct of the First, Second, and Third Incremental Auction for such Delivery Year.