

RPM Default Avoidable Cost Rates for the 2011/2012 Delivery Year\*

Technology Type	2011-2012 Mothball Avoidable Cost Rate (\$/MW-Day)	2011-2012 Retirement Avoidable Cost Rate (\$/MW-Day)
Nuclear	N/a	N/a
Pumped Storage	\$21.72	\$30.50
Hydro	\$74.24	\$97.10
Sub-Critical Coal	\$178.24	\$197.58
Super Critical Coal	\$184.15	\$201.42
Waste Coal - Small	\$235.06	\$284.70
Waste Coal - Large	\$86.94	\$105.02
Wind	N/a	N/a
CC - Two on One Frame F Technology	\$32.33	\$45.85
CC - Three on One Frame E/Siemens Technology	\$35.89	\$48.60
CC - Three or More on One or More Frame F Technology	\$27.98	\$38.85
CC - NUG Cogeneration Frame B or E Technology	\$120.16	\$161.45
CT - First & Second Generation Aero (P&W FT 4)	\$25.69	\$34.17
CT - First & Second Generation Frame B	\$25.38	\$33.87
CT - Second Generation Frame E	\$24.13	\$32.29
CT - Third Generation Aero (GE LM 6000)	\$58.42	\$86.10
CT - Third Generation Aero (P&W FT-8 TwinPak)	\$30.64	\$45.17
CT - Third Generation Frame F	\$24.77	\$35.68
Diesel	\$27.49	\$34.91
Oil and Gas Steam	\$68.18	\$83.01

\*Default ACR Values are determined as described in section 6.7(c) of the PJM OATT, Attachment DD. Capacity Market Sellers shall use the one-year mothball Avoidable Cost Rate shown above, unless the Capacity Market Seller satisfies the criteria set forth in section 6.7(e) of the PJM OATT, Attachment DD.