

PJM Interconnection, L.L.C. 2750 Monroe Blvd. Audubon, PA 19403

Pauline Foley Associate General Counsel T: (610) 666-8248 | F: (610) 666-8211 pauline.foley@pim.com

January 5, 2018

Honorable Kimberly D. Bose, Secretary Federal Energy Regulatory Commission 888 First Street, N.E., Room 1A Washington, D.C. 20426

Re: PJM Interconnection, L.L.C., Docket No. ER18-614-000

[30-Day Comment Period Requested]

Dear Secretary Bose:

In accordance with PJM Open Access Transmission Tariff, Schedule 12 ("Tariff" or "Schedule 12")¹ and Amended and Restated Operating Agreement of PJM Interconnection, L.L.C., Schedule 6, section 1.6 ("Operating Agreement" or "Schedule 6"), and pursuant to section 205 of the Federal Power Act,² PJM Interconnection, L.L.C. ("PJM") hereby submits amendments to the Tariff, Schedule 12-Appendix A to incorporate cost responsibility assignments for 45 new baseline upgrades, including its first interregional transmission projects ("Targeted Market Efficiency Projects") between PJM and Midcontinent Independent System Operator, Inc. ("MISO") under the MISO-PJM Joint Operating Agreement ("MISO-PJM JOA"), in the recent update to the Regional Transmission Expansion Plan ("RTEP") approved by the PJM Board of Managers ("PJM Board") on December 6, 2017. PJM requests that the revised Tariff sections become effective on April 5, 2018, 90 days after the date of this filing.

-

¹ All capitalized terms that are not otherwise defined herein have the meaning as defined in the Tariff, Operating Agreement, and Reliability Assurance Agreement Among Load Serving Entities in the PJM Region ("RAA").

² 16 U.S.C. § 824d.

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 2

I. DESCRIPTION OF FILING

A. Description of the PJM Board Approved Updated RTEP Upgrades

On December 6, 2017, the PJM Board approved changes to the RTEP, which included

approximately \$350.45 million in additional baseline transmission enhancements and

expansions.³ With these approvals, the PJM Board has authorized a total of more than

\$35 billion in investments since 2000.

B. Schedule 12 Requirements to Designate Cost Responsibility Assignments

This filing represents PJM's forty-second filing of cost responsibility assignments for

new RTEP baseline upgrades since the Federal Energy Regulatory Commission ("Commission")

directed such filings under the Tariff, Schedule 12. Pursuant to Schedule 12, PJM is required to

designate in the Tariff, Schedule 12-Appendix A cost responsibility assignments for all

transmission enhancements and expansions included in the RTEP.⁴ Similarly, Schedule 12

requires that within 30 days of the PJM Board's approval of each RTEP, or an addition to the

RTEP, PJM shall designate in Schedule 12-Appendix A, and in a report filed with the

Commission, the "Responsible Customers" that will be subject to charges related to transmission

enhancements and expansions included in the RTEP.⁵

_

³ The PJM Board also approved five interregional transmission projects known as Targeted Market Efficiency Projects between PJM and MISO as provided for under the MISO-PJM JOA. *See, supra* at 7. Four of the five Targeted Market Efficiency Projects are to be located in the MISO region. Therefore, the cost of the four Targeted Market Efficiency Projects to be located in the MISO region were not included in the \$350.45 million.

⁴ See Tariff, Schedule 12, § (b)(viii) (PJM "shall designate in the Schedule 12-Appendix A . . . the cost responsibility assignments determined pursuant to [§] (b)(i) through (v) of this Schedule 12.").

⁵ *Id.*; see also Operating Agreement, Schedule 6, § 1.6.

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 3

Schedule 12 further provides that customers designated to be responsible for assignments

of cost responsibility that PJM files with the Commission shall have 30 days from the date of

such filing to submit comments regarding the proposed cost responsibility assignments.⁶

C. Description of Proposed Amendments to Schedule 12-Appendix A

On March 22, 2013, the Commission accepted revisions to Schedule 12 modifying the

cost allocation methodologies for transmission projects included in the RTEP.⁷ These revisions

were filed by the PJM Transmission Owners in compliance with Order No. 1000 and revised the

methodologies for allocating cost responsibility for all RTEP transmission enhancements and

expansions, including reliability and economic projects, replacement projects, and high voltage

direct current transmission projects. These revisions only apply to the cost allocations for

projects included in the RTEP on a prospective basis and do not disturb the cost allocations for

projects previously included in the RTEP. Therefore, the cost responsibility assignments for

RTEP projects approved after the March 22 Order are segregated in a separate appendix from the

previously-approved cost responsibility assignments for RTEP upgrades. Going forward, cost

responsibility assignments for all new RTEP projects are located in Schedule 12-Appendix A.

As required by Schedule 12, PJM hereby submits amendments to Schedule 12-

Appendix A to include the new cost responsibility assignments for RTEP upgrades approved by

the PJM Board on December 6, 2017. This is the eighteenth filing to include cost responsibility

assignments following the March 22 Order in Schedule 12-Appendix A. The revised Tariff

⁶ Tariff, Schedule 12, § (b)(viii).

⁷ PJM Interconnection, L.L.C., et al., 142 FERC ¶ 61,214 at PP 411, 448 (2013) ("March 22 Order").

⁸ See Tariff, Schedule 12, § (b)(viii).

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 4

sections containing new language, including new cost responsibility assignments, are reflected in

redline and clean format in Attachments B and C, respectively, to this transmittal letter.⁹

1. Assignments of Cost Responsibility for Regional Facilities

On December 6, 2017, the PJM Board approved three new cost responsibility

assignments for transmission enhancements and expansions that are Regional Facilities or

Necessary Lower Voltage Facilities (collectively, "Regional Facilities") as defined in Tariff,

Schedule 12, section (b)(i). However, baseline upgrades b2953 and 2954 are allocated 100

percent to the zone in which the facility is located as the estimated cost of each enhancement

included for the first time in the RTEP does not equal or exceed \$5 million. 10 Additionally,

baseline upgrade b2960 qualifies as a Regional Facility but it is needed to address Form No. 715

criteria and, therefore, is allocated 100 percent to the zone of the transmission owner who filed

the criteria.¹¹

2. Assignments of Cost Responsibility for Lower Voltage Facilities Needed

for Reliability

a. Cost Responsibility Assignments that Address Transmission

Enhancements Costing More than \$5 Million and Require DFAX

Analysis

Consistent with the Tariff, Schedule 12, PJM submits amendments to the Tariff, Schedule

12-Appendix A to include the cost responsibility assignments for transmission enhancements and

expansions that are not Regional Facilities ("Lower Voltage Facilities"). 12 Twelve

⁹ The revised Tariff sections do not include any proposed rates or charges for recovery of any system upgrade costs. In accordance with Tariff, Schedule 12, recovery of the costs of such facilities that the RTEP requires Transmission

Owners to construct, own and/or finance is governed by the Transmission Owners' established rates.

¹⁰ See, supra at C.2b.

¹¹ See supra at C.2c.

¹² See Tariff, Schedule 12, § (b)(ii)(A) ("If the Lower Voltage Facility is a Reliability Project, [PJM] shall use the

DFAX analysis described in § (b)(iii) of this Schedule 12 ").

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 5

enhancements and expansions¹³ included in this filing, approved by the PJM Board on

December 6, 2017, are Lower Voltage Facilities required to address reliability needs for which

PJM applied the DFAX analysis described in the Tariff, Schedule 12, section (b)(iii).

b. <u>Cost Responsibility Assignments that Address Transmission</u> Enhancements Costing Less than \$5 Million

Schedule 12 section (b)(vi) provides that, notwithstanding the Schedule 12 sections (b)(i),

(b)(ii), (b)(iv) and (b)(v), cost responsibility for an enhancement for which the good faith

estimate of the cost of such enhancement included for the first time in the RTEP does not equal

or exceed \$5 million shall be assigned to the zone where the enhancement is to be located.

Consistent with Schedule 12 section (b)(vi), PJM proposes revisions to Schedule 12-Appendix A

to include cost responsibility assignments for 20 enhancements needed for reliability.¹⁴

Therefore, consistent with Schedule 12 section (b)(vi), cost responsibility for such enhancements

shall be allocated 100 percent to the zone of the Transmission Owner where the enhancements

are to be located.

c. Cost Responsibility Assignments that Address Form 715 Local

Planning Criteria

On February 12, 2016, the Commission accepted, effective May 25, 2015, the PJM

Transmission Owners' proposal to allocate 100 percent of the costs of a certain category of

RTEP projects, which would not otherwise be included in the RTEP but for the fact they address

local transmission owner planning criteria, to the zone of the Transmission Owner that filed the

¹³ The 12 Lower Voltage Facilities referenced include: b2761.3, b2952, b2955, b2956, b2959, b2965, b2967, b2970, b2970.1, b2970.2, b2970.3, and b2970.4.

¹⁴ The upgrades allocated pursuant to Schedule 12, § (b)(vi) include the following reliability upgrades: b2752.8, b2752.9, b2946, b2947.1, b2947.2, b2948, b2950, b2951, b2951.2, b2951.3, b2953, b2954, b2962, b2963, b2964.1, b2964.2, b2966, b2968, and b2969.

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 6

criteria in its FERC Form No. 715. 15 Consistent with Schedule 12 section (b)(xv), which details

the cost allocation methodology for projects selected solely to address Form 715 criteria, PJM

proposes revisions to Schedule 12-Appendix A to include cost responsibility assignments for

three lower voltage facility enhancements that solely address Form 715 local planning criteria. 16

d. Cost Responsibility Assignments for Reliability Violations on Facilities Operating Below 200 kV that are Exempted from PJM's

Competitive Proposal Window Process

On February 2, 2017, the Commission accepted, effective August 26, 2016, proposed

revisions to the PJM Tariff, Schedule 12 and the PJM Operating Agreement at Schedule 6,

submitted to comply with the Commission's August 26, 2016 order, ¹⁷ accepting PJM's April 1,

2016 filing 18 exempting from PJM's competitive proposal window process, except under certain

circumstances, reliability violations on transmission facilities operating below 200 kV. In its

September 26, 2016 compliance filing, ¹⁹ PJM, as authorized by the PJM Transmission Owners

acting through the Consolidated Transmission Owners Agreement, proposed to amend

Schedule 12 to include a new section (b)(xvi) to provide that solutions for reliability violations

on a facility operating at or below 200 kV transmission facility not included in a competitive

proposal window pursuant to section 1.5.8(c) of Schedule 6 of the Operating Agreement will be

allocated to the zone in which the transmission facility is to be located. Consistent with

Schedule 12 section (b)(xvi), which details the cost allocation methodology for transmission

facilities operating at or below 200 kV that were not included in a competitive proposal window,

¹⁵ *PJM Interconnection, L.L.C.*, 154 FERC ¶ 61,096 at P 13 (Feb. 12, 2016) ("February 12 Order").

¹⁶ The following upgrades were selected solely to address Form 715 criteria: b2958.1, b2958.2, and b2961.

¹⁷ *PJM Interconnection, L.L.C.*, 156 FERC ¶ 61,132 (Aug. 26, 2016) ("August 26 Order").

¹⁸ PJM Interconnection, L.L.C., Proposed Lower Voltage Threshold Exemption Filing Letter, Docket No. ER16-

1335-000 (Apr. 1, 2016) ("April 1 Filing").

¹⁹ PJM Interconnection, L.L.C., Compliance Filing, ER16-1335-002 (Sept. 26, 2016).

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 7

PJM proposes revisions to Schedule 12-Appendix A to include cost responsibility assignments

for two reliability enhancements operating at or below 200 kV that were not included in a

competitive proposal window.²⁰

3. Assignments of Cost Responsibility for Lower Voltage Facilities that

Address Market Efficiency Criteria

This filing includes six upgrades that were approved by the PJM Board to address market

efficiency needs. One of the market efficiency upgrades addresses regional needs.²¹ The

remaining five enhancements are interregional transmission projects identified as Targeted

Market Efficiency Projects in the MISO-PJM JOA.²²

a. Regional Market Efficiency Project

The cost responsibility assignment for the new enhancement or expansion to relieve one

or more economic constraints to zones²³ that show a decrease in the net present value of the

Changes in Load Energy and Capacity Payments are determined for the first 15 years of the life

of the Economic Project. Cost Responsibility is assigned based on each zone's pro rata share of

the sum of the net present values of the Changes in Load Energy and Capacity Payments only of

the zones in which the net present value of the Changes in Load Energy and Capacity Payments

show a decrease. The one regional market efficiency project b2976 approved by the PJM Board

on December 6, 2017, was allocated 100 percent to the zone of the Transmission Owner in which

the enhancement is to be located consistent with section (b)(vi) as the estimated cost of those

upgrade are less than \$5 million.

²⁰ The following upgrades are transmission facilities operating at or below 200 kV that were not included in a competitive proposal window: b2945.1, b2945.2 and b2945.3.

²¹ The regional market efficiency upgrade is b2976.

²² The Targeted Market Efficiency Projects include: b2971, b2972, b2973, b2974 and b2975.

²³ Economic constraints are described in the Operating Agreement, Schedule 6, § 1.5.7(b)(iii).

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 8

b. <u>Interregional Market Efficiency Projects</u>

On December 6, 2017, the PJM Board approved its first interregional transmission

projects between the PJM and MISO referred to as Targeted Market Efficiency Projects.

PJM, MISO and their respective transmission owners first proposed revisions to the

MISO-PJM JOA on December 30, 2016 to include a new category of interregional transmission

projects referred as Targeted Market Efficiency Projects, as well as a method for allocating the

costs of such projects between PJM and MISO.²⁴ Targeted Market Efficiency Projects were

proposed to reduce current congestion on Reciprocal Coordinated Flowgates along the MISO-

PJM border to benefit customers and improve coordination between the RTOs. The Targeted

Market Efficiency Project process is a streamlined process focused on relatively small, low cost,

short lead time upgrades to existing facilities intended to deliver "quick hit" solutions with a

payback period of only four years.²⁵

The method proposed to allocate costs of a Targeted Market Efficiency Project between

the RTOs was based on each RTO's share of the expected benefits from the transmission project,

i.e., each RTO's share of the total avoided congestion, as modified by market-to-market

settlements. The filing parties also subsequently filed separate methods for allocating PJM's and

MISO's share of the cost of a Targeted Market Efficiency Project within their respective regions.

In Docket No. ER17-1406-000, the PJM Transmission Owners proposed to revise Schedule 12

of the PJM Tariff²⁶ to assign the costs of a Targeted Market Efficiency Project to the zones and

²⁴ *PJM Interconnection, L.L.C.*, Proposed Revisions to MISO-PJM JOA for Targeted Market Efficiency Projects, Docket No. ER17-718-000 (Dec. 30, 2017; *Midcontinent Independent System Operator, Inc.*, Proposed Revisions to MISO-PJM JOA for Targeted Market Efficiency Projects Process and Cost Allocation, Docket No. ER17-719-000 (Dec. 30, 2017); and *PJM Interconnection, L.L.C.*, Proposed Revisions to MISO-PJM JOA for Targeted Market

Efficiency Projects Cost Allocation, Docket No. ER17-729-000 (Dec. 30, 2017).

²⁵ MISO-PJM JOA, §§ 9.3 and 9.4.

²⁶ PJM Tariff, Schedule 12 § (b)(xvii).

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 9

merchant transmission facilities in the PJM region that are shown to have experienced net

positive congestion over a two-year historical period as determined by PJM and MISO.

On October 3, 2017, the Commission accepted, subject to condition, the RTOs' proposed

revisions to the MISO-PJM JOA to add Targeted Market Efficiency Projects, as well as a method

for allocating the costs of these transmission projects between the RTOs, effective June 28,

2017.²⁷ Additionally, by letter order dated October 3, 2017, the Commission accepted the

revisions to Schedule 12 of the PJM Tariff as proposed by the PJM Transmission Owners in

Docket No. ER17-1406-000 to establish a method to allocate the costs of Targeted Market

Efficiency Projects within the PJM region.²⁸

Consistent with Schedule 12 section (b)(xvii), which details the cost allocation

methodology for a Targeted Market Efficiency Project to the zones and merchant transmission

facilities in the PJM region that are shown to have experienced net positive congestion over a

two-year historical period as determined by a TMEP study conducted by PJM and MISO, PJM

proposes revisions to Schedule 12-Appendix A to include the regional cost responsibility

assignments for five Targeted Market Efficiency Projects.²⁹

D. Cost Responsibility Assignment Summary

For informational purposes, PJM also includes in Attachment A to this transmittal letter a

Cost Responsibility Assignment Summary for the enhancements or expansions approved by the

PJM Board on December 6, 2017. In addition to specifying the cost responsibility assignments

for the enhancements and expansions, the summary sheets provide the criteria violation and test,

²⁷ See PJM Interconnection, L.L.C., 161 FERC ¶ 61,005 (Oct. 3, 2017).

²⁸ PJM Interconnection, L.L.C., Revisions to Schedule 12 for Targeted Market Efficiency Projects, Docket No.

ER17-1406-000 (accepted by letter order issued Oct. 3, 2017).

²⁹ The following Targeted Market Efficiency Projects include: b2971, b2972, b2973, b2974 and b2975.

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 10

a description of the upgrade, in-service date, estimated upgrade costs, and the entity designated

with construction responsibility for each enhancement or expansion.

II. COMMENT PERIOD

The Tariff, Schedule 12 section (b)(viii) provides that customers designated to be

responsible for assignments of cost responsibility shall have 30 days from the date of such filing

to submit comments regarding the proposed cost responsibility assignments. Consistent with this

provision, PJM requests that the comment date for this filing be set 30 days from the date of this

filing, i.e., February 4, 2018.³⁰ To accommodate such a comment date, PJM requests an

effective date of April 5, 2018 (90 days from the date of this filing) for all revised Tariff sections

submitted in this docket.³¹

III. DOCUMENTS ENCLOSED

PJM encloses the following:

a. This transmittal letter;

b. Attachment A – Cost Responsibility Assignment Summary sheets;

c. Attachment B – Revised Tariff, Schedule 12-Appendix A (in redlined form); and

d. Attachment C – Revised Tariff, Schedule 12-Appendix A (in clean form).

_

³⁰ Since February 4, 2018 falls on a Sunday, comments are due on Monday, February 5, 2018. *See* 18 C.F.R. § 385.2007(a)(2) (2017).

3 303.2007 (4)(2) (2017).

³¹ See, e.g., PJM Interconnection, L.L.C., Errata Notice of Extending Comment Period, Docket Nos. ER06-456-018, et al. (Dec. 2, 2008) (granting extension of time for filing protests or comments to accommodate Schedule 12 of the PJM Tariff); PJM Interconnection, L.L.C., Errata Notice Extending Comment Date, Docket No. ER08-229-000 (Nov. 30, 2007) (same); PJM Interconnection, L.L.C., Notice Extending Comment Date, Docket No. ER07-1186-000 (July 31, 2007) (same).

Re: PJM Interconnection, L.L.C.

January 5, 2018

Page 11

IV. CORRESPONDENCE AND COMMUNICATIONS

Correspondence and communications with respect to this filing should be sent to the

following persons:

Craig Glazer

Vice President–Federal Government Policy

PJM Interconnection, L.L.C.

1200 G Street, N.W., Suite 600

Washington, D.C. 20005

Ph: (202) 423-4743

Fax: (202) 393-7741

craig.glazer@pjm.com

Pauline Foley

Associate General Counsel

PJM Interconnection, L.L.C.

2750 Monroe Blvd.

Audubon, PA 19403

Ph: (610) 666-8248

Fax: (610) 666-4281

pauline.foley@pjm.com

V. SERVICE

PJM has served a copy of this filing on all PJM Members and on the affected state utility

regulatory commissions in the PJM Region by posting this filing electronically. In accordance

with the Commission's regulations,³² PJM will post a copy of this filing to the FERC filings

section of its internet site, located at the following link: http://www.pjm.com/documents/ferc-

manuals/ferc-filings.aspx with a specific link to the newly-filed document, and will send an e-

mail on the same date as this filing to all PJM Members and all state utility regulatory

commissions in the PJM Region³³ alerting them that this filing has been made by PJM and is

available by following such link. If the document is not immediately available by using the

referenced link, the document will be available through the referenced link within twenty-four

hours of the filing. Also, a copy of this filing will be available on the Commission's eLibrary

³² See 18 C.F.R. §§ 35.2(e) and 385.201(f)(3) (2017).

³³ PJM already maintains, updates, and regularly uses electronic mailing lists for all PJM Members and affected state commissions.

Honorable Kimberly D. Bose, Secretary Re: PJM Interconnection, L.L.C. January 5, 2018 Page 12

website located at the following link: http://www.ferc.gov/docs-filing/elibrary.asp in accordance with the Commission's regulations and Order No. 714.

Craig Glazer
Vice President – Federal Government Policy
PJM Interconnection, L.L.C.
1200 G Street, NW, Suite 600
Washington, DC 20005

Ph: (202) 423-4743 Fax: (202) 393-7741 craig.glazer@pjm.com Respectfully submitted,

By: Pauline Foley

Associate General Counsel PJM Interconnection, L.L.C. 2750 Monroe Blvd. Audubon, PA 19403

Ph: (610) 666-8248 Fax: (610) 666-4281 pauline.foley@pjm.com

Counsel for PJM Interconnection, L.L.C

Attachment A

Cost Responsibility Assignment Summary Sheets

Baseline Upgrade b2752.8

- Overview of Reliability Problem
 - o Criteria Violation: Overstress of the Conastone 230kV '2322 B5' breaker
 - o Contingency: Fault at Conastone
 - o Criteria test: Short Circuit
- Overview of Reliability Solution
 - Description of Upgrade: Replace the Conastone 230 kV '2322 B5' breaker with a 63kA breaker
 - o Upgrade In-Service Date: June 01, 2020
 - o Estimated Upgrade Cost: \$0.54 M
 - o Construction Responsibility: BGE
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to BGE

Baseline Upgrade b2752.9

- Overview of Reliability Problem
 - o Criteria Violation: Overstress of the Conastone 230kV '2322 B6' breaker
 - o Contingency: Fault at Conastone
 - o Criteria test: Short Circuit
- Overview of Reliability Solution
 - Description of Upgrade: Replace the Conastone 230 kV '2322 B6' breaker with a 63kA breaker
 - o Upgrade In-Service Date: June 01, 2020
 - o Estimated Upgrade Cost: \$0.54 M
 - o Construction Responsibility: BGE
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to BGE

Baseline Upgrade b2761.3

- Overview of Reliability Problem
 - Criteria Violation: Overload of Hazard 161/138 kV transformer and Hazard -Wooten 138 kV circuit
 - o Contingency: Multiple
 - o Criteria test: Summer and Winter Generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Rebuild the Hazard Wooton 161 kV line utilizing 795 26/7 ACSR conductor (300 MVA rating)
 - o Upgrade In-Service Date: June 01, 2021
 - o Estimated Upgrade Cost: \$16.48 M
 - o Construction Responsibility: AEP
- Cost Allocation
 - The cost for this network upgrade is allocated 100% to AEP. No zones had greater than a 0.01 DFAX.

Transmission Zone	Planned Load (MW)	DFAX	DFAX Allocation
AEP	23267	< 0.01	100.00%

Baseline Upgrade b2945.1

- Overview of Reliability Problem
 - o Criteria Violation: < 200 kV Violation N-1-1 and Common Mode outage
 - o Contingency: Multiple contingencies
 - o Criteria test: N-1-1 and Common Mode outage
- Overview of Reliability Solution
 - Description of Upgrade: Rebuild the BL England Middle Tap 138 kV line to 2000A on double circuited steel poles and new foundations
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$22.64 M
 - o Construction Responsibility: AEC
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to AEC

Baseline Upgrade b2945.2

- Overview of Reliability Problem
 - o Criteria Violation: N-1-1 and Common Mode outage
 - o Contingency: Few contingencies
 - o Criteria test: N-1-1 and Common Mode outage
- Overview of Reliability Solution
 - Description of Upgrade: Reconductor BL England Merion 138 kV (1.9 miles) line
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$3.92 M
 - o Construction Responsibility: AEC
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to AEC

Baseline Upgrade b2945.3

- Overview of Reliability Problem
 - o Criteria Violation: < 200 kV Violation N-1-1 and Common Mode outage
 - o Contingency: Few contingencies
 - o Criteria test: N-1-1 and Common Mode outage
- Overview of Reliability Solution
 - o Description of Upgrade: Reconductor Merion Corson 138 kV (8 miles) line
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$9.85 M
 - o Construction Responsibility: AEC
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to AEC

- Overview of Reliability Problem
 - o Criteria Violation: Common mode outage
 - o Contingency: loss of the Milford to Steele and Steele to Vienna 230 kV circuits
 - o Criteria test: Winter Generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Convert existing Preston 69 kV substation to DPL's current design standard of a 3-breaker ring bus
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$2.64 M
 - o Construction Responsibility: DPL
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to DPL

Baseline Upgrade b2947.1

- Overview of Reliability Problem
 - o Criteria Violation: Common mode outage
 - Contingency: loss of the Edge Moor to Claymont and Edge Moor to Linwood 230 kV circuits
 - o Criteria test: Summer Generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Upgrade terminal equipment at DPL's Naamans substation (Darley - Naamans 69 kV)
 - o Upgrade In-Service Date: June 01, 2022
 - Estimated Upgrade Cost: \$0.15 M
 - o Construction Responsibility: DPL
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to DPL

Baseline Upgrade b2947.2

- Overview of Reliability Problem
 - o Criteria Violation: Common mode outage
 - Contingency: loss of the Edge Moor to Claymont and Edge Moor to Linwood 230 kV circuits
 - o Criteria test: Summer Generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Reconductor 0.11 mile section of Darley Naamans 69 kV circuit
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$0.20 M
 - o Construction Responsibility: DPL
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to DPL

- Overview of Reliability Problem
 - o Criteria Violation: Common mode outage
 - Contingency: loss of the Edge Moor to Claymont and Edge Moor to Linwood 230 kV circuits
 - o Criteria test: Summer generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Upgrade terminal equipment at DPL's Silverside Road substation (Dupont Edge Moor – Silver R. 69 kV)
 - o Upgrade In-Service Date: June 01, 2022
 - Estimated Upgrade Cost: \$0.15 M
 - o Construction Responsibility: DPL
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to DPL

- Overview of Reliability Problem
 - o Criteria Violation: N-1
 - o Contingency: loss of the Hosensack to Steel City 500 kV circuit
 - o Criteria test: Summer generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Upgrade limiting 115 kV switches on the 115 kV side of the 230/115 kV Northwood substation and adjust setting on limiting ZR relay
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$0.10 M
 - o Construction Responsibility: ME
- Cost Allocation
 - The cost for this network upgrade is allocated 100% to ME

Baseline Upgrade b2951, b2951.1, b2951.2, b2951.3

- Overview of Reliability Problem
 - o Criteria Violation: Common mode outage
 - o Contingency: multiple contingencies
 - o Criteria test: Summer generation Deliverability
- Overview of Reliability Solution
 - o Description of Upgrade:
 - > Seward, Blairsville East, Shelocta work
 - ➤ Upgrade Florence 115 kV line terminal equipment at Seward SS
 - ➤ Replace Blairsville East / Seward 115 kV line tuner, coax, line relaying and carrier set at Shelocta SS
 - ➤ Replace Seward / Shelocta 115 kV line CVT, tuner, coax, and line relaying at Blairsville East SS
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$1.49 M
 - Construction Responsibility: PENELEC
- Cost Allocation
 - The cost for this network upgrade is allocated 100% to PENELEC

- Overview of Reliability Problem
 - o Criteria Violation: N-1
 - o Contingency: loss of the North Meshoppen Canyon E. Towanda 230 kV circuit and the North Meshoppen 230/115 kV transformer #4
 - o Criteria test: Winter Generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Replace the North Meshoppen #3 230/115 kV transformer eliminating the old reactor and installing two breakers to complete a 230 kV ring bus at North Meshoppen
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$6.80 M
 - o Construction Responsibility: PENELEC
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to PENELEC

Transmission Zone	Planned Load (MW)	DFAX	DFAX Allocation
PENELEC	2869	0.01057	100.00%

- Overview of Reliability Problem
 - o Criteria Violation: Overstress of the Keystone 500 kV "NO.14 Cabot" breaker
 - o Contingency: Fault at Keystone
 - o Criteria test: Short Circuit
- Overview of Reliability Solution
 - Description of Upgrade: Replace the Keystone 500 kV breaker "NO. 14 Cabot" with 50kA breaker
 - o Upgrade In-Service Date: June 01, 2020
 - o Estimated Upgrade Cost: \$1.24 M
 - o Construction Responsibility: PENELEC
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to PENELEC

- Overview of Reliability Problem
 - o Criteria Violation: Overstress of the Keystone 500 kV "NO.16 Cabot" breaker
 - o Contingency: Fault at Keystone
 - o Criteria test: Short Circuit
- Overview of Reliability Solution
 - Description of Upgrade: Replace the Keystone 500 kV breaker "NO. 16 Cabot" with 50kA breaker
 - o Upgrade In-Service Date: June 01, 2020
 - o Estimated Upgrade Cost: \$1.24 M
 - o Construction Responsibility: PENELEC
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to PENELEC

- Overview of Reliability Problem
 - o Criteria Violation: Multiple Violations
 - Contingency: FG# GD-S26, GD-S27, GD-S28, GD-S33, GD-S556, GD-W37, GD-W38, GD-W39, GD-W348, GD-W353
 - o Criteria test: Generation Deliverability (Summer and Winter)
- Overview of Reliability Solution
 - Description of Upgrade: Wreck and rebuild the VFT Warinanco Aldene 230 kV circuit with paired conductor
 - o Upgrade In-Service Date: June 01, 2018
 - o Estimated Upgrade Cost: \$90.40 M
 - o Construction Responsibility: PSEG
- Cost Allocation

	%FLOW(+)	%FLOW(-
Projected Usage	99.12%	0.88%

Transmission Zone	Planned Load (MW)	DFAX	DFAX Allocation
JCPL	6,014	0.01866	93.78%
NEPTUNE*	685	0.01086	6.22%

^{*}Neptune Regional Transmission System, LLC

• Overview of Reliability Problem

o Criteria Violation: Gen Deliv: Common Mode and Single

o Contingency: FG# GD-S601

o Criteria test: Generation Deliverability (Summer)

• Overview of Reliability Solution

 Description of Upgrade: Replace existing cable on Cedar Grove - Jackson Rd. with 5000kcmil XLPE cable

o Upgrade In-Service Date: June 01, 2018

o Estimated Upgrade Cost: \$80.00 M

o Construction Responsibility: PSEG

Cost Allocation

	%FLOW(+)	%FLOW(-
Projected Usage	99.94%	0.06%

Transmission Zone	Planned Load (MW)	DFAX	DFAX Allocation
JCPL	6,014	-0.01778	0.05%
NEPTUNE*	685	-0.0166	0.01%
PSEG	9963	0.01132	96.07%
RE	401	0.01132	3.87%

^{*}Neptune Regional Transmission System,

LLC

^{**}East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

Baseline Upgrade b2958.1

- Overview of Reliability Problem
 - Criteria Violation: FERC Form 715 Criteria Violation major load increases at MarkWest's Majorsville, WV facilities
 - o Contingency: several contingencies
 - o Criteria test: TO Criteria
- Overview of Reliability Solution
 - Description of Upgrade: Cut George Washington Tidd 138 kV circuit into Sand Hill and reconfigure Brues & Warton Hill line entrances
 - o Upgrade In-Service Date: July 01, 2017
 - o Estimated Upgrade Cost: \$2.19 M
 - o Construction Responsibility: AEP
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to AEP

Baseline Upgrade b2958.2

- Overview of Reliability Problem
 - Criteria Violation: FERC Form 715 Criteria Violation major load increases at MarkWest's Majorsville, WV facilities
 - o Contingency: several contingencies
 - o Criteria test: TO Criteria
- Overview of Reliability Solution
 - Description of Upgrade: Add 2 138 kV 3000 A 40 kA breakers, disconnect switches, and update relaying at Sand Hill station
 - o Upgrade In-Service Date: July 01, 2017
 - o Estimated Upgrade Cost: \$5.06 M
 - o Construction Responsibility: AEP
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to AEP

- Overview of Reliability Problem
 - Criteria Violation: Rock Falls Nelson 138KV Red line, Schauff Road (O09&O29) – Nelson Tap 138kV Red line and Schauff Road(O9&O29) – Rock Falls 138kV Red line overloads
 - o Contingency: multiple single contingencies
 - o Criteria test: Light Load
- Overview of Reliability Solution
 - Description of Upgrade: Install a new 138 kV circuit 18702 from Schauff Road to Rock Falls and install a fourth breaker and a half run at Schauff Road
 - o Upgrade In-Service Date: November 01, 2019
 - o Estimated Upgrade Cost: \$20.00 M
 - o Construction Responsibility: ComEd
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to ComEd. No zones had greater than a 0.01 DFAX.

Transmission Zone	Planned Load (MW)	DFAX	DFAX Allocation
ComEd	22406	< 0.01	100.00%

- Overview of Reliability Problem
 - o Criteria Violation: FERC Form 715 Criteria Violation Angular stability
 - o Contingency: Loss of fixed series capacitors on Line #547 & Line #548
 - Criteria test: "End of Life" Criteria
- Overview of Reliability Solution
 - Description of Upgrade: Replace fixed series capacitors on 500 kV Line #547 at Lexington and on 500 kV Line #548 at Valley
 - o Upgrade In-Service Date: April 01, 2020
 - o Estimated Upgrade Cost: \$28.90 M
 - o Construction Responsibility: Dominion
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to Dominion

- Overview of Reliability Problem
 - o Criteria Violation: FERC Form 715 Criteria Violation Loss of load (140 MW)
 - Contingency: Loss of Line #205 and Line #2003 from Chesterfield to Locks and Poe respectively
 - o Criteria test: "End of Life" Criteria
- Overview of Reliability Solution
 - Description of Upgrade: Rebuild approximately 3 miles of Line #205 & Line #2003 from Chesterfield to Locks & Poe respectively
 - o Upgrade In-Service Date: December 31, 2022
 - o Estimated Upgrade Cost: \$9.50 M
 - o Construction Responsibility: Dominion
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to Dominion

- Overview of Reliability Problem
 - Criteria Violation: Common mode outage, Thermal Pleasant View Ashburn 230 kV
 - o Contingency: Multiple contingencies
 - o Criteria test: Summer generation deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Split Line #227 (Brambleton Beaumeade 230 kV) and terminate into existing Belmont substation
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$3.05 M
 - o Construction Responsibility: Dominion
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to Dominion

- Overview of Reliability Problem
 - Criteria Violation: N-1, Thermal Possum Point Woodbridge Occoquan 230 kV
 - Contingency: loss of the Possum Point Possum Creek Woodbridge E.P.G.
 Hayfield 230 kV circuit
 - o Criteria test: Summer generation deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Reconductor the Woodbridge to Occoquan 230 kV line segment of Line #2001 with 1047 MVA conductor and replace line terminal equipment at Possum Point, Woodbridge, and Occoquan
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$4.49 M
 - o Construction Responsibility: Dominion
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to Dominion

Baseline Upgrade b2964.1

- Overview of Reliability Problem
 - Criteria Violation: Common mode outage, Thermal Pruntytown White Hall Junction - McAlpin - Glen Falls 138
 - Contingency: loss of the Pruntytown Maple Lake and Pruntytown Shinns Run 138 kV circuits.
 - o Criteria test: Summer generation deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Replace terminal equipment at Pruntytown and Glen Falls 138 kV station
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$0.26 M
 - o Construction Responsibility: APS
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to APS

Baseline Upgrade b2964.2

- Overview of Reliability Problem
 - Criteria Violation: Common mode outage, Thermal Pruntytown White Hall Junction - McAlpin - Glen Falls 138
 - Contingency: loss of the Pruntytown Maple Lake and Pruntytown Shinns Run 138 kV circuits.
 - o Criteria test: Summer generation deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Reconductor approximately 8.3 miles of the McAlpin - White Hall Junction 138 kV circuit
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$3.79 M
 - o Construction Responsibility: APS
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to APS

- Overview of Reliability Problem
 - Criteria Violation: N-1 and Common Mode Outage, Thermal Allenport Charleroi 138 kV
 - o Contingency: multiple contingencies
 - o Criteria test: Summer generation deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Reconductor the Charleroi –Allenport 138 kV line with 954 ACSR conductor. Replace breaker risers at Charleroi and Allenport
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$7.08 M
 - o Construction Responsibility: APS
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to DL

Transmission Zone	Planned Load (MW)	DFAX	DFAX Allocation
DL	2879	0.01549	100.00%

- Overview of Reliability Problem
 - Criteria Violation: N-1 and Common Mode Outage, Thermal Yukon Smithon - Shepler Hill Jct Tap 138 kV
 - o Contingency: multiple contingencies
 - o Criteria test: Summer generation deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Reconductor the Yukon Smithton Shepler Hill Jct 138 kV line with 795 ACSS conductor. Replace Line Disconnect Switch at Yukon
 - o Upgrade In-Service Date: June 01, 2022
 - Estimated Upgrade Cost: \$3.19 M
 - o Construction Responsibility: APS
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to APS

- Overview of Reliability Problem
 - Criteria Violation: N-1 and Common Mode Outage, Thermal Butler Shanor Manor - Krendale 138 kV
 - o Contingency: Several Contingencies
 - o Criteria test: Summer generation deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Convert the existing 6 wire Butler Shanor Manor -Krendale 138 kV line into two separate 138 kV lines. New lines will be Butler -Keisters and Butler - Shanor Manor - Krendale 138 kV
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$6.96 M
 - o Construction Responsibility: APS
- Cost Allocation
 - The cost for this network upgrade is allocated 100% to APS. No zones had greater than a 0.01 DFAX

Transmission Zone	Planned Load (MW)	DFAX	DFAX Allocation
APS	9004	< 0.01	100.00%

- Overview of Reliability Problem
 - o Criteria Violation: N-1, Thermal Tanner Miami Fort 345 kV
 - o Contingency: multiple contingencies
 - o Criteria test: Winter Generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Upgrade existing 345 kV terminal equipment at Tanner Creek station
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$1.20 M
 - o Construction Responsibility: AEP
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to AEP

- Overview of Reliability Problem
 - o Criteria Violation: N-1, Thermal Maddox East Lima 345 kV
 - o Contingency: loss of the Marysville Sorenson 765KV line
 - o Criteria test: Winter Generation Deliverability
- Overview of Reliability Solution
 - Description of Upgrade: Replace terminal equipment on Maddox Creek East Lima 345 kV circuit
 - o Upgrade In-Service Date: June 01, 2022
 - o Estimated Upgrade Cost: \$1.48 M
 - o Construction Responsibility: AEP
- Cost Allocation
 - o The cost for this network upgrade is allocated 100% to AEP

Baseline Upgrade b2970, b2970.1, b2970.2, b2970.3, b2970.4

- Overview of Reliability Problem
 - Criteria Violation: The Ringgold 230/138kV transformers #3 and #4 are overloaded for multiple contingencies
 - o Contingency: multiple contingencies
 - Criteria test: Winter and Summer Generation Deliverability, Baseline and N-1 1.
- Overview of Reliability Solution
 - Description of Upgrade:
 - Ringgold Catoctin Solution
 - ➤ Install two new 230 kV positions at Ringgold for 230/138 kV transformers
 - ➤ Install new 230 kV position for Ringgold Catoctin 230 kV line
 - ➤ Install one new 230 kV breaker at Catoctin substation
 - ➤ Install new 230/138 kV transformer at Catoctin substation. Convert Ringgold Catoctin 138 kV line to 230 kV operation
 - o Upgrade In-Service Date: June 01, 2020
 - Estimated Upgrade Cost: \$13.33 M
 - o Construction Responsibility: APS
- Cost Allocation
 - The cost for this network upgrade is allocated 100% to APS. No zones had greater than a 0.01 DFAX

Transmission Zone	Planned Load (MW)	DFAX	DFAX Allocation
APS	9004	< 0.01	100.00%

• Overview of Reliability Problem

o Criteria Violation: Congestion Relief

Criteria test: Market Efficiency

• Overview of Reliability Solution

o Description of Upgrade: Reconfigure Munster 345 kV as ring bus

o Upgrade In-Service Date: June 01, 2020

o Estimated Upgrade Cost: \$7.00 M

o Construction Responsibility: NIPSCO

Cost Allocation

The cost of this TMEP is allocated between PJM and MISO in proportion to the congestion relief benefits received by each region. Within PJM, cost responsibility is assigned based on each Zone's and Merchant Transmission Facility's pro rata share of the sum of the net Transmission Congestion Charges paid by Market Buyers only of the Zones and Merchant Transmission Facilities in which Market Buyers experienced

net Transmission Congestion Charges.

Transmission Zone	Congestion Benefits (\$M)	Allocation (%)
MISO	N/A	12.00%
AEC	\$311,227	0.97%
AEP	\$5,333,988	16.66%
APS	\$1,580,841	4.94%
ATSI	\$2,488,917	7.78%
BGE	\$1,666,336	5.21%
ComEd	(\$27,764,843)	0.00%
Dayton	\$593,037	1.85%
DEOK	\$734,830	2.30%
Dominion	\$4,869,399	15.21%
DPL	\$561,477	1.75%
DL	\$458,794	1.43%
EKPC	\$192,546	0.60%
JCPL	\$692,003	2.16%
ME	\$552,184	1.73%
PECO	\$1,384,183	4.32%
PENELEC	\$1,595,240	4.98%
PEPCO	\$1,857,298	5.80%
PPL	\$1,517,201	4.74%
PSEG	\$1,627,997	5.09%
RE	\$46,877	0.15%
NEPTUNE*	\$104,902	0.33%
ECP**	\$0	0.00%
HTP***	\$0	0.00%

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

• Overview of Reliability Problem

o Criteria Violation: Congestion Relief

o Criteria test: Market Efficiency

• Overview of Reliability Solution

Description of Upgrade: Reconductor limiting span of Lallendorf - Monroe 345 kV

o Upgrade In-Service Date: November 01, 2019

o Estimated Upgrade Cost: \$1.00 M

o Construction Responsibility: ATSI

• Cost Allocation

The cost of this TMEP is allocated between PJM and MISO in proportion to the congestion relief benefits received by each region. Within PJM, cost responsibility is assigned based on each Zone's and Merchant Transmission Facility's pro rata share of the sum of the net Transmission Congestion Charges paid by Market Buyers only of the

Zones and Merchant Transmission Facilities in which Market Buyers experienced net Transmission Congestion Charges.

Transmission Zone	Congestion Benefits (\$M)	Allocation (%)
MISO	N/A	11.00%
AEC	(\$106,449)	0.00%
AEP	\$418,227	5.38%
APS	\$331,974	4.27%
ATSI	\$5,167,349	66.48%
BGE	(\$62,232)	0.00%
ComEd	(\$5,168,366)	0.00%
Dayton	\$210,219	2.71%
DEOK	(\$47,218)	0.00%
Dominion	\$413,030	5.31%
DPL	(\$162,080)	0.00%
DL	\$376,550	4.85%
EKPC	(\$58,877)	0.00%
JCPL	(\$314,795)	0.00%
ME	(\$145,024)	0.00%
PECO	(\$442,602)	0.00%
PENELEC	(\$421,590)	0.00%
PEPCO	(\$3,493)	0.00%
PPL	(\$445,155)	0.00%
PSEG	(\$883,536)	0.00%
RE	(\$44,342)	0.00%
NEPTUNE*	(\$22,974)	0.00%
ECP**	\$0	0.00%
HTP***	\$0	0.00%

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

- Overview of Reliability Problem
 - o Criteria Violation: Congestion Relief
 - Criteria test: Market Efficiency
- Overview of Reliability Solution
 - o Description of Upgrade: Reconductor Michigan City Bosserman 138 kV
 - o Upgrade In-Service Date: December 01, 2019
 - o Estimated Upgrade Cost: \$4.60 M
 - o Construction Responsibility: NIPSCO

Cost Allocation

The cost of this TMEP is allocated between PJM and MISO in proportion to the congestion relief benefits received by each region. Within PJM, cost responsibility is assigned based on each Zone's and Merchant Transmission Facility's pro rata share of the sum of the net Transmission Congestion Charges paid by Market Buyers only of the Zones and Merchant Transmission Facilities in which Market Buyers experienced

net Transmission Congestion Charges.

Transmission Zone	Congestion Benefits (\$M)	Allocation (%)
MISO	N/A	10.00%
AEC	\$397,316	0.93%
AEP	\$11,136,907	26.05%
APS	\$1,791,147	4.19%
ATSI	\$2,544,987	5.95%
BGE	\$1,876,027	4.39%
ComEd	(\$37,707,354)	0.00%
Dayton	\$678,349	1.59%
DEOK	\$983,516	2.30%
Dominion	\$6,292,407	14.72%
DPL	\$655,833	1.53%
DL	\$537,741	1.26%
EKPC	\$417,857	0.98%
JCPL	\$820,140	1.92%
ME	\$593,334	1.39%
PECO	\$1,792,346	4.19%
PENELEC	\$1,857,917	4.35%
PEPCO	\$2,161,331	5.06%
PPL	\$1,725,036	4.03%
PSEG	\$1,918,110	4.49%
RE	\$52,350	0.12%
NEPTUNE*	\$238,136	0.56%
ECP**	\$0	0.00%
HTP***	\$0	0.00%

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

- Overview of Reliability Problem
 - o Criteria Violation: Congestion Relief
 - o Criteria test: Market Efficiency
- Overview of Reliability Solution
 - Description of Upgrade: Replace terminal equipment at Reynolds on the Reynolds -Magnetation 138 kV
 - o Upgrade In-Service Date: June 01, 2019
 - o Estimated Upgrade Cost: \$0.15 M
 - o Construction Responsibility: NIPSCO
- Cost Allocation

The cost of this TMEP is allocated between PJM and MISO in proportion to the congestion relief benefits received by each region. Within PJM, cost responsibility is assigned based on each Zone's and Merchant Transmission Facility's pro rata share of the sum of the net Transmission Congestion Charges paid by Market Buyers only of the Zones and Merchant Transmission Facilities in which Market Buyers experienced net Transmission Congestion Charges.

Transmission	Congestion Benefits	Allocation
Zone	(\$M)	(%)
MISO	N/A	59.00%
AEC	\$128	0.01%
AEP	\$614,466	40.32%
APS	\$1,986	0.13%
ATSI	\$696	0.05%
BGE	\$1,177	0.08%
ComEd	(\$674,733)	0.00%
Dayton	\$479	0.03%
DEOK	(\$600)	0.00%
Dominion	(\$1,508)	0.00%
DPL	\$174	0.01%
DL	\$2	0.00%
EKPC	(\$18,448)	0.00%
JCPL	(\$131)	0.00%
ME	\$677	0.04%
PECO	(\$283)	0.00%
PENELEC	\$898	0.06%
PEPCO	(\$733)	0.00%
PPL	\$3,136	0.20%
PSEG	\$417	0.03%
RE	(\$29)	0.00%
NEPTUNE*	\$588	0.04%
ECP**	\$0	0.00%
HTP***	\$0	0.00%

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

• Overview of Reliability Problem

o Criteria Violation: Congestion Relief

o Criteria test: Market Efficiency

• Overview of Reliability Solution

o Description of Upgrade: Reconductor Roxana - Praxair 138 kV

o Upgrade In-Service Date: June 01, 2020

o Estimated Upgrade Cost: \$4.50 M

Construction Responsibility: NIPSCO

Cost Allocation

The cost of this TMEP is allocated between PJM and MISO in proportion to the congestion relief benefits received by each region. Within PJM, cost responsibility is assigned based on each Zone's and Merchant Transmission Facility's pro rata share of the sum of the net Transmission Congestion Charges paid by Market Buyers only of the Zones and Merchant Transmission Facilities in which Market Buyers experienced

net Transmission Congestion Charges.

Transmission Zone	Congestion Benefits (\$M)	Allocation (%)
MISO	N/A	76.00%
AEC	\$96,402	0.28%
AEP	\$1,537,072	4.51%
APS	\$445,251	1.31%
ATSI	\$651,529	1.91%
BGE	\$475,562	1.40%
ComEd	(\$7,787,949)	0.00%
Dayton	\$166,858	0.49%
DEOK	\$236,794	0.70%
Dominion	\$1,481,872	4.35%
DPL	\$155,172	0.46%
DL	\$130,513	0.38%
EKPC	\$93,509	0.27%
JCPL	\$194,660	0.57%
ME	\$146,755	0.43%
PECO	\$425,264	1.25%
PENELEC	\$455,783	1.34%
PEPCO	\$522,218	1.53%
PPL	\$418,542	1.23%
PSEG	\$479,339	1.41%
RE	\$12,712	0.04%
NEPTUNE*	\$46,429	0.14%
ECP**	\$0	0.00%
HTP***	\$0	0.00%

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

• Overview of Reliability Problem

o Criteria Violation: Congestion Relief

o Criteria test: Market Efficiency

• Overview of Reliability Solution

 Description of Upgrade: Upgrade terminal equipment at Tanners Creek 345 kV station. Upgrade 345 kV bus and risers at Tanners Creek for the Dearborn circuit

o Upgrade In-Service Date: June 01, 2021

o Estimated Upgrade Cost: \$0.60 M

o Construction Responsibility: AEP

Cost Allocation

The cost for this network upgrade is allocated 100% to DEOK. The cost allocation for this network upgrade was determined through a cost/benefit analysis that considered the present value of 15 year projected Net Load Energy and Capacity benefits by transmission zone for zones with a decrease in Net Load Energy and Capacity Payments. DEOK was the only zone with a net positive cumulative present value of Load Benefit Metric.

Transmission Zone	Cumulative Present Value of Load Benefit Metric by Zone (\$M)	Allocation (%)
DEOK	\$124	100.00%

Attachment B

Schedule 12 – Appendix A of the PJM Open Access Transmission Tariff

(Marked / Redline Format)

SCHEDULE 12 – APPENDIX A

(1) Atlantic City Electric Company

required 1	Tarishiission Emiancements Ani	iuai Revenue Requirement	Responsible Customer(s)
b2123	Upgrade the 69 kV bus at Laurel		AEC (100%)
b2226	Upgrade the Tackahoe to Mill 69 kV circuit		AEC (100%)
b2227	50 MVAR shunt reactor at Mickleton 230 kV and relocate Mickleton #1 230 69 kV transformer		AEC (100%)
b2228	+150/-100 MVAR SVC at Cedar 230 kV		AEC (100%)
b2296	Replace the Mickleton 230kV breaker PCB U with 63kA breaker		AEC (100%)
b2297	Replace the Mickleton 230kV breaker PCB V with 63kA breaker		AEC (100%)
b2305	Rebuild and reconductor 1.2 miles of the US Silica to US Silica #1 69 kV circuit		AEC (100%)
b2306	Rebuild and reconductor 1.67 miles of the US Silica #1 to W1-089 TAP 69 kV circuit		AEC (100%)
b2351	Reconductor section A of Corson - Sea Isle - Swainton 69 kV line		AEC (100%)
b2353	Upgrade the overcurrent protective relaying at Middle T3 and T4 138/69 kV transformers		AEC (100%)
b2354	Install second 230/69 kV transformer and 230 kV circuit breaker at Churchtown substation		AEC (100%)

Atlantic City Electric Company (cont.)

required 1	Tansinission Enhancements An	nual Revenue Requirement	Responsible Customer(s)
b2354.1	Replace Churchtown 69kV breaker 'D'		AEC (100%)
b2476	Install new Dennis 230/69 kV transformer		AEC (100%)
b2477	Upgrade 138 kV and 69 kV breakers at Corson substation		AEC (100%)
b2478	Reconductor 2.74 miles of Sherman - Lincoln 138 kV line and associated substation upgrades		AEC (100%)
b2479	New Orchard - Cardiff 230 kV line (remove, rebuild and reconfigure existing 138 kV line) and associated substation upgrades		AEC (68.57%) / JCPL (31.43%)
b2480.1	New Upper Pittsgrove - Lewis 138 kV line and associated substation upgrades		AEC (100%)
b2480.2	Relocate Monroe to Deepwater Tap 138 kV to Landis 138 kV and associated substation upgrades		AEC (100%)
b2480.3	New Landis - Lewis 138 kV line and associated substation upgrades		AEC (100%)
b2481	New Cardiff - Lewis #2 138 kV line and associated substation upgrades		AEC (100%)
b2489	Install a 100 MVAR capacitor at BL England		AEC (100%)

Atlantic City Electric Company (cont.)

Required T	ransmission Enhancements Annu	al Revenue Requirement	Responsible Customer(s)
b2538	Replace the Mickleton 230kV 'MK' breaker with 63kA breaker		AEC (100%)
b2553	Replace Middle T3 138/69 kV transformer with 225 MVA nameplate		AEC (100%)
b2723.1	Replace the Mickleton 69 kV 'PCB A' breaker with 63kA breaker		AEC (100%)
b2723.2	Replace the Mickleton 69 kV 'PCB B' breaker with 63kA breaker		AEC (100%)
b2723.3	Replace the Mickleton 69 kV 'PCB C' breaker with 63kA breaker		AEC (100%)
b2723.4	Replace the Mickleton 69 kV 'PCB Q' breaker with 63kA breaker		AEC (100%)
b2839	Replace the Sickler 69 kV 'H' breaker with 63kA breaker		AEC (100%)
b2840	Replace the Sickler 69 kV 'M' breaker with 63kA breaker		AEC (100%)
b2841	Replace the Sickler 69 kV 'A' breaker with 63kA breaker		AEC (100%)
<u>b2945.1</u>	Rebuild the BL England – Middle Tap 138 kV line to 2000A on double circuited steel poles and new foundations		AEC (100%)
<u>b2945.2</u>	Reconductor BL England – Merion 138 kV (1.9 miles) <u>line</u>		AEC (100%)
<u>b2945.3</u>	Reconductor Merion – Corson 138 kV (8 miles) line		AEC (100%)

SCHEDULE 12 – APPENDIX A

(2) Baltimore Gas and Electric Company

Required 1	ransmission Enhancements	Annuai Revenue Requirement	Responsible Customer(s)
	Install a 115 kV tie		
	breaker at Wagner to		
b2219	create a separation from		BGE (100%)
	line 110535 and		
	transformer 110-2		
b2220	Install four 115 kV		BGE (100%)
02220	breakers at Chestnut Hill		BGE (100%)
	Install an SPS to trip		
b2221	approximately 19 MW		BGE (100%)
02221	load at Green St. and		BGE (100%)
	Concord		
	Install a 230/115kV		
	transformer at Raphael		
	Rd and construct		
	approximately 3 miles of		
b2307	115kV line from Raphael		BGE (100%)
	Rd. to Joppatowne.		
	Construct a 115kV three		
	breaker ring at		
	Joppatowne		
	Build approximately 3		
	miles of 115kV		
	underground line from		
	Bestgate tap to Waugh		
b2308	Chapel. Create two		BGE (100%)
	breaker bay at Waugh		
	Chapel to accommodate		
	the new underground		
	circuit		
	Build a new Camp Small		
b2396	115 kV station and install		BGE (100%)
	30 MVAR capacitor		

Baltimore Gas and Electric Company (cont.)

Required I	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
	Install a tie breaker at		
b2396.1	Mays Chapel 115 kV		BGE (100%)
	substation		
	Upgrade the Riverside		
	115kV substation strain		
	bus conductors on		
	circuits 115012 and		
b2567	115011 with double		BGE (100%)
	bundled 1272 ACSR to		
	achieve ratings of		
	491/577 MVA SN/SE on		
	both transformer leads		
	Reconductor Northwest –		
	Northwest #2 115kV		
b2568	110574 substation tie		BGE (100%)
02000	circuit with 2167 ACSR		202 (100%)
	to achieve ratings of		
	400/462 MVA SN/SE		
	Conastone 230 kV		AEP (6.46%) / APS
	substation tie-in work		(8.74%) / BGE (19.74%) /
	(install a new circuit		ComEd (2.16%) / Dayton
b2752.6	breaker at Conastone		(0.59%) / DEOK (1.02%) /
	230 kV and upgrade any		DL (0.01%) / Dominion
	required terminal		(39.95%) / EKPC (0.45%) /
	equipment to terminate		PEPCO (20.88%)
	the new circuit)		` '
			AEP (6.46%) / APS
	Reconductor/Rebuild the		(8.74%) / BGE (19.74%) /
1 0750 7	two Conastone –		ComEd (2.16%) / Dayton
b2752.7	Northwest 230 kV lines		(0.59%) / DEOK (1.02%) /
	and upgrade terminal		DL (0.01%) / Dominion
	equipment on both ends		(39.95%) / EKPC (0.45%) /
	Dente de C		PEPCO (20.88%)
	Replace the Conastone		
<u>b2752.8</u>	230 kV '2322 B5'		BGE (100%)
	breaker with a 63kA		
	<u>breaker</u>		

Baltimore Gas and Electric Company (cont.)

	1	<u> </u>	1 \ /
<u>b2752.9</u>	Replace the Conastone 230 kV '2322 B6' breaker with a 63kA breaker		BGE (100%)
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP
			(14.16%) / APS (5.73%) /
			ATSI (7.88%) / BGE
			(4.22%) / ComEd (13.31%)
			/ Dayton (2.11%) / DEOK
			(3.29%) / DL (1.75%) /
			DPL (2.50%) / Dominion
	Upgrade substation equipment at Conastone 500 kV to increase		(12.86%) / EKPC (1.87%) /
			JCPL (3.74%) / ME
			(1.90%) / NEPTUNE*
			(0.44%) / PECO (5.34%) /
			PENELEC (1.89%) /
			PEPCO (3.99%) / PPL
			(4.84%) / PSEG (6.26%) /
b2766.1	facility rating to 2826		RE (0.26%)
	MVA normal and 3525		KE (0.20%)
	MVA emergency		
			DFAX Allocation:
			AEC (0.05%) / APS
			(11.16%) / BGE (22.34%) /
			Dayton (2.18%) / DEOK
			(4.19%) / DPL (0.20%) /
			ECP** (1.03%) / EKPC
			(1.94%) / JCPL (10.82%) /
			NEPTUNE* (1.14%)/
			HTP*** (1.10%) /
			POSEIDON**** (0.63%) /
			PENELEC (0.06%) /
			PEPECO (18.97%) / PSEG
			(23.26%) / RECO (0.93%)

^{*}Neptune Regional Transmission System, LLC

^{**} East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

^{****}Poseidon Transmission 1, LLC

SCHEDULE 12 – APPENDIX A

(3) Delmarva Power & Light Company

required 11	ansimission Emancements An	inuai Revenue Requirement	responsible Customer(s)
b2288	Build a new 138 kV line from Piney Grove – Wattsville		DPL (100%)
b2395	Reconductor the Harmony - Chapel St 138 kV circuit		DPL (100%)
b2569	Replace Terminal equipment at Silverside 69 kV substation		DPL (100%)
b2633.7	Implement high speed relaying utilizing OPGW on Red Lion – Hope Creek 500 kV line		Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
b2633.10	Interconnect the new Silver Run 230 kV substation with existing Red Lion – Cartanza and Red Lion – Cedar Creek 230 kV lines		AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

Delmarva Power & Light Company (cont.)

rtequired Tit	distinssion Emidicements 7 mil	iaar revenue requirement	responsible editorier(s)
b2695	Rebuild Worcester –		
	Ocean Pine 69 kV ckt. 1 to		DPL (100%)
	1400A capability summer		, , ,
,	emergency		
	Convert existing Preston		
<u>b2946</u>	69 kV substation to DPL's		DPL (100%)
02940	current design standard of		<u>DFL (100%)</u>
	a 3-breaker ring bus		
	Upgrade terminal		
1-2047 1	equipment at DPL's		DDI (1000/)
<u>b2947.1</u>	Naamans substation		<u>DPL (100%)</u>
	(Darley - Naamans 69 kV)		
	Reconductor 0.11 mile		
<u>b2947.2</u>	section of Darley -		<u>DPL (100%)</u>
	Naamans 69 kV circuit		
	<u>Upgrade terminal</u>		
<u>b2948</u>	equipment at DPL's		
	Silverside Road substation		<u>DPL (100%)</u>
	(Dupont Edge Moor –		
	Silver R. 69 kV)		

SCHEDULE 12 – APPENDIX A

(5) Mid-Atlantic Interstate Transmission, LLC for the Metropolitan Edison Company Zone

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / Loop the 2026 (TMI – EKPC (1.87%) / JCPL (3.74%) / b2006.1.1 Hosensack 500 kV) line ME (1.90%) / NEPTUNE* in to the Lauschtown (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PPL (100%) Upgrade relay at South b2006.2.1 Reading on the 1072 230 ME (100%) V line Replace the South Reading 69 kV '81342' b2006.4 ME (100%) breaker with 40kA breaker Replace the South Reading 69 kV '82842' b2006.5 ME (100%) breaker with 40kA breaker APS (8.30%) / BGE (14.70%) / Install 2nd Hunterstown DEOK (0.48%) / Dominion b2452 (36.92%) / ME (23.85%) / 230/115 kV transformer

PEPCO (15.75%)

Mid-Atlantic Interstate Transmission, LLC for the Metropolitan Edison Company Zone (cont.)

Annual Revenue Requirement Responsible Customer(s)

Required Transmission Enhancements

CTs.

Germantown Substation: Replace 138/115 kV

transformer with a 135/180/224 MVA bank.

Replace Lincoln 115 kV

breaker, install new 138

kV breaker, upgrade bus

conductor and

adjust/replace CTs.

b2688.2

APS (8.30%) / BGE (14.70%) Reconductor / DEOK (0.48%) / Dominion b2452.1 Hunterstown - Oxford (36.92%) / ME (23.85%) / 115 kV line PEPCO (15.75%) Replace the Hunterstown 115 kV breaker '96192' b2452.3 ME (100%) with 40 kA Install a 36.6 MVAR 115 b2588 ME (100%) kV capacitor at North Bangor substation Convert Middletown Junction 230 kV b2637 substation to nine bay ME (100%) double breaker configuration. Install a 28.8 MVAR b2644 115 kV capacitor at the ME (100%) Mountain substation AEP (12.91%) / APS (19.04%)/ ATSI (1.24%)/ Lincoln Substation: ComEd (0.35%) / Dayton Upgrade the bus b2688.1 (1.45%) / DEOK (2.30%) / DL conductor and replace (1.11%)/ Dominion (44.85%)/

EKPC (0.78%)/ PEPCO (15.85%) / RECO (0.12%)

AEP (12.91%) / APS (19.04%) / ATSI (1.24%) /

ComEd (0.35%) / Dayton

(1.45%) / DEOK (2.30%) / DL

(1.11%)/ Dominion (44.85%) /

EKPC (0.78%)/ PEPCO

(15.85%) / RECO (0.12%)

Mid-Atlantic Interstate Transmission, LLC for the Metropolitan Edison Company Zone (cont.)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Upgrade terminal AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd equipment at Hunterstown 500 kV on (2.16%) / Dayton (0.59%) / b2743.4 the Conemaugh -DEOK (1.02%) / DL (0.01%) / Hunterstown 500 kV Dominion (39.95%) / EKPC circuit (0.45%) / PEPCO (20.88%) Upgrade terminal AEP (6.46%) / APS (8.74%) / equipment and required BGE (19.74%) / ComEd relay communication at (2.16%) / Dayton (0.59%) / b2752.4 TMI 500 kV: on the DEOK (1.02%) / DL (0.01%) / Beach Bottom - TMI Dominion (39.95%) / EKPC 500 kV circuit (0.45%) / PEPCO (20.88%) Replace relay at West Boyertown 69 kV station b2749 on the West Boyertown – ME (100%) North Boyertown 69 kV circuit Upgrade bus conductor at Gardners 115 kv substation; Upgrade bus b2765 ME (100%) conductor and adjust CT ratios at Carlisle Pike 115 kV Upgrade limiting 115 kV switches on the 115 kV side of the 230/115 kV b2950 ME (100%) Northwood substation and adjust setting on limiting ZR relay

SCHEDULE 12 – APPENDIX A

(7) Mid-Atlantic Interstate Transmission, LLC for the Pennsylvania Electric Company Zone

Required T	Transmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2212	Shawville Substation: Relocate 230 kV and 115 kV controls from the generating station building		PENELEC (100%)
b2293	to new control building Replace the Erie South 115 kV breaker 'Buffalo Rd' with 40kA breaker		PENELEC (100%)
b2294	Replace the Johnstown 115 kV breaker 'Bon Aire' with 40kA breaker		PENELEC (100%)
b2302	Replace the Erie South 115 kV breaker 'French #2' with 40kA breaker		PENELEC (100%)
b2304	Replace the substation conductor and switch at South Troy 115 kV substation		PENELEC (100%)
b2371	Install 75 MVAR capacitor at the Erie East 230 kV substation		PENELEC (100%)
b2441	Install +250/-100 MVAR SVC at the Erie South 230 kV station		PENELEC (100%)
b2442	Install three 230 kV breakers on the 230 kV side of the Lewistown #1, #2 and #3 transformers		PENELEC (100%)
b2450	Construct a new 115 kV line from Central City West to Bedford North		PENELEC (100%)
b2463	Rebuild and reconductor 115 kV line from East Towanda to S. Troy and upgrade terminal equipment at East Towanda, Tennessee Gas and South Troy		PENELEC (100%)

Required T	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
	Construct Warren 230 kV		
b2494	ring bus and install a		DENELEC (100%)
02494	second Warren 230/115		PENELEC (100%)
	kV transformer		
	Reconductor the North		
	Meshoppen – Oxbow-		
b2552.1	Lackawanna 230 kV		PENELEC (100%)
02332.1	circuit and upgrade		TENELLE (100%)
	terminal equipment		
	(MAIT portion)		
	Replace the Warren 115		
b2573	kV 'B12' breaker with a		PENELEC (100%)
	40kA breaker		
	Reconfigure Pierce Brook		
	345 kV station to a ring		
b2587	bus and install a 125		PENELEC (100%)
	MVAR shunt reactor at		
	the station		
	Replace relays at East		
b2621	Towanda and East Sayre		PENELEC (100%)
02021	115 kV substations		121,222 (100,0)
	(158/191 MVA SN/SE)		
	Replace wave trap, bus		
	conductor and relay at		
b2677	Hilltop 115 kV substation.		PENELEC (100%)
	Replace relays at Prospect		
	and Cooper substations		
	Convert the East Towarda		
b2678	115 kV substation to		PENELEC (100%)
	breaker and half		,
	configuration		
1.0670	Install a 115 kV Venango		DENEL EC (1000/)
b2679	Jct. line breaker at Edinboro South		PENELEC (100%)
1.0000	Install a 115 kV breaker		DENELEC (1000)
b2680	on Hooversville #1 115/23		PENELEC (100%)
	kV transformer		
1.0.01	Install a 115 kV breaker		DENEL EC (1999)
b2681	on the Eclipse #2 115/34.5		PENELEC (100%)
	kV transformer		

Required 1	ransmission Ennancements Ar	inual Revenue Requirement	Responsible Customer(s)
b2682	Install two 21.6 MVAR capacitors at the Shade Gap 115 kV substation		PENELEC (100%)
b2683	Install a 36 MVAR 115 kV capacitor and associated equipment at Morgan Street substation		PENELEC (100%)
b2684	Install a 36 MVAR 115 kV capacitor at Central City West substation		PENELEC (100%)
b2685	Install a second 115 kV 3000A bus tie breaker at Hooversville substation		PENELEC (100%)
b2735	Replace the Warren 115 kV 'NO. 2 XFMR' breaker with 40kA breaker		PENELEC (100%)
b2736	Replace the Warren 115 kV 'Warren #1' breaker with 40kA breaker		PENELEC (100%)
b2737	Replace the Warren 115 kV 'A TX #1' breaker with 40kA breaker		PENELEC (100%)
b2738	Replace the Warren 115 kV 'A TX #2' breaker with 40kA breaker		PENELEC (100%)
b2739	Replace the Warren 115 kV 'Warren #2' breaker with 40kA breaker		PENELEC (100%)
b2740	Revise the reclosing of the Hooversville 115 kV 'Ralphton' breaker		PENELEC (100%)
b2741	Revise the reclosing of the Hooversville 115 kV 'Statler Hill' breaker		PENELEC (100%)

required 1	ransmission Emancements Ar	inuai Revenue Requirement	Responsible Customer(s)
b2743.2	Tie in new Rice substation to Conemaugh – Hunterstown 500 kV		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)
b2743.3	Upgrade terminal equipment at Conemaugh 500 kV on the Conemaugh – Hunterstown 500 kV circuit		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)
b2748	Install two 28 MVAR capacitors at Tiffany 115 kV substation		PENELEC (100%)
b2767	Construct a new 345 kV breaker string with three (3) 345 kV breakers at Homer City and move the North autotransformer connection to this new breaker string		PENELEC (100%)
b2803	Reconductor 3.7 miles of the Bethlehem – Leretto 46 kV circuit and replace terminal equipment at Summit 46 kV		PENELEC (100%)
b2804	Install a new relay and replace 4/0 CU bus conductor at Huntingdon 46 kV station, on the Huntingdon – C tap 46 kV circuit		PENELEC (100%)
b2805	Install a new relay and replace 4/0 CU & 250 CU substation conductor at Hollidaysburg 46 kV station, on the Hollidaysburg – HCR Tap 46 kV circuit		PENELEC (100%)

Required 1	ransmission Enhancements Ai	nual Revenue Requirement	Responsible Customer(s)
	Install a new relay and		
b2806	replace meter at the		
	Raystown 46 kV		PENELEC (100%)
02000	substation, on the		I LINELLE (10070)
	Raystown – Smithfield 46		
	kV circuit		
	Replace the CHPV and		
	CRS relay, and adjust the		
	IAC overcurrent relay trip		
b2807	setting; or replace the relay		PENELEC (100%)
	at Eldorado 46 kV		
	substation, on the Eldorado		
	 Gallitzin 46 kV circuit 		
	Adjust the JBC overcurrent		
	relay trip setting at		
	Raystown 46 kV, and		
	replace relay and 4/0 CU		
b2808	bus conductor at		PENELEC (100%)
	Huntingdon 46 kV		
	substations, on the		
	Raystown – Huntingdon 46		
	kV circuit		
	Replace Seward 115 kV		
b2865	breaker "Jackson Road"		PENELEC (100%)
	with 63kA breaker		
	Replace Seward 115 kV		
b2866	breaker "Conemaugh N."		PENELEC (100%)
	with 63kA breaker		
	Replace Seward 115 kV		
b2867	breaker "Conemaugh S."		PENELEC (100%)
02007	with 63kA breaker		, , ,
	Replace Seward 115 kV		
b2868	breaker "No.8 Xfmr" with		PENELEC (100%)
	63kA breaker		
	Install two 345 kV 80		
b2944	MVAR shunt reactors at		PENELEC (100%)
	Mainesburg station		1 21,2220 (10070)
	1.1000000 S Station		

rtequired I	Taristrussion Linaneements An	maar Revenue Requirement	responsible editionicity
<u>b2951</u>	Seward, Blairsville East, Shelocta work		<u>PENELEC (100%)</u>
<u>b2951.1</u>	Upgrade Florence 115 kV line terminal equipment at Seward SS		<u>PENELEC (100%)</u>
<u>b2951.2</u>	Replace Blairsville East / Seward 115 kV line tuner, coax, line relaying and carrier set at Shelocta SS		<u>PENELEC (100%)</u>
<u>b2951.3</u>	Replace Seward / Shelocta 115 kV line CVT, tuner, coax, and line relaying at Blairsville East SS		PENELEC (100%)
<u>b2952</u>	Replace the North Meshoppen #3 230/115 kV transformer eliminating the old reactor and installing two breakers to complete a 230 kV ring bus at North Meshoppen		PENELEC (100%)
<u>b2953</u>	Replace the Keystone 500 kV breaker "NO. 14 Cabot" with 50kA breaker		PENELEC (100%)
<u>b2954</u>	Replace the Keystone 500 kV breaker "NO. 16 Cabot" with 50kA breaker		PENELEC (100%)

SCHEDULE 12 – APPENDIX A

(12) Public Service Electric and Gas Company

Required Tra	ansmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2218	Rebuild 4 miles of overhead line from Edison - Meadow Rd - Metuchen (Q 1317)		HTP (36.49%) / ECP** (63.51%)
b2239	50 MVAR reactor at Saddlebrook 230 kV		PSEG (100%)
b2240	50 MVAR reactor at Athenia 230 kV		PSEG (100%)
b2241	50 MVAR reactor at Bergen 230 kV		PSEG (100%)
b2242	50 MVAR reactor at Hudson 230 kV		PSEG (100%)
b2243	Two 50 MVAR reactors at Stanley Terrace 230 kV		PSEG (100%)
b2244	50 MVAR reactor at West Orange 230 kV		PSEG (100%)
b2245	50 MVAR reactor at Aldene 230 kV		PSEG (100%)
b2246	150 MVAR reactor at Camden 230 kV		PSEG (100%)
b2247	150 MVAR reactor at Gloucester 230 kV		PSEG (100%)
b2248	50 MVAR reactor at Clarksville 230 kV		PSEG (100%)
b2249	50 MVAR reactor at Hinchmans 230 kV		PSEG (100%)
b2250	50 MVAR reactor at Beaverbrook 230 kV		PSEG (100%)
b2251	50 MVAR reactor at Cox's Corner 230 kV		PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

The Annual Revenue Requirement for all Public Service Electric and Gas Company Projects (Required Transmission Enhancements) in this Section 12 shall be as specified in Attachment 7 of Attachment H-10A and under the procedures detailed in Attachment H-10B.

^{**}East Coast Power, L.L.C.

Public Service Electric and Gas Company (cont.)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Eliminate the Sewaren 138 kV bus by installing a new b2276 PSEG (100%) 230 kV bay at Sewaren 230 kV Convert the two 138 kV circuits from Sewaren -Metuchen to 230 kV b2276.1 PSEG (100%) circuits including Lafayette and Woodbridge substation Reconfigure the Metuchen 230 kV station to b2276.2 PSEG (100%) accommodate the two converted circuits Replace disconnect switches at Kilmer, Lake Nilson and Greenbrook b2290 PSEG (100%) 230 kV substations on the Raritian River - Middlesex (I-1023) circuit Replace circuit switcher at Lake Nelson 230 kV b2291 substation on the Raritian PSEG (100%) River - Middlesex (W-1037) circuit Replace the Salem 500 kV b2295 breaker 10X with 63kA PSEG (100%) breaker Install all 69kV lines to interconnect Plainfield, Greenbrook, and b2421 PSEG (100%) Bridgewater stations and establish the 69kV network Install two 18MVAR capacitors at Plainfield b2421.1 PSEG (100%) and S. Second St substation

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

Public Service Electric and Gas Company (cont.)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Install a second four (4) breaker 69kV ring bus at PSEG (100%) b2421.2 **Bridgewater Switching** Station **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL Convert the Bergen – (2.50%) / Dominion (12.86%) / Marion 138 kV path to EKPC (1.87%) / JCPL (3.74%) / b2436.10 double circuit 345 kV and ME (1.90%) / NEPTUNE* associated substation (0.44%) / PECO (5.34%) / upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (100%) **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK Convert the Marion -(3.29%) / DL (1.75%) / DPL Bayonne "L" 138 kV (2.50%) / Dominion (12.86%) / b2436.21 circuit to 345 kV and any EKPC (1.87%) / JCPL (3.74%) / associated substation ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

		 1
b2436.22	Convert the Marion - Bayonne "C" 138 kV circuit to 345 kV and any associated substation upgrades	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%)
b2436.33	Construct a new Bayway – Bayonne 345 kV circuit and any associated substation upgrades	PSEG (100%)
b2436.34	Construct a new North Ave – Bayonne 345 kV circuit and any associated substation upgrades	PSEG (100%)

^{*}Neptune Regional Transmission System, LLC **East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Construct a new North Ave - Airport 345 kV b2436.50 PSEG (100%) circuit and any associated substation upgrades Relocate the underground portion of North Ave -Linden "T" 138 kV circuit b2436.60 to Bayway, convert it to *PSEG* (96.13%) / *RE* (3.87%) 345 kV, and any associated substation upgrades Construct a new Airport -Bayway 345 kV circuit b2436.70 PSEG (100%) and any associated substation upgrades **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK Relocate the overhead (3.29%) / DL (1.75%) / DPL portion of Linden - North (2.50%) / Dominion (12.86%) / Ave "T" 138 kV circuit to b2436.81 EKPC (1.87%) / JCPL (3.74%) / Bayway, convert it to 345 ME (1.90%) / NEPTUNE* kV, and any associated (0.44%) / PECO (5.34%) / substation upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (96.13%) / RE (3.87%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL Convert the Bayway -Linden "Z" 138 kV circuit (2.50%) / Dominion (12.86%) / b2436.83 to 345 kV and any EKPC (1.87%) / JCPL (3.74%) / associated substation ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (96.13%) / RE (3.87%) **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL Convert the Bayway -(2.50%) / Dominion (12.86%) / Linden "W" 138 kV EKPC (1.87%) / JCPL (3.74%) / b2436.84 circuit to 345 kV and any ME (1.90%) / NEPTUNE* associated substation (0.44%) / PECO (5.34%) / upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (96.13%) / RE (3.87%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required Tra	ansmission Enhancements A	Annual Revenue Requirement Responsible Customer(s)
b2436.85	Convert the Bayway – Linden "M" 138 kV circuit to 345 kV and any associated substation upgrades	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%)
b2436.90	Relocate Farragut - Hudson "B" and "C" 345 kV circuits to Marion 345 kV and any associated substation upgrades	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: PSEG (96.13%) / RE (3.87%)
b2436.91	Relocate the Hudson 2 generation to inject into the 345 kV at Marion and any associated upgrades	PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

		 (~)
b2437.10	New Bergen 345/230 kV transformer and any associated substation upgrades	PSEG (96.13%) / RE (3.87%)
b2437.11	New Bergen 345/138 kV transformer #1 and any associated substation upgrades	PSEG (100%)
b2437.20	New Bayway 345/138 kV transformer #1 and any associated substation upgrades	PSEG (96.13%) / RE (3.87%)
b2437.21	New Bayway 345/138 kV transformer #2 and any associated substation upgrades	PSEG (96.13%) / RE (3.87%)
b2437.30	New Linden 345/230 kV transformer and any associated substation upgrades	PSEG (96.13%) / RE (3.87%)
b2437.33	New Bayonne 345/69 kV transformer and any associated substation upgrades	PSEG (100%)
b2438	Install two reactors at Tosco 230 kV	PSEG (100.00%)
b2439	Replace the Tosco 138kV breaker 'CB1/2 (CBT)' with 63kA	PSEG (100.00%)
b2474	Rebuild Athenia 138 kV to 80kA	PSEG (100%)
b2589	Install a 100 MVAR 230 kV shunt reactor at Mercer station	PSEG (100%)
b2590	Install two 75 MVAR 230 kV capacitors at Sewaren station	PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required Tra	ansmission Enhancements Anr	nual Revenue Requirement Responsible Customer(s)
b2633.3	Install an SVC at New Freedom 500 kV substation	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
b2633.4	Add a new 500 kV bay at Hope Creek (Expansion of Hope Creek substation)	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)

Load-Ratio Share Allocation	Required 11	ansmission Ennancements Ann	ual Revenue Requirement Responsible Customer(s)
AEC (1.66%) / AEP (14.16% APS (5.73%) / ATSI (7.88%) BGE (4.22%) / ComEd (13.31% BGE (4.22%) / Deok (3.29% Dayton (2.11%) / DEOK (3.29% DEOk) / Deok (3.29% DEOk	b2633.5	autotransformer at Hope Creek and a new Hope	AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
DFAX Allocation: AEC (0.01%) / DPL (99.98%) JCPL (0.01%)	b2633.8	relaying utilizing OPGW on Salem – Orchard 500 kV, Hope Creek – New Freedom 500 kV, New Freedom - Salem 500 kV, Hope Creek – Salem 500 kV, and New Freedom –	DFAX Allocation: AEC (0.01%) / DPL (99.98%) /

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

		dai Revenue Requirement - Responsible Customer(s)
b2633.91	Implement changes to the tap settings for the two Salem units' step up transformers	AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
b2633.92	Implement changes to the tap settings for the Hope Creek unit's step up transformers	AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
ь2702	Install a 350 MVAR reactor at Roseland 500 kV	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%)
b2703	Install a 100 MVAR reactor at Bergen 230 kV	PSEG (100%) PSEG (100%)
b2704	Install a 150 MVAR reactor at Essex 230 kV	PSEG (100%)
b2705	Install a 200 MVAR reactor (variable) at Bergen 345 kV	PSEG (100%)
b2706	Install a 200 MVAR reactor (variable) at Bayway 345 kV	PSEG (100%)
b2707	Install a 100 MVAR reactor at Bayonne 345 kV	PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required 118	ansmission Enhancements Ann	ual Revenue Requiremen	t Responsible Customer(s)
b2712	Replace the Bergen 138 kV '40P'breaker with 80kA breaker		PSEG (100%)
b2713	Replace the Bergen 138 kV '90P' breaker with 80kA breaker		PSEG (100%)
b2722	Reconductor the 1 mile Bergen – Bergen GT 138 kV circuit (B-1302)		PSEG (100%)
b2755	Build a third 345 kV source into Newark Airport		PSEG (100%)
b2810.1	Install second 230/69 kV transformer at Cedar Grove		PSEG (100%)
b2810.2	Build a new 69 kV circuit from Cedar Grove to Great Notch		PSEG (100%)
b2811	Build 69 kV circuit from Locust Street to Delair		PSEG (100%)
b2812	Construct River Road to Tonnelle Avenue 69kV Circuit		PSEG (100%)
b2825.1	Install 2X50 MVAR shunt reactors at Kearny 230 kV substation		PSEG (100%)
b2825.2	Increase the size of the Hudson 230 kV, 2X50 MVAR shunt reactors to 2X100 MVAR		PSEG (100%)
b2825.3	Install 2X100 MVAR shunt reactors at Bayway 345 kV substation		PSEG (100%)
b2825.4	Install 2X100 MVAR shunt reactors at Linden 345 kV substation		PSEG (100%)
b2835	Convert the R-1318 and Q1317 (Edison – Metuchen) 138 kV circuits to one 230 kV circuit		PSEG (100%)

Required 118	ansmission Enhancements Ai	nnual Revenue Requiremer	it Responsible Customer(s)
1.2026	Convert the N-1340 and T 1372/D-1330 (Brunswick		PGFG (1000)
b2836	Trenton) 138 kV circuits to		PSEG (100%)
	230 kV circuits		
	Convert the F-1358/Z1326	5	
	and K1363/Y-1325	,	
b2837	(Trenton – Burlington) 13	\mathbf{R}	PSEG (100%)
02057	kV circuits to 230 kV		1828 (10070)
	circuits		
	Build new 138/26 kV		
	Newark GIS station in a		
	building (layout #1A)		
b2870	located adjacent to the		PSEG (100%)
	existing Newark Switch an	d	
	demolish the existing		
	Newark Switch		
	Third Source for		
<i>b</i> 2933	Springfield Rd. and Stanle	y	PSEG (100%)
	Terrace Stations		
100001	Construct a 230/69 kV		Dana (1000()
b2933.1	station at Springfield	Field PSEG (1	PSEG (100%)
	Construct a 230/69 kV		
<i>b</i> 2933.2	station at Stanley Terrace		PSEG (100%)
	Construct a 69 kV network		
	between Front Street,		
1 0/911 1	Springfield and Stanley		PSEG (100%)
	Terrace		
	Build a new 69 kV line		
<i>b</i> 2934	between Hasbrouck Heigh	t _S	PSEG (100%)
	and Carlstadt		,
	Third Supply for		
b2935	Runnemede 69 kV and		PSEG (100%)
	Woodbury 69 kV		•
	Build a new 230/69 kV		
b2935.1	switching substation at		
	Hilltop utilizing the PSE&	G	PSEG (100%)
	property and the K-2237		
	230 kV line		
	Build a new line between		
<i>b</i> 2935.2	Hilltop and Woodbury 69		PSEG (100%)
	kV providing the 3rd suppl	y	

b2935.3	Convert Runnemede's straight bus to a ring bus and construct a 69 kV line from Hilltop to Runnemede 69 kV	PSEG (100%)
<u>b2955</u>	Wreck and rebuild the VFT - Warinanco - Aldene 230 kV circuit with paired conductor	JCPL (93.78%) / NEPTUNE* (6.22%)
<u>b2956</u>	Replace existing cable on Cedar Grove - Jackson Rd. with 5000kcmil XLPE cable	JCPL (0.05%) / NEPTUNE* (0.01%) / PSEG (96.07%) / RE (3.87%)

SCHEDULE 12 – APPENDIX A

(14) Monongahela Power Company, The Potomac Edison Company, and West Penn Power Company, all doing business as Allegheny Power

Required Transmission Enhancements Responsible Customer(s) Annual Revenue Requirement Reconductor 0.33 miles of the Parkersburg - Belpre line and upgrade b2117 APS (100%) Parkersburg terminal equipment Add 44 MVAR Cap at b2118 APS (100%) New Martinsville Six-Wire Lake Lynn b2120 APS (100%) Lardin 138 kV circuits Replace Weirton 138 kV breaker "Wylie Ridge 210" b2142 APS (100%) with 63 kA breaker Replace Weirton 138 kV b2143 breaker "Wylie Ridge 216" APS (100%) with 63 kA breaker Replace relays at Mitchell b2174.8 APS (100%) substation Replace primary relay at b2174.9 APS (100%) Piney Fork substation Perform relay setting b2174.10 changes at Bethel Park APS (100%) substation Armstrong Substation: Relocate 138 kV controls b2213 from the generating station APS (100%) building to new control building Albright Substation: Install a new control building in the switchyard and relocate b2214 controls and SCADA APS (100%) equipment from the generating station building the new control center Rivesville Switching Station: Relocate controls and SCADA equipment b2215 APS (100%) from the generating station building to new control building

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Willow Island: Install a new 138 kV cross bus at Belmont Substation and reconnect and reconfigure b2216 APS (100%) the 138 kV lines to facilitate removal of the equipment at Willow Island switching station 130 MVAR reactor at b2235 APS (100%) Monocacy 230 kV Install a 32.4 MVAR b2260 APS (100%) capacitor at Bartonville Install a 33 MVAR b2261 APS (100%) capacitor at Damascus Replace 1000 Cu substation conductor and b2267 APS (100%) 1200 amp wave trap at Marlowe Reconductor 6.8 miles of 138kV 336 ACSR with b2268 APS (100%) 336 ACSS from Double Toll Gate to Riverton Reconductor from Collins b2299 Ferry - West Run 138 kV APS (100%) with 556 ACSS Reconductor from Lake b2300 APS (100%) Lynn - West Run 138 kV Install 39.6 MVAR Capacitor at Shaffers b2341 APS (100%) Corner 138 kV Substation Construct a new 138 kV switching station (Shuman Hill substation), which is b2342 APS (100%) next the Mobley 138 kV substation and install a 31.7 MVAR capacitor Install a 31.7 MVAR b2343 capacitor at West Union APS (100%) 138 kV substation

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Install a 250 MVAR SVC b2362 APS (100%) at Squab Hollow 230 kV Install a 230 kV breaker at b2362.1 Squab Hollow 230 kV APS (100%) substation Convert the Shingletown b2363 230 kV bus into a 6 APS (100%) breaker ring bus Install a new 230/138 kV transformer at Squab Hollow 230 kV substation. Loop the Forest - Elko 230 b2364 APS (100%) kV line into Squab Hollow. Loop the Brookville - Elko 138 kV line into Squab Hollow Install a 44 MVAR 138 kV b2412 capacitor at the Hempfield APS (100%) 138 kV substation Install breaker and a half 138 kV substation (Waldo Run) with 4 breakers to accommodate service to b2433.1 MarkWest Sherwood APS (100%) Facility including metering which is cut into Glen Falls Lamberton 138 kV line Install a 70 MVAR SVC at the new WaldoRun 138 kV b2433.2 APS (100%) substation Install two 31.7 MVAR capacitors at the new b2433.3 APS (100%) WaldoRun 138 kV substation Replace the Weirton 138 kV breaker 'WYLIE b2424 APS (100%) RID210' with 63 kA breakers Replace the Weirton 138 kV breaker 'WYLIE b2425 APS (100%) RID216' with 63 kA breakers

Required Tra	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2426	Replace the Oak Grove 138 kV breaker 'OG1' wit	h	APS (100%)
b2427	63 kA breakers Replace the Oak Grove 138 kV breaker 'OG2' wit 63 kA breakers	h	APS (100%)
b2428	Replace the Oak Grove 138 kV breaker 'OG3' wit 63 kA breakers	h	APS (100%)
b2429	Replace the Oak Grove 138 kV breaker 'OG4' wit 63 kA breakers	h	APS (100%)
b2430	Replace the Oak Grove 138 kV breaker 'OG5' wit 63 kA breakers	h	APS (100%)
b2431	Replace the Oak Grove 138 kV breaker 'OG6' wit 63 kA breakers	h	APS (100%)
b2432	Replace the Ridgeley 138 kV breaker 'RC1' with a 4 kA rated breaker		APS (100%)
b2440	Replace the Cabot 138kV breaker 'C9-KISKI VLY with 63kA		APS (100%)
b2472	Replace the Ringgold 133 kV breaker 'RCM1' with 40kA breakers		APS (100%)
b2473	Replace the Ringgold 133 kV breaker '#4 XMFR' with 40kA breakers	8	APS (100%)
b2475	Construct a new line between Oak Mound 138 kV substation and Waldo Run 138 kV substation		APS (100%)
b2545.1	Construct a new 138 kV substation (Shuman Hill substation) connected to the Fairview –Willow Island (84) 138kV line		APS (100%)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Install a ring bus station with five active positions b2545.2 and two 52.8 MVAR APS (100%) capacitors with 0.941 mH reactors Install a +90/-30 MVAR b2545.3 SVC protected by a 138 APS (100%) kV breaker Remove the 31.7 MVAR b2545.4 capacitor bank at Mobley APS (100%) 138 kV Install a 51.8 MVAR (rated) 138 kV capacitor at b2546 APS (100%) Nyswaner 138 kV substation Construct a new 138 kV b2547.1 six breaker ring bus APS (100%) Hillman substation Loop Smith-Imperial 138 kV line into the new APS (100%) b2547.2 Hillman substation Install +125/-75 MVAR b2547.3 APS (100%) SVC at Hillman substation Install two 31.7 MVAR b2547.4 APS (100%) 138 kV capacitors Eliminate clearance de-rate on Wylie Ridge – Smith 138 kV line and upgrade b2548 terminals at Smith 138 kV, APS (100%) new line ratings 294 MVA (Rate A)/350 MVA (Rate B) Relocate All Dam 6 138 b2612.1 kV line and the 138 kV APS (100%) line to AE units 1&2 Install 138 kV, 3000A bustie breaker in the open bustie position next to the b2612.2 APS (100%) Shaffers corner 138 kV line

Required Tra	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2612.3	Install a 6-pole manual switch, foundation, control cable, and all associated facilities		APS (100%)
b2666	Yukon 138 kV Breaker Replacement		APS (100%)
b2666.1	Replace Yukon 138 kV breaker "Y-11(CHARL1)" with an 80 kA breaker		APS (100%)
b2666.2	Replace Yukon 138 kV breaker "Y-13(BETHEL)" with an 80 kA breaker		APS (100%)
b2666.3	Replace Yukon 138 kV breaker "Y-18(CHARL2)" with an 80 kA breaker		APS (100%)
b2666.4	Replace Yukon 138 kV breaker "Y-19(CHARL2)" with an 80 kA breaker		APS (100%)
b2666.5	Replace Yukon 138 kV breaker "Y-4(4B-2BUS)" with an 80 kA breaker		APS (100%)
b2666.6	Replace Yukon 138 kV breaker "Y-5(LAYTON)" with an 80 kA breaker		APS (100%)
b2666.7	Replace Yukon 138 kV breaker "Y-8(HUNTING)" with an 80 kA breaker		APS (100%)
b2666.8	Replace Yukon 138 kV breaker "Y-9(SPRINGD)" with an 80 kA breaker		APS (100%)
b2666.9	Replace Yukon 138 kV breaker "Y-10(CHRL-SP)" with an 80 kA breaker		APS (100%)
b2666.10	Replace Yukon 138 kV breaker "Y-12(1-1BUS)" with an 80 kA breaker		APS (100%)
b2666.11	Replace Yukon 138 kV breaker "Y-14(4-1BUS)" with an 80 kA breaker		APS (100%)

Required Trai	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2666.12	Replace Yukon 138 kV breaker "Y-2(1B- BETHE)" with an 80 kA breaker		APS (100%)
b2666.13	Replace Yukon 138 kV breaker "Y-21(SHEPJ)" with an 80 kA breaker		APS (100%)
b2666.14	Replace Yukon 138 kV breaker "Y-22(SHEPHJT)" with an 80 kA breaker		APS (100%)
b2672	Change CT Ratio at Seneca Caverns from 120/1 to 160/1 and adjust relay settings accordingly		APS (100%)
b2688.3	Carroll Substation: Replace the Germantown 138 kV wave trap, upgrade the bus conductor and adjust CT ratios		AEP (12.91%) / APS (19.04%) / ATSI (1.24%) / ComEd (0.35%) / Dayton (1.45%) / DEOK (2.30%) / DL (1.11%) / Dominion (44.85%) / EKPC (0.78%) / PEPCO (15.85%) / RECO (0.12%)
b2689.3	Upgrade terminal equipment at structure 27A		APS (100%)
b2696	Upgrade 138 kV substation equipment at Butler, Shanor Manor and Krendale substations. New rating of line will be 353 MVA summer normal/422 MVA emergency		APS (100%)
b2700	Remove existing Black Oak SPS		APS (100%)
b2743.6	Reconfigure the Ringgold 230 kV substation to double bus double breaker scheme		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)

Required Tran	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2743.6.1	Replace the two Ringgold 230/138 kV transformers		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)
b2743.7	Rebuild/Reconductor the Ringgold – Catoctin 138 kV circuit and upgrade terminal equipment on both ends		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)
b2763	Replace the breaker risers and wave trap at Bredinville 138 kV substation on the Cabrey Junction 138 kV terminal		APS (100%)
b2764	Upgrade Fairview 138 kV breaker risers and disconnect leads; Replace 500 CU breaker risers and 556 ACSR disconnect leads with 795 ACSR		APS (100%)
<u>b2964.1</u>	Replace terminal equipment at Pruntytown and Glen Falls 138 kV station		APS (100%)
<u>b2964.2</u>	Reconductor approximately 8.3 miles of the McAlpin - White Hall Junction 138 kV circuit		APS (100%)

Required Tra	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
12065	Reconductor the Charleroi - Allenport 138 kV line		DV (4000)
<u>b2965</u>	with 954 ACSR conductor. Replace breaker risers at Charleroi and Allenport		<u>DL (100%)</u>
<u>b2966</u>	Reconductor the Yukon - Smithton - Shepler Hill Jct 138 kV line with 795 ACSS conductor. Replace Line Disconnect Switch at		APS (100%)
	Yukon Convert the existing 6 wire Butler - Shanor Manor -		
<u>b2967</u>	Krendale 138 kV line into two separate 138 kV lines. New lines will be Butler - Keisters and Butler -		<u>APS (100%)</u>
	Shanor Manor - Krendale 138 kV		
<u>b2970</u>	Ringgold – Catoctin Solution		<u>APS (100%)</u>
<u>b2970.1</u>	Install two new 230 kV positions at Ringgold for 230/138 kV transformers		APS (100%)
<u>b2970.2</u>	Install new 230 kV position for Ringgold – Catoctin 230 kV line		APS (100%)
<u>b2970.3</u>	Install one new 230 kV breaker at Catoctin substation		APS (100%)
<u>b2970.4</u>	Install new 230/138 kV transformer at Catoctin substation. Convert Ringgold – Catoctin 138 kV line to 230 kV operation		APS (100%)

SCHEDULE 12 – APPENDIX A

(15) Commonwealth Edison Company and Commonwealth Edison Company of Indiana, Inc.

Remove Byron SPS upon completion of Byron Wayne 345 kV	required 1		iuai Revenue Requirement	Responsible Customer(s)
Wayne 345 kV Replace 138 kV bus tie 1-2 circuit breaker, station conductor, relays, and a wave trap at TSS 55 Hegewisch substation Reconductor 1.4 miles of 138 kV line 0112, Kickapoo Creek - LaSalle County 138kV line		•		7 7 1 (1001)
Replace 138 kV bus tie 1-2 circuit breaker, station conductor, relays, and a wave trap at TSS 55 Hegewisch substation	b2141.1	<u> </u>		ComEd (100%)
Circuit breaker, station conductor, relays, and a wave trap at TSS 55 Hegewisch substation				
b2365 conductor, relays, and a wave trap at TSS 55 Hegewisch substation Reconductor 1.4 miles of 138 kV line 0112, Kickapoo Creek - LaSalle County 138kV line Install a 138 kV Red Blue bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		*		
wave trap at TSS 55 Hegewisch substation Reconductor 1.4 miles of 138 kV line 0112, Kickapoo Creek - LaSalle County 138kV line Install a 138 kV Red Blue bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%)		,		
Hegewisch substation Reconductor 1.4 miles of 138 kV line 0112, Kickapoo Creek - LaSalle County 138kV line	b2365	_		ComEd (100%)
Reconductor 1.4 miles of 138 kV line 0112, Kickapoo Creek - LaSalle County 138kV line		-		
b2366		Hegewisch substation		
Creek - LaSalle County 138kV line		Reconductor 1.4 miles of		
Install a 138 kV Red Blue bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)	b2266	138 kV line 0112, Kickapoo		ComEd (100%)
Install a 138 kV Red Blue bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)	02300	Creek - LaSalle County		Comed (100%)
b2415 bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		138kV line		
cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		Install a 138 kV Red Blue		
Comed (100%) Comed (100%)	b2415	bus tie with underground		ComEd (1000/)
Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with Reconductor 0.125 miles of ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)	02413	cable and a line 15913 CB		Comed (100%)
b2416 the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of b2418 Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV b2465 Preaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		at Highland Park		
138 kV line L6604 Replace Ridgeland 138 kV		Reconductor 0.125 miles of		
Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%)	b2416	the East Frankfort - Mokena		ComEd (100%)
b2417 bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		138 kV line L6604		
ComEd (100%) Cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of b2418				
Cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV ComEd (100%)	b2/17	bus tie CB and underground		ComEd (100%)
Reconductor 7.5 miles of Waukegan - Gurnee 138 kV Iine L1607	02417	cable at TSS 192 Ridgeland		Comed (100%)
b2418 Waukegan - Gurnee 138 kV ComEd (100%) line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV b2466 breaker '88 L8810' with ComEd (100%)		138 kV substation		
Bine L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324)				
Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324)	b2418	Waukegan - Gurnee 138 kV		ComEd (100%)
b2419 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%)		line L1607		
on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV b2465 breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV b2466 breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%)		Reconductor 0.33 miles of		
Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV b2465 breaker '88 L8809' with a ComEd (100%) 63 kA breaker Replace the Skokie 138 kV b2466 breaker '88 L8810' with ComEd (100%)	b 2410	138 kV underground cable		ComEd (100%)
Replace the Skokie 138 kV breaker '88 L8809' with a ComEd (100%)	02419	on the Sawyer - Crawford		Comed (100%)
b2465 breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%)		138 kV Blue line (L1324)		
63 kA breaker Replace the Skokie 138 kV b2466 breaker '88 L8810' with ComEd (100%)		Replace the Skokie 138 kV		
Replace the Skokie 138 kV b2466 breaker '88 L8810' with ComEd (100%)	b2465	breaker '88 L8809' with a		ComEd (100%)
b2466 breaker '88 L8810' with ComEd (100%)		63 kA breaker		
, , , , , , , , , , , , , , , , , , , ,	b2466	breaker '88 L8810' with		ComEd (100%)
63kA breaker		63kA breaker		
Replace the Skokie 138 kV		Replace the Skokie 138 kV		
b2467 breaker '88 L11416' with ComEd (100%)	b2467	breaker '88 L11416' with		ComEd (100%)
63 kA breaker		63 kA breaker		

Commonwealth Edison Company and Commonwealth Edison Company of Indiana, Inc. (cont.)

Annual Revenue Requirement Required Transmission Enhancements Responsible Customer(s) Replace the Skokie 138 kV breaker '88 L8803' with b2468 ComEd (100%) 63kA breaker Replace the Des Plaines 138 kV breaker '46 11702' with b2469 ComEd (100%) 63 kA breaker Install a new 345 kV circuit b2561 breaker 5-7 at Elwood ComEd (100%) substation Remove 2.0 miles of wood poles on 138 kV line 17105, erect new steel structures, b2562 ComEd (100%) and install new 1113 kcmil ACSR conductor from Roscoe Bert to Harlem Replace relays at Mazon b2613 ComEd (100%) substation AEC (0.18%) / AEP (18.68%) / APS (5.86%) / ATSI (7.85%) / BGE (3.32%) / ComEd (38.21%) / Dayton (2.76%) / DEOK (4.13%) / DL (2.23%) / Dominion (5.15%) / Replace station equipment DPL (1.97%) / EKPC b2692.1 at Nelson, ESS H-471 and (1.36%) / HTP (0.05%) / **Ouad Cities** JCPL (0.52%) / MetED (0.04%) / Neptune (0.04%) / PECO (1.08%) / PENELEC (1.25%) / PEPCO (3.56%) / PPL (0.45%) /

PSEG (1.17%) / RECO (0.14%)

Commonwealth Edison Company and Commonwealth Edison Company of Indiana, Inc. (cont.)

Required T	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
			AEC (0.18%) / AEP
			(18.68%) / APS (5.86%)
			/ ATSI (7.85%) / BGE
			(3.32%) / ComEd
			(38.21%) / Dayton
			(2.76%) / DEOK
	Upgrade conductor ratings		(4.13%) / DL (2.23%) /
	of Cordova – Nelson, Quad		Dominion (5.15%) /
b2692.2	Cities – ESS H-471 and		DPL (1.97%) / EKPC
02072.2	ESS H-471 – Nelson 345		(1.36%) / HTP (0.05%) /
	kV lines and mitigating sag		JCPL (0.52%) / MetED
	limitations		(0.04%) / Neptune
			(0.04%) / PECO
			(1.08%) / PENELEC
			(1.25%) / PEPCO
			(3.56%) / PPL (0.45%) /
			PSEG (1.17%) / RECO
			(0.14%)
b2693	Replace L7815 B phase line		ComEd (100%)
	trap at Wayne substation		
	Replace 5 Powerton 345 kV		
	CB's with 2 cycle IPO		
	breakers, install one new		
b2699.1	345 kV CB; swap line 0302		ComEd (100%)
	and line 0303 bus positions;		, ,
	reconfigure Powerton 345		
	kV bus as single ring		
	configuration		
	Remove SPS logic at		
b2699.2	Powerton that trips		
	generators or sectionalizes		ComEd (100%)
	bus under normal		, ,
	conditions; minimal SPS		
	logic will remain		
b2721	Goodings Grove – Balance		
	Station Load (swap bus		
	positions for 345 kV lines		ComEd (100%)
	1312 & 11620 and 345 kV		` '
	lines 11604 & 11622) and		
	replace 138 kV bus tie 2-3		

Commonwealth Edison Company and Commonwealth Edison Company of Indiana, Inc. (cont.)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Mitigate sag limitations on ATSI (3.43%) / AEP Loretto – Wilton Center 345 (3.34%) / ComEd b2728 kV Line and replace station (92.02%) / DLCO conductor at Wilton Center (1.21%)Cut-in of line 93505 b2732.1 Tazewell - Kendall 345 kV ComEd (100%) line into Dresden Raise towers to remove the b2732.2 ComEd (100%) sag limitations on Pontiac – Loretto 345 kV line *Upgrade capacity on E.* b2930 Frankfort – University Park ComEd (100%) 345 kV Upgrade substation equipment at Pontiac b2931 *Midpoint station to increase* ComEd (100%) capacity on Pontiac -Brokaw 345 kV line Build an indoor new Elk Grove 138 kV GIS substation at the point where Rolling Meadows & Schaumburg tap off from the main lines, between Landmeier and Busse. The b2941 four 345 kV circuits in the ComEd (100%) ROW will be diverted into Gas Insulated Bus (GIB) and go through the basement of the building to provide clearance for the above ground portion of the building Install a new 138 kV circuit 18702 from Schauff Road to b2959 Rock Falls and install a ComEd (100%) fourth breaker and a half run at Schauff Road

SCHEDULE 12 – APPENDIX A

(17) AEP Service Corporation on behalf of its Affiliate Companies (AEP Indiana Michigan Transmission Company, AEP Kentucky Transmission Company, AEP Ohio Transmission Company, AEP West Virginia Transmission Company, Appalachian Power Company, Indiana Michigan Power Company, Kentucky Power Company, Kingsport Power Company, Ohio Power Company and Wheeling Power Company)

Kequileu 11	ansinission Emiancements Ami	uai Kevenue Kequirement	responsible customer(s)
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP
			(14.16%) / APS (5.73%) /
			ATSI (7.88%) / BGE
			(4.22%) / ComEd (13.31%) /
			Dayton (2.11%) / DEOK
	Cloverdale: install 6-765 kV		(3.29%) / DL (1.75%) / DPL
	breakers, incremental work		(2.50%) / Dominion
	for 2 additional breakers,		(12.86%) / EKPC (1.87%) /
1.1660.1	reconfigure and relocate		JCPL (3.74%) / ME (1.90%)
b1660.1	miscellaneous facilities, establish 500 kV station and		/ NEPTUNE* (0.44%) /
			PECO (5.34%) / PENELEC
	500 kV tie with 765 kV		(1.89%) / PEPCO (3.99%) /
	station		PPL (4.84%) / PSEG
		!	(6.26%) / RE (0.26%)
			DFAX Allocation:
			APS (97.94%) / DEOK
			(0.54%) / Dominion (1.33%)
			/ EKPC (0.19%)
			, 212 0 (0.15 / 0)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

required 11d	HISTHISSION EIHANCEMENTS ATTIC	iai Revenue Requirement	` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP
			(14.16%) / APS (5.73%) /
			ATSI (7.88%) / BGE
			(4.22%) / ComEd (13.31%) /
			Dayton (2.11%) / DEOK
			(3.29%) / DL (1.75%) / DPL
			(2.50%) / Dominion
	Reconductor the AEP		(12.86%) / EKPC (1.87%) /
1.4505.4	portion of the Cloverdale -		JCPL (3.74%) / ME (1.90%)
b1797.1	Lexington 500 kV line with		/ NEPTUNE* (0.44%) /
	2-1780 ACSS		PECO (5.34%) / PENELEC
			(1.89%) / PEPCO (3.99%) /
			PPL (4.84%) / PSEG
			(6.26%) / RE (0.26%)
			DFAX Allocation:
			APS (55.05%) / ATSI
			(2.77%) / Dayton (0.84%) /
			DEOK (2.06%) / Dominion
			(5.76%) / EKPC (0.72%) /
			PEPCO (32.80%)
	Upgrade relay at Brues		, ,
b2055	station		AEP (100%)
	Upgrade terminal		
	equipment at Howard on		
b2122.3	the Howard - Brookside		AEP (100%)
02122.3	138 kV line to achieve		(/
	ratings of 252/291 (SN/SE)		
b2122.4	Perform a sag study on the		
	Howard - Brookside 138		AEP (100%)
	kV line		` ′
1.0000	Install a 300 MVAR		A ED (1000()
b2229	reactor at Dequine 345 kV		AEP (100%)
	i 17 control of the first	IIC	

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

required 11		iai Revenue Requirement	` ` `
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP (14.16%)
			/ APS (5.73%) / ATSI
			(7.88%) / BGE (4.22%) /
			ComEd (13.31%) / Dayton
	Replace existing 150		(2.11%) / DEOK (3.29%) /
	MVAR reactor at Amos 765		DL (1.75%) / DPL (2.50%) /
b2230	kV substation on Amos - N.		Dominion (12.86%) / EKPC
	Proctorville - Hanging Rock		(1.87%) / JCPL (3.74%) / ME
	with 300 MVAR reactor		(1.90%) / NEPTUNE*
			(0.44%) / PECO (5.34%) /
			PENELEC (1.89%) / PEPCO
			(3.99%) / PPL (4.84%) /
			PSEG (6.26%) / RE (0.26%)
			DFAX Allocation:
			AEP (100%)
	Install 765 kV reactor		
b2231	breaker at Dumont 765 kV		AEP (100%)
02231	substation on the Dumont -		AEI (100%)
	Wilton Center line		
	Install 765 kV reactor		
	breaker at Marysville 765		
b2232	kV substation on the		AEP (100%)
	Marysville - Maliszewski		
	line		
	Change transformer tap		
b2233	settings for the Baker		AEP (100%)
	765/345 kV transformer		
b2252	Loop the North Muskingum		
	- Crooksville 138 kV line		
	into AEP's Philo 138 kV	AED (1000/)	AEP (100%)
	station which lies		AEF (100%)
	approximately 0.4 miles		
	from the line		
	1.00		

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

Tequiled 11		iai Kevenue Kequirement	Responsible Customer(s)
	Install an 86.4 MVAR		
b2253	capacitor bank at Gorsuch		AEP (100%)
	138 kV station in Ohio		
	Rebuild approximately 4.9		
b2254	miles of Corner - Degussa		AEP (100%)
	138 kV line in Ohio		
	Rebuild approximately 2.8		
b2255	miles of Maliszewski -		AEP (100%)
	Polaris 138 kV line in Ohio		
	Upgrade approximately 36		
	miles of 138 kV through		
b2256	path facilities between		AEP (100%)
	Harrison 138 kV station and		
	Ross 138 kV station in Ohio		
	Rebuild the Pokagon -		
	Corey 69 kV line as a		
	double circuit 138 kV line		
b2257	with one side at 69 kV and		AEP (100%)
	the other side as an express		
	circuit between Pokagon		
	and Corey stations		
	Rebuild 1.41 miles of #2		
	CU 46 kV line between		
b2258	Tams Mountain - Slab Fork		AEP (100%)
02238	to 138 kV standards. The		AEF (100%)
	line will be strung with		
	1033 ACSR		
	Install a new 138/69 kV		
	transformer at George		
b2259	Washington 138/69 kV		AEP (100%)
	substation to provide		ALF (100%)
	support to the 69 kV system		
	in the area		
	Rebuild 4.7 miles of		
b2286	Muskingum River - Wolf		
	Creek 138 kV line and		AEP (100%)
	remove the 138/138 kV		ALF (100%)
	transformer at Wolf Creek		
	Station		
			-

required 11	ansimission Emancements Amin	aar Revenue Requirement	responsible Customer(s)
b2287	Loop in the Meadow Lake - Olive 345 kV circuit into		AEP (100%)
02207	Reynolds 765/345 kV		ALI (100%)
	station		
	Establish a new 138/12 kV		
	station, transfer and		
b2344.1	consolidate load from its		AEP (100%)
02344.1	Nicholsville and Marcellus		71L1 (10070)
	34.5 kV stations at this new		
	station		
	Tap the Hydramatic –		
	Valley 138 kV circuit (~		
b2344.2	structure 415), build a new		AEP (100%)
	138 kV line (~3.75 miles) to		
	this new station		
	From this station, construct		
b2344.3	a new 138 kV line (~1.95		AEP (100%)
02311.3	miles) to REA's Marcellus		1121 (10070)
	station		
	From REA's Marcellus		
	station construct new 138		
b2344.4	kV line (~2.35 miles) to a		AEP (100%)
020	tap point on Valley –		(10070)
	Hydramatic 138 kV ckt		
	(~structure 434)		
10044.5	Retire sections of the 138		A ED (1000)
b2344.5	kV line in between structure		AEP (100%)
	415 and 434 (~ 2.65 miles)		
	Retire AEP's Marcellus		
b2344.6	34.5/12 kV and Nicholsville		A ED (1000)
	34.5/12 kV stations and also		AEP (100%)
	the Marcellus – Valley 34.5		
	kV line		
1.0045.1	Construct a new 69 kV line		AED (1000)
b2345.1	from Hartford to Keeler (~8		AEP (100%)
	miles)		

Required 11		iai Kevenue Kequirement	Responsible Customer(s)
	Rebuild the 34.5 kV lines		
b2345.2	between Keeler - Sister		AEP (100%)
	Lakes and Glenwood tap		, , ,
	switch to 69 kV (~12 miles)		
1 22 45 2	Implement in - out at Keeler		A E.D. (1000()
b2345.3	and Sister Lakes 34.5 kV		AEP (100%)
	stations		
	Retire Glenwood tap switch		
1 22 45 4	and construct a new		A ED (1000()
b2345.4	Rothadew station. These		AEP (100%)
	new lines will continue to		
	operate at 34.5 kV		
	Perform a sag study for		
1.0046	Howard - North Bellville -		AED (1000()
b2346	Millwood 138 kV line		AEP (100%)
	including terminal		
	equipment upgrades		
	Replace the North Delphos		
	600A switch. Rebuild		
L2247	approximately 18.7 miles of		AED (1000/)
b2347	138 kV line North Delphos		AEP (100%)
	- S073. Reconductor the		
	line and replace the existing		
	tower structures		
	Construct a new 138 kV		
h 2240	line from Richlands Station		AED (1000/)
b2348	to intersect with the Hales		AEP (100%)
	Branch - Grassy Creek 138		
	kV circuit		
	Change the existing CT		
h2274	ratios of the existing		AED (1000/)
b2374	equipment along Bearskin -		AEP (100%)
	Smith Mountain 138kV circuit		
	Change the existing CT		
b2375	ratios of the existing		AED (1000/)
023/3	equipment along East Danville-Banister 138kV		AEP (100%)
	circuit		

b2376	Replace the Turner 138 kV breaker 'D'	AEP (100%)
b2377	Replace the North Newark 138 kV breaker 'P'	AEP (100%)
b2378	Replace the Sporn 345 kV breaker 'DD'	AEP (100%)
b2379	Replace the Sporn 345 kV breaker 'DD2'	AEP (100%)
b2380	Replace the Muskingum 345 kV breaker 'SE'	AEP (100%)
b2381	Replace the East Lima 138 kV breaker 'E1'	AEP (100%)
b2382	Replace the Delco 138 kV breaker 'R'	AEP (100%)
b2383	Replace the Sporn 345 kV breaker 'AA2'	AEP (100%)
b2384	Replace the Sporn 345 kV breaker 'CC'	AEP (100%)
b2385	Replace the Sporn 345 kV breaker 'CC2'	AEP (100%)
b2386	Replace the Astor 138 kV breaker '102'	AEP (100%)
b2387	Replace the Muskingum 345 kV breaker 'SH'	AEP (100%)
b2388	Replace the Muskingum 345 kV breaker 'SI'	AEP (100%)
b2389	Replace the Hyatt 138 kV breaker '105N'	AEP (100%)
b2390	Replace the Muskingum 345 kV breaker 'SG'	AEP (100%)
b2391	Replace the Hyatt 138 kV breaker '101C'	AEP (100%)
b2392	Replace the Hyatt 138 kV breaker '104N'	AEP (100%)
b2393	Replace the Hyatt 138 kV breaker '104S'	AEP (100%)

required 11	I	iai Kevenue Kequiteriletii Ke	sponsible Customer(s)
b2394	Replace the Sporn 345 kV breaker 'CC1'		AEP (100%)
b2409	Install two 56.4 MVAR capacitor banks at the Melmore 138 kV station in Ohio		AEP (100%)
b2410	Convert Hogan Mullin 34.5 kV line to 138 kV, establish 138 kV line between Jones Creek and Strawton, rebuild existing Mullin Elwood 34.5 kV and terminate line into Strawton station, retire Mullin station		AEP (100%)
b2411	Rebuild the 3/0 ACSR portion of the Hadley - Kroemer Tap 69 kV line utilizing 795 ACSR conductor		AEP (100%)
b2423	Install a 300 MVAR shunt reactor at AEP's Wyoming 765 kV station		Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s)			
	Willow - Eureka 138 kV		
b2444	line: Reconductor 0.26 mile		AEP (100%)
	of 4/0 CU with 336 ACSS		
	Complete a sag study of		
b2445	Tidd - Mahans Lake 138 kV		AEP (100%)
	line		
	Rebuild the 7-mile 345 kV		
b2449	line between Meadow Lake		AED (100%)
02449	and Reynolds 345 kV		AEP (100%)
	stations		
	Add two 138 kV circuit		
b2462	breakers at Fremont station		AEP (100%)
02402	to fix tower contingency		ALI (100%)
	'408 <u>2</u> '		
	Construct a new 138/69 kV		
	Yager station by tapping 2-		
b2501	138 kV FE circuits		AEP (100%)
	(Nottingham-Cloverdale,		
	Nottingham-Harmon)		
	Build a new 138 kV line		AEP (100%)
b2501.2	from new Yager station to		
	Azalea station		
	Close the 138 kV loop back		
b2501.3	into Yager 138 kV by		AEP (100%)
02301.3	converting part of local 69		ALI (100%)
	kV facilities to 138 kV		
b2501.4	Build 2 new 69 kV exits to		
	reinforce 69 kV facilities		
	and upgrade conductor		AEP (100%)
	between Irish Run 69 kV		
	Switch and Bowerstown 69		
	kV Switch		

required 11	Required Transmission Eminancements Annual Revenue Requirement Responsible Customer(s)			
	Construct new 138 kV			
	switching station			
	Nottingham tapping 6-138			
	kV FE circuits (Holloway-			
	Brookside, Holloway-			
b2502.1	Harmon #1 and #2,		AEP (100%)	
	Holloway-Reeds,			
	Holloway-New Stacy,			
	Holloway-Cloverdale). Exit			
	a 138 kV circuit from new			
	station to Freebyrd station			
b2502.2	Convert Freebyrd 69 kV to		AED (1000/)	
	138 kV		AEP (100%)	
	Rebuild/convert Freebyrd-			
b2502.3	South Cadiz 69 kV circuit		AEP (100%)	
	to 138 kV		, , ,	
1.0500.4	Upgrade South Cadiz to 138		A ED (1000()	
b2502.4	kV breaker and a half		AEP (100%)	
	Replace the Sporn 138 kV			
b2530	breaker 'G1' with 80kA		AEP (100%)	
	breaker		· · ·	
	Replace the Sporn 138 kV			
b2531	breaker 'D' with 80kA		AEP (100%)	
	breaker		, , ,	
b2532	Replace the Sporn 138 kV			
	breaker 'O1' with 80kA		AEP (100%)	
	breaker		, , ,	
b2533	Replace the Sporn 138 kV			
	breaker 'P2' with 80kA		AEP (100%)	
	breaker		` ′	
b2534	Replace the Sporn 138 kV			
	breaker 'U' with 80kA		AEP (100%)	
	breaker		(,	
b2535	Replace the Sporn 138 kV			
	breaker 'O' with 80 kA		AEP (100%)	
	breaker		(20070)	
		I	l	

Required 11	Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s)			
b2536	Replace the Sporn 138 kV		AED (1000)	
	breaker 'O2' with 80 kA breaker		AEP (100%)	
	Replace the Robinson Park			
b2537	138 kV breakers A1, A2,			
	B1, B2, C1, C2, D1, D2,		AEP (100%)	
	E1, E2, and F1 with 63 kA		71L1 (10070)	
	breakers			
	Reconductor 0.5 miles			
	Tiltonsville – Windsor 138			
1.2555	kV and string the vacant		A ED (1000()	
b2555	side of the 4.5 mile section		AEP (100%)	
	using 556 ACSR in a six			
	wire configuration			
	Install two 138 kV prop			
	structures to increase the			
b2556	maximum operating		AEP (100%)	
02330	temperature of the Clinch		ALI (100%)	
	River- Clinch Field 138 kV			
	line			
	Temporary operating			
	procedure for delay of			
	upgrade b1464. Open the			
	Corner 138 kV circuit			
	breaker 86 for an overload			
b2581	of the Corner – Washington MP 138 kV line. The tower		AEP (100%)	
	contingency loss of Belmont – Trissler 138 kV			
	and Belmont – Edgelawn			
	138 kV should be added to			
	Operational contingency			

1		
b2591	Construct a new 69 kV line	
	approximately 2.5 miles	
	from Colfax to Drewry's.	A ED (1000())
	Construct a new Drewry's	AEP (100%)
	station and install a new	
	circuit breaker at Colfax	
	station.	
	Rebuild existing East	
	Coshocton – North	
	Coshocton double circuit	
b2592	line which contains	AEP (100%)
02372	Newcomerstown – N.	ALI (100/0)
	Coshocton 34.5 kV Circuit	
	and Coshocton – North	
	Coshocton 69 kV circuit	
	Rebuild existing West	
	Bellaire – Glencoe 69 kV	
1.2502	line with 138 kV & 69 kV	AED (1000())
b2593	circuits and install 138/69	AEP (100%)
	kV transformer at Glencoe	
	Switch	
	Rebuild 1.0 mile of	
1.0504	Brantley – Bridge Street 69	A FID (1000())
b2594	kV Line with 1033 ACSR	AEP (100%)
	overhead conductor	
	Rebuild 7.82 mile Elkhorn	
1.000	City – Haysi S.S 69 kV line	
b2595.1	utilizing 1033 ACSR built	AEP (100%)
	to 138 kV standards	
	Rebuild 5.18 mile Moss –	
	Haysi SS 69 kV line	
b2595.2	utilizing 1033 ACSR built	AEP (100%)
	to 138 kV standards	
b2596	Move load from the 34.5	
	kV bus to the 138 kV bus	
		AEP (100%)
	by installing a new 138/12 kV XF at New Carlisle	AEF (100%)
	station in Indiana	

110000111001111		an revenue requirement - re	esponsible edistanter(s)
	Rebuild approximately 1		
	mi. section of Dragoon-		
	Virgil Street 34.5 kV line		
	between Dragoon and		
b2597	Dodge Tap switch and		AEP (100%)
	replace Dodge switch		
	MOAB to increase thermal		
	capability of Dragoon-		
	Dodge Tap branch		
	Rebuild approximately 1		
	mile section of the Kline-		
	Virgil Street 34.5 kV line		
b2598	between Kline and Virgil		AEP (100%)
02370	Street tap. Replace MOAB		ALI (10070)
	switches at Beiger, risers at		
	Kline, switches and bus at		
	Virgil Street.		
	Rebuild approximately 0.1		
b2599	miles of 69 kV line between		AEP (100%)
	Albion and Albion tap		
b2600	Rebuild Fremont – Pound		AEP (100%)
02000	line as 138 kV		AEI (100%)
b2601	Fremont Station		ΛED (100%)
02001	Improvements		AEP (100%)
	Replace MOAB towards		
b2601.1	Beaver Creek with 138 kV		AEP (100%)
	breaker		
	Replace MOAB towards		
b2601.2	Clinch River with 138 kV		AEP (100%)
	breaker		
1-2001-2	Replace 138 kV Breaker A		AED (1000()
b2601.3	with new bus-tie breaker		AEP (100%)
	Re-use Breaker A as high		
b2601.4	side protection on		AEP (100%)
	transformer #1		
	Install two (2) circuit		
	switchers on high side of		
b2601.5	transformers # 2 and 3 at		AEP (100%)
	Fremont Station		
	1 Telliont Station		

Required 11		iai Revenue Requirement	Responsible Customer(s)
b2602.1	Install 138 kV breaker E2 at		AEP (100%)
	North Proctorville		(100,0)
	Construct 2.5 Miles of 138		
b2602.2	kV 1033 ACSR from East		AEP (100%)
02002.2	Huntington to Darrah 138		7127 (10070)
	kV substations		
	Install breaker on new line		
b2602.3	exit at Darrah towards East		AEP (100%)
	Huntington		
	Install 138 kV breaker on		
b2602.4	new line at East Huntington		AEP (100%)
	towards Darrah		
	Install 138 kV breaker at		
b2602.5	East Huntington towards		AEP (100%)
	North Proctorville		
b2603	Boone Area Improvements		AEP (100%)
	Purchase approximately a		
	200X300 station site near		
b2603.1	Slaughter Creek 46 kV		AEP (100%)
	station (Wilbur Station)		
	Install 3 138 kV circuit		
b2603.2	breakers, Cabin Creek to		AEP (100%)
02000.2	Hernshaw 138 kV circuit		(100,0)
	Construct 1 mi. of double		
	circuit 138 kV line on		
	Wilbur – Boone 46 kV line		
1-2602.2	with 1590 ACSS 54/19		AED (1000()
b2603.3	conductor @ 482 Degree		AEP (100%)
	design temp. and 1-159 12/7		
	ACSR and one 86 Sq.MM.		
	0.646" OPGW Static wires		
b2604	Bellefonte Transformer		AED (1000/)
02004	Addition		AEP (100%)
		•	

		iai Kevenue Kequirement	Responsible Customer(s)
	Rebuild and reconductor		
	Kammer – George		
	Washington 69 kV circuit		
	and George Washington –		
b2605	Moundsville ckt #1,		AEP (100%)
	designed for 138kV.		
	Upgrade limiting equipment		
	at remote ends and at tap		
	stations		
	Convert Bane –		
b2606	Hammondsville from 23 kV		AEP (100%)
	to 69 kV operation		
1.2607	Pine Gap Relay Limit		A ED (1000()
62607	Increase		AEP (100%)
1.2.500	D		A FIR (1000())
62608	Richlands Relay Upgrade		AEP (100%)
	Thorofare – Goff Run –		
b2609	Powell Mountain 138 kV		AEP (100%)
	Build		` ,
1.0610	Rebuild Pax Branch –		A ED (1000()
62610	Scaraboro as 138 kV		AEP (100%)
1.0611	Skin Fork Area		AED (1000()
02011	Improvements		AEP (100%)
	New 138/46 kV station near		
b2611.1	Skin Fork and other		AEP (100%)
	components		` ,
	Construct 3.2 miles of 1033		
	ACSR double circuit from		
b2611.2			AEP (100%)
			, , ,
	line		
	Replace metering BCT on		
b2634.1	Tanners Creek CB T2 with		
	_		AEP (100%)
	remove 1193 MVA limit on		, ,
	Tanners Creek 345 kV line)		
b2610 b2611 b2611.1 b2611.2	Increase Richlands Relay Upgrade Thorofare – Goff Run – Powell Mountain 138 kV Build Rebuild Pax Branch – Scaraboro as 138 kV Skin Fork Area Improvements New 138/46 kV station near Skin Fork and other components Construct 3.2 miles of 1033 ACSR double circuit from new Station to cut into Sundial-Baileysville 138 kV line Replace metering BCT on Tanners Creek CB T2 with a slip over CT with higher thermal rating in order to remove 1193 MVA limit on facility (Miami Fort-		AEP (100%) AEP (100%) AEP (100%) AEP (100%) AEP (100%) AEP (100%) AEP (100%)

Required 11	ansmission Enhancements Anni	ual Revenue Requirement	Responsible Customer(s)
b2643	Replace the Darrah 138 kV breaker 'L' with 40kA rated breaker		AEP (100%)
b2645	Ohio Central 138 kV Loop		AEP (100%)
b2667	Replace the Muskingum 138 kV bus # 1 and 2		AEP (100%)
b2668	Reconductor Dequine to Meadow Lake 345 kV circuit #1 utilizing dual 954 ACSR 54/7 cardinal conductor		AEP (100%)
b2669	Install a second 345/138 kV transformer at Desoto		AEP (100%)
b2670	Replace switch at Elk Garden 138 kV substation (on the Elk Garden – Lebanon 138 kV circuit)		AEP (100%)
b2671	Replace/upgrade/add terminal equipment at Bradley, Mullensville, Pinnacle Creek, Itmann, and Tams Mountain 138 kV substations. Sag study on Mullens – Wyoming and Mullens – Tams Mt. 138 kV circuits		AEP (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***} Hudson Transmission Partners, LLC

b2687.2	Install a 300 MVAR shunt line reactor on the Broadford end of the	an revenue requirement	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) /
	Broadford – Jacksons Ferry 765 kV line		JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEP (100%)
b2697.1	Mitigate violations identified by sag study to operate Fieldale-Thornton-Franklin 138 kV overhead line conductor at its max. operating temperature. 6 potential line crossings to be addressed.		AEP (100%)
b2697.2	Replace terminal equipment at AEP's Danville and East Danville substations to improve thermal capacity of Danville – East Danville 138 kV circuit		AEP (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***} Hudson Transmission Partners, LLC

required 11		a revenue requirement	Responsible Customer(s)
	Replace relays at AEP's Cloverdale and Jackson's		
b2698	Ferry substations to improve		AEP (100%)
02070	the thermal capacity of		71L1 (10070)
	Cloverdale – Jackson's Ferry		
	765 kV line		
	Construct Herlan station as		
	breaker and a half		((22.1)
b2701.1	configuration with 9-138 kV		AEP (100%)
	CB's on 4 strings and with 2-		
	28.8 MVAR capacitor banks		
	Construct new 138 kV line		
	from Herlan station to Blue		
b2701.2	Racer station. Estimated		AEP (100%)
	approx. 3.2 miles of 1234		(===,=,
	ACSS/TW Yukon and		
	OPGW		
0701.2	Install 1-138 kV CB at Blue		A ED (1000/)
2701.3	Racer to terminate new		AEP (100%)
	Herlan circuit		
1-0714	Rebuild/upgrade line		A ED (1000/)
b2714	between Glencoe and		AEP (100%)
	Willow Grove Switch 69 kV		
	Build approximately 11.5		
	miles of 34.5 kV line with 556.5 ACSR 26/7 Dove		
b2715			AEP (100%)
	conductor on wood poles		
	from Flushing station to Smyrna station		
	·		
	Replace the South Canton 138 kV breakers 'K', 'J',		
b2727	'J1', and 'J2' with 80kA		AEP (100%)
	breakers		
	UICANCIS		

Required 11	ansmission Ennancements Annua	ai Revenue Requirement	Responsible Customer(s)
	Convert the Sunnyside – East Sparta – Malvern 23 kV		
b2731	sub-transmission network to		AEP (100%)
	69 kV. The lines are already		
	built to 69 kV standards		
	Replace South Canton 138		
b2733	kV breakers 'L' and 'L2'		AEP (100%)
	with 80 kA rated breakers		
	Retire Betsy Layne		
	138/69/43 kV station and		
b2750.1	replace it with the greenfield		AEP (100%)
	Stanville station about a half		, ,
	mile north of the existing		
	Betsy Layne station Relocate the Betsy Layne		
	capacitor bank to the		
b2750.2	Stanville 69 kV bus and		AEP (100%)
02730.2	increase the size to 14.4		71L1 (10070)
	MVAR		
	Replace existing George		
	Washington station 138 kV		
	yard with GIS 138 kV		
b2753.1	breaker and a half yard in		AED (1000/)
02/33.1	existing station footprint.		AEP (100%)
	Install 138 kV revenue		
	metering for new IPP		
	connection		
	Replace Dilles Bottom 69/4		
	kV Distribution station as		
	breaker and a half 138 kV		
b2753.2	yard design including AEP		AEP (100%)
02.00.2	Distribution facilities but		, , ,
	initial configuration will		
	constitute a 3 breaker ring		
	bus		

Required 11		ai Revenue Requirement	Responsible Customer(s)
	Connect two 138 kV 6-wired circuits from "Point A"		
b2753.3	(currently de-energized and		
	owned by FirstEnergy) in		
	circuit positions previously		AEP (100%)
	designated Burger #1 &		(100/0)
	Burger #2 138 kV. Install		
	interconnection settlement		
	metering on both circuits		
	exiting Holloway		
	Build double circuit 138 kV		
	line from Dilles Bottom to		
	"Point A". Tie each new		
h2752.6	AEP circuit in with a 6-wired		AED (1000/)
b2753.6	line at Point A. This will create a Dilles Bottom –		AEP (100%)
	Holloway 138 kV circuit and		
	a George Washington –		
	Holloway 138 kV circuit		
	Retire line sections (Dilles		
	Bottom – Bellaire and		
	Moundsville – Dilles Bottom		
	69 kV lines) south of		
	FirstEnergy 138 kV line		177 (1001)
b2753.7	corridor, near "Point A". Tie		AEP (100%)
	George Washington –		
	Moundsville 69 kV circuit to		
	George Washington – West		
	Bellaire 69 kV circuit		
	Rebuild existing 69 kV line		
	as double circuit from		
	George Washington – Dilles		
b2753.8	Bottom 138 kV. One circuit		AEP (100%)
02/33.8	will cut into Dilles Bottom		ALI (100%)
	138 kV initially and the other		
	will go past with future plans		
	to cut in		

<u> </u>	ansimission Emianeements Amida	· · · · · · · · · · · · · · · · ·	Tropondio Customer(s)
b2760	Perform a Sag Study of the Saltville – Tazewell 138 kV line to increase the thermal rating of the line		AEP (100%)
b2761.1	Replace the Hazard 161/138 kV transformer		AEP (100%)
b2761.2	Perform a Sag Study of the Hazard – Wooten 161 kV line to increase the thermal rating of the line		AEP (100%)
<u>b2761.3</u>	Rebuild the Hazard – Wooton 161 kV line utilizing 795 26/7 ACSR conductor (300 MVA rating)		AEP (100%)
b2762	Perform a Sag Study of Nagel - West Kingsport 138 kV line to increase the thermal rating of the line		AEP (100%)
b2776	Reconductor the entire Dequine – Meadow Lake 345 kV circuit #2		AEP (100%)
b2777	Reconductor the entire Dequine – Eugene 345 kV circuit #1		AEP (100%)
b2779.1	Construct a new 138 kV station, Campbell Road, tapping into the Grabill – South Hicksville138 kV line		AEP (100%)
b2779.2	Reconstruct sections of the Butler-N.Hicksville and Auburn-Butler 69 kV circuits as 138 kV double circuit and extend 138 kV from Campbell Road station		AEP (100%)

required 11		Revenue Requirement	Responsible Customer(s)
b2779.3	Construct a new 345/138 kV SDI Wilmington Station which will be sourced from Collingwood 345 kV and serve the SDI load at 345 kV and 138 kV, respectively		AEP (100%)
b2779.4	Loop 138 kV circuits in-out of the new SDI Wilmington 138 kV station resulting in a direct circuit to Auburn 138 kV and an indirect circuit to Auburn and Rob Park via Dunton Lake, and a circuit to Campbell Road; Reconductor 138 kV line section between Dunton Lake – SDI Wilmington		AEP (100%)
b2779.5	Expand Auburn 138 kV bus		AEP (100%)
b2787	Reconductor 0.53 miles (14 spans) of the Kaiser Jct Air Force Jct. Sw section of the Kaiser - Heath 69 kV circuit/line with 336 ACSR to match the rest of the circuit (73 MVA rating, 78% loading)		AEP (100%)
b2788	Install a new 3-way 69 kV line switch to provide service to AEP's Barnesville distribution station. Remove a portion of the #1 copper T-Line from the 69 kV throughpath		AEP (100%)

Required Tr	ansmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
	Rebuild the Brues - Glendale		
b2789	Heights 69 kV line section (5		AEP (100%)
02/09	miles) with 795 ACSR (128		AEF (100/6)
	MVA rating, 43% loading)		
	Install a 3 MVAR, 34.5 kV		
<i>b</i> 2790	cap bank at Caldwell		AEP (100%)
	substation		
b2791	Rebuild Tiffin – Howard, new		AEP (100%)
02/91	transformer at Chatfield		AEF (100%)
	Rebuild portions of the East		
	Tiffin - Howard 69 kV line		
	from East Tiffin to West		
b2791.1	Rockaway Switch (0.8 miles)		AEP (100%)
	using 795 ACSR Drake		
	conductor (129 MVA rating,		
	50% loading)		
	Rebuild Tiffin - Howard 69		
	kV line from St. Stephen's		
	Switch to Hinesville (14.7		
b2791.2	miles) using 795 ACSR Drake		AEP (100%)
	conductor (90 MVA rating,		
	non-conductor limited, 38%		
	loading)		
	New 138/69 kV transformer		
b2791.3	with 138/69 kV protection at		AEP (100%)
	Chatfield		
b2791.4	New 138/69 kV protection at		AEP (100%)
02/91.4	existing Chatfield transformer		ALI (10070)
	Replace the Elliott		
	transformer with a 130 MVA		
b2792	unit, reconductor 0.42 miles		
	of the Elliott – Ohio		
	University 69 kV line with		AEP (100%)
	556 ACSR to match the rest of		11L1 (10070)
	the line conductor (102 MVA		
	rating, 73% loading) and		
	rebuild 4 miles of the Clark		
	Street – Strouds R		

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Energize the spare Fremont Center 138/69 kV 130 MVA b2793 transformer #3. Reduces AEP (100%) overloaded facilities to 46% loading Construct new 138/69/34 kV station and 1-34 kV circuit (designed for 69 kV) from b2794 AEP (100%) new station to Decliff station, approximately 4 miles, with 556 ACSR conductor (51 MVA rating) Install a 34.5 kV 4.8 MVAR b2795 capacitor bank at Killbuck AEP (100%) 34.5 kV station Rebuild the Malvern - Oneida Switch 69 kV line section with b2796 AEP (100%) 795 ACSR (1.8 miles, 125 MVA rating, 55% loading) Rebuild the Ohio Central -Conesville 69 kV line section (11.8 miles) with 795 ACSR AEP (100%) b2797 conductor (128 MVA rating, 57% loading). Replace the 50 MVA Ohio Central 138/69 kV XFMR with a 90 MVA unit Install a 14.4 MVAR capacitor bank at West Hicksville station. Replace b2798 AEP (100%) ground switch/MOAB at West Hicksville with a circuit switcher Rebuild Valley - Almena, Almena - Hartford, Riverside - South Haven 69 kV lines. b2799 AEP (100%) New line exit at Valley Station. New transformers at

Almena and Hartford

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Rebuild 12 miles of Valley – Almena 69 kV line as a double circuit 138/69 kV line using 795 ACSR conductor b2799.1 AEP (100%) (360 MVA rating) to introduce a new 138 kV source into the 69 kV load pocket around Almena station Rebuild 3.2 miles of Almena to Hartford 69 kV line using b2799.2 AEP (100%) 795 ACSR conductor (90 MVA rating) Rebuild 3.8 miles of Riverside - South Haven 69 kV line b2799.3 AEP (100%) using 795 ACSR conductor (90 MVA rating) At Valley station, add new 138 kV line exit with a 3000 A 40 kA breaker for the new 138 b2799.4 AEP (100%) kV line to Almena and replace CB D with a 3000 A 40 kA breaker At Almena station, install a 90 MVA 138/69 kV transformer with low side 3000 A 40 kA b2799.5 AEP (100%) breaker and establish a new 138 kV line exit towards Valley At Hartford station, install a second 90 MVA 138/69 kV b2799.6 AEP (100%) transformer with a circuit switcher and 3000 A 40 kA low side breaker

MISHUSSION LINUMCCHICIUS	Thuma Revenue Requirement	Responsible Customer(s)
Replace Delaware 138 kV breaker 'P' with a 40 kA		AEP (100%)
kV breaker 'F' with a 40 kA		AEP (100%)
breaker		
Replace Madison 138 kV		
breaker 'V' with a 63 kA		AEP (100%)
breaker		
Replace Sterling 138 kV		
breaker 'G' with a 40 kA		AEP (100%)
breaker		
Replace Morse 138 kV		
breakers '103', '104', '105',		AED (1000/)
and '106' with 63 kA		AEP (100%)
breakers		
Replace Clinton 138 kV		
breakers '105' and '107' with		AEP (100%)
63 kA breakers		, ,
Install 300 MVAR reactor at		
Ohio Central 345 kV		AEP (100%)
substation		
	Replace Delaware 138 kV breaker 'P' with a 40 kA breaker Replace West Huntington 138 kV breaker 'F' with a 40 kA breaker Replace Madison 138 kV breaker 'V' with a 63 kA breaker Replace Sterling 138 kV breaker 'G' with a 40 kA breaker Replace Morse 138 kV breakers '103', '104', '105', and '106' with 63 kA breakers Replace Clinton 138 kV breakers '105' and '107' with 63 kA breakers Install 300 MVAR reactor at Ohio Central 345 kV	Replace Delaware 138 kV breaker 'P' with a 40 kA breaker Replace West Huntington 138 kV breaker 'F' with a 40 kA breaker Replace Madison 138 kV breaker 'V' with a 63 kA breaker Replace Sterling 138 kV breaker 'G' with a 40 kA breaker Replace Morse 138 kV breakers '103', '104', '105', and '106' with 63 kA breakers Replace Clinton 138 kV breakers '105' and '107' with 63 kA breakers Install 300 MVAR reactor at Ohio Central 345 kV

Required Tra	ansmission Enhancements Annual	Revenue Requirement	Responsible Customer(s)
b2826.2	Install 300 MVAR reactor at West Bellaire 345 kV substation		AEP (100%)
b2831.1	Upgrade the Tanner Creek – Miami Fort 345 kV circuit (AEP portion)		DFAX Allocation: Dayton (34.34%) / DEOK (56.45%) / EKPC (9.21%)
b2832	Six wire the Kyger Creek – Sporn 345 kV circuits #1 and #2 and convert them to one circuit		AEP (100%)
b2833	Reconductor the Maddox Creek – East Lima 345 kV circuit with 2-954 ACSS Cardinal conductor		DFAX Allocation: Dayton (100%)
b2834	Reconductor and string open position and sixwire 6.2 miles of the Chemical – Capitol Hill 138 kV circuit		AEP (100%)
b2872	Replace the South Canton 138 kV breaker 'K2' with a 80 kA breaker		AEP (100%)
b2873	Replace the South Canton 138 kV breaker "M" with a 80 kA breaker		AEP (100%)
b2874	Replace the South Canton 138 kV breaker "M2" with a 80 kA breaker		AEP (100%)
b2878	Upgrade the Clifty Creek 345 kV risers		AEP (100%)
b2880	Rebuild approximately 4.77 miles of the Cannonsburg – South Neal 69 kV line section utilizing 795 ACSR conductor (90 MVA rating)		AEP (100%)

		1	1 ()
b2881	Rebuild ~1.7 miles of the Dunn Hollow – London 46 kV line section utilizing 795 26/7 ACSR conductor (58 MVA rating, non-conductor limited)		AEP (100%)
b2882	Rebuild Reusens - Peakland Switch 69 kV line. Replace Peakland Switch		AEP (100%)
b2882.1	Rebuild the Reusens - Peakland Switch 69 kV line (approximately 0.8 miles) utilizing 795 ACSR conductor (86 MVA rating, non- conductor limited)		AEP (100%)
b2882.2	Replace existing Peakland S.S with new 3 way switch phase over phase structure		AEP (100%)
b2883	Rebuild the Craneco – Pardee – Three Forks – Skin Fork 46 kV line section (approximately 7.2 miles) utilizing 795 26/7 ACSR conductor (108 MVA rating)		AEP (100%)
b2884	Install a second transformer at Nagel station, comprised of 3 single phase 250 MVA 500/138 kV transformers. Presently, TVA operates their end of the Boone Dam – Holston 138 kV interconnection as normally open preemptively for the loss of the existing Nagel		AEP (100%)
b2885	New delivery point for City of Jackson		AEP (100%)

Annual Revenue Requirement Responsible Customer(s)

Required Transmission Enhancements

Morse circuit at Morse Road
Retire Poston substation.

Install new Lemaster

substation
Remove and retire the Poston

138 kV station
Install a new greenfield

station, Lemaster 138 kV

Station, in the clear

b2888

b2888.1

b2888.2

Install a new Ironman Switch to serve a new delivery point b2885.1 requested by the City of AEP (100%) Jackson for a load increase request Install a new 138/69 kV station (Rhodes) to serve as a b2885.2 third source to the area to AEP (100%) help relieve overloads caused by the customer load increase Replace Coalton Switch with b2885.3 a new three breaker ring bus AEP (100%) (Heppner) Install 90 MVA 138/69 kV transformer, new transformer high and low side 3000 A 40 b2886 AEP (100%) kA CBs, and a 138 kV 40 kA bus tie breaker at West End Fostoria Add 2-138 kV CB's and relocate 2-138 kV circuit exits to different bays at Morse b2887 AEP (100%) Road. Eliminate 3 terminal line by terminating Genoa -

AEP (100%)

AEP (100%)

AEP (100%)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Relocate the Trimble 69 kV AEP Ohio radial delivery point to 138 kV, to be served off of the Poston – Strouds b2888.3 AEP (100%) Run – Crooksville 138 kV circuit via a new three-way switch. Retire the Poston -Trimble 69 kV line AEP (100%) b2889 Expand Cliffview station Cliffview Station: Establish 138 kV bus. Install two 138/69 kV XFRs (130 MVA), b2889.1 AEP (100%) six 138 kV CBs (40 kA 3000 A) and four 69 kV CBs (40 kA $3000\,A)$ *Byllesby – Wythe 69 kV:* Retire all 13.77 miles (1/0 b2889.2 AEP (100%) CU) of this circuit (~4 miles *currently in national forest)* Galax – Wythe 69 kV: Retire 13.53 miles (1/0 CU section) of line from Lee Highway down to Byllesby. This section is currently double b2889.3 AEP (100%) circuited with Byllesby – Wythe 69 kV. Terminate the southern 3/0 ACSR section into the newly opened position at Byllesby Cliffview Line: Tap the existing Pipers Gap – Jubal Early 138 kV line section. Construct double circuit b2889.4 AEP (100%) in/out (~2 miles) to newly established 138 kV bus, utilizing 795 26/7 ACSR conductor

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Rebuild 23.55 miles of the East Cambridge – Smyrna b2890.1 34.5 kV circuit with 795 AEP (100%) ACSR conductor (128 MVA rating) and convert to 69 kV East Cambridge: Install a 2000 A 69 kV 40 kA circuit b2890.2 breaker for the East AEP (100%) Cambridge – Smyrna 69 kV circuit Old Washington: Install 69 b2890.3 kV 2000 A two way phase AEP (100%) over phase switch Install 69 kV 2000 A two way b2890.4 AEP (100%) phase over phase switch Rebuild the Midland Switch to East Findlay 34.5 kV line b2891 (3.31 miles) with 795 ACSR AEP (100%) (63 MVA rating) to match other conductor in the area Install new 138/12 kV transformer with high side circuit switcher at Leon and a new 138 kV line exit towards Ripley. Establish 138 kV at b2892 AEP (100%) the Ripley station with a new 138/69 kV 130 MVA transformer and move the distribution load to 138 kV service Rebuild approximately 6.7 miles of 69 kV line between Mottville and Pigeon River using 795 ACSR conductor b2936.1 AEP (100%) (129 MVA rating). New construction will be designed to 138 kV standards but operated at 69 kV

Annual Revenue Requirement Responsible Customer(s)

Required Transmission Enhancements

Pigeon River Station: Replace

<u>Upgrade existing 345 kV</u> terminal equipment at Tanner

<u>Creek station</u>
Replace terminal equipment

on Maddox Creek - East

Lima 345 kV circuit
Upgrade terminal equipment
at Tanners Creek 345 kV
station. Upgrade 345 kV bus

and risers at Tanners Creek for the Dearborn circuit

b2968

b2969

b2976

existing MOAB Sw. 'W' with a new 69 kV 3000 A 40 kA b2936.2 breaker, and upgrade existing AEP (100%) relays towards HMD station. Replace CB H with a 3000 A 40 kA breaker Replace the existing 636 ACSR 138 kV bus at Fletchers b2937 AEP (100%) Ridge with a larger 954 ACSR conductor Perform a sag mitigations on *the Broadford – Wolf Hills* 138 kV circuit to allow the b2938 AEP (100%) line to operate to a higher maximum temperature Cut George Washington -Tidd 138 kV circuit into Sand b2958.1 <u>AEP (100%)</u> Hill and reconfigure Brues & Warton Hill line entrances Add 2 138 kV 3000 A 40 kA breakers, disconnect switches, b2958.2 AEP (100%) and update relaying at Sand Hill station

AEP (100%)

AEP (100%)

DEOK (100%)

SCHEDULE 12 – APPENDIX A

(19) Northern Indiana Public Service Company

Required Tra	nsmission Enhancements A	Annual Revenue Requirement Responsible Customer(s)
		MISO (12.00%) / AEC (0.97%) / AEP (16.66%) / APS (4.94%) / ATSI (7.78%) / PCE (5.21%) /
		ATSI (7.78%) / BGE (5.21%) / Dayton (1.85%) / DEOK (2.30%) /
	D M 245	Dominion (15.21%) / DPL (1.75%)
<u>b2971</u>	Reconfigure Munster 345 kV as ring bus	<u>/DL(1.43%)/EKPC(0.60%)/</u>
	K V ds Hilg ods	<u>JCPL (2.16%) / ME (1.73%) /</u>
		PECO (4.32%) / PENELEC
		(4.98%)/PEPCO (5.80%)/PPL (4.74%)/PSEG (5.09%)/RE
		(0.15%)/NEPTUNE* (0.33%)
		MISO (10.00%) / AEC (0.93%) /
		<u>AEP (26.05%) / APS (4.19%) /</u>
		<u>ATSI (5.95%) / BGE (4.39%) /</u>
		Dayton (1.59%) / DEOK (2.30%) /
1.2072	Reconductor Michigan	Dominion (14.72%) / DPL (1.53%)
<u>b2973</u>	City - Bosserman 138 kV	/ DL (1.26%) / EKPC (0.98%) / JCPL (1.92%) / ME (1.39%) /
		PECO (4.19%) / PENELEC
		(4.35%)/PEPCO(5.06%)/PPL
		(4.03%) / PSEG (4.49%) / RE
		(0.12%)/NEPTUNE*(0.56%)
		MISO (59.00%) / AEC (0.01%) /
	Replace terminal equipment at Reynolds on the Reynolds - Magnetation 138 kV	AEP (40.32%) / APS (0.13%) /
<u>b2974</u>		ATSI (0.05%) / BGE (0.08%) / Dayton (0.03%) / DPL (0.01%) /
<u>02774</u>		ME (0.04%) / PENELEC (0.06%) /
		PPL (0.20%) / PSEG (0.03%) /
		<u>NEPTUNE* (0.04%)</u>
		MISO (76.00%) / AEC (0.28%) /
		<u>AEP (4.51%) / APS (1.31%) /</u>
		ATSI (1.91%) / BGE (1.40%) /
		Dayton (0.49%) / DEOK (0.70%) / Dominion (4.35%) / DPL (0.46%) /
<u>b2975</u>	Reconductor Roxana -	DL (0.38%) / EKPC (0.27%) /
	Praxair 138 kV	JCPL (0.57%) / ME (0.43%) /
		PECO (1.25%) / PENELEC
		(1.34%)/PEPCO(1.53%)/PPL
		(1.23%)/PSEG (1.41%)/RE
		(0.04%)/NEPTUNE* (0.14%)

SCHEDULE 12 – APPENDIX A

(20) Virginia Electric and Power Company

Required 1		al Revenue Requirement	Responsible Customer(s)
b1698.7	Replace Loudoun 230 kV breaker '203052' with 63kA rating		Dominion (100%)
b1696.1	Replace the Idylwood 230 kV '25112' breaker with 50kA breaker		Dominion (100%)
b1696.2	Replace the Idylwood 230 kV '209712' breaker with 50kA breaker		Dominion (100%)
b1793.1	Remove the Carolina 22 SPS to include relay logic changes, minor control wiring, relay resets and SCADA programming upon completion of project		Dominion (100%)
b2281	Additional Temporary SPS at Bath County		Dominion (100%)
b2350	Reconductor 211 feet of 545.5 ACAR conductor on 59 Line Elmont - Greenwood DP 115 kV to achieve a summer emergency rating of 906 amps or greater		Dominion (100%)
b2358	Install a 230 kV 54 MVAR capacitor bank on the 2016 line at Harmony Village Substation		Dominion (100%)
b2359	Wreck and rebuild approximately 1.3 miles of existing 230 kV line between Cochran Mill - X4-039 Switching Station		Dominion (100%)
b2360	Build a new 39 mile 230 kV transmission line from Dooms - Lexington on existing right- of-way		Dominion (100%)
b2361	Construct 230 kV OH line along existing Line #2035 corridor, approx. 2.4 miles from Idylwood - Dulles Toll Road (DTR) and 2.1 miles on new right-of-way along DTR to new Scott's Run Substation		Dominion (100%)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s)

	Tanbinibbion Emancements 7 miles	
b2368	Replace the Brambleton 230 kV breaker '209502' with 63kA breaker	Dominion (100%)
b2369	Replace the Brambleton 230 kV breaker '213702' with 63kA breaker	Dominion (100%)
b2370	Replace the Brambleton 230 kV breaker 'H302' with 63kA breaker	Dominion (100%)
b2373	Build a 2nd Loudoun - Brambleton 500 kV line within the existing ROW. The Loudoun - Brambleton 230 kV line will be relocated as an underbuild on the new 500 kV line	Dominion (100%)
b2397	Replace the Beaumeade 230 kV breaker '2079T2116' with 63kA	Dominion (100%)
b2398	Replace the Beaumeade 230 kV breaker '2079T2130' with 63kA	Dominion (100%)
b2399	Replace the Beaumeade 230 kV breaker '208192' with 63kA	Dominion (100%)
b2400	Replace the Beaumeade 230 kV breaker '209592' with 63kA	Dominion (100%)
b2401	Replace the Beaumeade 230 kV breaker '211692' with 63kA	Dominion (100%)
b2402	Replace the Beaumeade 230 kV breaker '227T2130' with 63kA	Dominion (100%)
b2403	Replace the Beaumeade 230 kV breaker '274T2130' with 63kA	Dominion (100%)

The Annual Revenue Requirement for all Virginia Electric and Power Company projects in this Section 20 shall be as specified in Attachment 7 to Appendix A of Attachment H-16A and under the procedures detailed in Attachment H-16B.

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required I	ransmission Enhancements A	nnual Revenue Requirement	Responsible Customer(s)
b2404	Replace the Beaumeade 230 kV breaker '227T2095' with 63kA		Dominion (100%)
b2405	Replace the Pleasant view 230 kV breaker '203T274' with 63kA		Dominion (100%)
b2443	Construct new underground 230 kV line from Glebe to Station C, rebuild Glebe Substation, construct 230 kV high side bus at Station C with option to install 800 MVA PAR		Dominion (97.11%) / ME (0.18%) / PEPCO (2.71%)
b2443.1	Replace the Idylwood 230 kV breaker '203512' with 50kA		Dominion (100%)
b2443.2	Replace the Ox 230 kV breaker '206342' with 63kA breaker		Dominion (100%)
b2443.3	Glebe – Station C PAR		DFAX Allocation: Dominion (22.57%) / PEPCO (77.43%)
b2457	Replace 24 115 kV wood h-frames with 230 kV Dominion pole H-frame structures on the Clubhouse – Purdy 115 kV line		Dominion (100%)
b2458.1	Replace 12 wood H-frame structures with steel H- frame structures and install shunts on all conductor splices on Carolina – Woodland 115 kV		Dominion (100%)
b2458.2	Upgrade all line switches and substation components at Carolina 115 kV to meet or exceed new conductor rating of 174 MVA		Dominion (100%)
b2458.3	Replace 14 wood H-frame structures on Carolina – Woodland 115 kV		Dominion (100%)
b2458.4	Replace 2.5 miles of static wire on Carolina – Woodland 115 kV		Dominion (100%)

required 1		uniuai Revenue Requirement	responsible Customer(s)
b2458.5	Replace 4.5 miles of conductor between Carolina 115 kV and Jackson DP 115 kV with min. 300 MVA summer STE rating; Replace 8 wood H-frame structures located between Carolina and Jackson DP with steel H-frames		Dominion (100%)
b2460.1	Replace Hanover 230 kV substation line switches with 3000A switches		Dominion (100%)
b2460.2	Replace wave traps at Four River 230 kV and Elmont 230 kV substations with 3000A wave traps		Dominion (100%)
b2461	Wreck and rebuild existing Remington CT – Warrenton 230 kV (approx. 12 miles) as a double-circuit 230 kV line		Dominion (100%)
b2461.1	Construct a new 230 kV line approximately 6 miles from NOVEC's Wheeler Substation a new 230 kV switching station in Vint Hill area		Dominion (100%)
b2461.2	Convert NOVEC's Gainesville – Wheeler line (approximately 6 miles) to 230 kV		Dominion (100%)
b2461.3	Complete a Vint Hill – Wheeler – Loudoun 230 kV networked line		Dominion (100%)

required 1	Talishiission Eiliancements Ainua	ai Kevenue Kequirement	Responsible Customer(s)
			Load-Ratio Share Allocation:
			AEC (1.66%) / AEP (14.16%)
			/ APS (5.73%) / ATSI (7.88%)
			/ BGE (4.22%) / ComEd
	D 1 M:11 (1: 500 13)		(13.31%) / Dayton (2.11%) /
	Replace Midlothian 500 kV breaker 563T576 and motor		DEOK (3.29%) / DL (1.75%) /
	operated switches with 3		DPL (2.50%) / Dominion
10454	breaker 500 kV ring bus.		(12.86%) / EKPC (1.87%) /
b2471	Terminate Lines # 563 Carson		JCPL (3.74%) / ME (1.90%) /
	– Midlothian, #576		NEPTUNE* (0.44%) / PECO
	Midlothian –North Anna,		` ′
	Transformer #2 in new ring		(5.34%) / PENELEC (1.89%) /
			PEPCO (3.99%) / PPL (4.84%)
			/ PSEG (6.26%) / RE (0.26%)
			DFAX Allocation:
			Dominion (100%)
	Rebuild 115 kV Line #32		Dominion (10070)
	from Halifax-South Boston (6		
	miles) for min. of 240 MVA		
b2504	and transfer Welco tap to Line		Dominion (100%)
	#32. Moving Welco to Line		Dominion (100%)
	#32 requires disabling auto-		
	sectionalizing scheme Install structures in river to		
	remove the 115 kV #65 line		
b2505	(Whitestone-Harmony Village		T (1000)
02000	115 kV) from bridge and		Dominion (100%)
	improve reliability of the line		
10715	Replace the Loudoun 500 kV		
b2542	'H2T502' breaker with a		Dominion (100%)
	50kA breaker Replace the Loudoun 500 kV		(
b2543	'H2T584' breaker with a		
02343	50kA breaker		Dominion (100%)
	Reconductor wave trap at		
b2565	Carver Substation with a		Dominion (100%)
	2000A wave trap		Dominion (100%)
	Reconductor 1.14 miles of		
b2566	existing line between ACCA and Hermitage and upgrade		Dominion (100%)
	associated terminal equipment		Dominion (100%)
L	associated terminal equipment		

		 T
b2582	Rebuild the Elmont – Cunningham 500 kV line	Dominion (100%)
b2583	Install 500 kV breaker at Ox Substation to remove Ox Tx#1 from H1T561 breaker failure outage.	Dominion (100%)
b2584	Relocate the Bremo load (transformer #5) to #2028 (Bremo-Charlottesville 230 kV) line and Cartersville distribution station to #2027 (Bremo- Midlothian 230 kV) line	Dominion (100%)
b2585	Reconductor 7.63 miles of existing line between Cranes and Stafford, upgrade associated line switches at Stafford	DFAX Allocation: PEPCO (100%)
b2620	Wreck and rebuild the Chesapeake – Deep Creek – Bowers Hill – Hodges Ferry 115 kV line; minimum rating 239 MVA normal/emergency, 275 MVA load dump rating	Dominion (100%)

Required 1		inual Revenue Requirement	Responsible Customer(s)
b2622	Rebuild Line #47 between Kings Dominion 115 kV and Fredericksburg 115 kV to current standards with summer emergency rating of 353 MVA at 115 kV		Dominion (100%)
b2623	Rebuild Line #4 between Bremo and Structure 8474 (4.5 miles) to current standards with a summer emergency rating of 261 MVA at 115 kV		Dominion (100%)
b2624	Rebuild 115 kV Lines #18 and #145 between Possum Point Generating Station and NOVEC's Smoketown DP (approx. 8.35 miles) to current 230 kV standards with a normal continuous summer rating of 524 MVA at 115 kV		Dominion (100%)
b2625	Rebuild 115 kV Line #48 between Thole Street and Structure 48/71 to current standard. The remaining line to Sewells Point is 2007 vintage. Rebuild 115 kV Line #107 line, Sewells Point to Oakwood, between structure 107/17 and 107/56 to current standard.		Dominion (100%)
b2626	Rebuild 115 kV Line #34 between Skiffes Creek and Yorktown and the double circuit portion of 115 kV Line #61 to current standards with a summer emergency rating of 353 MVA at 115 kV		Dominion (100%)
b2627	Rebuild 115 kV Line #1 between Crewe 115 kV and Fort Pickett DP 115 kV (12.2 miles) to current standards with summer emergency rating of 261 MVA at 115 kV		Dominion (100%)

Required I	ransmission Enhancements Annu	al Revenue Requirement	Responsible Customer(s)
b2628	Rebuild 115 kV Line #82 Everetts – Voice of America (20.8 miles) to current standards with a summer emergency rating of 261 MVA at 115 kV		Dominion (100%)
b2629	Rebuild the 115 kV Lines #27 and #67 lines from Greenwich 115 kV to Burton 115 kV Structure 27/280 to current standard with a summer emergency rating of 262 MVA at 115 kV		Dominion (100%)
b2630	Install circuit switchers on Gravel Neck Power Station GSU units #4 and #5. Install two 230 kV CCVT's on Lines #2407 and #2408 for loss of source sensing		Dominion (100%)
b2636	Install three 230 kV bus breakers and 230 kV, 100 MVAR Variable Shunt Reactor at Dahlgren to provide line protection during maintenance, remove the operational hazard and provide voltage reduction during light load conditions		Dominion (100%)
b2647	Rebuild Boydton Plank Rd – Kerr Dam 115 kV Line #38 (8.3 miles) to current standards with summer emergency rating of 353 MVA at 115 kV.		Dominion (100%)
b2648	Rebuild Carolina – Kerr Dam 115 kV Line #90 (38.7 miles) to current standards with summer emergency rating of 353 MVA 115 kV.		Dominion (100%)
b2649	Rebuild Clubhouse – Carolina 115 kV Line #130 (17.8 miles) to current standards with summer emergency rating of 353 MVA at 115 kV.		Dominion (100%)

Required 1	ransmission Emiancements Anni	ıcıı Kevenue Kequiremeni	Responsible Customer(s)
b2649.1	Rebuild of 1.7 mile tap to Metcalf and Belfield DP (MEC) due to poor condition. The existing summer rating of the tap is 48 MVA and existing conductor is 4/0 ACSR on wood H-frames. The proposed new rating is 176 MVA using 636 ACSR conductor		Dominion (100%)
b2649.2	Rebuild of 4.1 mile tap to Brinks DP (MEC) due to wood poles built in 1962. The existing summer rating of the tap is 48 MVA and existing conductor is 4/0 ACSR and 393.6 ACSR on wood H-frames. The proposed new rating is 176 MVA using 636 ACSR conductor		Dominion (100%)
b2650	Rebuild Twittys Creek – Pamplin 115 kV Line #154 (17.8 miles) to current standards with summer emergency rating of 353 MVA at 115 kV.		Dominion (100%)

Required 116	ansmission Enhancements Annu	iai Revenue Requirement	Responsible Customer(s)
b2651	Rebuild Buggs Island – Plywood 115 kV Line #127 (25.8 miles) to current standards with summer emergency rating of 353 MVA at 115 kV. The line should be rebuilt for 230 kV and operated at 115 kV.		Dominion (100%)
b2652	Rebuild Greatbridge – Hickory 115 kV Line #16 and Greatbridge – Chesapeake E.C. to current standard with summer emergency rating of 353 MVA at 115 kV.		Dominion (100%)
b2653.1	Build 20 mile 115 kV line from Pantego to Trowbridge with summer emergency rating of 353 MVA.		Dominion (100%)
b2653.2	Install 115 kV four-breaker ring bus at Pantego		Dominion (100%)
b2653.3	Install 115 kV breaker at Trowbridge		Dominion (100%)
b2654.1	Build 15 mile 115 kV line from Scotland Neck to S Justice Branch with summer emergency rating of 353 MVA. New line will be routed to allow HEMC to convert Dawson's Crossroads RP from 34.5 kV to 115 kV.		Dominion (100%)
b2654.2	Install 115 kV three-breaker ring bus at S Justice Branch		Dominion (100%)
b2654.3	Install 115 kV breaker at Scotland Neck		Dominion (100%)

		<u> </u>	
b2665	Rebuild the Cunningham – Dooms 500 kV line		Dominion (100%)
b2686	Pratts Area Improvement		Dominion (100%)
b2686.1	Build a 230 kV line from Remington Substation to Gordonsville Substation utilizing existing ROW		Dominion (100%)
b2686.11	Upgrading sections of the Gordonsville – Somerset 115 kV circuit		Dominion (100%)
b2686.12	Upgrading sections of the Somerset – Doubleday 115 kV circuit		Dominion (100%)
b2686.13	Upgrading sections of the Orange – Somerset 115 kV circuit		Dominion (100%)
b2686.14	Upgrading sections of the Mitchell – Mt. Run 115 kV circuit		Dominion (100%)
b2686.2	Install a 3rd 230/115 kV transformer at Gordonsville Substation		Dominion (100%)

^{*}Neptune Regional Transmission System, LLC

^{**} East Coast Power, LLC ***Hudson Transmission Partners, LLC

Required Transmission Emilancements Annual Revenue Requirement Responsible Customer(s)			in Responsible Customer(s)
b2686.3	Upgrade Line 2088 between Gordonsville Substation and Louisa CT Station		Dominion (100%)
b2717.1	De-energize Davis – Rosslyn #179 and #180 69 kV lines		Dominion (100%)
b2717.2	Remove splicing and stop joints in manholes		Dominion (100%)
b2717.3	Evacuate and dispose of insulating fluid from various reservoirs and cables		Dominion (100%)
b2717.4	Remove all cable along the approx. 2.5 mile route, swab and cap-off conduits for future use, leave existing communication fiber in place		Dominion (100%)
b2719.1	Expand Perth substation and add a 115 kV four breaker ring		Dominion (100%)
b2719.2	Extend the Hickory Grove DP tap 0.28 miles to Perth and terminate it at Perth		Dominion (100%)
b2719.3	Split Line #31 at Perth and terminate it into the new ring bus with 2 breakers separating each of the line terminals to prevent a breaker failure from taking out both 115 kV lines		Dominion (100%)
b2720	Replace the Loudoun 500 kV 'H1T569' breakers with 50kA breaker		Dominion (100%)
b2729	Optimal Capacitors Configuration: New 175 MVAR capacitor at Brambleton, new 175 MVAR capacitor at Ashburn, new 300 MVAR capacitor at Shelhorm, new 150 MVAR capacitor at Liberty		AEC (1.96%) / BGE (14.37%) / Dominion (35.11%) / DPL (3.76%) / ECP (0.29%) / HTP (0.34%) / JCPL (3.31%) / ME (2.51%) / Neptune (0.63%) / PECO (6.26%) / PEPCO (20.23%) / PPL (3.94%) /PSEG (7.29%)

Required Tra	ansmission Enhancements Annual	Revenue Requirement	Responsible Customer(s)
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP (14.16%)
			/ APS (5.73%) / ATSI
			(7.88%) / BGE (4.22%) /
			ComEd (13.31%) / Dayton
			(2.11%) / DEOK (3.29%) /
	Rebuild the Carson – Rogers Rd 500 kV circuit		DL (1.75%) / DPL (2.50%) /
b2744			Dominion (12.86%) / EKPC
02744			(1.87%) / JCPL (3.74%) / ME
			(1.90%) / NEPTUNE*
			(0.44%) / PECO (5.34%) /
			PENELEC (1.89%) / PEPCO
			(3.99%) / PPL (4.84%) /
			PSEG (6.26%) / RE (0.26%)
			DFAX Allocation:
			Dominion (100%)
	Rebuild 21.32 miles of		
b2745	existing line between		Dominion (100%)
027.10	Chesterfield – Lakeside 230 kV		2 03333333 (10070)
	Rebuild Line #137 Ridge Rd		
b2746.1	 Kerr Dam 115 kV, 8.0 		Dominion (100%)
02/40.1	miles, for 346 MVA summer		Dominion (100%)
	emergency rating Rebuild Line #1009 Ridge Rd		
	- Chase City 115 kV, 9.5		
b2746.2	miles, for 346 MVA summer		Dominion (100%)
	emergency rating		
	Install a second 4.8 MVAR		
b2746.3	capacitor bank on the 13.8 kV bus of each transformer at		Dominion (100%)
	Ridge Rd		, , ,
b2747	Install a Motor Operated		
	Switch and SCADA control		
	between Dominion's		Dominion (100%)
	Gordonsville 115 kV bus and FirstEnergy's 115 kV line		
	I Hatchergy S 113 KV IIIIC		

required 11	ansmission Emancements – Annuai Revenue Requirement	Responsible Customer(s)
b2757	Install a +/-125 MVAr Statcom at Colington 230 kV	Dominion (100%)
b2758	Rebuild Line #549 Dooms – Valley 500kV	Dominion (100%)
b2759	Rebuild Line #550 Mt. Storm - Valley 500kV	Dominion (100%)
b2800	The 7 mile section from Dozier to Thompsons Corner of line #120 will be rebuilt to current standards using 768.2 ACSS conductor with a summer emergency rating of 346 MVA at 115 kV. Line is proposed to be rebuilt on single circuit steel monopole structure	Dominion (100%)
b2801	Lines #76 and #79 will be rebuilt to current standard using 768.2 ACSS conductor with a summer emergency rating of 346 MVA at 115 kV. Proposed structure for rebuild is double circuit steel monopole structure	Dominion (100%)
b2802	Rebuild Line #171 from Chase City – Boydton Plank Road tap by removing end- of-life facilities and installing 9.4 miles of new conductor. The conductor used will be at current standards with a summer emergency rating of 393 MVA at 115kV	Dominion (100%)
b2815	Build a new Pinewood 115kV switching station at the tap serving North Doswell DP with a 115kV four breaker ring bus	Dominion (100%)
b2842	Update the nameplate for Mount Storm 500 kV "57272" to be 50kA breaker	Dominion (100%)
b2843	Replace the Mount Storm 500 kV "G2TY" with 50kA breaker	Dominion (100%)
b2844	Replace the Mount Storm 500 kV "G2TZ" with 50kA breaker	Dominion (100%)

Virginia Electric and Power Company (cont.)

xequirea 17	ansmission Enhancements - Annual Revenue R	requirement Responsible Customer(s)
b2845	Update the nameplate for Mount Storm 500 kV "G3TSX1" to be 50kA breaker	Dominion (100%)
b2846	Update the nameplate for Mount Storm 500 kV "SX172" to be 50kA breaker	Dominion (100%)
b2847	Update the nameplate for Mount Storm 500 kV "Y72" to be 50kA breaker	Dominion (100%)
b2848	Replace the Mount Storm 500 kV "Z72" with 50kA breaker	Dominion (100%)
b2871	Rebuild 230 kV line #247 from Swamp to Suffolk (31 miles) to current standards with a summer emergency rating of 1047 MVA at 230 kV	Dominion (100%)
b2876	Rebuild line #101 from Mackeys — Creswell 115 kV, 14 miles, with double circuit structures. Install one circuit with provisions for a second circuit. The conductor used will be at current standards with a summer emergency rating of 262 MVA at 115 kV	Dominion (100%)
b2877	Rebuild line #112 from Fudge Hollow – Lowmoor 138 kV (5.16 miles) to current standards with a summer emergency rating of 314 MVA at 138 kV	Dominion (100%)
b2899	Rebuild 230 kV line #231 to current standard with a summer emergency rating of 1046 MVA. Proposed conductor is 2-636 ACSR	Dominion (100%)
b2900	Build a new 230/115 kV switching station connecting to 230 kV network line #2014 (Earleys – Everetts). Provide a 115 kV source from the new station to serve Windsor DP	Dominion (100%)

Virginia Electric and Power Company (cont.)

Required Tr	ansmission Enhancements Annual Revenue Requirement	Responsible Customer(s)
b2922	Rebuild 8 of 11 miles of 230 kV lines #211 and #228 to current standard with a summer emergency rating of 1046 MVA for rebuilt section. Proposed conductor is 2-636 ACSR	Dominion (100%)
b2928	Rebuild four structures of 500 kV line #567 from Chickahominy to Surry using galvanized steel and replace the river crossing conductor with 3-1534 ACSR. This will increase the line #567 line rating from 1954 MVA to 2600 MVA	Dominion (100%)
b2929	Rebuild 230 kV line #2144 from Winfall to Swamp (4.3 miles) to current standards with a standard conductor (bundled 636 ACSR) having a summer emergency rating of 1047 MVA at 230 kV	Dominion (100%)
<u>b2960</u>	Replace fixed series capacitors on 500 kV Line #547 at Lexington and on 500 kV Line #548 at Valley	Dominion (100%)
<u>b2961</u>	Rebuild approximately 3 miles of Line #205 & Line #2003 from Chesterfield to Locks & Poe respectively	Dominion (100%)
<u>b2962</u>	Split Line #227 (Brambleton — Beaumeade 230 kV) and terminate into existing Belmont substation	Dominion (100%)
<u>b2963</u>	Reconductor the Woodbridge to Occoquan 230 kV line segment of Line #2001 with 1047 MVA conductor and replace line terminal equipment at Possum Point, Woodbridge, and Occoquan	Dominion (100%)

SCHEDULE 12 – APPENDIX A

(23) American Transmission Systems, Inc.

Required T	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2019.2	Terminate Burger – Longview 138 kV, Burger – Brookside 138 kV, Burger – Cloverdale 138 kV #1, and Burger – Harmon 138 kV #2 into Holloway substation; Loop Burger – Harmon #1 138 kV and Burger – Knox 138 kV into Holloway substation		ATSI (100%)
b2019.3	Reconfigure Burger 138 kV substation to accommodate two 138 kV line exits and generation facilities		ATSI (100%)
b2019.4	Remove both Burger 138 kV substations (East and West 138 kV buses) and all 138 kV lines on the property		ATSI (100%)
b2019.5	Terminate and de- energize the 138 kV lines on the last structure before the Burger Plant property		ATSI (100%)
b2122.1	Reconductor the ATSI portion of the Howard – Brookside 138 kV line		ATSI (100%)
b2122.2	Upgrade terminal equipment at Brookside on the Howard – Brookside 138 kV line to achieve ratings of 252/291 (SN/SE)		ATSI (100%)
b2188	Revise the reclosing for the Bluebell 138 kV breaker '301-B-94'		ATSI (100%)
b2192	Replace the Longview 138 kV breaker '651-B-32'		ATSI (100%)
b2193	Replace the Lowellville 138 kV breaker '1-10-B 4'		ATSI (100%)

Required T	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2195	Replace the Roberts 138 kV breaker '601-B-60'		ATSI (100%)
b2196	Replace the Sammis 138 kV breaker '780-B-76'		ATSI (100%)
b2262	New Castle Generating Station – Relocate 138kV, 69kV, and 23kV controls from the generating station building to new control building		ATSI (100%)
b2263	Niles Generation Station – Relocate 138kV and 23kV controls from the generation station building to new control building		ATSI (100%)
b2265	Ashtabula Generating Station – Relocate 138kV controls from the generating station building to new control building		ATSI (100%)
b2284	Increase the design operating temperature on the Cloverdale – Barberton 138kV line		ATSI (100%)
b2285	Increase the design operating temperature on the Cloverdale – Star 138kV line		ATSI (100%)
b2301	Reconductor 0.7 miles of 605 ACSR conductor on the Beaver Black River 138kV line		ATSI (100%)
b2301.1	Wave trap and line drop replacement at Beaver (312/380 MVA SN/SE)		ATSI (100%)
b2349	Replace the East Springfield 138kV breaker 211-B-63 with 40kA		ATSI (100%)
b2367	Replace the East Akron 138kV breaker 36-B-46 with 40kA		ATSI (100%)

Required T	ransmission Enhancements A	nnual Revenue Requirement	Responsible Customer(s)
b2413	Replace a relay at McDowell 138 kV substation		ATSI (100%)
b2434	Build a new London – Tangy 138 kV line		ATSI (100%)
b2435	Build a new East Springfield – London #2 138 kV line		ATSI (100%)
b2459	Install +260/-150 MVAR SVC at Lake Shore		ATSI (100%)
b2492	Replace the Beaver 138 kV breaker '426-B-2' with 63kA breaker		ATSI (100%)
b2493	Replace the Hoytdale 138kV breaker '83-B-30' with 63kA breaker		ATSI (100%)
b2557	At Avon substation, replace the existing 345/138 kV 448 MVA #92 transformer with a 560 MVA unit		ATSI (100%)
b2558	Close normally open switch A 13404 to create a Richland J Bus – Richland K Bus 138 kV line		ATSI (100%)
b2559	Reconductor the Black River – Lorain 138 kV line and upgrade Black River and Lorain substation terminal end equipment		ATSI (100%)
b2560	Construct a second 138 kV line between West Fremont and Hayes substation on open tower position of the West Fremont –Groton –Hayes 138 kV line		ATSI (100%)
b2616	Addition of 4th 345/138 kV transformer at Harding		ATSI (100%)

Required T	ransmission Enhancements An	inual Revenue Requirement	Responsible Customer(s)
b2673	Rebuild the existing double circuit tower line section from Beaver substation to Brownhelm Jct. approx. 2.8 miles		ATSI (100%)
b2674	Rebuild the 6.6 miles of Evergreen to Ivanhoe 138 kV circuit with 477 ACSS conductor		ATSI (100%)
b2675	Install 26.4 MVAR capacitor and associated terminal equipment at Lincoln Park 138 kV substation		ATSI (100%)
b2725	Build new 345/138 kV Lake Avenue substation w/ breaker and a half high side (2 strings), 2-345/138 kV transformers and breaker and a half (2 strings) low side (138 kV). Substation will tie Avon – Beaver 345 kV #1/#2 and Black River – Johnson #1/#2 lines		ATSI (100%)
b2725.1	Replace the Murray 138 kV breaker '453-B-4' with 40kA breaker		ATSI (100%)
b2742	Replace the Hoytdale 138 kV '83-B-26' and '83-B- 30' breakers with 63kA breakers		ATSI (100%)
b2753.4	Double capacity for 6 wire "Burger-Cloverdale No. 2" 138 kV line and connect at Holloway and "Point A"		ATSI (100%)
b2753.5	Double capacity for 6 wire "Burger-Longview" 138 kV line and connect at Holloway and "Point A"		ATSI (100%)
b2778	Add 2nd 345/138 kV transformer at Chamberlin substation		ATSI (100%)
b2780	Replace Bruce Mansfield 345 kV breaker 'B57' with an 80 kA breaker, and associated gang-operated disconnect switches D56 and D58		ATSI (100%)

	Tanishingston Emiliancements 7 in	maar revenae regamemen	(-)
b2869	Replace the Crossland 138 kV breaker "B-16" with a 40kA breaker		ATSI (100%)
b2875	Relocate the Richland to Ridgeville 138 kV line from Richland J bus to K, extend the K bus and install a new breaker		ATSI (100%)
b2896	Rebuild/Reconductor the Black River – Lorain 138 kV circuit		ATSI (100%)
b2897	Reconductor the Avon – Lorain 138 kV section and upgrade line drop at Avon		ATSI (100%)
b2898	Reconductor the Beaver – Black River 138 kV with 954Kcmil ACSS conductor and upgrade terminal equipment on both stations		ATSI (100%)
b2942.1	Install a 100 MVAR 345 kV shunt reactor at Hayes substation		ATSI (100%)
b2942.2	Install a 200 MVAR 345 kV shunt reactor at Bayshore substation		ATSI (100%)
<u>b2972</u>	Reconductor limiting span of Lallendorf – Monroe 345 kV		MISO (11.00%) / AEP (5.38%) / APS (4.27%) / ATSI (66.48%) / Dayton (2.71%) / Dominion (5.31%) / DL (4.85%)

Attachment C

Schedule 12 – Appendix A of the PJM Open Access Transmission Tariff

(Clean Format)

SCHEDULE 12 – APPENDIX A

(1) Atlantic City Electric Company

required 1	Tarishiission Emiancements Ani	iuai Revenue Requirement	Responsible Customer(s)
b2123	Upgrade the 69 kV bus at Laurel		AEC (100%)
b2226	Upgrade the Tackahoe to Mill 69 kV circuit		AEC (100%)
b2227	50 MVAR shunt reactor at Mickleton 230 kV and relocate Mickleton #1 230 69 kV transformer		AEC (100%)
b2228	+150/-100 MVAR SVC at Cedar 230 kV		AEC (100%)
b2296	Replace the Mickleton 230kV breaker PCB U with 63kA breaker		AEC (100%)
b2297	Replace the Mickleton 230kV breaker PCB V with 63kA breaker		AEC (100%)
b2305	Rebuild and reconductor 1.2 miles of the US Silica to US Silica #1 69 kV circuit		AEC (100%)
b2306	Rebuild and reconductor 1.67 miles of the US Silica #1 to W1-089 TAP 69 kV circuit		AEC (100%)
b2351	Reconductor section A of Corson - Sea Isle - Swainton 69 kV line		AEC (100%)
b2353	Upgrade the overcurrent protective relaying at Middle T3 and T4 138/69 kV transformers		AEC (100%)
b2354	Install second 230/69 kV transformer and 230 kV circuit breaker at Churchtown substation		AEC (100%)

Atlantic City Electric Company (cont.)

required 1	Tansinission Enhancements An	nual Revenue Requirement	Responsible Customer(s)
b2354.1	Replace Churchtown 69kV breaker 'D'		AEC (100%)
b2476	Install new Dennis 230/69 kV transformer		AEC (100%)
b2477	Upgrade 138 kV and 69 kV breakers at Corson substation		AEC (100%)
b2478	Reconductor 2.74 miles of Sherman - Lincoln 138 kV line and associated substation upgrades		AEC (100%)
b2479	New Orchard - Cardiff 230 kV line (remove, rebuild and reconfigure existing 138 kV line) and associated substation upgrades		AEC (68.57%) / JCPL (31.43%)
b2480.1	New Upper Pittsgrove - Lewis 138 kV line and associated substation upgrades		AEC (100%)
b2480.2	Relocate Monroe to Deepwater Tap 138 kV to Landis 138 kV and associated substation upgrades		AEC (100%)
b2480.3	New Landis - Lewis 138 kV line and associated substation upgrades		AEC (100%)
b2481	New Cardiff - Lewis #2 138 kV line and associated substation upgrades		AEC (100%)
b2489	Install a 100 MVAR capacitor at BL England		AEC (100%)

Atlantic City Electric Company (cont.)

Required I	ransmission Enhancements Anni	ual Revenue Requirement	Responsible Customer(s)
b2538	Replace the Mickleton 230kV 'MK' breaker with 63kA breaker		AEC (100%)
b2553	Replace Middle T3 138/69 kV transformer with 225 MVA nameplate		AEC (100%)
b2723.1	Replace the Mickleton 69 kV 'PCB A' breaker with 63kA breaker		AEC (100%)
b2723.2	Replace the Mickleton 69 kV 'PCB B' breaker with 63kA breaker		AEC (100%)
b2723.3	Replace the Mickleton 69 kV 'PCB C' breaker with 63kA breaker		AEC (100%)
b2723.4	Replace the Mickleton 69 kV 'PCB Q' breaker with 63kA breaker		AEC (100%)
b2839	Replace the Sickler 69 kV 'H' breaker with 63kA breaker		AEC (100%)
b2840	Replace the Sickler 69 kV 'M' breaker with 63kA breaker		AEC (100%)
b2841	Replace the Sickler 69 kV 'A' breaker with 63kA breaker		AEC (100%)
b2945.1	Rebuild the BL England – Middle Tap 138 kV line to 2000A on double circuited steel poles and new foundations		AEC (100%)
b2945.2	Reconductor BL England – Merion 138 kV (1.9 miles) line		AEC (100%)
b2945.3	Reconductor Merion – Corson 138 kV (8 miles) line		AEC (100%)

SCHEDULE 12 – APPENDIX A

(2) Baltimore Gas and Electric Company

Required 1	ransmission Enhancements	Annuai Revenue Requirement	Responsible Customer(s)
	Install a 115 kV tie		
	breaker at Wagner to		
b2219	create a separation from		BGE (100%)
	line 110535 and		
	transformer 110-2		
b2220	Install four 115 kV		BGE (100%)
02220	breakers at Chestnut Hill		BGE (100%)
	Install an SPS to trip		
b2221	approximately 19 MW		BGE (100%)
02221	load at Green St. and		BGE (100%)
	Concord		
	Install a 230/115kV		
	transformer at Raphael		
	Rd and construct		
	approximately 3 miles of		
b2307	115kV line from Raphael		BGE (100%)
	Rd. to Joppatowne.		
	Construct a 115kV three		
	breaker ring at		
	Joppatowne		
	Build approximately 3		
	miles of 115kV		
	underground line from		
	Bestgate tap to Waugh		
b2308	Chapel. Create two		BGE (100%)
	breaker bay at Waugh		
	Chapel to accommodate		
	the new underground		
	circuit		
	Build a new Camp Small		
b2396	115 kV station and install		BGE (100%)
	30 MVAR capacitor		

Baltimore Gas and Electric Company (cont.)

required 1	ransmission Emancements	Allitual Revenue Requirement	Responsible Customer(s)
b2396.1	Install a tie breaker at Mays Chapel 115 kV		BGE (100%)
	substation		
	Upgrade the Riverside		
	115kV substation strain		
	bus conductors on		
	circuits 115012 and		
b2567	115011 with double		BGE (100%)
	bundled 1272 ACSR to		
	achieve ratings of		
	491/577 MVA SN/SE on		
	both transformer leads		
	Reconductor Northwest -		
	Northwest #2 115kV		
b2568	110574 substation tie		BGE (100%)
02300	circuit with 2167 ACSR		BGL (100%)
	to achieve ratings of		
	400/462 MVA SN/SE		
	Conastone 230 kV		AEP (6.46%) / APS
	substation tie-in work		(8.74%) / BGE (19.74%) /
	(install a new circuit		ComEd (2.16%) / Dayton
b2752.6	breaker at Conastone		(0.59%) / DEOK (1.02%) /
02732.0	230 kV and upgrade any		DL (0.01%) / Dominion
	required terminal		(39.95%) / EKPC (0.45%) /
	equipment to terminate		PEPCO (20.88%)
	the new circuit)		, , ,
	D 1 / /D 1 11.1		AEP (6.46%) / APS
	Reconductor/Rebuild the		(8.74%) / BGE (19.74%) /
1 0750 7	two Conastone –		ComEd (2.16%) / Dayton
b2752.7	Northwest 230 kV lines		(0.59%) / DEOK (1.02%) /
	and upgrade terminal		DL (0.01%) / Dominion
	equipment on both ends		(39.95%) / EKPC (0.45%) / PEPCO (20.88%)
	Replace the Conastone		
h2752 0	230 kV '2322 B5'		DCE (1000/)
b2752.8	breaker with a 63kA		BGE (100%)
	breaker		

Baltimore Gas and Electric Company (cont.)

rtequired I		Tillian Revenue Requirement	rtesponsiere eusterner(s)
b2752.9	Replace the Conastone 230 kV '2322 B6' breaker with a 63kA breaker		BGE (100%)
b2766.1	Upgrade substation equipment at Conastone 500 kV to increase facility rating to 2826 MVA normal and 3525 MVA emergency		Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEC (0.05%) / APS (11.16%) / BGE (22.34%) / Dayton (2.18%) / DEOK (4.19%) / DPL (0.20%) / ECP** (1.03%) / EKPC (1.94%) / JCPL (10.82%) / NEPTUNE* (1.14%) / HTP*** (1.10%) / POSEIDON**** (0.63%) /
			PENELEC (0.06%) / PEPECO (18.97%) / PSEG (23.26%) / RECO (0.93%)

^{*}Neptune Regional Transmission System, LLC

^{**} East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

^{****}Poseidon Transmission 1, LLC

SCHEDULE 12 – APPENDIX A

Delmarva Power & Light Company (3)

ansimission Emancements Ai	inuai Kevenue Kequiremeni	Responsible Customer(s)
Build a new 138 kV line from Piney Grove – Wattsville		DPL (100%)
Reconductor the Harmony - Chapel St 138 kV circuit		DPL (100%)
Replace Terminal equipment at Silverside 69 kV substation		DPL (100%)
Implement high speed relaying utilizing OPGW on Red Lion – Hope Creek 500 kV line		Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
Interconnect the new Silver Run 230 kV substation with existing Red Lion – Cartanza and Red Lion – Cedar Creek 230 kV lines		AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
	Build a new 138 kV line from Piney Grove – Wattsville Reconductor the Harmony – Chapel St 138 kV circuit Replace Terminal equipment at Silverside 69 kV substation Implement high speed relaying utilizing OPGW on Red Lion – Hope Creek 500 kV line Interconnect the new Silver Run 230 kV substation with existing Red Lion – Cartanza and Red Lion – Cedar Creek 230 kV lines	Build a new 138 kV line from Piney Grove — Wattsville Reconductor the Harmony — Chapel St 138 kV circuit Replace Terminal equipment at Silverside 69 kV substation Implement high speed relaying utilizing OPGW on Red Lion — Hope Creek 500 kV line Interconnect the new Silver Run 230 kV substation with existing Red Lion — Cartanza and Red Lion — Cedar Creek

^{**}East Coast Power, LLC

^{***}Hudson Transmission Partners, LLC

Delmarva Power & Light Company (cont.)

		 • ` '
b2695	Rebuild Worcester – Ocean Pine 69 kV ckt. 1 to 1400A capability summer emergency	DPL (100%)
b2946	Convert existing Preston 69 kV substation to DPL's current design standard of a 3-breaker ring bus	DPL (100%)
b2947.1	Upgrade terminal equipment at DPL's Naamans substation (Darley - Naamans 69 kV)	DPL (100%)
b2947.2	Reconductor 0.11 mile section of Darley - Naamans 69 kV circuit	DPL (100%)
b2948	Upgrade terminal equipment at DPL's Silverside Road substation (Dupont Edge Moor – Silver R. 69 kV)	DPL (100%)

SCHEDULE 12 – APPENDIX A

(5) Mid-Atlantic Interstate Transmission, LLC for the Metropolitan Edison Company Zone

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / Loop the 2026 (TMI – EKPC (1.87%) / JCPL (3.74%) / b2006.1.1 Hosensack 500 kV) line ME (1.90%) / NEPTUNE* in to the Lauschtown (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PPL (100%) Upgrade relay at South b2006.2.1 Reading on the 1072 230 ME (100%) V line Replace the South Reading 69 kV '81342' b2006.4 ME (100%) breaker with 40kA breaker Replace the South Reading 69 kV '82842' b2006.5 ME (100%) breaker with 40kA breaker APS (8.30%) / BGE (14.70%) / Install 2nd Hunterstown DEOK (0.48%) / Dominion b2452 (36.92%) / ME (23.85%) / 230/115 kV transformer

PEPCO (15.75%)

Mid-Atlantic Interstate Transmission, LLC for the Metropolitan Edison Company Zone (cont.)

Required Tra	insmission Enhancements	Annual Revenue Requiremen	<u> </u>
b2452.1	Reconductor Hunterstown - Oxford 115 kV line		APS (8.30%) / BGE (14.70%) / DEOK (0.48%) / Dominion (36.92%) / ME (23.85%) / PEPCO (15.75%)
b2452.3	Replace the Hunterstown 115 kV breaker '96192' with 40 kA		ME (100%)
b2588	Install a 36.6 MVAR 115 kV capacitor at North Bangor substation		ME (100%)
b2637	Convert Middletown Junction 230 kV substation to nine bay double breaker configuration.		ME (100%)
b2644	Install a 28.8 MVAR 115 kV capacitor at the Mountain substation		ME (100%)
b2688.1	Lincoln Substation: Upgrade the bus conductor and replace CTs.		AEP (12.91%) / APS (19.04%) / ATSI (1.24%) / ComEd (0.35%) / Dayton (1.45%) / DEOK (2.30%) / DL (1.11%) / Dominion (44.85%) / EKPC (0.78%) / PEPCO (15.85%) / RECO (0.12%)
b2688.2	Germantown Substation: Replace 138/115 kV transformer with a 135/180/224 MVA bank. Replace Lincoln 115 kV breaker, install new 138 kV breaker, upgrade bus conductor and adjust/replace CTs.		AEP (12.91%) / APS (19.04%) / ATSI (1.24%) / ComEd (0.35%) / Dayton (1.45%) / DEOK (2.30%) / DL (1.11%) / Dominion (44.85%) / EKPC (0.78%) / PEPCO (15.85%) / RECO (0.12%)

Mid-Atlantic Interstate Transmission, LLC for the Metropolitan Edison Company Zone (cont.)

Required Tra	nsmission Enhancements	Annual Revenue Requiremen	it Responsible Customer(s)
	Upgrade terminal		AEP (6.46%) / APS (8.74%) /
	equipment at		BGE (19.74%) / ComEd
b2743.4	Hunterstown 500 kV on		(2.16%) / Dayton (0.59%) /
02743.4	the Conemaugh –		DEOK (1.02%) / DL (0.01%) /
	Hunterstown 500 kV		Dominion (39.95%) / EKPC
	circuit		(0.45%) / PEPCO (20.88%)
	Upgrade terminal		AEP (6.46%) / APS (8.74%) /
	equipment and required		BGE (19.74%) / ComEd
b2752.4	relay communication at		(2.16%) / Dayton (0.59%) /
02732.4	TMI 500 kV: on the		DEOK (1.02%) / DL (0.01%) /
	Beach Bottom – TMI		Dominion (39.95%) / EKPC
	500 kV circuit		(0.45%) / PEPCO (20.88%)
	Replace relay at West		
	Boyertown 69 kV station		
b2749	on the West Boyertown –		ME (100%)
	North Boyertown 69 kV		
	circuit		
	Upgrade bus conductor at		
	Gardners 115 kv		
b2765	substation; Upgrade bus		ME (100%)
02703	conductor and adjust CT		WIE (10070)
	ratios at Carlisle Pike 115		
	kV		
	Upgrade limiting 115 kV		
	switches on the 115 kV		
b2950	side of the 230/115 kV		ME (100%)
02930	Northwood substation		WIL (10070)
	and adjust setting on		
	limiting ZR relay		

SCHEDULE 12 – APPENDIX A

(7) Mid-Atlantic Interstate Transmission, LLC for the Pennsylvania Electric Company Zone

Required T	Transmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2212	Shawville Substation: Relocate 230 kV and 115 kV controls from the generating station building		PENELEC (100%)
b2293	to new control building Replace the Erie South 115 kV breaker 'Buffalo Rd' with 40kA breaker		PENELEC (100%)
b2294	Replace the Johnstown 115 kV breaker 'Bon Aire' with 40kA breaker		PENELEC (100%)
b2302	Replace the Erie South 115 kV breaker 'French #2' with 40kA breaker		PENELEC (100%)
b2304	Replace the substation conductor and switch at South Troy 115 kV substation		PENELEC (100%)
b2371	Install 75 MVAR capacitor at the Erie East 230 kV substation		PENELEC (100%)
b2441	Install +250/-100 MVAR SVC at the Erie South 230 kV station		PENELEC (100%)
b2442	Install three 230 kV breakers on the 230 kV side of the Lewistown #1, #2 and #3 transformers		PENELEC (100%)
b2450	Construct a new 115 kV line from Central City West to Bedford North		PENELEC (100%)
b2463	Rebuild and reconductor 115 kV line from East Towanda to S. Troy and upgrade terminal equipment at East Towanda, Tennessee Gas and South Troy		PENELEC (100%)

Required T	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
	Construct Warren 230 kV		
b2494	ring bus and install a		PENELEC (100%)
	second Warren 230/115		TENELLE (100%)
	kV transformer		
	Reconductor the North		
	Meshoppen – Oxbow-		
b2552.1	Lackawanna 230 kV		PENELEC (100%)
02332.1	circuit and upgrade		TENEEDE (10070)
	terminal equipment		
	(MAIT portion)		
	Replace the Warren 115		
b2573	kV 'B12' breaker with a		PENELEC (100%)
	40kA breaker		
	Reconfigure Pierce Brook		
1.4.5.5	345 kV station to a ring		
b2587	bus and install a 125		PENELEC (100%)
	MVAR shunt reactor at		
	the station		
	Replace relays at East		
b2621	Towanda and East Sayre		PENELEC (100%)
	115 kV substations		,
	(158/191 MVA SN/SE)		
	Replace wave trap, bus		
1.0677	conductor and relay at		DENEL EC (1000/)
b2677	Hilltop 115 kV substation.		PENELEC (100%)
	Replace relays at Prospect		
	and Cooper substations Convert the East Towarda		
	115 kV substation to		
b2678	breaker and half		PENELEC (100%)
	configuration		
b2670	Install a 115 kV Venango Jct. line breaker at		PENELEC (100%)
b2679	Edinboro South		FENELEC (100%)
	Install a 115 kV breaker		
b2680	on Hooversville #1 115/23		DENEL EC (100%)
			PENELEC (100%)
	kV transformer		
L2 (01	Install a 115 kV breaker		DENIEL EC (1000/)
b2681	on the Eclipse #2 115/34.5		PENELEC (100%)
	kV transformer		

Required 1	ransmission Ennancements Ar	inual Revenue Requirement	Responsible Customer(s)
b2682	Install two 21.6 MVAR capacitors at the Shade Gap 115 kV substation		PENELEC (100%)
b2683	Install a 36 MVAR 115 kV capacitor and associated equipment at Morgan Street substation		PENELEC (100%)
b2684	Install a 36 MVAR 115 kV capacitor at Central City West substation		PENELEC (100%)
b2685	Install a second 115 kV 3000A bus tie breaker at Hooversville substation		PENELEC (100%)
b2735	Replace the Warren 115 kV 'NO. 2 XFMR' breaker with 40kA breaker		PENELEC (100%)
b2736	Replace the Warren 115 kV 'Warren #1' breaker with 40kA breaker		PENELEC (100%)
b2737	Replace the Warren 115 kV 'A TX #1' breaker with 40kA breaker		PENELEC (100%)
b2738	Replace the Warren 115 kV 'A TX #2' breaker with 40kA breaker		PENELEC (100%)
b2739	Replace the Warren 115 kV 'Warren #2' breaker with 40kA breaker		PENELEC (100%)
b2740	Revise the reclosing of the Hooversville 115 kV 'Ralphton' breaker		PENELEC (100%)
b2741	Revise the reclosing of the Hooversville 115 kV 'Statler Hill' breaker		PENELEC (100%)

Required T	ransmission Enhancements A	nnual Revenue Requirement	Responsible Customer(s)
b2743.2	Tie in new Rice substation to Conemaugh – Hunterstown 500 kV		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)
b2743.3	Upgrade terminal equipment at Conemaugh 500 kV on the Conemaugh – Hunterstown 500 kV circuit		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)
b2748	Install two 28 MVAR capacitors at Tiffany 115 kV substation		PENELEC (100%)
b2767	Construct a new 345 kV breaker string with three (3) 345 kV breakers at Homer City and move the North autotransformer connection to this new breaker string		PENELEC (100%)
b2803	Reconductor 3.7 miles of the Bethlehem – Leretto 46 kV circuit and replace terminal equipment at Summit 46 kV		PENELEC (100%)
b2804	Install a new relay and replace 4/0 CU bus conductor at Huntingdon 46 kV station, on the Huntingdon – C tap 46 kV circuit		PENELEC (100%)
b2805	Install a new relay and replace 4/0 CU & 250 CU substation conductor at Hollidaysburg 46 kV station, on the Hollidaysburg – HCR Tap 46 kV circuit		PENELEC (100%)

required I	ransmission Enhancements Ai	nual Revenue Requirement	Responsible Customer(s)
	Install a new relay and		
b2806	replace meter at the		
	Raystown 46 kV		PENELEC (100%)
02000	substation, on the		I LINELLE (10070)
	Raystown – Smithfield 46		
	kV circuit		
	Replace the CHPV and		
	CRS relay, and adjust the		
	IAC overcurrent relay trip		
b2807	setting; or replace the relay		PENELEC (100%)
	at Eldorado 46 kV		
	substation, on the Eldorado		
	 Gallitzin 46 kV circuit 		
	Adjust the JBC overcurrent		
	relay trip setting at		
	Raystown 46 kV, and		
	replace relay and 4/0 CU		
b2808	bus conductor at		PENELEC (100%)
	Huntingdon 46 kV		
	substations, on the		
	Raystown – Huntingdon 46		
	kV circuit		
	Replace Seward 115 kV		
b2865	breaker "Jackson Road"		PENELEC (100%)
	with 63kA breaker		
	Replace Seward 115 kV		
b2866	breaker "Conemaugh N."		PENELEC (100%)
	with 63kA breaker		
	Replace Seward 115 kV		
b2867	breaker "Conemaugh S."		PENELEC (100%)
	with 63kA breaker		, , ,
	Replace Seward 115 kV		
b2868	breaker "No.8 Xfmr" with		PENELEC (100%)
	63kA breaker		
	Install two 345 kV 80		
b2944	MVAR shunt reactors at		PENELEC (100%)
	Mainesburg station		1 21,2220 (10070)
<u> </u>	1.10000000 Stanton		

required 1	Taristrussion Linauccincias 741	inuai Revenue Requirement	responsible edistorier(s)
b2951	Seward, Blairsville East, Shelocta work		PENELEC (100%)
b2951.1	Upgrade Florence 115 kV line terminal equipment at Seward SS		PENELEC (100%)
b2951.2	Replace Blairsville East / Seward 115 kV line tuner, coax, line relaying and carrier set at Shelocta SS		PENELEC (100%)
b2951.3	Replace Seward / Shelocta 115 kV line CVT, tuner, coax, and line relaying at Blairsville East SS		PENELEC (100%)
b2952	Replace the North Meshoppen #3 230/115 kV transformer eliminating the old reactor and installing two breakers to complete a 230 kV ring bus at North Meshoppen		PENELEC (100%)
b2953	Replace the Keystone 500 kV breaker "NO. 14 Cabot" with 50kA breaker		PENELEC (100%)
b2954	Replace the Keystone 500 kV breaker "NO. 16 Cabot" with 50kA breaker		PENELEC (100%)

SCHEDULE 12 – APPENDIX A

(12) Public Service Electric and Gas Company

Required Tra	ansmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2218	Rebuild 4 miles of overhead line from Edison - Meadow Rd - Metuchen (Q 1317)		HTP (36.49%) / ECP** (63.51%)
b2239	50 MVAR reactor at Saddlebrook 230 kV		PSEG (100%)
b2240	50 MVAR reactor at Athenia 230 kV		PSEG (100%)
b2241	50 MVAR reactor at Bergen 230 kV		PSEG (100%)
b2242	50 MVAR reactor at Hudson 230 kV		PSEG (100%)
b2243	Two 50 MVAR reactors at Stanley Terrace 230 kV		PSEG (100%)
b2244	50 MVAR reactor at West Orange 230 kV		PSEG (100%)
b2245	50 MVAR reactor at Aldene 230 kV		PSEG (100%)
b2246	150 MVAR reactor at Camden 230 kV		PSEG (100%)
b2247	150 MVAR reactor at Gloucester 230 kV		PSEG (100%)
b2248	50 MVAR reactor at Clarksville 230 kV		PSEG (100%)
b2249	50 MVAR reactor at Hinchmans 230 kV		PSEG (100%)
b2250	50 MVAR reactor at Beaverbrook 230 kV		PSEG (100%)
b2251	50 MVAR reactor at Cox's Corner 230 kV		PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

The Annual Revenue Requirement for all Public Service Electric and Gas Company Projects (Required Transmission Enhancements) in this Section 12 shall be as specified in Attachment 7 of Attachment H-10A and under the procedures detailed in Attachment H-10B.

^{**}East Coast Power, L.L.C.

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Eliminate the Sewaren 138 kV bus by installing a new b2276 PSEG (100%) 230 kV bay at Sewaren 230 kV Convert the two 138 kV circuits from Sewaren -Metuchen to 230 kV b2276.1 PSEG (100%) circuits including Lafayette and Woodbridge substation Reconfigure the Metuchen 230 kV station to b2276.2 PSEG (100%) accommodate the two converted circuits Replace disconnect switches at Kilmer, Lake Nilson and Greenbrook b2290 PSEG (100%) 230 kV substations on the Raritian River - Middlesex (I-1023) circuit Replace circuit switcher at Lake Nelson 230 kV b2291 substation on the Raritian PSEG (100%) River - Middlesex (W-1037) circuit Replace the Salem 500 kV b2295 breaker 10X with 63kA PSEG (100%) breaker Install all 69kV lines to interconnect Plainfield, Greenbrook, and b2421 PSEG (100%) Bridgewater stations and establish the 69kV network Install two 18MVAR capacitors at Plainfield b2421.1 PSEG (100%) and S. Second St substation

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Install a second four (4) breaker 69kV ring bus at PSEG (100%) b2421.2 **Bridgewater Switching** Station **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL Convert the Bergen – (2.50%) / Dominion (12.86%) / Marion 138 kV path to EKPC (1.87%) / JCPL (3.74%) / b2436.10 double circuit 345 kV and ME (1.90%) / NEPTUNE* associated substation (0.44%) / PECO (5.34%) / upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (100%) **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK Convert the Marion -(3.29%) / DL (1.75%) / DPL Bayonne "L" 138 kV (2.50%) / Dominion (12.86%) / b2436.21 circuit to 345 kV and any EKPC (1.87%) / JCPL (3.74%) / associated substation ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

		 1
b2436.22	Convert the Marion - Bayonne "C" 138 kV circuit to 345 kV and any associated substation upgrades	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%)
b2436.33	Construct a new Bayway – Bayonne 345 kV circuit and any associated substation upgrades	PSEG (100%)
b2436.34	Construct a new North Ave – Bayonne 345 kV circuit and any associated substation upgrades	PSEG (100%)

^{*}Neptune Regional Transmission System, LLC **East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Construct a new North Ave - Airport 345 kV b2436.50 PSEG (100%) circuit and any associated substation upgrades Relocate the underground portion of North Ave -Linden "T" 138 kV circuit b2436.60 to Bayway, convert it to *PSEG* (96.13%) / *RE* (3.87%) 345 kV, and any associated substation upgrades Construct a new Airport -Bayway 345 kV circuit b2436.70 PSEG (100%) and any associated substation upgrades **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK Relocate the overhead (3.29%) / DL (1.75%) / DPL portion of Linden - North (2.50%) / Dominion (12.86%) / Ave "T" 138 kV circuit to b2436.81 EKPC (1.87%) / JCPL (3.74%) / Bayway, convert it to 345 ME (1.90%) / NEPTUNE* kV, and any associated (0.44%) / PECO (5.34%) / substation upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (96.13%) / RE (3.87%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL Convert the Bayway -Linden "Z" 138 kV circuit (2.50%) / Dominion (12.86%) / b2436.83 to 345 kV and any EKPC (1.87%) / JCPL (3.74%) / associated substation ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (96.13%) / RE (3.87%) **Load-Ratio Share Allocation:** AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL Convert the Bayway -(2.50%) / Dominion (12.86%) / Linden "W" 138 kV EKPC (1.87%) / JCPL (3.74%) / b2436.84 circuit to 345 kV and any ME (1.90%) / NEPTUNE* associated substation (0.44%) / PECO (5.34%) / upgrades PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) **DFAX Allocation:** PSEG (96.13%) / RE (3.87%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required Tra	ansmission Enhancements A	Annual Revenue Requirement Responsible Customer(s)
b2436.85	Convert the Bayway – Linden "M" 138 kV circuit to 345 kV and any associated substation upgrades	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: PSEG (96.13%) / RE (3.87%)
b2436.90	Relocate Farragut - Hudson "B" and "C" 345 kV circuits to Marion 345 kV and any associated substation upgrades	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: PSEG (96.13%) / RE (3.87%)
b2436.91	Relocate the Hudson 2 generation to inject into the 345 kV at Marion and any associated upgrades	PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

		1 1
b2437.10	New Bergen 345/230 kV transformer and any associated substation upgrades	PSEG (96.13%) / RE (3.87%)
b2437.11	New Bergen 345/138 kV transformer #1 and any associated substation upgrades	PSEG (100%)
b2437.20	New Bayway 345/138 kV transformer #1 and any associated substation upgrades	PSEG (96.13%) / RE (3.87%)
b2437.21	New Bayway 345/138 kV transformer #2 and any associated substation upgrades	PSEG (96.13%) / RE (3.87%)
b2437.30	New Linden 345/230 kV transformer and any associated substation upgrades	PSEG (96.13%) / RE (3.87%)
b2437.33	New Bayonne 345/69 kV transformer and any associated substation upgrades	PSEG (100%)
b2438	Install two reactors at Tosco 230 kV	PSEG (100.00%)
b2439	Replace the Tosco 138kV breaker 'CB1/2 (CBT)' with 63kA	PSEG (100.00%)
b2474	Rebuild Athenia 138 kV to 80kA	PSEG (100%)
b2589	Install a 100 MVAR 230 kV shunt reactor at Mercer station	PSEG (100%)
b2590	Install two 75 MVAR 230 kV capacitors at Sewaren station	PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required Tra	Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s)		
b2633.3	Install an SVC at New Freedom 500 kV substation	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)	
b2633.4	Add a new 500 kV bay at Hope Creek (Expansion of Hope Creek substation)	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)	

b2633.5	Add a new 500/230 kV autotransformer at Hope Creek and a new Hope Creek 230 kV substation	AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
b2633.8	Implement high speed relaying utilizing OPGW on Salem – Orchard 500 kV, Hope Creek – New Freedom 500 kV, New Freedom - Salem 500 kV, Hope Creek – Salem 500 kV, and New Freedom – Orchard 500 kV lines	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

b2633.91	Implement changes to the tap settings for the two Salem units' step up transformers	AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
b2633.92	Implement changes to the tap settings for the Hope Creek unit's step up transformers	AEC (0.01%) / DPL (99.98%) / JCPL (0.01%)
b2702	Install a 350 MVAR reactor at Roseland 500 kV	Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%)
b2703	Install a 100 MVAR reactor at Bergen 230 kV	PSEG (100%) PSEG (100%)
b2704	Install a 150 MVAR reactor at Essex 230 kV	PSEG (100%)
b2705	Install a 200 MVAR reactor (variable) at Bergen 345 kV	PSEG (100%)
b2706	Install a 200 MVAR reactor (variable) at Bayway 345 kV	PSEG (100%)
b2707	Install a 100 MVAR reactor at Bayonne 345 kV	PSEG (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Public Service Electric and Gas Company (cont.)

Required 11	ansmission Emancements Anni	iai Kevenue Kequitement	Responsible Customer(s)
b2712	Replace the Bergen 138 kV '40P'breaker with 80kA breaker		PSEG (100%)
b2713	Replace the Bergen 138 kV '90P' breaker with 80kA breaker		PSEG (100%)
b2722	Reconductor the 1 mile Bergen – Bergen GT 138 kV circuit (B-1302)		PSEG (100%)
b2755	Build a third 345 kV source into Newark Airport		PSEG (100%)
b2810.1	Install second 230/69 kV transformer at Cedar Grove		PSEG (100%)
b2810.2	Build a new 69 kV circuit from Cedar Grove to Great Notch		PSEG (100%)
b2811	Build 69 kV circuit from Locust Street to Delair		PSEG (100%)
b2812	Construct River Road to Tonnelle Avenue 69kV Circuit		PSEG (100%)
b2825.1	Install 2X50 MVAR shunt reactors at Kearny 230 kV substation		PSEG (100%)
b2825.2	Increase the size of the Hudson 230 kV, 2X50 MVAR shunt reactors to 2X100 MVAR		PSEG (100%)
b2825.3	Install 2X100 MVAR shunt reactors at Bayway 345 kV substation		PSEG (100%)
b2825.4	Install 2X100 MVAR shunt reactors at Linden 345 kV substation		PSEG (100%)
b2835	Convert the R-1318 and Q1317 (Edison – Metuchen) 138 kV circuits to one 230 kV circuit		PSEG (100%)

Public Service Electric and Gas Company (cont.)

Required 11	ansmission Enhancements Ai	nnual Revenue Requiremen	it Responsible Customer(s)
1.2026	Convert the N-1340 and T 1372/D-1330 (Brunswick		DGEG (100%)
b2836	Trenton) 138 kV circuits to		PSEG (100%)
	230 kV circuits		
	Convert the F-1358/Z1326	5	
	and K1363/Y-1325		
b2837	(Trenton – Burlington) 13	R	PSEG (100%)
02027	kV circuits to 230 kV		1523 (10070)
	circuits		
	Build new 138/26 kV		
	Newark GIS station in a		
	building (layout #1A)		
b2870	located adjacent to the		PSEG (100%)
020.0	existing Newark Switch an	d	1220 (10070)
	demolish the existing		
	Newark Switch		
	Third Source for		
<i>b</i> 2933	Springfield Rd. and Stanle	y	PSEG (100%)
	Terrace Stations		` ,
	Construct a 230/69 kV		
b2933.1	station at Springfield		PSEG (100%)
	Construct a 230/69 kV		
<i>b</i> 2933.2	station at Stanley Terrace		PSEG (100%)
	Construct a 69 kV network		
		3	
b2933.3	between Front Street,		PSEG (100%)
	Springfield and Stanley		
	Terrace Build a new 69 kV line		
b2934		ta	DSEC (1000/)
02934	between Hasbrouck Height and Carlstadt	.s	PSEG (100%)
b2935	Third Supply for Runnemede 69 kV and		PSEG (100%)
04933	Woodbury 69 kV		1 SEG (10070)
	Build a new 230/69 kV		
	switching substation at		
b2935.1	Hilltop utilizing the PSE&		PSEG (100%)
	property and the K-2237		1 SEG (10070)
	230 kV line		
	Build a new line between		
b2935.2	Hilltop and Woodbury 69		PSEG (100%)
02733.2	kV providing the 3rd suppl		1 5LO (10070)
	1 K. providing the sta suppl	<i>y</i>	

Public Service Electric and Gas Company (cont.)

b2935.3	Convert Runnemede's straight bus to a ring bus and construct a 69 kV line from Hilltop to Runnemede 69 kV	PSEG (100%)
b2955	Wreck and rebuild the VFT - Warinanco - Aldene 230 kV circuit with paired conductor	JCPL (93.78%) / NEPTUNE* (6.22%)
b2956	Replace existing cable on Cedar Grove - Jackson Rd. with 5000kcmil XLPE cable	JCPL (0.05%) / NEPTUNE* (0.01%) / PSEG (96.07%) / RE (3.87%)

SCHEDULE 12 – APPENDIX A

(14) Monongahela Power Company, The Potomac Edison Company, and West Penn Power Company, all doing business as Allegheny Power

Required Transmission Enhancements Responsible Customer(s) Annual Revenue Requirement Reconductor 0.33 miles of the Parkersburg - Belpre line and upgrade b2117 APS (100%) Parkersburg terminal equipment Add 44 MVAR Cap at b2118 APS (100%) New Martinsville Six-Wire Lake Lynn b2120 APS (100%) Lardin 138 kV circuits Replace Weirton 138 kV breaker "Wylie Ridge 210" b2142 APS (100%) with 63 kA breaker Replace Weirton 138 kV b2143 breaker "Wylie Ridge 216" APS (100%) with 63 kA breaker Replace relays at Mitchell b2174.8 APS (100%) substation Replace primary relay at b2174.9 APS (100%) Piney Fork substation Perform relay setting b2174.10 changes at Bethel Park APS (100%) substation Armstrong Substation: Relocate 138 kV controls b2213 from the generating station APS (100%) building to new control building Albright Substation: Install a new control building in the switchyard and relocate b2214 controls and SCADA APS (100%) equipment from the generating station building the new control center Rivesville Switching Station: Relocate controls and SCADA equipment b2215 APS (100%) from the generating station building to new control building

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Willow Island: Install a new 138 kV cross bus at Belmont Substation and reconnect and reconfigure b2216 APS (100%) the 138 kV lines to facilitate removal of the equipment at Willow Island switching station 130 MVAR reactor at b2235 APS (100%) Monocacy 230 kV Install a 32.4 MVAR b2260 APS (100%) capacitor at Bartonville Install a 33 MVAR b2261 APS (100%) capacitor at Damascus Replace 1000 Cu substation conductor and b2267 APS (100%) 1200 amp wave trap at Marlowe Reconductor 6.8 miles of 138kV 336 ACSR with b2268 APS (100%) 336 ACSS from Double Toll Gate to Riverton Reconductor from Collins b2299 Ferry - West Run 138 kV APS (100%) with 556 ACSS Reconductor from Lake b2300 APS (100%) Lynn - West Run 138 kV Install 39.6 MVAR Capacitor at Shaffers b2341 APS (100%) Corner 138 kV Substation Construct a new 138 kV switching station (Shuman Hill substation), which is b2342 APS (100%) next the Mobley 138 kV substation and install a 31.7 MVAR capacitor Install a 31.7 MVAR b2343 capacitor at West Union APS (100%) 138 kV substation

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Install a 250 MVAR SVC b2362 APS (100%) at Squab Hollow 230 kV Install a 230 kV breaker at b2362.1 Squab Hollow 230 kV APS (100%) substation Convert the Shingletown b2363 230 kV bus into a 6 APS (100%) breaker ring bus Install a new 230/138 kV transformer at Squab Hollow 230 kV substation. Loop the Forest - Elko 230 b2364 APS (100%) kV line into Squab Hollow. Loop the Brookville - Elko 138 kV line into Squab Hollow Install a 44 MVAR 138 kV b2412 capacitor at the Hempfield APS (100%) 138 kV substation Install breaker and a half 138 kV substation (Waldo Run) with 4 breakers to accommodate service to b2433.1 MarkWest Sherwood APS (100%) Facility including metering which is cut into Glen Falls Lamberton 138 kV line Install a 70 MVAR SVC at the new WaldoRun 138 kV b2433.2 APS (100%) substation Install two 31.7 MVAR capacitors at the new b2433.3 APS (100%) WaldoRun 138 kV substation Replace the Weirton 138 kV breaker 'WYLIE b2424 APS (100%) RID210' with 63 kA breakers Replace the Weirton 138 kV breaker 'WYLIE b2425 APS (100%) RID216' with 63 kA breakers

Required Tra	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2426	Replace the Oak Grove 138 kV breaker 'OG1' wit	h	APS (100%)
b2427	63 kA breakers Replace the Oak Grove 138 kV breaker 'OG2' wit 63 kA breakers	h	APS (100%)
b2428	Replace the Oak Grove 138 kV breaker 'OG3' wit 63 kA breakers	h	APS (100%)
b2429	Replace the Oak Grove 138 kV breaker 'OG4' wit 63 kA breakers	h	APS (100%)
b2430	Replace the Oak Grove 138 kV breaker 'OG5' wit 63 kA breakers	h	APS (100%)
b2431	Replace the Oak Grove 138 kV breaker 'OG6' wit 63 kA breakers	h	APS (100%)
b2432	Replace the Ridgeley 138 kV breaker 'RC1' with a 4 kA rated breaker		APS (100%)
b2440	Replace the Cabot 138kV breaker 'C9-KISKI VLY with 63kA		APS (100%)
b2472	Replace the Ringgold 133 kV breaker 'RCM1' with 40kA breakers		APS (100%)
b2473	Replace the Ringgold 133 kV breaker '#4 XMFR' with 40kA breakers	8	APS (100%)
b2475	Construct a new line between Oak Mound 138 kV substation and Waldo Run 138 kV substation		APS (100%)
b2545.1	Construct a new 138 kV substation (Shuman Hill substation) connected to the Fairview –Willow Island (84) 138kV line		APS (100%)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Install a ring bus station with five active positions b2545.2 and two 52.8 MVAR APS (100%) capacitors with 0.941 mH reactors Install a +90/-30 MVAR b2545.3 SVC protected by a 138 APS (100%) kV breaker Remove the 31.7 MVAR b2545.4 capacitor bank at Mobley APS (100%) 138 kV Install a 51.8 MVAR (rated) 138 kV capacitor at b2546 APS (100%) Nyswaner 138 kV substation Construct a new 138 kV b2547.1 six breaker ring bus APS (100%) Hillman substation Loop Smith-Imperial 138 kV line into the new APS (100%) b2547.2 Hillman substation Install +125/-75 MVAR b2547.3 APS (100%) SVC at Hillman substation Install two 31.7 MVAR b2547.4 APS (100%) 138 kV capacitors Eliminate clearance de-rate on Wylie Ridge – Smith 138 kV line and upgrade b2548 terminals at Smith 138 kV, APS (100%) new line ratings 294 MVA (Rate A)/350 MVA (Rate B) Relocate All Dam 6 138 b2612.1 kV line and the 138 kV APS (100%) line to AE units 1&2 Install 138 kV, 3000A bustie breaker in the open bustie position next to the b2612.2 APS (100%) Shaffers corner 138 kV line

Required Tra	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2612.3	Install a 6-pole manual switch, foundation, control cable, and all associated facilities		APS (100%)
b2666	Yukon 138 kV Breaker Replacement		APS (100%)
b2666.1	Replace Yukon 138 kV breaker "Y-11(CHARL1)" with an 80 kA breaker		APS (100%)
b2666.2	Replace Yukon 138 kV breaker "Y-13(BETHEL)" with an 80 kA breaker		APS (100%)
b2666.3	Replace Yukon 138 kV breaker "Y-18(CHARL2)" with an 80 kA breaker		APS (100%)
b2666.4	Replace Yukon 138 kV breaker "Y-19(CHARL2)" with an 80 kA breaker		APS (100%)
b2666.5	Replace Yukon 138 kV breaker "Y-4(4B-2BUS)" with an 80 kA breaker		APS (100%)
b2666.6	Replace Yukon 138 kV breaker "Y-5(LAYTON)" with an 80 kA breaker		APS (100%)
b2666.7	Replace Yukon 138 kV breaker "Y-8(HUNTING)" with an 80 kA breaker		APS (100%)
b2666.8	Replace Yukon 138 kV breaker "Y-9(SPRINGD)" with an 80 kA breaker		APS (100%)
b2666.9	Replace Yukon 138 kV breaker "Y-10(CHRL-SP)" with an 80 kA breaker		APS (100%)
b2666.10	Replace Yukon 138 kV breaker "Y-12(1-1BUS)" with an 80 kA breaker		APS (100%)
b2666.11	Replace Yukon 138 kV breaker "Y-14(4-1BUS)" with an 80 kA breaker		APS (100%)

Required Tran	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2666.12	Replace Yukon 138 kV breaker "Y-2(1B- BETHE)" with an 80 kA breaker		APS (100%)
b2666.13	Replace Yukon 138 kV breaker "Y-21(SHEPJ)" with an 80 kA breaker		APS (100%)
b2666.14	Replace Yukon 138 kV breaker "Y-22(SHEPHJT)" with an 80 kA breaker		APS (100%)
b2672	Change CT Ratio at Seneca Caverns from 120/1 to 160/1 and adjust relay settings accordingly		APS (100%)
b2688.3	Carroll Substation: Replace the Germantown 138 kV wave trap, upgrade the bus conductor and adjust CT ratios		AEP (12.91%) / APS (19.04%) / ATSI (1.24%) / ComEd (0.35%) / Dayton (1.45%) / DEOK (2.30%) / DL (1.11%) / Dominion (44.85%) / EKPC (0.78%) / PEPCO (15.85%) / RECO (0.12%)
b2689.3	Upgrade terminal equipment at structure 27A		APS (100%)
b2696	Upgrade 138 kV substation equipment at Butler, Shanor Manor and Krendale substations. New rating of line will be 353 MVA summer normal/422 MVA emergency		APS (100%)
b2700	Remove existing Black Oak SPS		APS (100%)
b2743.6	Reconfigure the Ringgold 230 kV substation to double bus double breaker scheme		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)

Required Trai	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2743.6.1	Replace the two Ringgold 230/138 kV transformers		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)
b2743.7	Rebuild/Reconductor the Ringgold – Catoctin 138 kV circuit and upgrade terminal equipment on both ends		AEP (6.46%) / APS (8.74%) / BGE (19.74%) / ComEd (2.16%) / Dayton (0.59%) / DEOK (1.02%) / DL (0.01%) / Dominion (39.95%) / EKPC (0.45%) / PEPCO (20.88%)
b2763	Replace the breaker risers and wave trap at Bredinville 138 kV substation on the Cabrey Junction 138 kV terminal		APS (100%)
b2764	Upgrade Fairview 138 kV breaker risers and disconnect leads; Replace 500 CU breaker risers and 556 ACSR disconnect leads with 795 ACSR		APS (100%)
b2964.1	Replace terminal equipment at Pruntytown and Glen Falls 138 kV station		APS (100%)
b2964.2	Reconductor approximately 8.3 miles of the McAlpin - White Hall Junction 138 kV circuit		APS (100%)

Required Tra	nsmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2965	Reconductor the Charleroi – Allenport 138 kV line with 954 ACSR conductor. Replace breaker risers at Charleroi and Allenport		DL (100%)
b2966	Reconductor the Yukon - Smithton - Shepler Hill Jct 138 kV line with 795 ACSS conductor. Replace Line Disconnect Switch at Yukon		APS (100%)
b2967	Convert the existing 6 wire Butler - Shanor Manor - Krendale 138 kV line into two separate 138 kV lines. New lines will be Butler - Keisters and Butler - Shanor Manor - Krendale 138 kV		APS (100%)
b2970	Ringgold – Catoctin Solution		APS (100%)
b2970.1	Install two new 230 kV positions at Ringgold for 230/138 kV transformers		APS (100%)
b2970.2	Install new 230 kV position for Ringgold – Catoctin 230 kV line		APS (100%)
b2970.3	Install one new 230 kV breaker at Catoctin substation		APS (100%)
b2970.4	Install new 230/138 kV transformer at Catoctin substation. Convert Ringgold – Catoctin 138 kV line to 230 kV operation		APS (100%)

SCHEDULE 12 – APPENDIX A

(15) Commonwealth Edison Company and Commonwealth Edison Company of Indiana, Inc.

Remove Byron SPS upon completion of Byron - Wayne 345 kV	required 1		iuai Revenue Requirement	Responsible Customer(s)
Wayne 345 kV Replace 138 kV bus tie 1-2 circuit breaker, station conductor, relays, and a wave trap at TSS 55 Hegewisch substation Reconductor 1.4 miles of 138 kV line 0112, Kickapoo Creek - LaSalle County 138kV line Install a 138 kV Red Blue bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV Breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) Replace the Skokie 138 kV ComEd (100%) ComEd (1		•		7 7 1 (1001)
Replace 138 kV bus tie 1-2 circuit breaker, station conductor, relays, and a wave trap at TSS 55 Hegewisch substation	b2141.1	<u> </u>		ComEd (100%)
Comed (100%)				
b2365		*		
wave trap at TSS 55 Hegewisch substation		,		
Hegewisch substation Reconductor 1.4 miles of 138 kV line 0112, Kickapoo Creek - LaSalle County 138kV line	b2365	_		ComEd (100%)
Reconductor 1.4 miles of 138 kV line 0112, Kickapoo Creek - LaSalle County 138kV line		-		
b2366		Hegewisch substation		
Creek - LaSalle County 138kV line Install a 138 kV Red Blue bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		Reconductor 1.4 miles of		
Install a 138 kV Red Blue bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)	b2266	138 kV line 0112, Kickapoo		ComEd (100%)
Install a 138 kV Red Blue bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)	02300	Creek - LaSalle County		Comed (100%)
b2415 bus tie with underground cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		138kV line		
cable and a line 15913 CB at Highland Park Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		Install a 138 kV Red Blue		
ComEd (100%) ComEd (100%)	b2415	bus tie with underground		ComEd (1000/)
Reconductor 0.125 miles of the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with Reconductor 0.125 miles of ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)	02413	cable and a line 15913 CB		Comed (100%)
the East Frankfort - Mokena 138 kV line L6604 Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%) ComEd (100%)		at Highland Park		
138 kV line L6604 Replace Ridgeland 138 kV		Reconductor 0.125 miles of		
Replace Ridgeland 138 kV bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%)	b2416	the East Frankfort - Mokena		ComEd (100%)
b2417 bus tie CB and underground cable at TSS 192 Ridgeland 138 kV substation ComEd (100%) b2418 Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607 ComEd (100%) b2419 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) ComEd (100%) b2465 Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker ComEd (100%) b2466 Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%)		138 kV line L6604		
ComEd (100%) Cable at TSS 192 Ridgeland 138 kV substation				
Cable at TSS 192 Ridgeland 138 kV substation Reconductor 7.5 miles of Waukegan - Gurnee 138 kV Iine L1607 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%)	b2/17	bus tie CB and underground		ComEd (100%)
Reconductor 7.5 miles of Waukegan - Gurnee 138 kV line L1607	02417	cable at TSS 192 Ridgeland		Comed (100%)
b2418 Waukegan - Gurnee 138 kV line L1607 ComEd (100%) b2419 Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) ComEd (100%) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker ComEd (100%) Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%)		138 kV substation		
Beconductor 0.33 miles of 138 kV underground cable 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd				
Reconductor 0.33 miles of 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324)	b2418	Waukegan - Gurnee 138 kV		ComEd (100%)
b2419 138 kV underground cable on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%)		line L1607		
on the Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%) ComEd (100%)		Reconductor 0.33 miles of		
Sawyer - Crawford 138 kV Blue line (L1324) Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%)	b 2410	138 kV underground cable		ComEd (100%)
Replace the Skokie 138 kV breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%)	02419	on the Sawyer - Crawford		Comed (100%)
b2465 breaker '88 L8809' with a 63 kA breaker Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%) ComEd (100%)		138 kV Blue line (L1324)		
63 kA breaker Replace the Skokie 138 kV b2466 breaker '88 L8810' with ComEd (100%)		Replace the Skokie 138 kV		
Replace the Skokie 138 kV breaker '88 L8810' with ComEd (100%)	b2465	breaker '88 L8809' with a		ComEd (100%)
b2466 breaker '88 L8810' with ComEd (100%)		63 kA breaker		
· · · · · ·				
63kA breaker	b2466	breaker '88 L8810' with		ComEd (100%)
		63kA breaker		
Replace the Skokie 138 kV		Replace the Skokie 138 kV		
b2467 breaker '88 L11416' with ComEd (100%)	b2467	breaker '88 L11416' with		ComEd (100%)
63 kA breaker		63 kA breaker		

Commonwealth Edison Company and Commonwealth Edison Company of Indiana, Inc. (cont.)

Annual Revenue Requirement Required Transmission Enhancements Responsible Customer(s) Replace the Skokie 138 kV breaker '88 L8803' with b2468 ComEd (100%) 63kA breaker Replace the Des Plaines 138 kV breaker '46 11702' with b2469 ComEd (100%) 63 kA breaker Install a new 345 kV circuit b2561 breaker 5-7 at Elwood ComEd (100%) substation Remove 2.0 miles of wood poles on 138 kV line 17105, erect new steel structures, b2562 ComEd (100%) and install new 1113 kcmil ACSR conductor from Roscoe Bert to Harlem Replace relays at Mazon b2613 ComEd (100%) substation AEC (0.18%) / AEP (18.68%) / APS (5.86%) / ATSI (7.85%) / BGE (3.32%) / ComEd (38.21%) / Dayton (2.76%) / DEOK (4.13%) / DL (2.23%) / Dominion (5.15%) / Replace station equipment DPL (1.97%) / EKPC b2692.1 at Nelson, ESS H-471 and (1.36%) / HTP (0.05%) / **Ouad Cities** JCPL (0.52%) / MetED (0.04%) / Neptune (0.04%) / PECO (1.08%) / PENELEC (1.25%) / PEPCO (3.56%) / PPL (0.45%) / PSEG (1.17%) / RECO (0.14%)

Commonwealth Edison Company and Commonwealth Edison Company of Indiana, Inc. (cont.)

Required T	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2692.2	Upgrade conductor ratings of Cordova – Nelson, Quad Cities – ESS H-471 and ESS H-471 – Nelson 345 kV lines and mitigating sag limitations		AEC (0.18%) / AEP (18.68%) / APS (5.86%) / ATSI (7.85%) / BGE (3.32%) / ComEd (38.21%) / Dayton (2.76%) / DEOK (4.13%) / DL (2.23%) / Dominion (5.15%) / DPL (1.97%) / EKPC (1.36%) / HTP (0.05%) / JCPL (0.52%) / MetED (0.04%) / PECO (1.08%) / PENELEC (1.25%) / PEPCO (3.56%) / PPL (0.45%) / PSEG (1.17%) / RECO (0.14%)
b2693	Replace L7815 B phase line trap at Wayne substation		ComEd (100%)
b2699.1	Replace 5 Powerton 345 kV CB's with 2 cycle IPO breakers, install one new 345 kV CB; swap line 0302 and line 0303 bus positions; reconfigure Powerton 345 kV bus as single ring configuration		ComEd (100%)
b2699.2	Remove SPS logic at Powerton that trips generators or sectionalizes bus under normal conditions; minimal SPS logic will remain		ComEd (100%)
b2721	Goodings Grove – Balance Station Load (swap bus positions for 345 kV lines 1312 & 11620 and 345 kV lines 11604 & 11622) and replace 138 kV bus tie 2-3		ComEd (100%)

Commonwealth Edison Company and Commonwealth Edison Company of Indiana, Inc. (cont.)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s) Mitigate sag limitations on ATSI (3.43%) / AEP Loretto – Wilton Center 345 (3.34%) / ComEd b2728 kV Line and replace station (92.02%) / DLCO conductor at Wilton Center (1.21%)Cut-in of line 93505 b2732.1 Tazewell – Kendall 345 kV ComEd (100%) line into Dresden Raise towers to remove the b2732.2 ComEd (100%) sag limitations on Pontiac – Loretto 345 kV line *Upgrade capacity on E.* b2930 Frankfort – University Park ComEd (100%) 345 kV Upgrade substation equipment at Pontiac b2931 Midpoint station to increase ComEd (100%) capacity on Pontiac -Brokaw 345 kV line Build an indoor new Elk Grove 138 kV GIS substation at the point where Rolling Meadows & Schaumburg tap off from the main lines, between Landmeier and Busse. The b2941 four 345 kV circuits in the ComEd (100%) ROW will be diverted into Gas Insulated Bus (GIB) and go through the basement of the building to provide clearance for the above ground portion of the building Install a new 138 kV circuit 18702 from Schauff Road to b2959 Rock Falls and install a ComEd (100%) fourth breaker and a half run at Schauff Road

SCHEDULE 12 – APPENDIX A

(17) AEP Service Corporation on behalf of its Affiliate Companies (AEP Indiana Michigan Transmission Company, AEP Kentucky Transmission Company, AEP Ohio Transmission Company, AEP West Virginia Transmission Company, Appalachian Power Company, Indiana Michigan Power Company, Kentucky Power Company, Kingsport Power Company, Ohio Power Company and Wheeling Power Company)

required 11	distinssion Linancements Ann	dai Revenue Requirement	responsible Customer(s)
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP
			(14.16%) / APS (5.73%) /
			ATSI (7.88%) / BGE
			(4.22%) / ComEd (13.31%) /
			Dayton (2.11%) / DEOK
	Cloverdale: install 6-765 kV		(3.29%) / DL (1.75%) / DPL
	breakers, incremental work		(2.50%) / Dominion
	for 2 additional breakers,		(12.86%) / EKPC (1.87%) /
1 1 6 6 0 1	reconfigure and relocate		JCPL (3.74%) / ME (1.90%)
b1660.1	miscellaneous facilities,		/ NEPTUNE* (0.44%) /
	establish 500 kV station and		PECO (5.34%) / PENELEC
	500 kV tie with 765 kV		(1.89%) / PEPCO (3.99%) /
	station		PPL (4.84%) / PSEG
			(6.26%) / RE (0.26%)
			(3.2.3,7, 2.2. (3.2.3,7)
			DFAX Allocation:
			APS (97.94%) / DEOK
			(0.54%) / Dominion (1.33%)
			/ EKPC (0.19%)
			/ LIG C (0.1770)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

required 11d	HISTHISSION EMILIANCEMENTS ATTITU	iai Kevenue Kequiterileni	
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP
			(14.16%) / APS (5.73%) /
			ATSI (7.88%) / BGE
			(4.22%) / ComEd (13.31%) /
			Dayton (2.11%) / DEOK
			(3.29%) / DL (1.75%) / DPL
			(2.50%) / Dominion
	Reconductor the AEP		(12.86%) / EKPC (1.87%) /
1.4505.4	portion of the Cloverdale -		JCPL (3.74%) / ME (1.90%)
b1797.1	Lexington 500 kV line with		/ NEPTUNE* (0.44%) /
	2-1780 ACSS		PECO (5.34%) / PENELEC
			(1.89%) / PEPCO (3.99%) /
			PPL (4.84%) / PSEG
			(6.26%) / RE (0.26%)
			DFAX Allocation:
			APS (55.05%) / ATSI
			(2.77%) / Dayton (0.84%) /
			DEOK (2.06%) / Dominion
			(5.76%) / EKPC (0.72%) /
			PEPCO (32.80%)
	Upgrade relay at Brues		, ,
b2055	station		AEP (100%)
	Upgrade terminal		
	equipment at Howard on		
b2122.3	the Howard - Brookside		AEP (100%)
	138 kV line to achieve		(/
	ratings of 252/291 (SN/SE)		
b2122.4	Perform a sag study on the		
	Howard - Brookside 138		AEP (100%)
	kV line		` ′
1.0000	Install a 300 MVAR		A FID (1000())
b2229	reactor at Dequine 345 kV		AEP (100%)
<u> </u>	i 17 control of the first	IIC	1

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

required 11		iai Revenue Requirement	
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP (14.16%)
			/ APS (5.73%) / ATSI
			(7.88%) / BGE (4.22%) /
			ComEd (13.31%) / Dayton
	Replace existing 150		(2.11%) / DEOK (3.29%) /
	MVAR reactor at Amos 765		DL (1.75%) / DPL (2.50%) /
b2230	kV substation on Amos - N.		Dominion (12.86%) / EKPC
	Proctorville - Hanging Rock		(1.87%) / JCPL (3.74%) / ME
	with 300 MVAR reactor		(1.90%) / NEPTUNE*
			(0.44%) / PECO (5.34%) /
			PENELEC (1.89%) / PEPCO
			(3.99%) / PPL (4.84%) /
			PSEG (6.26%) / RE (0.26%)
			DFAX Allocation:
			AEP (100%)
	Install 765 kV reactor		
b2231	breaker at Dumont 765 kV		AEP (100%)
	substation on the Dumont -		ALF (100%)
	Wilton Center line		
	Install 765 kV reactor		
	breaker at Marysville 765		
b2232	kV substation on the		AEP (100%)
	Marysville - Maliszewski		
	line		
	Change transformer tap		
b2233	settings for the Baker		AEP (100%)
	765/345 kV transformer		
	Loop the North Muskingum		
	- Crooksville 138 kV line		
b2252	into AEP's Philo 138 kV		ΔED (100%)
02232	station which lies		AEP (100%)
	approximately 0.4 miles		
	from the line		
	1.00		

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

required Tre		iai Revenue Requirement	Responsible Customer(s)
	Install an 86.4 MVAR		
b2253	capacitor bank at Gorsuch		AEP (100%)
	138 kV station in Ohio		
	Rebuild approximately 4.9		
b2254	miles of Corner - Degussa		AEP (100%)
	138 kV line in Ohio		
	Rebuild approximately 2.8		
b2255	miles of Maliszewski -		AEP (100%)
	Polaris 138 kV line in Ohio		
	Upgrade approximately 36		
	miles of 138 kV through		
b2256	path facilities between		AEP (100%)
	Harrison 138 kV station and		
	Ross 138 kV station in Ohio		
	Rebuild the Pokagon -		
	Corey 69 kV line as a		
	double circuit 138 kV line		
b2257	with one side at 69 kV and		AEP (100%)
	the other side as an express		
	circuit between Pokagon		
	and Corey stations		
	Rebuild 1.41 miles of #2		
	CU 46 kV line between		
b2258	Tams Mountain - Slab Fork		AEP (100%)
02230	to 138 kV standards. The		(100/0)
	line will be strung with		
	1033 ACSR		
	Install a new 138/69 kV		
	transformer at George		
b2259	Washington 138/69 kV		AEP (100%)
02207	substation to provide		(100/0)
	support to the 69 kV system		
	in the area		
	Rebuild 4.7 miles of		
	Muskingum River - Wolf		
b2286	Creek 138 kV line and		AEP (100%)
02200	remove the 138/138 kV		(10070)
	transformer at Wolf Creek		
	Station		

required 11	1	iai Revenue Requirement	Responsible Customer(s)
	Loop in the Meadow Lake -		
b2287	Olive 345 kV circuit into		AEP (100%)
	Reynolds 765/345 kV		(200/0)
	station		
	Establish a new 138/12 kV		
	station, transfer and		
b2344.1	consolidate load from its		AEP (100%)
023TT.1	Nicholsville and Marcellus		1121 (10070)
	34.5 kV stations at this new		
	station		
	Tap the Hydramatic –		
	Valley 138 kV circuit (~		
b2344.2	structure 415), build a new		AEP (100%)
	138 kV line (~3.75 miles) to		
	this new station		
	From this station, construct		
b2344.3	a new 138 kV line (~1.95		AEP (100%)
043 44 .3	miles) to REA's Marcellus		ALI (100%)
	station		
	From REA's Marcellus		
	station construct new 138		
b2344.4	kV line (~2.35 miles) to a		AEP (100%)
043 44.4	tap point on Valley –		ALI (100%)
	Hydramatic 138 kV ckt		
	(~structure 434)		
	Retire sections of the 138		
b2344.5	kV line in between structure		AEP (100%)
	415 and 434 (~ 2.65 miles)		
	Retire AEP's Marcellus		
	34.5/12 kV and Nicholsville		
b2344.6	34.5/12 kV stations and also		AEP (100%)
	the Marcellus – Valley 34.5		
	kV line		
	Construct a new 69 kV line		
b2345.1	from Hartford to Keeler (~8		AEP (100%)
	miles)		

required 11		iai Kevenue Kequirement	Responsible Customer(s)
	Rebuild the 34.5 kV lines		
b2345.2	between Keeler - Sister		AEP (100%)
	Lakes and Glenwood tap		, ,
	switch to 69 kV (~12 miles)		
1 22 45 2	Implement in - out at Keeler		A ED (1000)
b2345.3	and Sister Lakes 34.5 kV		AEP (100%)
	stations		
	Retire Glenwood tap switch		
1.00.45.4	and construct a new		A ED (1000()
b2345.4	Rothadew station. These		AEP (100%)
	new lines will continue to		
	operate at 34.5 kV		
	Perform a sag study for		
1.0046	Howard - North Bellville -		AED (1000/)
b2346	Millwood 138 kV line		AEP (100%)
	including terminal		
	equipment upgrades		
	Replace the North Delphos		
	600A switch. Rebuild		
L2247	approximately 18.7 miles of		AED (1000/)
b2347	138 kV line North Delphos		AEP (100%)
	- S073. Reconductor the		
	line and replace the existing		
	tower structures		
	Construct a new 138 kV		
1-0240	line from Richlands Station		AED (1000/)
b2348	to intersect with the Hales		AEP (100%)
	Branch - Grassy Creek 138		
	kV circuit		
	Change the existing CT		
1-0074	ratios of the existing		AED (1000/)
b2374	equipment along Bearskin -		AEP (100%)
	Smith Mountain 138kV		
	circuit		
	Change the existing CT		
1.0075	ratios of the existing		AED (1000()
b2375	equipment along East		AEP (100%)
	Danville-Banister 138kV		
	circuit		

b2376	Replace the Turner 138 kV breaker 'D'	AEP (100%)
b2377	Replace the North Newark 138 kV breaker 'P'	AEP (100%)
b2378	Replace the Sporn 345 kV breaker 'DD'	AEP (100%)
b2379	Replace the Sporn 345 kV breaker 'DD2'	AEP (100%)
b2380	Replace the Muskingum 345 kV breaker 'SE'	AEP (100%)
b2381	Replace the East Lima 138 kV breaker 'E1'	AEP (100%)
b2382	Replace the Delco 138 kV breaker 'R'	AEP (100%)
b2383	Replace the Sporn 345 kV breaker 'AA2'	AEP (100%)
b2384	Replace the Sporn 345 kV breaker 'CC'	AEP (100%)
b2385	Replace the Sporn 345 kV breaker 'CC2'	AEP (100%)
b2386	Replace the Astor 138 kV breaker '102'	AEP (100%)
b2387	Replace the Muskingum 345 kV breaker 'SH'	AEP (100%)
b2388	Replace the Muskingum 345 kV breaker 'SI'	AEP (100%)
b2389	Replace the Hyatt 138 kV breaker '105N'	AEP (100%)
b2390	Replace the Muskingum 345 kV breaker 'SG'	AEP (100%)
b2391	Replace the Hyatt 138 kV breaker '101C'	AEP (100%)
b2392	Replace the Hyatt 138 kV breaker '104N'	AEP (100%)
b2393	Replace the Hyatt 138 kV breaker '104S'	AEP (100%)

required 11	I	iai Kevenue Kequiteriletii Ke	sponsible Customer(s)
b2394	Replace the Sporn 345 kV breaker 'CC1'		AEP (100%)
b2409	Install two 56.4 MVAR capacitor banks at the Melmore 138 kV station in Ohio		AEP (100%)
b2410	Convert Hogan Mullin 34.5 kV line to 138 kV, establish 138 kV line between Jones Creek and Strawton, rebuild existing Mullin Elwood 34.5 kV and terminate line into Strawton station, retire Mullin station		AEP (100%)
b2411	Rebuild the 3/0 ACSR portion of the Hadley - Kroemer Tap 69 kV line utilizing 795 ACSR conductor		AEP (100%)
b2423	Install a 300 MVAR shunt reactor at AEP's Wyoming 765 kV station		Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%)

Required Tra	ansmission Enhancements Annu	al Revenue Requirement	Responsible Customer(s)
	Willow - Eureka 138 kV		
b2444	line: Reconductor 0.26 mile		AEP (100%)
	of 4/0 CU with 336 ACSS		
	Complete a sag study of		
b2445	Tidd - Mahans Lake 138 kV		AEP (100%)
	line		
	Rebuild the 7-mile 345 kV		
b2449	line between Meadow Lake		AEP (100%)
02449	and Reynolds 345 kV		ALF (100%)
	stations		
	Add two 138 kV circuit		
b2462	breakers at Fremont station		AEP (100%)
02402	to fix tower contingency		ALI (100%)
	'408 <u>2</u> '		
	Construct a new 138/69 kV		
	Yager station by tapping 2-		
b2501	138 kV FE circuits		AEP (100%)
	(Nottingham-Cloverdale,		
	Nottingham-Harmon)		
	Build a new 138 kV line		
b2501.2	from new Yager station to		AEP (100%)
	Azalea station		
	Close the 138 kV loop back		
b2501.3	into Yager 138 kV by		AEP (100%)
02301.3	converting part of local 69		AEI (100%)
	kV facilities to 138 kV		
	Build 2 new 69 kV exits to		
	reinforce 69 kV facilities		
b2501.4	and upgrade conductor		AEP (100%)
02301.4	between Irish Run 69 kV		AEI (10070)
	Switch and Bowerstown 69		
	kV Switch		

Construct new 138 kV switching station	1100		The state of the s	responsible Constanter(b)
Nottingham tapping 6-138 kV FE circuits (Holloway- Brookside, Holloway-				
kV FE circuits (Holloway- Brookside, Holloway- Harmon #1 and #2, Holloway-Reeds, Holloway-New Stacy, Holloway-New Stacy, Holloway-Cloverdale). Exit a 138 kV circuit from new station to Freebyrd 69 kV to 138 kV Rebuild/convert Freebyrd- South Cadiz 69 kV circuit to 138 kV b2502.4 Upgrade South Cadiz to 138 kV breaker and a half Replace the Sporn 138 kV b2530 Feelace the Sporn 138 kV b2531 Replace the Sporn 138 kV b2532 Replace the Sporn 138 kV b2533 Replace the Sporn 138 kV b2534 Replace the Sporn 138 kV b2535 Replace the Sporn 138 kV b2536 Replace the Sporn 138 kV b2537 Replace the Sporn 138 kV b2538 Replace the Sporn 138 kV b2539 Replace the Sporn 138 kV b2531 Replace the Sporn 138 kV b2532 Replace the Sporn 138 kV b2533 Replace the Sporn 138 kV b2534 Replace the Sporn 138 kV b2535 Replace the Sporn 138 kV b2536 Replace the Sporn 138 kV b2537 Replace the Sporn 138 kV b2538 Replace the Sporn 138 kV b2539 Replace the Sporn 138 kV b2530 Replace the Sporn 138 kV b2531 Replace the Sporn 138 kV b2533 Replace the Sporn 138 kV b2534 Replace the Sporn 138 kV b2535 Replace the Sporn 138 kV				
Brookside, Holloway- Harmon #1 and #2, Holloway-Reeds, Holloway-Cloverdale). Exit a 138 kV circuit from new station to Freebyrd 69 kV to 138 kV Rebuild/convert Freebyrd- b2502.3 South Cadiz 69 kV circuit to 138 kV Upgrade South Cadiz to 138 kV breaker and a half Replace the Sporn 138 kV b2530 Feelace the Sporn 138 kV b2531 Replace the Sporn 138 kV b2532 Replace the Sporn 138 kV b2533 Replace the Sporn 138 kV b2534 Replace the Sporn 138 kV breaker Replace the Sporn 138 kV b2535 Replace the Sporn 138 kV breaker Replace the Sporn 138 kV breaker 'D' with 80kA breaker Replace the Sporn 138 kV breaker 'P2' with 80kA breaker Replace the Sporn 138 kV breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker 'O' with 80kA breaker Replace the Sporn 138 kV breaker 'O' with 80kA breaker Replace the Sporn 138 kV breaker 'O' with 80kA breaker				
b2502.1 Harmon #1 and #2,		,		
Holloway-Reeds, Holloway-New Stacy, Holloway-Cloverdale). Exit a 138 kV circuit from new station to Freebyrd station				. ==
Holloway-New Stacy, Holloway-Cloverdale). Exit a 138 kV circuit from new station to Freebyrd station Convert Freebyrd 69 kV to 138 kV Rebuild/convert Freebyrd- b2502.3 South Cadiz 69 kV circuit to 138 kV b2502.4 Upgrade South Cadiz to 138 kV breaker and a half Replace the Sporn 138 kV b2530 Preaker Replace the Sporn 138 kV b2531 Replace the Sporn 138 kV breaker 'O' with 80kA breaker Replace the Sporn 138 kV b2532 Preaker 'O' with 80kA breaker Replace the Sporn 138 kV b2533 Preaker 'O' with 80kA breaker Replace the Sporn 138 kV b2534 Preaker 'Ye' with 80kA breaker Replace the Sporn 138 kV b2535 Preaker 'O' with 80kA breaker Replace the Sporn 138 kV b2534 Preaker 'Ye' with 80kA breaker Replace the Sporn 138 kV b2534 Preaker 'O' with 80kA breaker Replace the Sporn 138 kV b2535 Preaker 'O' with 80kA AEP (100%)	b2502.1	,		AEP (100%)
Holloway-Cloverdale). Exit a 138 kV circuit from new station to Freebyrd station b2502.2 Convert Freebyrd 69 kV to 138 kV Rebuild/convert Freebyrd- b2502.3 South Cadiz 69 kV circuit to 138 kV b2502.4 Upgrade South Cadiz to 138 kV breaker and a half Replace the Sporn 138 kV breaker (G1' with 80kA breaker Replace the Sporn 138 kV breaker 'D' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker Replace the Sporn 138 kV breaker (O1' with 80kA breaker		,		
a 138 kV circuit from new station to Freebyrd station b2502.2				
Station to Freebyrd station				
b2502.2 Convert Freebyrd 69 kV to 138 kV Rebuild/convert Freebyrd-				
Rebuild/convert Freebyrd- South Cadiz 69 kV circuit to 138 kV				
Rebuild/convert Freebyrd- South Cadiz 69 kV circuit to 138 kV	h2502 2	•		ΔFP (100%)
December 2013 South Cadiz 69 kV circuit to 138 kV	02302.2			ALI (100%)
to 138 kV b2502.4 Upgrade South Cadiz to 138 kV breaker and a half Replace the Sporn 138 kV b2530 breaker 'G1' with 80kA breaker Replace the Sporn 138 kV b2531 breaker 'D' with 80kA AEP (100%) B2532 breaker 'O1' with 80kA AEP (100%) B2532 breaker 'O1' with 80kA AEP (100%) B2533 breaker 'P2' with 80kA AEP (100%) B2534 breaker 'U' with 80kA AEP (100%) B2534 breaker 'U' with 80kA AEP (100%) B2535 breaker 'O' with 80kA AEP (100%) B2536 breaker 'U' with 80kA AEP (100%) B2537 AEP (100%) B2538 AEP (100%) B2539 AEP (100%) B2539 AEP (100%) B2530 AEP (100%) B2531 AEP (100%) B2532 AEP (100%) B2533 AEP (100%)				
b2502.4 Upgrade South Cadiz to 138	b2502.3	South Cadiz 69 kV circuit		AEP (100%)
Replace the Sporn 138 kV		to 138 kV		
Replace the Sporn 138 kV b2530 breaker 'G1' with 80kA breaker Replace the Sporn 138 kV b2531 breaker 'D' with 80kA breaker Replace the Sporn 138 kV b2532 breaker 'O1' with 80kA breaker Replace the Sporn 138 kV b2533 breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%)	h2502 4	10		AED (100%)
b2530 breaker 'G1' with 80kA	02302.4	kV breaker and a half		ALF (100%)
breaker Replace the Sporn 138 kV breaker 'D' with 80kA breaker Replace the Sporn 138 kV b2532 breaker 'O1' with 80kA breaker Replace the Sporn 138 kV b2533 breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker 'U' with 80kA breaker Replace the Sporn 138 kV				
Replace the Sporn 138 kV breaker 'D' with 80kA breaker Replace the Sporn 138 kV bb2532 Breaker 'O1' with 80kA breaker Replace the Sporn 138 kV breaker Replace the Sporn 138 kV bb2533 Breaker 'P2' with 80kA breaker Replace the Sporn 138 kV bb2534 Breaker 'U' with 80kA breaker Replace the Sporn 138 kV bb2535 Breaker 'O' with 80 kA AEP (100%) AEP (100%) AEP (100%)	b2530	breaker 'G1' with 80kA		AEP (100%)
b2531 breaker 'D' with 80kA breaker Replace the Sporn 138 kV b2532 breaker 'O1' with 80kA breaker Replace the Sporn 138 kV b2533 breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%) AEP (100%) AEP (100%) AEP (100%) AEP (100%)				
breaker Replace the Sporn 138 kV b2532 breaker 'O1' with 80kA breaker Replace the Sporn 138 kV b2533 breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%) AEP (100%)				
Replace the Sporn 138 kV breaker 'O1' with 80kA breaker Replace the Sporn 138 kV b2533 breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%) AEP (100%) AEP (100%) AEP (100%)	b2531	breaker 'D' with 80kA		AEP (100%)
b2532 breaker 'O1' with 80kA breaker Replace the Sporn 138 kV b2533 breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%) AEP (100%) AEP (100%)				
breaker Replace the Sporn 138 kV breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker Replace the Sporn 138 kV breaker AEP (100%)				
Replace the Sporn 138 kV breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV breaker Replace the Sporn 138 kV breaker Replace the Sporn 138 kV breaker 'O' with 80 kA AEP (100%)	b2532	breaker 'O1' with 80kA		AEP (100%)
b2533 breaker 'P2' with 80kA breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%) AEP (100%)				
breaker Replace the Sporn 138 kV b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%)				
Replace the Sporn 138 kV breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%) AEP (100%)	b2533	breaker 'P2' with 80kA		AEP (100%)
b2534 breaker 'U' with 80kA breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%) AEP (100%)				
breaker Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%)				
Replace the Sporn 138 kV b2535 breaker 'O' with 80 kA AEP (100%)	b2534			AEP (100%)
b2535 breaker 'O' with 80 kA AEP (100%)		breaker		
		Replace the Sporn 138 kV		
breaker	b2535	breaker 'O' with 80 kA		AEP (100%)
		breaker		

Required Tr	ansmission Enhancements Anni	ual Revenue Requirement	Responsible Customer(s)
1.2526	Replace the Sporn 138 kV		AED (1000()
b2536	breaker 'O2' with 80 kA breaker		AEP (100%)
	Replace the Robinson Park		
	138 kV breakers A1, A2,		
b2537	B1, B2, C1, C2, D1, D2,		AEP (100%)
02007	E1, E2, and F1 with 63 kA		(100/0)
	breakers		
	Reconductor 0.5 miles		
	Tiltonsville – Windsor 138		
b2555	kV and string the vacant		AED (1000/)
02333	side of the 4.5 mile section		AEP (100%)
	using 556 ACSR in a six		
	wire configuration		
	Install two 138 kV prop		
	structures to increase the		
b2556	maximum operating		AEP (100%)
02330	temperature of the Clinch		(10070)
	River- Clinch Field 138 kV		
	line		
	Temporary operating		
	procedure for delay of		
	upgrade b1464. Open the		
	Corner 138 kV circuit		
	breaker 86 for an overload		
b2581	of the Corner – Washington		AEP (100%)
	MP 138 kV line. The tower		
	contingency loss of Belmont – Trissler 138 kV		
	and Belmont – Edgelawn		
	138 kV should be added to		
	Operational contingency		
	Speranonal contingency		

1		
1.2.704	Construct a new 69 kV line	
	approximately 2.5 miles	
	from Colfax to Drewry's.	AED (1000()
b2591	Construct a new Drewry's	AEP (100%)
	station and install a new	
	circuit breaker at Colfax	
	station.	
	Rebuild existing East	
	Coshocton – North	
	Coshocton double circuit	
b2592	line which contains	AEP (100%)
02392	Newcomerstown – N.	ALF (100%)
	Coshocton 34.5 kV Circuit	
	and Coshocton – North	
	Coshocton 69 kV circuit	
	Rebuild existing West	
	Bellaire – Glencoe 69 kV	
1.2702	line with 138 kV & 69 kV	A FID (4000)
b2593	circuits and install 138/69	AEP (100%)
	kV transformer at Glencoe	
	Switch	
	Rebuild 1.0 mile of	
1.2.5.4	Brantley – Bridge Street 69	177 (1001)
b2594	kV Line with 1033 ACSR	AEP (100%)
	overhead conductor	
	Rebuild 7.82 mile Elkhorn	
	City – Haysi S.S 69 kV line	
b2595.1	utilizing 1033 ACSR built	AEP (100%)
	to 138 kV standards	
	Rebuild 5.18 mile Moss –	
	Haysi SS 69 kV line	
b2595.2	utilizing 1033 ACSR built	AEP (100%)
	to 138 kV standards	
	Move load from the 34.5	
1.0506	kV bus to the 138 kV bus	AED (1000/)
b2596	by installing a new 138/12	AEP (100%)
	kV XF at New Carlisle	
	station in Indiana	

1100/000000 11		iai icvenue requirement	topolisioic Castollier(b)
	Rebuild approximately 1		
	mi. section of Dragoon-		
	Virgil Street 34.5 kV line		
10505	between Dragoon and		A FID (1000()
b2597	Dodge Tap switch and		AEP (100%)
	replace Dodge switch		
	MOAB to increase thermal		
	capability of Dragoon-		
	Dodge Tap branch		
	Rebuild approximately 1		
	mile section of the Kline-		
	Virgil Street 34.5 kV line		
b2598	between Kline and Virgil		AEP (100%)
02370	Street tap. Replace MOAB		(10070)
	switches at Beiger, risers at		
	Kline, switches and bus at		
	Virgil Street.		
	Rebuild approximately 0.1		
b2599	miles of 69 kV line between		AEP (100%)
	Albion and Albion tap		
b2600	Rebuild Fremont – Pound		AEP (100%)
02000	line as 138 kV		1111 (10070)
b2601	Fremont Station		AEP (100%)
02001	Improvements		7111 (10070)
	Replace MOAB towards		
b2601.1	Beaver Creek with 138 kV		AEP (100%)
	breaker		
	Replace MOAB towards		
b2601.2	Clinch River with 138 kV		AEP (100%)
	breaker		
b2601.3	Replace 138 kV Breaker A		AEP (100%)
02001.3	with new bus-tie breaker		ALF (100%)
	Re-use Breaker A as high		
b2601.4	side protection on		AEP (100%)
	transformer #1		
	Install two (2) circuit		
h2601 5	switchers on high side of		AED (1000()
b2601.5	transformers # 2 and 3 at		AEP (100%)
	Fremont Station		

	au revenue requiement	Responsible Customer(s)
Install 138 kV breaker E2 at		AEP (100%)
		(10070)
Construct 2.5 Miles of 138		
kV 1033 ACSR from East		AEP (100%)
Huntington to Darrah 138		AEI (100%)
kV substations		
Install breaker on new line		
exit at Darrah towards East		AEP (100%)
Huntington		
_		AEP (100%)
		AEP (100%)
North Proctorville		
Boone Area Improvements		AEP (100%)
		AEP (100%)
`		
		AEP (100%)
· · · · · · · · · · · · · · · · · · ·		(100/0)
circuit 138 kV line on		
Wilbur – Boone 46 kV line		
with 1590 ACSS 54/19		AED (1000/)
conductor @ 482 Degree		AEP (100%)
design temp. and 1-159 12/7		
ACSR and one 86 Sq.MM.		
0.646" OPGW Static wires		
Bellefonte Transformer		AEP (100%)
Addition		AEP (100%)
	Install 138 kV breaker E2 at North Proctorville Construct 2.5 Miles of 138 kV 1033 ACSR from East Huntington to Darrah 138 kV substations Install breaker on new line exit at Darrah towards East Huntington Install 138 kV breaker on new line at East Huntington towards Darrah Install 138 kV breaker at East Huntington towards North Proctorville Boone Area Improvements Purchase approximately a 200X300 station site near Slaughter Creek 46 kV station (Wilbur Station) Install 3 138 kV circuit breakers, Cabin Creek to Hernshaw 138 kV circuit Construct 1 mi. of double circuit 138 kV line on Wilbur – Boone 46 kV line with 1590 ACSS 54/19 conductor @ 482 Degree design temp. and 1-159 12/7 ACSR and one 86 Sq.MM. 0.646" OPGW Static wires Bellefonte Transformer	North Proctorville Construct 2.5 Miles of 138 kV 1033 ACSR from East Huntington to Darrah 138 kV substations Install breaker on new line exit at Darrah towards East Huntington Install 138 kV breaker on new line at East Huntington towards Darrah Install 138 kV breaker at East Huntington towards North Proctorville Boone Area Improvements Purchase approximately a 200X300 station site near Slaughter Creek 46 kV station (Wilbur Station) Install 3 138 kV circuit breakers, Cabin Creek to Hernshaw 138 kV circuit Construct 1 mi. of double circuit 138 kV line on Wilbur – Boone 46 kV line with 1590 ACSS 54/19 conductor @ 482 Degree design temp. and 1-159 12/7 ACSR and one 86 Sq.MM. 0.646° OPGW Static wires Bellefonte Transformer

	du Revenue Requirement	Responsible Customer(s)
_		
Washington 69 kV circuit		
and George Washington –		
Moundsville ckt #1,		AEP (100%)
designed for 138kV.		
Upgrade limiting equipment		
at remote ends and at tap		
stations		
Convert Bane –		
Hammondsville from 23 kV		AEP (100%)
to 69 kV operation		
Pine Gap Relay Limit		A ED (1000()
Increase		AEP (100%)
D		1 TD (1000())
Richlands Relay Upgrade		AEP (100%)
Thorofare – Goff Run –		
Powell Mountain 138 kV		AEP (100%)
Build		
Rebuild Pax Branch –		AED (1000/)
Scaraboro as 138 kV		AEP (100%)
Skin Fork Area		AED (1000/)
Improvements		AEP (100%)
New 138/46 kV station near		
Skin Fork and other		AEP (100%)
components		
Construct 3.2 miles of 1033		
ACSR double circuit from		
new Station to cut into		AEP (100%)
Sundial-Baileysville 138 kV		
line		
Replace metering BCT on		
Tanners Creek CB T2 with		
a slip over CT with higher		
thermal rating in order to		AEP (100%)
remove 1193 MVA limit on		, , ,
facility (Miami Fort-		
Tanners Creek 345 kV line)		
	Rebuild and reconductor Kammer – George Washington 69 kV circuit and George Washington – Moundsville ckt #1, designed for 138kV. Upgrade limiting equipment at remote ends and at tap stations Convert Bane – Hammondsville from 23 kV to 69 kV operation Pine Gap Relay Limit Increase Richlands Relay Upgrade Thorofare – Goff Run – Powell Mountain 138 kV Build Rebuild Pax Branch – Scaraboro as 138 kV Skin Fork Area Improvements New 138/46 kV station near Skin Fork and other components Construct 3.2 miles of 1033 ACSR double circuit from new Station to cut into Sundial-Baileysville 138 kV line Replace metering BCT on Tanners Creek CB T2 with a slip over CT with higher thermal rating in order to remove 1193 MVA limit on facility (Miami Fort-	Kammer – George Washington 69 kV circuit and George Washington – Moundsville ckt #1, designed for 138kV. Upgrade limiting equipment at remote ends and at tap stations Convert Bane – Hammondsville from 23 kV to 69 kV operation Pine Gap Relay Limit Increase Richlands Relay Upgrade Thorofare – Goff Run – Powell Mountain 138 kV Build Rebuild Pax Branch – Scaraboro as 138 kV Skin Fork Area Improvements New 138/46 kV station near Skin Fork and other components Construct 3.2 miles of 1033 ACSR double circuit from new Station to cut into Sundial-Baileysville 138 kV line Replace metering BCT on Tanners Creek CB T2 with a slip over CT with higher thermal rating in order to remove 1193 MVA limit on facility (Miami Fort-

Required 11	ansmission Enhancements Annu	ial Revenue Requirement	Responsible Customer(s)
b2643	Replace the Darrah 138 kV breaker 'L' with 40kA rated breaker		AEP (100%)
b2645	Ohio Central 138 kV Loop		AEP (100%)
b2667	Replace the Muskingum 138 kV bus # 1 and 2		AEP (100%)
b2668	Reconductor Dequine to Meadow Lake 345 kV circuit #1 utilizing dual 954 ACSR 54/7 cardinal conductor		AEP (100%)
b2669	Install a second 345/138 kV transformer at Desoto		AEP (100%)
b2670	Replace switch at Elk Garden 138 kV substation (on the Elk Garden – Lebanon 138 kV circuit)		AEP (100%)
b2671	Replace/upgrade/add terminal equipment at Bradley, Mullensville, Pinnacle Creek, Itmann, and Tams Mountain 138 kV substations. Sag study on Mullens – Wyoming and Mullens – Tams Mt. 138 kV circuits		AEP (100%)

Required 11	ansinission Enhancements Ann	uai Revenue Requirement	Responsible Customer(s)
b2687.1	Install a +/- 450 MVAR SVC at Jacksons Ferry 765 kV substation		Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%) DFAX Allocation: AEP (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***} Hudson Transmission Partners, LLC

required 11		dai Revenue Requirement	Responsible Customer(s)
b2687.2	Install a 300 MVAR shunt line reactor on the Broadford end of the Broadford – Jacksons Ferry 765 kV line		Load-Ratio Share Allocation: AEC (1.66%) / AEP (14.16%) / APS (5.73%) / ATSI (7.88%) / BGE (4.22%) / ComEd (13.31%) / Dayton (2.11%) / DEOK (3.29%) / DL (1.75%) / DPL (2.50%) / Dominion (12.86%) / EKPC (1.87%) / JCPL (3.74%) / ME (1.90%) / NEPTUNE* (0.44%) / PECO (5.34%) / PENELEC (1.89%) / PEPCO (3.99%) / PPL (4.84%) / PSEG (6.26%) / RE (0.26%)
b2697.1	Mitigate violations identified by sag study to operate Fieldale-Thornton-Franklin 138 kV overhead line conductor at its max. operating temperature. 6 potential line crossings to be addressed.		DFAX Allocation: AEP (100%) AEP (100%)
b2697.2	Replace terminal equipment at AEP's Danville and East Danville substations to improve thermal capacity of Danville – East Danville 138 kV circuit		AEP (100%)

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***} Hudson Transmission Partners, LLC

Required 11		ai Revenue Requirement	Responsible Customer(s)
	Replace relays at AEP's		
b2698	Cloverdale and Jackson's		
	Ferry substations to improve		AEP (100%)
	the thermal capacity of		71L1 (10070)
	Cloverdale – Jackson's Ferry		
	765 kV line		
	Construct Herlan station as		
	breaker and a half		
b2701.1	configuration with 9-138 kV		AEP (100%)
	CB's on 4 strings and with 2-		
	28.8 MVAR capacitor banks		
	Construct new 138 kV line		
	from Herlan station to Blue		
b2701.2	Racer station. Estimated		AEP (100%)
02701.2	approx. 3.2 miles of 1234		1121 (10070)
	ACSS/TW Yukon and		
	OPGW		
	Install 1-138 kV CB at Blue		
2701.3	Racer to terminate new		AEP (100%)
	Herlan circuit		
	Rebuild/upgrade line		
b2714	between Glencoe and		AEP (100%)
	Willow Grove Switch 69 kV		
	Build approximately 11.5		
	miles of 34.5 kV line with		
b2715	556.5 ACSR 26/7 Dove		AEP (100%)
	conductor on wood poles		(100,0)
	from Flushing station to		
	Smyrna station		
b2727	Replace the South Canton		
	138 kV breakers 'K', 'J',		AEP (100%)
	'J1', and 'J2' with 80kA		(100,0)
	breakers		

Required Tr	ansmission Enhancements Annua	al Revenue Requirement	Responsible Customer(s)
	Convert the Sunnyside –		
b2731	East Sparta – Malvern 23 kV		
	sub-transmission network to		AEP (100%)
	69 kV. The lines are already		
	built to 69 kV standards		
	Replace South Canton 138		
b2733	kV breakers 'L' and 'L2'		AEP (100%)
	with 80 kA rated breakers		
	Retire Betsy Layne		
	138/69/43 kV station and		
b2750.1	replace it with the greenfield		AED (1000()
02/30.1	Stanville station about a half		AEP (100%)
	mile north of the existing		
	Betsy Layne station		
	Relocate the Betsy Layne		
	capacitor bank to the		
b2750.2	Stanville 69 kV bus and		AEP (100%)
	increase the size to 14.4		
	MVAR		
	Replace existing George		
	Washington station 138 kV		
	yard with GIS 138 kV		
b2753.1	breaker and a half yard in		AED (1000/)
02/33.1	existing station footprint.		AEP (100%)
	Install 138 kV revenue		
	metering for new IPP		
	connection		
b2753.2	Replace Dilles Bottom 69/4		
	kV Distribution station as		
	breaker and a half 138 kV		
	yard design including AEP		A ED (1000/)
	Distribution facilities but		AEP (100%)
	initial configuration will		
	constitute a 3 breaker ring		
	bus		
	1		1

Connect two 138 kV 6-wired circuits from "Point A" (currently de-energized and owned by FirstEnergy) in circuit positions previously designated Burger #1 & Burger #2 138 kV. Install interconnection settlement		Connect true 120 la V 6 viginal	I	
b2753.3 (currently de-energized and owned by FirstEnergy) in circuit positions previously designated Burger #1 & Burger #2 138 kV. Install	1			
owned by FirstEnergy) in circuit positions previously designated Burger #1 & Burger #2 138 kV. Install				
b2753.3 circuit positions previously designated Burger #1 & Burger #2 138 kV. Install		, ,		
designated Burger #1 & Burger #2 138 kV. Install				
designated Burger #1 & Burger #2 138 kV. Install	b2753 3			AEP (100%)
	02733.3			1121 (10070)
interconnection settlement				
		interconnection settlement		
metering on both circuits		_		
exiting Holloway				
Build double circuit 138 kV				
line from Dilles Bottom to				
"Point A". Tie each new		"Point A". Tie each new		
AEP circuit in with a 6-wired				
b2753.6 line at Point A. This will AEP (100%)	b2753.6			AEP (100%)
create a Dilles Bottom –				
Holloway 138 kV circuit and		Holloway 138 kV circuit and		
a George Washington –		a George Washington –		
Holloway 138 kV circuit		·		
Retire line sections (Dilles		`		
Bottom – Bellaire and				
Moundsville – Dilles Bottom		Moundsville – Dilles Bottom		
69 kV lines) south of		69 kV lines) south of		
b2753.7 FirstEnergy 138 kV line AEP (100%)	h2753 7	FirstEnergy 138 kV line		AED (100%)
corridor, near "Point A". Tie	02733.7	,		AEI (100%)
George Washington –		George Washington –		
Moundsville 69 kV circuit to		Moundsville 69 kV circuit to		
George Washington – West		George Washington – West		
Bellaire 69 kV circuit		Bellaire 69 kV circuit		
Rebuild existing 69 kV line		_		
as double circuit from				
George Washington – Dilles		George Washington – Dilles		
b2753.8 Bottom 138 kV. One circuit AEP (100%)	b2753.8	Bottom 138 kV. One circuit		AED (100%)
will cut into Dilles Bottom		will cut into Dilles Bottom		ALI (100%)
138 kV initially and the other		138 kV initially and the other		
will go past with future plans		will go past with future plans		
to cut in		to cut in		

Required Tra	ansmission Enhancements Annual	Revenue Requirement	Responsible Customer(s)
b2760	Perform a Sag Study of the Saltville – Tazewell 138 kV line to increase the thermal rating of the line		AEP (100%)
b2761.1	Replace the Hazard 161/138 kV transformer		AEP (100%)
b2761.2	Perform a Sag Study of the Hazard – Wooten 161 kV line to increase the thermal rating of the line		AEP (100%)
b2761.3	Rebuild the Hazard – Wooton 161 kV line utilizing 795 26/7 ACSR conductor (300 MVA rating)		AEP (100%)
b2762	Perform a Sag Study of Nagel - West Kingsport 138 kV line to increase the thermal rating of the line		AEP (100%)
b2776	Reconductor the entire Dequine – Meadow Lake 345 kV circuit #2		AEP (100%)
b2777	Reconductor the entire Dequine – Eugene 345 kV circuit #1		AEP (100%)
b2779.1	Construct a new 138 kV station, Campbell Road, tapping into the Grabill – South Hicksville138 kV line		AEP (100%)
b2779.2	Reconstruct sections of the Butler-N.Hicksville and Auburn-Butler 69 kV circuits as 138 kV double circuit and extend 138 kV from Campbell Road station		AEP (100%)

required 11		Revenue Requirement	Responsible Customer(s)
b2779.3	Construct a new 345/138 kV SDI Wilmington Station which will be sourced from Collingwood 345 kV and serve the SDI load at 345 kV and 138 kV, respectively		AEP (100%)
b2779.4	Loop 138 kV circuits in-out of the new SDI Wilmington 138 kV station resulting in a direct circuit to Auburn 138 kV and an indirect circuit to Auburn and Rob Park via Dunton Lake, and a circuit to Campbell Road; Reconductor 138 kV line section between Dunton Lake – SDI Wilmington		AEP (100%)
b2779.5	Expand Auburn 138 kV bus		AEP (100%)
b2787	Reconductor 0.53 miles (14 spans) of the Kaiser Jct Air Force Jct. Sw section of the Kaiser - Heath 69 kV circuit/line with 336 ACSR to match the rest of the circuit (73 MVA rating, 78% loading)		AEP (100%)
b2788	Install a new 3-way 69 kV line switch to provide service to AEP's Barnesville distribution station. Remove a portion of the #1 copper T-Line from the 69 kV throughpath		AEP (100%)

Required 11	ansmission Ennancements	Annuai Kevenue Kequiremeni	Responsible Cusiomer(s)
	Rebuild the Brues - Glendale Heights 69 kV line section (5		
<i>b</i> 2789	miles) with 795 ACSR (128		AEP (100%)
	MVA rating, 43% loading)		
	Install a 3 MVAR, 34.5 kV		
h2700	•		AED (1000/)
<i>b</i> 2790	cap bank at Caldwell		AEP (100%)
	substation		
<i>b</i> 2791	Rebuild Tiffin – Howard, new		AEP (100%)
	transformer at Chatfield		. , ,
	Rebuild portions of the East		
	Tiffin - Howard 69 kV line		
	from East Tiffin to West		177 (1000)
b2791.1	Rockaway Switch (0.8 miles)		AEP (100%)
	using 795 ACSR Drake		
	conductor (129 MVA rating,		
	50% loading)		
	Rebuild Tiffin - Howard 69		
	kV line from St. Stephen's		
	Switch to Hinesville (14.7		
<i>b</i> 2791.2	miles) using 795 ACSR Drake		AEP (100%)
	conductor (90 MVA rating,		
	non-conductor limited, 38%		
	loading)		
	New 138/69 kV transformer		
b2791.3	with 138/69 kV protection at		AEP (100%)
	Chatfield		
b2791.4	New 138/69 kV protection at		AEP (100%)
02/91.4	existing Chatfield transformer		AEF (100/0)
	Replace the Elliott		
	transformer with a 130 MVA		
	unit, reconductor 0.42 miles		
	of the Elliott – Ohio		
1.2702	University 69 kV line with		AED (1000Z)
b2792	556 ACSR to match the rest of		AEP (100%)
	the line conductor (102 MVÅ		
	rating, 73% loading) and		
	rebuild 4 miles of the Clark		
	Street – Strouds R		
L	1	ı	

Kequirea 11	ansmission Ennancements	Annual Revenue Requirement	Responsible Customer(s)
	Energize the spare Fremont Center 138/69 kV 130 MVA		
<i>b</i> 2793	transformer #3. Reduces		AEP (100%)
	overloaded facilities to 46%		
	loading		
	Construct new 138/69/34 kV		
	station and 1-34 kV circuit		
	(designed for 69 kV) from		
b2794	new station to Decliff station,		AEP (100%)
	approximately 4 miles, with		
	556 ACSR conductor (51		
	MVA rating)		
	Install a 34.5 kV 4.8 MVAR		
<i>b</i> 2795	capacitor bank at Killbuck		AEP (100%)
	34.5 kV station		
	Rebuild the Malvern - Oneida		
b2796	Switch 69 kV line section with		AEP (100%)
02790	795 ACSR (1.8 miles, 125		ALI (10070)
	MVA rating, 55% loading)		
	Rebuild the Ohio Central -		
	Conesville 69 kV line section		
	(11.8 miles) with 795 ACSR		
b2797	conductor (128 MVA rating,		AEP (100%)
	57% loading). Replace the 50		
	MVA Ohio Central 138/69 kV		
	XFMR with a 90 MVA unit		
	Install a 14.4 MVAR		
	capacitor bank at West		
<i>b</i> 2798	Hicksville station. Replace		AEP (100%)
02790	ground switch/MOAB at West		1121 (10070)
	Hicksville with a circuit		
	switcher		
	Rebuild Valley - Almena,		
	Almena - Hartford, Riverside		
b2799	- South Haven 69 kV lines.		AEP (100%)
	New line exit at Valley		(100/0)
	Station. New transformers at		
	Almena and Hartford		

Required Tr	ansmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
	Rebuild 12 miles of Valley – Almena 69 kV line as a		
	double circuit 138/69 kV line		
b2799.1	using 795 ACSR conductor		AEP (100%)
02///	(360 MVA rating) to		1121 (10070)
	introduce a new 138 kV		
	source into the 69 kV load		
	pocket around Almena station		
	Rebuild 3.2 miles of Almena		
b2799.2	to Hartford 69 kV line using		AEP (100%)
	795 ACSR conductor (90		
	MVA rating)		
	Rebuild 3.8 miles of Riverside		
b2799.3	- South Haven 69 kV line		AEP (100%)
	using 795 ACSR conductor		
	(90 MVA rating)		
	At Valley station, add new 138 kV line exit with a 3000 A		
b2799.4	40 kA breaker for the new 138 kV line to Almena and replace		AEP (100%)
	CB D with a 3000 A 40 kA		
	breaker		
	At Almena station, install a 90		
	MVA 138/69 kV transformer		
	with low side 3000 A 40 kA		
b2799.5	breaker and establish a new		AEP (100%)
	138 kV line exit towards		
	Valley		
	At Hartford station, install a		
	second 90 MVA 138/69 kV		
b2799.6	transformer with a circuit		AEP (100%)
	switcher and 3000 A 40 kA		
	low side breaker		

Kequirea 11	ansmission Ennancements	Annuai Kevenue Kequiremeni	Responsible Customer(s)
	Replace Delaware 138 kV		
b2817	breaker 'P' with a 40 kA		AEP (100%)
	breaker		
	Replace West Huntington 138		
b2818	kV breaker 'F' with a 40 kA		AEP (100%)
	breaker		
	Replace Madison 138 kV		
b2819	breaker 'V' with a 63 kA		AEP (100%)
	breaker		
	Replace Sterling 138 kV		
b2820	breaker 'G' with a 40 kA		AEP (100%)
	breaker		
	Replace Morse 138 kV		
b2821	breakers '103', '104', '105',		AEP (100%)
02821	and '106' with 63 kA		ALF (100%)
	breakers		
	Replace Clinton 138 kV		
b2822	breakers '105' and '107' with		AEP (100%)
	63 kA breakers		
	Install 300 MVAR reactor at		
b2826.1	Ohio Central 345 kV		AEP (100%)
	substation		

required 11	ansinission Emiancements Amida	revenue requirement	responsible editioner(s)
b2826.2	Install 300 MVAR reactor at West Bellaire 345 kV substation		AEP (100%)
b2831.1	Upgrade the Tanner Creek – Miami Fort 345 kV circuit (AEP portion)		DFAX Allocation: Dayton (34.34%) / DEOK (56.45%) / EKPC (9.21%)
b2832	Six wire the Kyger Creek – Sporn 345 kV circuits #1 and #2 and convert them to one circuit		AEP (100%)
b2833	Reconductor the Maddox Creek – East Lima 345 kV circuit with 2-954 ACSS Cardinal conductor		DFAX Allocation: Dayton (100%)
b2834	Reconductor and string open position and sixwire 6.2 miles of the Chemical – Capitol Hill 138 kV circuit		AEP (100%)
b2872	Replace the South Canton 138 kV breaker 'K2' with a 80 kA breaker		AEP (100%)
b2873	Replace the South Canton 138 kV breaker "M" with a 80 kA breaker		AEP (100%)
b2874	Replace the South Canton 138 kV breaker "M2" with a 80 kA breaker		AEP (100%)
b2878	Upgrade the Clifty Creek 345 kV risers		AEP (100%)
b2880	Rebuild approximately 4.77 miles of the Cannonsburg – South Neal 69 kV line section utilizing 795 ACSR conductor (90 MVA rating)		AEP (100%)

Required 110	ansmission Ennancements	Annuai Kevenue Kequirement	Responsible Cusiomer(s)
	Rebuild ~1.7 miles of the		
12001	Dunn Hollow – London 46 kV		
	line section utilizing 795 26/7		AED (1000/)
b2881	ACSR conductor (58 MVA		AEP (100%)
	rating, non-conductor		
	limited)		
	Rebuild Reusens - Peakland		
b2882	Switch 69 kV line. Replace		AEP (100%)
	Peakland Switch		
	Rebuild the Reusens -		
	Peakland Switch 69 kV line		
1,2002.1	(approximately 0.8 miles)		AED (1000/)
b2882.1	utilizing 795 ACSR conductor		AEP (100%)
	(86 MVA rating, non-		
	conductor limited)		
	Replace existing Peakland S.S		
b2882.2	with new 3 way switch phase		AEP (100%)
	over phase structure		
	Rebuild the Craneco – Pardee		
	– Three Forks – Skin Fork 46		
b2883	kV line section		AED (1000/)
02003	(approximately 7.2 miles)		AEP (100%)
	utilizing 795 26/7 ACSR		
	conductor (108 MVA rating)		
	Install a second transformer		
	at Nagel station, comprised of		
	3 single phase 250 MVA		
	500/138 kV transformers.		
b2884	Presently, TVA operates their		AED (1000/)
02004	end of the Boone Dam –		AEP (100%)
	Holston 138 kV		
	interconnection as normally		
	open preemptively for the loss		
	of the existing Nagel		
b2885	New delivery point for City of		AEP (100%)
02003	Jackson		ALI (100/0)

Required Tr	ansmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
	Install a new Ironman Switch		
	to serve a new delivery point		
b2885.1	requested by the City of		AEP (100%)
	Jackson for a load increase		
	request		
	Install a new 138/69 kV		
	station (Rhodes) to serve as a		
b2885.2	third source to the area to		AEP (100%)
	help relieve overloads caused		
	by the customer load increase		
	Replace Coalton Switch with		
<i>b</i> 2885.3	a new three breaker ring bus		AEP (100%)
	(Heppner)		
	Install 90 MVA 138/69 kV		
	transformer, new transformer		
b2886	high and low side 3000 A 40		AED (1000/)
02000	kA CBs, and a 138 kV 40 kA		AEP (100%)
	bus tie breaker at West End		
	Fostoria		
	Add 2-138 kV CB's and		
	relocate 2-138 kV circuit exits		
b2887	to different bays at Morse		AED (1000/)
02007	Road. Eliminate 3 terminal		AEP (100%)
	line by terminating Genoa -		
	Morse circuit at Morse Road		
	Retire Poston substation.		
<i>b</i> 2888	Install new Lemaster		AEP (100%)
	substation		,
10000	Remove and retire the Poston		AED (1000/)
b2888.1	138 kV station		AEP (100%)
	Install a new greenfield		
b2888.2	station, Lemaster 138 kV		AEP (100%)
	Station, in the clear		

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s)

Relocate the Trimble 69 kV

		<u> </u>	1 ()
b2888.3	Relocate the Trimble 69 kV AEP Ohio radial delivery point to 138 kV, to be served off of the Poston – Strouds Run – Crooksville 138 kV circuit via a new three-way switch. Retire the Poston - Trimble 69 kV line		AEP (100%)
b2889	Expand Cliffview station		AEP (100%)
b2889.1	Cliffview Station: Establish 138 kV bus. Install two 138/69 kV XFRs (130 MVA), six 138 kV CBs (40 kA 3000 A) and four 69 kV CBs (40 kA 3000 A)		AEP (100%)
b2889.2	Byllesby – Wythe 69 kV: Retire all 13.77 miles (1/0 CU) of this circuit (~4 miles currently in national forest)		AEP (100%)
b2889.3	Galax – Wythe 69 kV: Retire 13.53 miles (1/0 CU section) of line from Lee Highway down to Byllesby. This section is currently double circuited with Byllesby – Wythe 69 kV. Terminate the southern 3/0 ACSR section into the newly opened position at Byllesby		AEP (100%)
b2889.4	Cliffview Line: Tap the existing Pipers Gap – Jubal Early 138 kV line section. Construct double circuit in/out (~2 miles) to newly established 138 kV bus, utilizing 795 26/7 ACSR conductor		AEP (100%)

Required Tre	ansmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
	Rebuild 23.55 miles of the		
b2890.1	East Cambridge – Smyrna		
	34.5 kV circuit with 795		AEP (100%)
	ACSR conductor (128 MVA		
	rating) and convert to 69 kV		
	East Cambridge: Install a		
	2000 A 69 kV 40 kA circuit		
b2890.2	breaker for the East		AEP (100%)
	Cambridge – Smyrna 69 kV		
	circuit		
	Old Washington: Install 69		
b2890.3	kV 2000 A two way phase		AEP (100%)
	over phase switch		
b2890.4	Install 69 kV 2000 A two way		AEP (100%)
02090.4	phase over phase switch		AEI (10076)
	Rebuild the Midland Switch to		
	East Findlay 34.5 kV line		
b2891	(3.31 miles) with 795 ACSR		AEP (100%)
	(63 MVA rating) to match		
	other conductor in the area		
	Install new 138/12 kV		
	transformer with high side		
	circuit switcher at Leon and a		
	new 138 kV line exit towards		
b2892	Ripley. Establish 138 kV at		AEP (100%)
02072	the Ripley station with a new		<i>ILLI</i> (10070)
	138/69 kV 130 MVA		
	transformer and move the		
	distribution load to 138 kV		
	service		
	Rebuild approximately 6.7		
	miles of 69 kV line between		
	Mottville and Pigeon River		
b2936.1	using 795 ACSR conductor		AEP (100%)
	(129 MVA rating). New		(100/0)
	construction will be designed		
	to 138 kV standards but		
	operated at 69 kV		

Required Tr	ansmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2936.2	Pigeon River Station: Replace existing MOAB Sw. 'W' with a new 69 kV 3000 A 40 kA breaker, and upgrade existing relays towards HMD station. Replace CB H with a 3000 A 40 kA breaker		AEP (100%)
b2937	Replace the existing 636 ACSR 138 kV bus at Fletchers Ridge with a larger 954 ACSR conductor		AEP (100%)
b2938	Perform a sag mitigations on the Broadford – Wolf Hills 138 kV circuit to allow the line to operate to a higher maximum temperature		AEP (100%)
b2958.1	Cut George Washington – Tidd 138 kV circuit into Sand Hill and reconfigure Brues & Warton Hill line entrances		AEP (100%)
b2958.2	Add 2 138 kV 3000 A 40 kA breakers, disconnect switches, and update relaying at Sand Hill station		AEP (100%)
b2968	Upgrade existing 345 kV terminal equipment at Tanner Creek station		AEP (100%)
b2969	Replace terminal equipment on Maddox Creek - East Lima 345 kV circuit		AEP (100%)
b2976	Upgrade terminal equipment at Tanners Creek 345 kV station. Upgrade 345 kV bus and risers at Tanners Creek for the Dearborn circuit		DEOK (100%)

SCHEDULE 12 – APPENDIX A

(19) Northern Indiana Public Service Company

Required Train	smission Enhancements A	Annual Revenue Requirement Responsible Customer(s)
		MISO (12.00%) / AEC (0.97%) /
		AEP (16.66%) / APS (4.94%) /
		ATSI (7.78%) / BGE (5.21%) /
		Dayton (1.85%) / DEOK (2.30%) /
	Decemberry Muncter 245	Dominion (15.21%) / DPL (1.75%)
b2971	Reconfigure Munster 345 kV as ring bus	/DL(1.43%)/EKPC(0.60%)/
	K v as fing ous	JCPL (2.16%) / ME (1.73%) /
		PECO (4.32%) / PENELEC
		(4.98%)/PEPCO(5.80%)/PPL
		(4.74%)/PSEG (5.09%)/RE
		(0.15%)/NEPTUNE* (0.33%)
		MISO (10.00%) / AEC (0.93%) /
		AEP (26.05%) / APS (4.19%) /
		ATSI (5.95%) / BGE (4.39%) /
		Dayton (1.59%) / DEOK (2.30%) /
	Reconductor Michigan	Dominion (14.72%) / DPL (1.53%)
b2973	City - Bosserman 138 kV	/ DL (1.26%) / EKPC (0.98%) /
	City - Bosserman 136 kV	JCPL (1.92%)/ME (1.39%)/
		PECO (4.19%) / PENELEC
		(4.35%)/PEPCO(5.06%)/PPL
		(4.03%)/PSEG (4.49%)/RE
		(0.12%) / NEPTUNE* (0.56%)
	Replace terminal equipment at Reynolds on the Reynolds - Magnetation 138 kV	MISO (59.00%) / AEC (0.01%) /
		AEP (40.32%) / APS (0.13%) /
		ATSI (0.05%) / BGE (0.08%) /
b2974		Dayton (0.03%) / DPL (0.01%) /
		ME (0.04%) / PENELEC (0.06%) /
	Wingheumon 130 K	PPL (0.20%) / PSEG (0.03%) /
		NEPTUNE* (0.04%)
		MISO (76.00%) / AEC (0.28%) /
		AEP (4.51%) / APS (1.31%) /
		ATSI (1.91%) / BGE (1.40%) /
		Dayton (0.49%) / DEOK (0.70%) /
	Reconductor Roxana -	Dominion (4.35%) / DPL (0.46%) /
b2975	Praxair 138 kV	DL (0.38%) / EKPC (0.27%) /
	F14X411 130 KV	JCPL (0.57%) / ME (0.43%) /
		PECO (1.25%)/PENELEC
		(1.34%)/PEPCO(1.53%)/PPL
		(1.23%)/PSEG (1.41%)/RE
		(0.04%)/NEPTUNE* (0.14%)

SCHEDULE 12 – APPENDIX A

(20) Virginia Electric and Power Company

Required 1	Tarishinssion Elinancements Annua	ai Revenue Requirement	Responsible Customer(s)
b1698.7	Replace Loudoun 230 kV breaker '203052' with 63kA rating		Dominion (100%)
b1696.1	Replace the Idylwood 230 kV '25112' breaker with 50kA breaker		Dominion (100%)
b1696.2	Replace the Idylwood 230 kV '209712' breaker with 50kA breaker		Dominion (100%)
b1793.1	Remove the Carolina 22 SPS to include relay logic changes, minor control wiring, relay resets and SCADA programming upon completion of project		Dominion (100%)
b2281	Additional Temporary SPS at Bath County		Dominion (100%)
b2350	Reconductor 211 feet of 545.5 ACAR conductor on 59 Line Elmont - Greenwood DP 115 kV to achieve a summer emergency rating of 906 amps or greater		Dominion (100%)
b2358	Install a 230 kV 54 MVAR capacitor bank on the 2016 line at Harmony Village Substation		Dominion (100%)
b2359	Wreck and rebuild approximately 1.3 miles of existing 230 kV line between Cochran Mill - X4-039 Switching Station		Dominion (100%)
b2360	Build a new 39 mile 230 kV transmission line from Dooms - Lexington on existing right- of-way		Dominion (100%)
b2361	Construct 230 kV OH line along existing Line #2035 corridor, approx. 2.4 miles from Idylwood - Dulles Toll Road (DTR) and 2.1 miles on new right-of-way along DTR to new Scott's Run Substation		Dominion (100%)

Required Transmission Enhancements Annual Revenue Requirement Responsible Customer(s)

1	Tanoninosion Emilancemento 7 mina	
b2368	Replace the Brambleton 230 kV breaker '209502' with 63kA breaker	Dominion (100%)
b2369	Replace the Brambleton 230 kV breaker '213702' with 63kA breaker	Dominion (100%)
b2370	Replace the Brambleton 230 kV breaker 'H302' with 63kA breaker	Dominion (100%)
b2373	Build a 2nd Loudoun - Brambleton 500 kV line within the existing ROW. The Loudoun - Brambleton 230 kV line will be relocated as an underbuild on the new 500 kV line	Dominion (100%)
b2397	Replace the Beaumeade 230 kV breaker '2079T2116' with 63kA	Dominion (100%)
b2398	Replace the Beaumeade 230 kV breaker '2079T2130' with 63kA	Dominion (100%)
b2399	Replace the Beaumeade 230 kV breaker '208192' with 63kA	Dominion (100%)
b2400	Replace the Beaumeade 230 kV breaker '209592' with 63kA	Dominion (100%)
b2401	Replace the Beaumeade 230 kV breaker '211692' with 63kA	Dominion (100%)
b2402	Replace the Beaumeade 230 kV breaker '227T2130' with 63kA	Dominion (100%)
b2403	Replace the Beaumeade 230 kV breaker '274T2130' with 63kA	Dominion (100%)

The Annual Revenue Requirement for all Virginia Electric and Power Company projects in this Section 20 shall be as specified in Attachment 7 to Appendix A of Attachment H-16A and under the procedures detailed in Attachment H-16B.

^{*}Neptune Regional Transmission System, LLC

^{**}East Coast Power, L.L.C.

^{***}Hudson Transmission Partners, LLC

Required T	ransmission Enhancements A	Annual Revenue Requirement	Responsible Customer(s)
b2404	Replace the Beaumeade 230 kV breaker '227T2095' with 63kA		Dominion (100%)
b2405	Replace the Pleasant view 230 kV breaker '203T274' with 63kA		Dominion (100%)
b2443	Construct new underground 230 kV line from Glebe to Station C, rebuild Glebe Substation, construct 230 kV high side bus at Station C with option to install 800 MVA PAR		Dominion (97.11%) / ME (0.18%) / PEPCO (2.71%)
b2443.1	Replace the Idylwood 230 kV breaker '203512' with 50kA		Dominion (100%)
b2443.2	Replace the Ox 230 kV breaker '206342' with 63kA breaker		Dominion (100%)
b2443.3	Glebe – Station C PAR		DFAX Allocation: Dominion (22.57%) / PEPCO (77.43%)
b2457	Replace 24 115 kV wood h-frames with 230 kV Dominion pole H-frame structures on the Clubhouse – Purdy 115 kV line		Dominion (100%)
b2458.1	Replace 12 wood H-frame structures with steel H- frame structures and install shunts on all conductor splices on Carolina – Woodland 115 kV		Dominion (100%)
b2458.2	Upgrade all line switches and substation components at Carolina 115 kV to meet or exceed new conductor rating of 174 MVA		Dominion (100%)
b2458.3	Replace 14 wood H-frame structures on Carolina – Woodland 115 kV		Dominion (100%)
b2458.4	Replace 2.5 miles of static wire on Carolina – Woodland 115 kV		Dominion (100%)

Required 1		Annual Revenue Requirement	Responsible Customer(s)
b2458.5	Replace 4.5 miles of conductor between Carolina 115 kV and Jackson DP 115 kV with min. 300 MVA summer STE rating; Replace 8 wood H-frame structures located between Carolina and Jackson DP with steel H-frames		Dominion (100%)
b2460.1	Replace Hanover 230 kV substation line switches with 3000A switches		Dominion (100%)
b2460.2	Replace wave traps at Four River 230 kV and Elmont 230 kV substations with 3000A wave traps		Dominion (100%)
b2461	Wreck and rebuild existing Remington CT – Warrenton 230 kV (approx. 12 miles) as a double-circuit 230 kV line		Dominion (100%)
b2461.1	Construct a new 230 kV line approximately 6 miles from NOVEC's Wheeler Substation a new 230 kV switching station in Vint Hill area		Dominion (100%)
b2461.2	Convert NOVEC's Gainesville – Wheeler line (approximately 6 miles) to 230 kV		Dominion (100%)
b2461.3	Complete a Vint Hill – Wheeler – Loudoun 230 kV networked line		Dominion (100%)

Required 1	ransmission Ennancements Annua	al Revenue Requirement	Responsible Customer(s)
			Load-Ratio Share Allocation:
			AEC (1.66%) / AEP (14.16%)
			/ APS (5.73%) / ATSI (7.88%)
			/ BGE (4.22%) / ComEd
			(13.31%) / Dayton (2.11%) /
	Replace Midlothian 500 kV		DEOK (3.29%) / DL (1.75%) /
	breaker 563T576 and motor operated switches with 3		DPL (2.50%) / Dominion
	breaker 500 kV ring bus.		(12.86%) / EKPC (1.87%) /
b2471	Terminate Lines # 563 Carson		` ' '
	– Midlothian, #576		JCPL (3.74%) / ME (1.90%) /
	Midlothian –North Anna,		NEPTUNE* (0.44%) / PECO
	Transformer #2 in new ring		(5.34%) / PENELEC (1.89%) /
			PEPCO (3.99%) / PPL (4.84%)
			/ PSEG (6.26%) / RE (0.26%)
			DFAX Allocation:
	Rebuild 115 kV Line #32		Dominion (100%)
	from Halifax-South Boston (6		
	miles) for min. of 240 MVA		
b2504	and transfer Welco tap to Line		D :: (1000()
0200.	#32. Moving Welco to Line		Dominion (100%)
	#32 requires disabling auto-		
	sectionalizing scheme		
	Install structures in river to		
1-2505	remove the 115 kV #65 line		
b2505	(Whitestone-Harmony Village 115 kV) from bridge and		Dominion (100%)
	improve reliability of the line		, ,
	Replace the Loudoun 500 kV		
b2542	'H2T502' breaker with a		D (1000/)
	50kA breaker		Dominion (100%)
	Replace the Loudoun 500 kV		
b2543	'H2T584' breaker with a		Dominion (100%)
	50kA breaker		Bollillon (10070)
1-05.65	Reconductor wave trap at Carver Substation with a		
b2565	2000A wave trap		Dominion (100%)
	Reconductor 1.14 miles of		` ′
	existing line between ACCA		
b2566	and Hermitage and upgrade		Dominion (100%)
	associated terminal equipment		2011111011 (10070)

11040111111	Terrisminission Emiliancements 1	 Trosponorero Constanter(s)
b2582	Rebuild the Elmont – Cunningham 500 kV line	Dominion (100%)
b2583	Install 500 kV breaker at Ox Substation to remove Ox Tx#1 from H1T561 breaker failure outage.	Dominion (100%)
b2584	Relocate the Bremo load (transformer #5) to #2028 (Bremo-Charlottesville 230 kV) line and Cartersville distribution station to #2027 (Bremo- Midlothian 230 kV) line	Dominion (100%)
b2585	Reconductor 7.63 miles of existing line between Cranes and Stafford, upgrade associated line switches at Stafford	DFAX Allocation: PEPCO (100%)
b2620	Wreck and rebuild the Chesapeake – Deep Creek – Bowers Hill – Hodges Ferry 115 kV line; minimum rating 239 MVA normal/emergency, 275 MVA load dump rating	Dominion (100%)

Required 1		inual Revenue Requirement	Responsible Customer(s)
b2622	Rebuild Line #47 between Kings Dominion 115 kV and Fredericksburg 115 kV to current standards with summer emergency rating of 353 MVA at 115 kV		Dominion (100%)
b2623	Rebuild Line #4 between Bremo and Structure 8474 (4.5 miles) to current standards with a summer emergency rating of 261 MVA at 115 kV		Dominion (100%)
b2624	Rebuild 115 kV Lines #18 and #145 between Possum Point Generating Station and NOVEC's Smoketown DP (approx. 8.35 miles) to current 230 kV standards with a normal continuous summer rating of 524 MVA at 115 kV		Dominion (100%)
b2625	Rebuild 115 kV Line #48 between Thole Street and Structure 48/71 to current standard. The remaining line to Sewells Point is 2007 vintage. Rebuild 115 kV Line #107 line, Sewells Point to Oakwood, between structure 107/17 and 107/56 to current standard.		Dominion (100%)
b2626	Rebuild 115 kV Line #34 between Skiffes Creek and Yorktown and the double circuit portion of 115 kV Line #61 to current standards with a summer emergency rating of 353 MVA at 115 kV		Dominion (100%)
b2627	Rebuild 115 kV Line #1 between Crewe 115 kV and Fort Pickett DP 115 kV (12.2 miles) to current standards with summer emergency rating of 261 MVA at 115 kV		Dominion (100%)

Required 1		ual Revenue Requirement	Responsible Customer(s)
	Rebuild 115 kV Line #82		
b2628	Everetts – Voice of America		
	(20.8 miles) to current		Dominion (100%)
02020	standards with a summer		20111111011 (10070)
	emergency rating of 261		
	MVA at 115 kV		
	Rebuild the 115 kV Lines		
	#27 and #67 lines from		
	Greenwich 115 kV to Burton		
b2629	115 kV Structure 27/280 to		Dominion (100%)
02023	current standard with a		2 0111111011 (10070)
	summer emergency rating of		
	262 MVA at 115 kV		
	Install circuit switchers on		
	Gravel Neck Power Station		
	GSU units #4 and #5. Install		
b2630	two 230 kV CCVT's on		Dominion (100%)
			` ′
	Lines #2407 and #2408 for		
	loss of source sensing		
	Install three 230 kV bus		
	breakers and 230 kV, 100		
	MVAR Variable Shunt		
	Reactor at Dahlgren to		
b2636	provide line protection		Dominion (100%)
	during maintenance, remove		
	the operational hazard and		
	provide voltage reduction		
	during light load conditions		
	Rebuild Boydton Plank Rd –		
	Kerr Dam 115 kV Line #38		
1.0647	(8.3 miles) to current		D :: (1000()
b2647	standards with summer		Dominion (100%)
	emergency rating of 353		
	MVA at 115 kV.		
	Rebuild Carolina – Kerr		
	Dam 115 kV Line #90 (38.7		
b2648	miles) to current standards		Dominion (100%)
02048	with summer emergency		Dominion (100%)
	rating of 353 MVA 115 kV.		
	Rebuild Clubhouse –		
	Carolina 115 kV Line #130		
b2649	(17.8 miles) to current		Dominion (100%)
02047	standards with summer		
	emergency rating of 353		
	MVA at 115 kV.		

Kequirea 1	ransmission Ennancements - Anni	ıcı Kevenue Kequiremeni	Responsible Customer(s)
b2649.1	Rebuild of 1.7 mile tap to Metcalf and Belfield DP (MEC) due to poor condition. The existing summer rating of the tap is 48 MVA and existing conductor is 4/0 ACSR on wood H-frames. The proposed new rating is 176 MVA using 636 ACSR conductor		Dominion (100%)
b2649.2	Rebuild of 4.1 mile tap to Brinks DP (MEC) due to wood poles built in 1962. The existing summer rating of the tap is 48 MVA and existing conductor is 4/0 ACSR and 393.6 ACSR on wood H-frames. The proposed new rating is 176 MVA using 636 ACSR conductor		Dominion (100%)
b2650	Rebuild Twittys Creek – Pamplin 115 kV Line #154 (17.8 miles) to current standards with summer emergency rating of 353 MVA at 115 kV.		Dominion (100%)

Required 116	ansmission Enhancements Annu	iai Revenue Requirement	Responsible Customer(s)
b2651	Rebuild Buggs Island – Plywood 115 kV Line #127 (25.8 miles) to current standards with summer emergency rating of 353 MVA at 115 kV. The line should be rebuilt for 230 kV and operated at 115 kV.		Dominion (100%)
b2652	Rebuild Greatbridge – Hickory 115 kV Line #16 and Greatbridge – Chesapeake E.C. to current standard with summer emergency rating of 353 MVA at 115 kV.		Dominion (100%)
b2653.1	Build 20 mile 115 kV line from Pantego to Trowbridge with summer emergency rating of 353 MVA.		Dominion (100%)
b2653.2	Install 115 kV four-breaker ring bus at Pantego		Dominion (100%)
b2653.3	Install 115 kV breaker at Trowbridge		Dominion (100%)
b2654.1	Build 15 mile 115 kV line from Scotland Neck to S Justice Branch with summer emergency rating of 353 MVA. New line will be routed to allow HEMC to convert Dawson's Crossroads RP from 34.5 kV to 115 kV.		Dominion (100%)
b2654.2	Install 115 kV three-breaker ring bus at S Justice Branch		Dominion (100%)
b2654.3	Install 115 kV breaker at Scotland Neck		Dominion (100%)

		1	· '/
b2665	Rebuild the Cunningham – Dooms 500 kV line		Dominion (100%)
b2686	Pratts Area Improvement		Dominion (100%)
b2686.1	Build a 230 kV line from Remington Substation to Gordonsville Substation utilizing existing ROW		Dominion (100%)
b2686.11	Upgrading sections of the Gordonsville – Somerset 115 kV circuit		Dominion (100%)
b2686.12	Upgrading sections of the Somerset – Doubleday 115 kV circuit		Dominion (100%)
b2686.13	Upgrading sections of the Orange – Somerset 115 kV circuit		Dominion (100%)
b2686.14	Upgrading sections of the Mitchell – Mt. Run 115 kV circuit		Dominion (100%)
b2686.2	Install a 3rd 230/115 kV transformer at Gordonsville Substation		Dominion (100%)

^{*}Neptune Regional Transmission System, LLC

** East Coast Power, LLC

***Hudson Transmission Partners, LLC

Required 118	ansmission Ennancements	Annual Revenue Requireme	ent Responsible Customer(s)
b2686.3	Upgrade Line 2088 between Gordonsville Substation and Louisa CT Station		Dominion (100%)
b2717.1	De-energize Davis – Rosslyn #179 and #180 69 kV lines		Dominion (100%)
b2717.2	Remove splicing and stop joints in manholes		Dominion (100%)
b2717.3	Evacuate and dispose of insulating fluid from various reservoirs and cables		Dominion (100%)
b2717.4	Remove all cable along the approx. 2.5 mile route, swab and cap-off conduits for future use, leave existing communication fiber in place		Dominion (100%)
b2719.1	Expand Perth substation and add a 115 kV four breaker ring		Dominion (100%)
b2719.2	Extend the Hickory Grove DP tap 0.28 miles to Perth and terminate it at Perth		Dominion (100%)
b2719.3	Split Line #31 at Perth and terminate it into the new ring bus with 2 breakers separating each of the line terminals to prevent a breaker failure from taking out both 115 kV lines		Dominion (100%)
b2720	Replace the Loudoun 500 kV 'H1T569' breakers with 50kA breaker		Dominion (100%)
b2729	Optimal Capacitors Configuration: New 175 MVAR capacitor at Brambleton, new 175 MVAR capacitor at Ashburn, new 300 MVAR capacitor at Shelhorm, new 150 MVAR capacitor at Liberty		AEC (1.96%) / BGE (14.37%) / Dominion (35.11%) / DPL (3.76%) / ECP (0.29%) / HTP (0.34%) / JCPL (3.31%) / ME (2.51%) / Neptune (0.63%) / PECO (6.26%) / PEPCO (20.23%) / PPL (3.94%) /PSEG (7.29%)

Required Tra	ansmission Enhancements Annual	Revenue Requirement	Responsible Customer(s)
			Load-Ratio Share
			Allocation:
			AEC (1.66%) / AEP (14.16%)
			/ APS (5.73%) / ATSI
			(7.88%) / BGE (4.22%) /
			ComEd (13.31%) / Dayton
			(2.11%) / DEOK (3.29%) /
			DL (1.75%) / DPL (2.50%) /
b2744	Rebuild the Carson – Rogers		Dominion (12.86%) / EKPC
02744	Rd 500 kV circuit		(1.87%) / JCPL (3.74%) / ME
			(1.90%) / NEPTUNE*
			(0.44%) / PECO (5.34%) /
			PENELEC (1.89%) / PEPCO
			(3.99%) / PPL (4.84%) /
			PSEG (6.26%) / RE (0.26%)
			DFAX Allocation:
			Dominion (100%)
	Rebuild 21.32 miles of		. ,
b2745	existing line between		Dominion (100%)
	Chesterfield – Lakeside 230 kV		_ ::::::: (- : : / · / /
	Rebuild Line #137 Ridge Rd		
b2746.1	– Kerr Dam 115 kV, 8.0		Dominion (100%)
02/40.1	miles, for 346 MVA summer		Dominion (100%)
	emergency rating Rebuild Line #1009 Ridge Rd		
	- Chase City 115 kV, 9.5		
b2746.2	miles, for 346 MVA summer		Dominion (100%)
	emergency rating		
	Install a second 4.8 MVAR		
b2746.3	capacitor bank on the 13.8 kV bus of each transformer at		Dominion (100%)
	Ridge Rd		
	Install a Motor Operated		
1.07.45	Switch and SCADA control		D :: (1000)
b2747	between Dominion's Gordonsville 115 kV bus and		Dominion (100%)
	FirstEnergy's 115 kV line		
	I HOLLHOLEY STILL KY IIIIC		

Required 11	ansmission Emhancements Annual	Revenue Requirement	Responsible Customer(s)
b2757	Install a +/-125 MVAr Statcom at Colington 230 kV		Dominion (100%)
b2758	Rebuild Line #549 Dooms – Valley 500kV		Dominion (100%)
b2759	Rebuild Line #550 Mt. Storm – Valley 500kV		Dominion (100%)
b2800	The 7 mile section from Dozier to Thompsons Corner of line #120 will be rebuilt to current standards using 768.2 ACSS conductor with a summer emergency rating of 346 MVA at 115 kV. Line is proposed to be rebuilt on single circuit steel monopole structure		Dominion (100%)
b2801	Lines #76 and #79 will be rebuilt to current standard using 768.2 ACSS conductor with a summer emergency rating of 346 MVA at 115 kV. Proposed structure for rebuild is double circuit steel monopole structure		Dominion (100%)
b2802	Rebuild Line #171 from Chase City – Boydton Plank Road tap by removing end- of-life facilities and installing 9.4 miles of new conductor. The conductor used will be at current standards with a summer emergency rating of 393 MVA at 115kV		Dominion (100%)
b2815	Build a new Pinewood 115kV switching station at the tap serving North Doswell DP with a 115kV four breaker ring bus		Dominion (100%)
b2842	Update the nameplate for Mount Storm 500 kV "57272" to be 50kA breaker		Dominion (100%)
b2843	Replace the Mount Storm 500 kV "G2TY" with 50kA breaker		Dominion (100%)
b2844	Replace the Mount Storm 500 kV "G2TZ" with 50kA breaker		Dominion (100%)

Required 11	ansmission Ennancements Annual Revenue Requirement	Responsible Customer(s)
b2845	Update the nameplate for Mount Storm 500 kV "G3TSX1" to be 50kA breaker	Dominion (100%)
b2846	Update the nameplate for Mount Storm 500 kV "SX172" to be 50kA breaker	Dominion (100%)
b2847	Update the nameplate for Mount Storm 500 kV "Y72" to be 50kA breaker	Dominion (100%)
b2848	Replace the Mount Storm 500 kV "Z72" with 50kA breaker	Dominion (100%)
b2871	Rebuild 230 kV line #247 from Swamp to Suffolk (31 miles) to current standards with a summer emergency rating of 1047 MVA at 230 kV	Dominion (100%)
b2876	Rebuild line #101 from Mackeys — Creswell 115 kV, 14 miles, with double circuit structures. Install one circuit with provisions for a second circuit. The conductor used will be at current standards with a summer emergency rating of 262 MVA at 115 kV	Dominion (100%)
b2877	Rebuild line #112 from Fudge Hollow – Lowmoor 138 kV (5.16 miles) to current standards with a summer emergency rating of 314 MVA at 138 kV	Dominion (100%)
b2899	Rebuild 230 kV line #231 to current standard with a summer emergency rating of 1046 MVA. Proposed conductor is 2-636 ACSR	Dominion (100%)
b2900	Build a new 230/115 kV switching station connecting to 230 kV network line #2014 (Earleys – Everetts). Provide a 115 kV source from the new station to serve Windsor DP	Dominion (100%)

Required Tre	ansmission Enhancements - Annual	Revenue Requirement	Responsible Customer(s)
b2922	Rebuild 8 of 11 miles of 230 kV lines #211 and #228 to current standard with a summer emergency rating of 1046 MVA for rebuilt section. Proposed conductor is 2-636 ACSR		Dominion (100%)
b2928	Rebuild four structures of 500 kV line #567 from Chickahominy to Surry using galvanized steel and replace the river crossing conductor with 3-1534 ACSR. This will increase the line #567 line rating from 1954 MVA to 2600 MVA		Dominion (100%)
b2929	Rebuild 230 kV line #2144 from Winfall to Swamp (4.3 miles) to current standards with a standard conductor (bundled 636 ACSR) having a summer emergency rating of 1047 MVA at 230 kV		Dominion (100%)
b2960	Replace fixed series capacitors on 500 kV Line #547 at Lexington and on 500 kV Line #548 at Valley		Dominion (100%)
b2961	Rebuild approximately 3 miles of Line #205 & Line #2003 from Chesterfield to Locks & Poe respectively		Dominion (100%)
b2962	Split Line #227 (Brambleton – Beaumeade 230 kV) and terminate into existing Belmont substation		Dominion (100%)
b2963	Reconductor the Woodbridge to Occoquan 230 kV line segment of Line #2001 with 1047 MVA conductor and replace line terminal equipment at Possum Point, Woodbridge, and Occoquan		Dominion (100%)

SCHEDULE 12 – APPENDIX A

(23) American Transmission Systems, Inc.

Required T	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2019.2	Terminate Burger – Longview 138 kV, Burger – Brookside 138 kV, Burger – Cloverdale 138 kV #1, and Burger – Harmon 138 kV #2 into Holloway substation; Loop Burger – Harmon #1 138 kV and Burger – Knox 138 kV into Holloway substation		ATSI (100%)
b2019.3	Reconfigure Burger 138 kV substation to accommodate two 138 kV line exits and generation facilities		ATSI (100%)
b2019.4	Remove both Burger 138 kV substations (East and West 138 kV buses) and all 138 kV lines on the property		ATSI (100%)
b2019.5	Terminate and de- energize the 138 kV lines on the last structure before the Burger Plant property		ATSI (100%)
b2122.1	Reconductor the ATSI portion of the Howard – Brookside 138 kV line		ATSI (100%)
b2122.2	Upgrade terminal equipment at Brookside on the Howard – Brookside 138 kV line to achieve ratings of 252/291 (SN/SE)		ATSI (100%)
b2188	Revise the reclosing for the Bluebell 138 kV breaker '301-B-94'		ATSI (100%)
b2192	Replace the Longview 138 kV breaker '651-B-32'		ATSI (100%)
b2193	Replace the Lowellville 138 kV breaker '1-10-B 4'		ATSI (100%)

Required T	ransmission Enhancements	Annual Revenue Requirement	Responsible Customer(s)
b2195	Replace the Roberts 138 kV breaker '601-B-60'		ATSI (100%)
b2196	Replace the Sammis 138 kV breaker '780-B-76'		ATSI (100%)
b2262	New Castle Generating Station – Relocate 138kV, 69kV, and 23kV controls from the generating station building to new control building		ATSI (100%)
b2263	Niles Generation Station – Relocate 138kV and 23kV controls from the generation station building to new control building		ATSI (100%)
b2265	Ashtabula Generating Station – Relocate 138kV controls from the generating station building to new control building		ATSI (100%)
b2284	Increase the design operating temperature on the Cloverdale – Barberton 138kV line		ATSI (100%)
b2285	Increase the design operating temperature on the Cloverdale – Star 138kV line		ATSI (100%)
b2301	Reconductor 0.7 miles of 605 ACSR conductor on the Beaver Black River 138kV line		ATSI (100%)
b2301.1	Wave trap and line drop replacement at Beaver (312/380 MVA SN/SE)		ATSI (100%)
b2349	Replace the East Springfield 138kV breaker 211-B-63 with 40kA		ATSI (100%)
b2367	Replace the East Akron 138kV breaker 36-B-46 with 40kA		ATSI (100%)

required 1	ransmission Enhancements A	innual Revenue Requirement	Responsible Customer(s)
b2413	Replace a relay at McDowell 138 kV substation		ATSI (100%)
b2434	Build a new London – Tangy 138 kV line		ATSI (100%)
b2435	Build a new East Springfield – London #2 138 kV line		ATSI (100%)
b2459	Install +260/-150 MVAR SVC at Lake Shore		ATSI (100%)
b2492	Replace the Beaver 138 kV breaker '426-B-2' with 63kA breaker		ATSI (100%)
b2493	Replace the Hoytdale 138kV breaker '83-B-30' with 63kA breaker		ATSI (100%)
b2557	At Avon substation, replace the existing 345/138 kV 448 MVA #92 transformer with a 560 MVA unit		ATSI (100%)
b2558	Close normally open switch A 13404 to create a Richland J Bus – Richland K Bus 138 kV line		ATSI (100%)
b2559	Reconductor the Black River – Lorain 138 kV line and upgrade Black River and Lorain substation terminal end equipment		ATSI (100%)
b2560	Construct a second 138 kV line between West Fremont and Hayes substation on open tower position of the West Fremont –Groton –Hayes 138 kV line		ATSI (100%)
b2616	Addition of 4th 345/138 kV transformer at Harding		ATSI (100%)

Required T	ransmission Enhancements An	inual Revenue Requirement	Responsible Customer(s)
b2673	Rebuild the existing double circuit tower line section from Beaver substation to Brownhelm Jct. approx. 2.8 miles		ATSI (100%)
b2674	Rebuild the 6.6 miles of Evergreen to Ivanhoe 138 kV circuit with 477 ACSS conductor		ATSI (100%)
b2675	Install 26.4 MVAR capacitor and associated terminal equipment at Lincoln Park 138 kV substation		ATSI (100%)
b2725	Build new 345/138 kV Lake Avenue substation w/ breaker and a half high side (2 strings), 2-345/138 kV transformers and breaker and a half (2 strings) low side (138 kV). Substation will tie Avon – Beaver 345 kV #1/#2 and Black River – Johnson #1/#2 lines		ATSI (100%)
b2725.1	Replace the Murray 138 kV breaker '453-B-4' with 40kA breaker		ATSI (100%)
b2742	Replace the Hoytdale 138 kV '83-B-26' and '83-B- 30' breakers with 63kA breakers		ATSI (100%)
b2753.4	Double capacity for 6 wire "Burger-Cloverdale No. 2" 138 kV line and connect at Holloway and "Point A"		ATSI (100%)
b2753.5	Double capacity for 6 wire "Burger-Longview" 138 kV line and connect at Holloway and "Point A"		ATSI (100%)
b2778	Add 2nd 345/138 kV transformer at Chamberlin substation		ATSI (100%)
b2780	Replace Bruce Mansfield 345 kV breaker 'B57' with an 80 kA breaker, and associated gang-operated disconnect switches D56 and D58		ATSI (100%)

1	idiomission Emidicements 7 in	 (-)
b2869	Replace the Crossland 138 kV breaker "B-16" with a 40kA breaker	ATSI (100%)
b2875	Relocate the Richland to Ridgeville 138 kV line from Richland J bus to K, extend the K bus and install a new breaker	ATSI (100%)
b2896	Rebuild/Reconductor the Black River – Lorain 138 kV circuit	ATSI (100%)
b2897	Reconductor the Avon – Lorain 138 kV section and upgrade line drop at Avon	ATSI (100%)
b2898	Reconductor the Beaver – Black River 138 kV with 954Kcmil ACSS conductor and upgrade terminal equipment on both stations	ATSI (100%)
b2942.1	Install a 100 MVAR 345 kV shunt reactor at Hayes substation	ATSI (100%)
b2942.2	Install a 200 MVAR 345 kV shunt reactor at Bayshore substation	ATSI (100%)
b2972	Reconductor limiting span of Lallendorf – Monroe 345 kV	MISO (11.00%) / AEP (5.38%) / APS (4.27%) / ATSI (66.48%) / Dayton (2.71%) / Dominion (5.31%) / DL (4.85%)