

PJM Interconnection, L.L.C. 2750 Monroe Blvd. Audubon, PA 19403

Daniel Vinnik Counsel T: (267) 858-9451 daniel.vinnik@pjm.com

March 28, 2025

The Honorable Debbie-Anne A. Reese Secretary Federal Energy Regulatory Commission 888 First Street, N.E. Washington, D.C. 20426-0001

Re: PJM Interconnection L.L.C., Docket No. ER25-1813-000, Proposal to Add Two New ELCC Classes (i.e., Oil Fired Combustion Turbine Class and Waste to Energy Steam Class) and Make Conforming Revisions

Dear Secretary Reese:

Pursuant to section 205 of the Federal Power Act ("FPA"), 16 U.S.C. § 824d, and the Federal Energy Regulatory Commission's ("Commission") Regulations,¹ PJM Interconnection, L.L.C. ("PJM") hereby submits revisions to the PJM Reliability Assurance Agreement Among Load Serving Entities ("RAA") to add two new effective load carrying capability classes ("ELCC Classes") effective with the 2027/2028 Delivery Year,² and conforming clarifications. Specifically, this proposal will add two new definitions, one for a steam powered "Waste to Energy Steam Class" and another for an "Oil Fired Combustion Turbine Class." This filing also proposes conforming changes to the current definition of "Steam Class" definition is being proposed for

¹ 18 C.F.R. Part 35.

² For the purpose of this filing, capitalized terms not defined herein shall have the meaning as contained in the PJM Open Access Transmission Tariff, Amended and Restated Operating Agreement, and the Reliability Assurance Agreement Among Load Serving Entities in the PJM Region.

steam units. Finally, this filing proposes conforming changes to RAA, Schedule 9.2, section B(1)(d) to include these new and modified ELCC Classes for Unlimited Resources.

On March 19, 2025, this proposal was endorsed by PJM's Markets and Reliability Committee ("MRC") and approved by PJM's Members Committee ("MC"). PJM requests the proposed revisions become effective on May 28, 2025.

I. BACKGROUND

a. Resources are Accredited Based on their ELCC Class

To accredit the capacity capability for Capacity Resources, PJM employs an ELCC methodology, which, as a general matter, is a technology-neutral probabilistic approach to simulate loss-of-load probability across scenarios designed to determine resources' effective contribution to resource adequacy.³ Using probabilistic modeling, the ELCC analysis evaluates a resource's contribution to system reliability; the analysis distinguishes among resources with differing levels of reliability, size, and hourly output profiles to determine an ELCC rating for a given resource or a class of resources (an "ELCC Class Rating"). Resources that are able to consistently produce energy or reduce demand during hours with load shed risk have a higher ELCC rating than resources less able to do so.

The ELCC methodology recognizes and accounts for the unique characteristics of diverse resource types. It compares the expected hourly output of a resource (or resource class) against expected hourly load for all hours of a planned year. It captures variations in hourly variable resource availability, any correlation in hourly output with load patterns, seasonal variations, and the limited duration characteristic associated with resources with a storage component. PJM's

³ RAA, Schedule 9.2; *see PJM Interconnection, L.L.C.*, Capacity Market Reforms to Accommodate the Energy Transition While Maintaining Resource Adequacy, Docket No. ER24-99-000 (Oct. 13, 2023) ("2023 ELCC Filing").

ELCC methodology accounts for this interrelationship between the output of different resources within distinct categories, resources outside of those categories, and load.⁴

The capacity capability determined through the ELCC approach, i.e., a resource's "Accredited UCAP," is a function of the resource's installed capacity and its expected individual performance during expected periods of resource adequacy risk. Therefore, in general, Accredited UCAP is the product of (1) the output capability of the resource, (2) the output of the ELCC analysis (by way of the class rating), and, as applicable, and (3) the resource's performance relative to other members of the ELCC Resource's class. In short, a resource's Accredited UCAP reflects the resource's expected performance during hours of resource adequacy risk.

For Unlimited Resources, which are resources capable of "maintain[ing] output at a stated capability continuously on a daily basis without interruption,"⁵ the RAA currently lists nine ELCC Classes: Nuclear Class, Coal Class, Gas Combined Cycle Class, Gas Combustion Turbine Class, Gas Combined Cycle Dual Fuel Class, Gas Combustion Turbine Dual Fuel Class, Diesel Utility Class, Steam Class, and Other Unlimited Resource Class.⁶ Previously, the Commission noted that further differentiation in ELCC Class definitions may be appropriate and that PJM could propose RAA changes to add or remove ELCC Classes, as necessary.⁷ This filing serves to further refine and improve the ELCC framework PJM established to expand the ELCC Classes with two additional types of resources, thereby allowing more granularity for those resource classes.

⁴ 2023 ELCC Filing, Attachment E, Affidavit of Dr. Patricio Rocha-Garrido on Behalf of PJM Interconnection, L.L.C.

^{¶ 27(}a) ("Rocha-Garrido Affidavit").

⁵ RAA, Article 1, Definitions.

⁶ 2023 ELCC Filing at 39; RAA, Schedule 9.2, section (B)(1)(d).

⁷ *PJM Interconnection, L.L.C.*, 186 FERC ¶ 61,080, at PP 105-06 (2024).

II. PJM PROPOSES DEFINITIONS FOR TWO NEW ELCC CLASSES AND CONFORMING CHANGES

As demonstrated below, the changes PJM is proposing in this filing further expand the existing ELCC accreditation model to determine the accredited capacity levels of two additional classes of Generation Capacity Resources: Oil Fired Combustion Turbine Class and Waste to Energy Steam Class.

A. PJM Proposes to Define Two New ELCC Classes.

PJM proposes to add definitions for two new, distinct ELCC Classes for Unlimited Resources: the Oil Fired Combustion Turbine Class and the Waste to Energy Steam Class.

The proposed Oil Fired Combustion Turbine Class consists of certain generators that currently fall in the "Other Unlimited Resource Class" and that utilize combustion turbine technology with a primary fuel source of oil or diesel. No ELCC Class Rating is determined for any units in the Other Unlimited Resource Class, which was developed for resource classes whose members are so distinct from one another that a single ELCC Class Rating would fail to capture their physical characteristics.⁸ As a result, oil fired units are currently only provided a unit-specific Accredited UCAP. However, combustion turbine units that are primarily fueled by oil have meaningfully similar characteristics, and there are a sufficiently large number of such resources such that they can be grouped and assessed as a separate and distinct ELCC Class.

Accordingly, PJM proposes to extract oil fired units from the "Other Unlimited ELCC Class" and form a more granular oil fired class that will allow for the calculation of an Oil Fired Combustion Turbine Class ELCC Class Rating based on the operating characteristics of these

⁸ RAA, Schedule 9.2, section (C)(2).

types of resources.⁹ Unlike resources in the Gas Combustion Turbine Class, resources in the Oil Fired Combustion Turbine Class use oil as their primary fuel,¹⁰ which can impact the ELCC Class Rating because different fuels have different characteristics, such as oil being stored on site instead of delivered by pipeline. The accreditation for the ELCC Class Rating for the proposed Oil Fired Combustion Turbine Class was estimated to be approximately 85%.¹¹

The proposed Waste to Energy Steam Class consists of certain generators that currently fall under the broader "steam" category of ELCC Classes listed in RAA, Schedule 9.2, section (B)(1)(d) today that utilize steam technology with a primary fuel source of municipal waste or wood waste. Steam resources currently include waste-to-energy plants (i.e., plants that are generally burning municipal solid waste or trash, or wood waste and use the heat to produce steam in a boiler to power an electric generator), which are distinguishable from other typical steam resources in the broader Steam Class. More particularly, waste-to-energy plants tend to be relatively small, frequently operated plants (typically in the tens of MW), whereas the remaining plants in the Steam Class tend to be significantly larger plants (typically in the range of hundreds or many hundreds of MW) that are operated as needed to meet system load. As a result, it is appropriate to establish a separate ELCC Class for waste-to-energy resources. The accreditation

⁹ As resources in the Oil Fired Combustion Turbine Class were in the Other Unlimited Class that did not have an ELCC Class Rating, there is no impact from the removal of oil fired combustion turbine resources to the ELCC Class Rating of other resources in that class.

¹⁰ Although the large majority of resources that will be in the proposed Oil Fired Combustion Turbine Class use oil as their only source of fuel, the proposed definition appropriately refers to using oil as a primary fuel because there are some units currently on the PJM system that primarily burn oil but are also capable of using gas that are nevertheless more like other units in the Oil Fired Combustion Turbine Class than in any other class. In addition, PJM's other definitions for ELCC Classes such as the Coal Class, Nuclear Class, Steam Class, and Gas Combustion Turbine Class specify the class by their primary fuel. *See* RAA, Article 1, Definitions.

¹¹ This information was based on a sensitivity run of the 2025/2026 Third Incremental Auction ELCC analysis and shared with stakeholders on slide seven of PJM's proposal presentation for the February 20, 2025 Markets and Reliability Committee, which is available at: <u>https://www.pjm.com/-/media/DotCom/committees-groups/committees/mrc/2025/20250220/20250220-item-03a-b---1-elccstf-update-and-solution-packages---presentation.pdf</u>.

for the ELCC Class Rating for the Waste to Energy Steam Class was estimated to be approximately 83%¹² given the better performance of waste-to-energy resources compared with other resources in the Steam Class.¹³

PJM defines ELCC Classes based on common sets of operational characteristics which allow for PJM's effective load carrying capability analysis to establish a unique and corresponding ELCC Class Rating. Both of these proposed ELCC Classes align with this definition and improve upon the existing set of ELCC Classes by allowing for greater granularity in the grouping of resources that share similar operating characteristics that allow for the establishment of a unique and corresponding ELCC Class Rating, therefore improving the accuracy of the ELCC Class ratings and accreditation for the resource types. Separating out oil fired combustion turbine resources and waste-to-energy resources from the "Other Unlimited Resource Class" and "Steam Class," respectively, allows for greater granularity and accuracy of the ELCC Class ratings for these resource types.

The proposed definitions for these two new ELCC Classes are shown in blackline below:

Reliability Assurance Agreement, Schedule 1, Definitions

"Oil Fired Combustion Turbine Class" shall mean an ELCC Class consisting of Unlimited Resources of the combustion turbine technology type that are primarily fueled by oil.

"Waste to Energy Steam Class" shall mean an ELCC Class consisting of Unlimited Resources of the steam technology type whose primary fuel is municipal waste or wood waste.

¹² *Id.* This information was based on a sensitivity run of the 2025/2026 Third Incremental Auction ELCC analysis for which the Steam Class had an ELCC Class Rating of 74%.

¹³ The removal of resources from the Steam Class to the proposed Waste to Energy Steam Class is expected to have a less than 1% impact on the ELCC Class Rating of the broader Steam Class due to the significantly larger quantity of MW for the remaining units in the Steam Class.

B. PJM Proposes Conforming Revisions to the "Other Steam Class" Definition in Consideration of the New Waste to Energy Steam Class of Steam Resources.

PJM proposes to make conforming revisions to the existing definition of "Steam Class" by renaming it "Other Steam Class" and clarifying that such resources do not qualify for the Waste to Energy Steam Class beginning with the 2027/2028 Delivery Year, in addition to the Coal Class and Nuclear Class that do not qualify for the Steam Class currently and will continue not to qualify for the Steam Class under this proposal, as shown in blackline below:

Reliability Assurance Agreement, Schedule 1, Definitions

"<u>Other</u> Steam Class" shall mean an ELCC Class consisting of Unlimited Resources of the steam technology type and <u>do not qualify for the Coal Class, Nuclear Class</u>, or Waste to Energy Steam Class (beginning with the 2027/2028 Delivery Year).

C. PJM Proposes Conforming Revisions to the ELCC Class List.

In addition to the proposal to memorialize and clarify the definitions described above, PJM also proposes to make supplemental revisions to the list of ELCC Classes in RAA, Schedule 9.2, section (B)(1)(d). Specifically, PJM proposes to add the two classes proposed in this filing, the Oil Fired Combustion Turbine Class and the Waste to Energy Steam Class, to the list of ELCC Classes for Unlimited Resources beginning with the 2027/2028 Delivery Year.¹⁴ It is appropriate to begin utilizing these two new ELCC Classes beginning with the 2027/2028 Delivery Year given that ELCC Class Ratings for the Base Residual Auction for the 2026/2027 Delivery Year have already been determined and recalculating ELCC Class Ratings to account for these two proposed classes would unnecessarily further delay the upcoming Base Residual Auction for the 2026/2027 Delivery Year.

¹⁴ In addition, PJM proposes to modify the listing for "Steam Class" to specify that it will henceforth refer to the "<u>Other</u> Steam Class" in the proposed RAA, Schedule 9.2, section (B)(1)(d) section given the newly proposed Waste to Energy Steam Class is based on steam.

ELCC Classes beginning with the 2027/2028 Delivery Year. To be clear, this proposal only adds the two additional classes described above, and does not modify the methodology for calculating ELCC Class Ratings, which remains the same as currently set forth in Reliability Assurance Agreement, Schedule 9.2.

III. STAKEHOLDER PROCESS

Review of this issue charge for ELCC accreditation methodology began on December 5, 2024.¹⁵ This proposal was endorsed by the ELCC senior task force on February 10, 2025.¹⁶ Subsequently, on March 19, 2025, this proposal was endorsed by PJM's Markets and Reliability Committee ("MRC") and PJM's Members Committee ("MC") by acclamation with no objections or abstentions.

IV. PROPOSED EFFECTIVE DATES

PJM proposes an effective date of May 28, 2025, for the proposed RAA revisions referenced herein. PJM requests that the Commission issue an order on this filing by May 27, 2025.

V. DESCRIPTION OF SUBMITTAL

This filing consists of the following:

- 1. This transmittal letter;
- 2. Attachment A Revisions to the Tariff, in redline format;
- 3. Attachment B Revisions to the Tariff, in clean format; and

¹⁵ The issue charge for this proposal is available at: <u>https://www.pjm.com/-/media/DotCom/committees-groups/task-forces/elccstf/2024/20241205/20241205-item-01---elcc-capacity-accreditation-methodology---issue-charge.pdf</u>. The problem statement for this proposal is available at: <u>https://www.pjm.com/-/media/DotCom/committees-groups/task-forces/elccstf/2024/20241205/20241205-item-01---elcc-capacity-accreditation-methodology---problem-statement.pdf</u>.

¹⁶ The voting results from the February 4, 2025 ELCC senior task force are available at: <u>https://www.pjm.com/-/media/DotCom/committees-groups/task-forces/elccstf/2025/20250204/20250204-elccstf-voting-result-report.pdf</u>.

VI. CORRESPONDENCE

The following individuals are designated for inclusion on the official service list in this proceeding and for receipt of any communications regarding this filing:

Daniel Vinnik Counsel PJM Interconnection, L.L.C. 2750 Monroe Boulevard Audubon, Pennsylvania 19403 (267) 858-9451 daniel.vinnik@pjm.com Craig Glazer Vice President - Federal Government Policy PJM Interconnection, L.L.C. 1200 G Street, N.W, Suite 600 Washington, D.C. 20005 (202) 423-4743 craig.glazer@pjm.com

VII. SERVICE

PJM has served a copy of this filing on all PJM Members and on all state utility regulatory commissions in the PJM Region by posting this filing electronically. In accordance with the Commission's regulations,¹⁷ PJM will post a copy of this filing to the FERC filings section of its internet site, located at the following link: https://www.pjm.com/library/filing-order with a specific link to the newly-filed document, and will send an e-mail on the same date as this filing to all PJM Members and all state utility regulatory commissions in the PJM Region¹⁸ alerting them that this filing has been made by PJM and is available by following such link. If the document is not immediately available by using the referenced link, the document will be available through the referenced link within 24 hours of the filing. Also, a copy of this filing will be available on the FERC's eLibrary website located the following link: at

¹⁷ See 18 C.F.R. §§ 35.2(e) and 385.2010(f)(3).

¹⁸ PJM already maintains, updates and regularly uses e-mail lists for all PJM Members and affected state commissions.

Debbie-Ann Reese, Secretary March 28, 2025 Page 10

http://www.ferc.gov/docsfiling/elibrary.asp in accordance with the Commission's regulations and

Order No. 714.

VIII. CONCLUSION

Based on the foregoing, PJM respectfully requests that the Commission accept these proposed amendments as filed.

Respectfully submitted,

/s/ Daniel Vinnik

Daniel Vinnik

Craig Glazer Vice President – Federal Government Policy PJM Interconnection, L.L.C. 1200 G Street, N.W. Suite 600 Washington, D.C. 20005 (202) 423-4743 Craig.Glazer@pjm.com

Counsel PJM Interconnection, L.L.C. 2750 Monroe Boulevard Audubon, PA* 19403 (*Barred in the District of Columbia and Illinois) (267) 858-9451 Daniel.Vinnik @pjm.com

Chenchao Lu Associate General Counsel PJM Interconnection, L.L.C. 2750 Monroe Boulevard Audubon, PA 19403 (610) 666-2255 Chenchao.Lu@pjm.com

On behalf of *PJM Interconnection*, *L.L.C.*

Attachment A

Revisions to the PJM Reliability Assurance Agreement

(Marked / Redline Format)

ARTICLE 1 – DEFINITIONS

Unless the context otherwise specifies or requires, capitalized terms used herein shall have the respective meanings assigned herein or in the Schedules hereto, or in the PJM Tariff or PJM Operating Agreement if not otherwise defined in this Agreement, for all purposes of this Agreement (such definitions to be equally applicable to both the singular and the plural forms of the terms defined). Unless otherwise specified, all references herein to Articles, Sections or Schedules, are to Articles, Sections or Schedules of this Agreement. As used in this Agreement:

Accredited UCAP:

"Accredited UCAP" shall mean the quantity of Unforced Capacity, as denominated in Effective UCAP, that an ELCC Resource is capable of providing in a given Delivery Year.

Accredited UCAP Factor:

"Accredited UCAP Factor" shall mean, through the 2024/2025 Delivery Year, one minus EFORd, and for 2025/2026 Delivery Year and subsequent Delivery Years, the ratio of the Capacity Resource's Accredited UCAP to the Capacity Resource's installed capacity.

Agreement:

"Agreement" shall mean this Reliability Assurance Agreement, together with all Schedules hereto, as amended from time to time.

Annual Demand Resource:

"Annual Demand Resource" shall mean a resource that is placed under the direction of the Office of the Interconnection during the Delivery Year, and will be available for an unlimited number of interruptions during such Delivery Year by the Office of the Interconnection, and will be capable of maintaining each such interruption between the hours of 10:00AM to 10:00PM Eastern Prevailing Time for the months of June through October and the following May, and 6:00AM through 9:00PM Eastern Prevailing Time for the months of November through April unless there is an Office of the Interconnection approved maintenance outage during October through April. The Annual Demand Resource must be available in the corresponding Delivery year to be offered for sale or Self-Supplied in an RPM Auction, or included as an Annual Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Annual Energy Efficiency Resource:

"Annual Energy Efficiency Resource" shall mean a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, meeting the requirements of Reliability Assurance Agreement, Schedule 6 and exceeding thencurrent building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during the summer and winter periods described in such Schedule 6 and the PJM Manuals) reduction in electric energy consumption that is not reflected in the peak load forecast prepared for the Delivery Year for which the Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention.

Applicable Regional Entity:

"Applicable Regional Entity" shall have the same meaning as in the PJM Tariff.

Base Capacity Demand Resource:

"Base Capacity Demand Resource" shall mean, for the 2018/2019 and 2019/2020 Delivery Years, a resource that is placed under the direction of the Office of the Interconnection and that will be available June through September of a Delivery Year, and will be available to the Office of the Interconnection for an unlimited number of interruptions during such months, and will be capable of maintaining each such interruption for at least a 10-hour duration between the hours of 10:00AM to 10:00PM Eastern Prevailing Time. The Base Capacity Demand Resource must be available June through September in the corresponding Delivery Year to be offered for sale or self-supplied in an RPM Auction, or included as a Base Capacity Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Base Capacity Energy Efficiency Resource:

"Base Capacity Energy Efficiency Resource" shall mean, for the 2018/2019 and 2019/2020 Delivery Years, a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, meeting the requirements of RAA, Schedule 6 and exceeding then-current building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during the summer peak periods as described in Reliability Assurance Agreement, Schedule 6 and the PJM Manuals) reduction in electric energy consumption that is not reflected in the peak load forecast prepared for the Delivery Year for which the Base Capacity Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention.

Base Capacity Resource:

"Base Capacity Resource" shall have the same meaning as in Tariff, Attachment DD.

Base Residual Auction:

"Base Residual Auction" shall have the same meaning as in Tariff, Attachment DD.

Behind The Meter Generation:

"Behind The Meter Generation" shall refer to a generating unit that delivers energy to load without using the Transmission System or any distribution facilities (unless the entity that owns or leases the distribution facilities consented to such use of the distribution facilities and such consent has been demonstrated to the satisfaction of the Office of the Interconnection; provided, however, that Behind The Meter Generation does not include (i) at any time, any portion of such generating unit's capacity that is designated as a Capacity Resource or (ii) in any hour, any portion of the output of such generating unit that is sold to another entity for consumption at another electrical location or into the PJM Interchange Energy Market.

Black Start Capability:

"Black Start Capability" shall mean the ability of a generating unit or station to go from a shutdown condition to an operating condition and start delivering power without assistance from the power system.

Capacity Emergency Transfer Objective (CETO):

"Capacity Emergency Transfer Objective" or "CETO" shall mean, through the 2024/2025 Delivery Year, the amount of electric energy that a given area must be able to import in order to remain within a loss of load expectation of one event in 25 years when the area is experiencing a localized capacity emergency, as determined in accordance with the PJM Manuals. Without limiting the foregoing, CETO shall be, for Delivery Years through 2024/2025, calculated based in part on EFORD determined in accordance with Reliability Assurance Agreement, Schedule 5, Paragraph C. Beginning with the 2025/2026 Delivery Year, CETO shall mean the amount of electric energy that a given area must be able to import in order to satisfy a normalized expected unserved energy for the area that is equal to forty percent of the normalized expected unserved energy is the expected unserved energy (for the area or RTO, as appropriate) divided by the forecasted annual energy (for the area or RTO, as appropriate), when the area is experiencing a localized capacity emergency, as determined in accordance with the PJM Manuals.

Capacity Emergency Transfer Limit (CETL):

Capacity Emergency Transfer Limit" or "CETL" shall mean the capability of the transmission system to support deliveries of electric energy to a given area experiencing a localized capacity emergency as determined in accordance with the PJM Manuals.

Capacity Import Limit:

For any Delivery Year up to and including the 2019/2020 Delivery Year, "Capacity Import Limit" shall mean, (a) for the PJM Region, (1) the maximum megawatt quantity of external Generation Capacity Resources that PJM determines for each Delivery Year, through appropriate modeling and the application of engineering judgment, the transmission system can receive, in aggregate at the interface of the PJM Region with all external balancing authority areas and deliver to load in the PJM Region under capacity emergency conditions without violating applicable reliability criteria on any bulk electric system facility of 100kV or greater, internal or external to the PJM Region, that has an electrically significant response to transfers on such interface, minus (2) the then-applicable Capacity Benefit Margin; and (b) for certain source zones identified in the PJM manuals as groupings of one or more balancing authority areas, (1) the maximum megawatt quantity of external Generation Capacity Resources that PJM determines the transmission system can receive at the interface of the PJM Region with each such source zone and deliver to load in the PJM Region under capacity emergency conditions without violating applicable reliability criteria on any bulk electric system facility of 100kV or greater, internal or external to the PJM Region, that has an electrically significant response to transfers on such interface, minus the then-applicable Capacity Benefit Margin times (2) the ratio of the maximum import quantity from each such source zone divided by the PJM total maximum import quantity. As more fully set forth in the PJM Manuals, PJM shall make such determination based on the latest peak load forecast for the studied period, the same computer simulation model of loads, generation and transmission topography employed in the determination of Capacity Emergency Transfer Limit for such Delivery Year, including external facilities from an industry standard model of the loads, generation, and transmission topography of the Eastern Interconnection under peak conditions. PJM shall specify in the PJM Manuals the areas and minimum distribution factors for identifying monitored bulk electric system facilities that have an electrically significant response to such transfers on the PJM interface. Employing such tools, PJM shall model increased power transfers from external areas into PJM to determine the transfer level at which one or more reliability criteria is violated on any monitored bulk electric system facilities that have an electrically significant response to such transfers. For the PJM Region Capacity Import Limit, PJM shall optimize transfers from other source areas not experiencing any reliability criteria violations as appropriate to increase the Capacity Import Limit. The aggregate megawatt quantity of transfers into PJM at the point where any increase in transfers on the interface would violate reliability criteria will establish the Capacity Import Limit. Notwithstanding the foregoing, a Capacity Resource located outside the PJM Region shall not be subject to the Capacity Import Limit if the Capacity Market Seller seeks an exception thereto by demonstrating to PJM, by no later than five (5) business days prior to the commencement of the offer period for the relevant RPM Auction, that such resource meets all of the following requirements:

(i) it has, at the time such exception is requested, met all applicable requirements to be pseudo-tied into the PJM Region, or the Capacity Market Seller has committed in writing that it will meet such requirements, unless prevented from doing so by circumstances beyond the control of the Capacity Market Seller, prior to the relevant Delivery Year;

(ii) at the time such exception is requested, it has long-term firm transmission service confirmed on the complete transmission path from such resource into PJM; and

(iii) it is, by written commitment of the Capacity Market Seller, subject to the same obligations imposed on Generation Capacity Resources located in the PJM Region by Tariff, Attachment DD, section 6.6 to offer their capacity into RPM Auctions; provided, however, that (a) the total megawatt quantity of all exceptions granted hereunder for a Delivery Year, plus the Capacity Import Limit for the applicable interface determined for such Delivery Year, may not exceed the total megawatt quantity of Network External Designated Transmission Service on such interface that PJM has confirmed for such Delivery Year; and (b) if granting a qualified exception would result in a violation of the rule in clause (a), PJM shall grant the requested exception but reduce the Capacity Import Limit by the quantity necessary to ensure that the total quantity of Network External Designated Transmission Service is not exceeded.

Capacity Only Option:

"Capacity Only Option" shall mean participation in Emergency Load Response Program or Pre-Emergency Program which allows, pursuant to Tariff, Attachment DD and as applicable, a capacity payment for the ability to reduce load during a pre-emergency or emergency event.

Capacity Performance Resource:

"Capacity Performance Resource" shall have the same meaning as in Tariff, Attachment DD.

Capacity Resources:

"Capacity Resources" shall mean megawatts of (i) net capacity from Existing Generation Capacity Resources or Planned Generation Capacity Resources meeting the requirements of the Reliability Assurance Agreement, Schedules 9 and Reliability Assurance Agreement, Schedule 10 that are or will be owned by or contracted to a Party and that are or will be committed to satisfy that Party's obligations under the Reliability Assurance Agreement, or to satisfy the reliability requirements of the PJM Region, for a Delivery Year; (ii) net capacity from Existing Generation Capacity Resources or Planned Generation Capacity Resources not owned or contracted for by a Party which are accredited to the PJM Region pursuant to the procedures set forth in such Schedules 9 and 10; or (iii) load reduction capability provided by Demand Resources or Energy Efficiency Resources that are accredited to the PJM Region pursuant to the procedures set forth in the Reliability Assurance Agreement, Schedule 6.

Capacity Storage Resource Class:

"Capacity Storage Resource Class" shall mean the ELCC Classes specified in Schedules 9.1 and 9.2, section B of this Agreement, each of which is composed of Capacity Storage Resources with the same specified characteristic duration of 4, 6, 8, and 10 hours. The characteristic duration of an Energy Storage Resource Class is the ratio of the modeled MWh energy storage capability of members of the class to the modeled MW power capability of members of the class.

Capacity Transfer Right:

"Capacity Transfer Right" shall have the meaning specified in Tariff, Attachment DD.

Coal Class:

"Coal Class" shall mean an ELCC Class consisting of Unlimited Resources primarily fueled by coal.

Combination Resource:

"Combination Resource" shall mean a Generation Capacity Resource that has a component that has the characteristics of a Limited Duration Resource combined with (i) a component that has

the characteristics of an Unlimited Resource or (ii) a component that has the characteristics of a Variable Resource.

Compliance Aggregation Area (CAA):

"Compliance Aggregation Area" or "CAA" shall have the same meaning as in the Tariff.

Complex Hybrid Class:

"Complex Hybrid Class" shall mean an ELCC Class composed of Combination Resources that combine three or more components, whereby one component is a class of Limited Duration Resource, and the other components are different Variable Resource classes, and such Combination Resources cannot be included in any other Combination Resource class. A resource that is a member of a Complex Hybrid Class has a single Point Of Interconnection, unless the resource is controlled in an integrated fashion, is at a single site, and is approved by PJM to be considered a single resource in accordance with the PJM Manuals.

Consolidated Transmission Owners Agreement, PJM Transmission Owners Agreement or Transmission Owners Agreement:

"Consolidated Transmission Owners Agreement," "PJM Transmission Owners Agreement" or "Transmission Owners Agreement" shall mean that certain Consolidated Transmission Owners Agreement, dated as of December 15, 2005, by and among the Transmission Owners and by and between the Transmission Owners and PJM Interconnection, L.L.C. on file with the Commission, as amended from time to time.

Control Area:

"Control Area" shall mean an electric power system or combination of electric power systems bounded by interconnection metering and telemetry to which a common generation control scheme is applied in order to:

(a) match the power output of the generators within the electric power system(s) and energy purchased from entities outside the electric power system(s), with the load within the electric power system(s);

(b) maintain scheduled interchange with other Control Areas, within the limits of Good Utility Practice;

(c) maintain the frequency of the electric power system(s) within reasonable limits in accordance with Good Utility Practice and the criteria of NERC and each Applicable Regional Entity;

(d) maintain power flows on transmission facilities within appropriate limits to preserve reliability; and

(e) provide sufficient generating capacity to maintain operating reserves in accordance with Good Utility Practice.

Daily Unforced Capacity Obligation:

"Daily Unforced Capacity Obligation" shall mean the capacity obligation of a Load Serving Entity during the Delivery Year, determined in accordance with the Reliability Assurance Agreement, Schedule 8 or, as to an FRR Entity, in the Reliability Assurance Agreement, Schedule 8.1.

Delivery Year:

"Delivery Year" shall mean a Planning Period for which a Capacity Resource is committed pursuant to the auction procedures specified in Tariff, Attachment DD or pursuant to an FRR Capacity Plan under RAA, Schedule 8.1.

Demand Resource (DR):

"Demand Resource" or "DR" shall mean a Limited Demand Resource, Extended Summer Demand Resource, Annual Demand Resource, Base Capacity Demand Resource or Summer-Period Demand Resource with a demonstrated capability to provide a reduction in demand or otherwise control load in accordance with the requirements of RAA, Schedule 6 that offers and that clears load reduction capability in a Base Residual Auction or Incremental Auction or that is committed through an FRR Capacity Plan.

Demand Resource Factor or DR Factor:

"Demand Resource Factor" or "DR Factor" shall mean, for Delivery Years through May 31, 2018, that factor approved from time to time by the PJM Board used to determine the unforced capacity value of a Demand Resource in accordance with Reliability Assurance Agreement, Schedule 6

Demand Resource Officer Certification Form:

"Demand Resource Officer Certification Form" shall mean a certification as to an intended Demand Resource Sell Offer, in accordance with Reliability Assurance Agreement, Schedule 6 and Reliability Assurance Agreement, Schedule 8.1 and the PJM Manuals.

Demand Resource Registration:

"Demand Resource Registration" shall mean a registration in the Full Program Option or Capacity Only Option of the Emergency or Pre-Emergency Load Resource Program in accordance with Tariff, Attachment K-Appendix, section 8.

Demand Resource Sell Offer Plan:

"Demand Resource Sell Offer Plan" shall mean the plan required by Reliability Assurance Agreement, Schedule 6 and Reliability Assurance Agreement, Schedule 8.1 in support of an intended offer of Demand Resources in an RPM Auction, or an intended inclusion of Demand Resources in an FRR Capacity Plan.

Diesel Utility Class:

"Diesel Utility Class" shall mean an ELCC Class consisting of Unlimited Resources of the diesel technology type that is not primarily fueled by landfill gas.

Effective Nameplate Capacity:

"Effective Nameplate Capacity" shall mean (i) for each Variable Resource and Combination Resource, the resource's Maximum Facility Output (or, for a Co-Located Resource, the applicable share of the Mixed Technology Facility's Maximum Facility Output); (ii) for each Limited Duration Resource, the sustained level of output that the unit can provide and maintain over a continuous period, whereby the duration of that continuous period matches the characteristic duration of the corresponding ELCC Class, with consideration given to ambient conditions expected to exist at the time of PJM system peak load, to the extent that such conditions impact such resource's capability, not to exceed the Maximum Facility Output (or, for a Co-Located Resource, the applicable share of the Mixed Technology Facility's Maximum Facility Output). For the 2025/2026 Delivery Year and subsequent Delivery Years, the Effective Nameplate Capacity of each Limited Duration Resource shall not exceed the greater of the Capacity Interconnection Rights of such Limited Duration Resource, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year.

Effective UCAP:

"Effective UCAP" shall mean a unit of measure that represents the capacity product transacted in the Reliability Pricing Model and included in FRR Capacity Plans. One megawatt of Effective UCAP has the same capacity value of one megawatt of Unforced Capacity.

ELCC Class:

"ELCC Class" shall mean a defined group of ELCC Resources that share a common set of operational characteristics and for which effective load carrying capability analysis, as set forth in RAA, Schedules 9.1 and 9.2, will establish a unique ELCC Class UCAP and corresponding ELCC Class Rating(s). ELCC Classes shall be defined in the Schedules 9.1 and 9.2, section B of this Agreement. Members of an ELCC Class shall share a common method of calculating the ELCC Resource Performance Adjustment, provided that the individual ELCC Resource Performance Adjustment values will generally differ among ELCC Resources.

ELCC Class Rating:

"ELCC Class Rating" shall mean the rating factor, based on effective load carrying capability analysis, that applies to ELCC Resources that are members of an ELCC Class as part of the calculation of their Accredited UCAP.

ELCC Class UCAP:

"ELCC Class UCAP" shall mean the aggregate Effective UCAP all modeled ELCC Resources in a given ELCC Class are capable of providing in a given Delivery Year.

ELCC Portfolio UCAP:

"ELCC Portfolio UCAP" shall mean the aggregate Effective UCAP that all modeled ELCC Resources are capable of providing in a given Delivery Year.

ELCC Resource:

"ELCC Resource" shall mean, through the 2024/2025 Delivery Year, a Generation Capacity Resource that is a Variable Resource, a Limited Duration Resource, or a Combination Resource, and beginning with the 2025/2026 Delivery Year, a Generation Capacity Resource or a Demand Resource.

ELCC Resource Performance Adjustment:

"ELCC Resource Performance Adjustment" shall mean the performance of a specific ELCC Resource relative to the aggregate performance of the ELCC Class to which it belongs as further described in RAA, Schedule 9.1, section F and RAA, Schedule 9.2, section D.

Electric Cooperative:

"Electric Cooperative" shall mean an entity owned in cooperative form by its customers that is engaged in the generation, transmission, and/or distribution of electric energy.

Electric Distributor:

"Electric Distributor" shall mean a Member that 1) owns or leases with rights equivalent to ownership of electric distribution facilities that are used to provide electric distribution service to electric load within the PJM Region; or 2) is a generation and transmission cooperative or a joint municipal agency that has a member that owns electric distribution facilities used to provide electric distribution service to electric load within the PJM Region.

Emergency:

"Emergency" shall mean (i) an abnormal system condition requiring manual or automatic action to maintain system frequency, or to prevent loss of firm load, equipment damage, or tripping of system elements that could adversely affect the reliability of an electric system or the safety of persons or property; or (ii) a fuel shortage requiring departure from normal operating procedures in order to minimize the use of such scarce fuel; or (iii) a condition that requires implementation of emergency procedures as defined in the PJM Manuals.

End-Use Customer:

"End-Use Customer" shall mean a Member that is a retail end-user of electricity within the PJM Region. For purposes of Members Committee sector classification, a Member that is a retail end-user that owns generation may qualify as an End-Use customer if: (1) the average physical unforced capacity owned by the Member and its affiliates in the PJM region over the five Planning Periods immediately preceding the relevant Planning Period does not exceed the average PJM capacity obligation for the Member and its affiliates over the same time period; or (2) the average energy produced by the Member and its affiliates within the PJM region over the five Planning Periods immediately preceding the relevant Planning Period does not exceed the average energy consumed by that Member and its affiliates within the PJM region over the same time period. The foregoing notwithstanding, taking retail service may not be sufficient to qualify a Member as an End-Use Customer.

Energy Efficiency Resource:

"Energy Efficiency Resource" shall mean a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, meeting the requirements of RAA, Schedule 6 and exceeding then-current building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during the periods described in Reliability Assurance Agreement, Schedule 6 and the PJM Manuals) reduction in electric energy consumption that is not reflected in the peak load forecast prepared for the Delivery Year for which the Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention. Annual Energy Efficiency Resources, Base Capacity Energy Efficiency Resources and Summer-Period Energy Efficiency Resources are types of Energy Efficiency Resources.

Exigent Water Storage:

"Exigent Water Storage" shall mean water stored in the pondage or reservoir of a hydropower resource which is not typically available during normal operating conditions (as those conditions are described in the relevant FERC hydropower license), but which can be drawn upon during emergency conditions (as described in the FERC hydropower license), including in order to avoid a load shed. In an effective load carrying capability analysis, exigent storage capability from an upstream hydro facility can be considered relative to a downstream hydro facility by assessing cascading storage and flows.

Existing Demand Resource:

"Existing Demand Resource" shall mean a Demand Resource for which the Demand Resource Provider has identified existing end-use customer sites that are registered for the current Delivery Year with PJM (even if not registered by such Demand Resource Provider) and that the Demand Resource Provider reasonably expects to have under a contract to reduce load based on PJM dispatch instructions by the start of the Delivery Year for which such resource is offered.

Existing Generation Capacity Resource:

"Existing Generation Capacity Resource" shall mean, for purposes of the must-offer requirement and mitigation of offers for any RPM Auction for a Delivery Year, a Generation Capacity Resource that, as of the date on which bidding commences for such auction: (a) is in service; or (b) is not yet in service, but has cleared any RPM Auction for any prior Delivery Year. A Generation Capacity Resource shall be deemed to be in service if interconnection service has ever commenced (for resources located in the PJM Region), or if it is physically and electrically interconnected to an external Control Area and is in full commercial operation (for resources not located in the PJM Region). The additional megawatts of a Generation Capacity Resource that is being, or has been, modified to increase the number of megawatts of available installed capacity thereof shall not be deemed to be an Existing Generation Capacity Resource until such time as those megawatts (a) are in service; or (b) are not yet in service, but have cleared any RPM Auction for any prior Delivery Year.

Extended Summer Demand Resource:

"Extended Summer Demand Resource" shall mean, for Delivery Years through May 31, 2018, and for FRR Capacity Plans Delivery Years through May 31, 2019, a resource that is placed under the direction of the Office of the Interconnection and that will be available June through October and the following May, and will be available for an unlimited number of interruptions during such months by the Office of the Interconnection, and will be capable of maintaining each such interruption for at least a 10-hour duration between the hours of 10:00AM to 10:00PM Eastern Prevailing Time. The Extended Summer Demand Resource must be available June through October and the following May in the corresponding Delivery Year to be offered for sale or Self-Supplied in an RPM Auction, or included as an Extended Summer Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Facilities Study Agreement:

"Facilities Study Agreement" shall have the same meaning as in Tariff, Part VI, section 206.

FERC or Commission:

"FERC" or "Commission" shall mean the Federal Energy Regulatory Commission or any successor federal agency, commission or department exercising jurisdiction over the Tariff, Operating Agreement and Reliability Assurance Agreement.

Firm Point-To-Point Transmission Service:

"Firm Point-To-Point Transmission Service" shall have the meaning specified in the Tariff.

Firm Service Level:

"Firm Service Level" or "FSL" of Price Responsive Demand for the 2022/2023 Delivery Year and subsequent Delivery Years shall mean the level, determined at a PRD Substation level, to which Price Responsive Demand shall be reduced during the Delivery Year when an Emergency Action that triggers a Performance Assessment Interval is declared and the Locational Marginal Price exceeds the price associated with such Price Responsive Demand identified by the PRD Provider in its PRD Plan. "Firm Service Level" or "FSL" of Demand Resource shall mean the pre-determined level for which an end-use customer's load shall be reduced, upon notification from the Curtailment Service Provider's market operations center or its agent.

Firm Transmission Service:

"Firm Transmission Service" shall mean transmission service that is intended to be available at all times to the maximum extent practicable, subject to an Emergency, an unanticipated failure of a facility, or other event beyond the control of the owner or operator of the facility or the Office of the Interconnection.

Fixed Resource Requirement Alternative or FRR Alternative:

"Fixed Resource Requirement Alternative" or "FRR Alternative" shall mean an alternative method for a Party to satisfy its obligation to provide Unforced Capacity hereunder, as set forth in the Reliability Assurance Agreement, Schedule 8.1.

Fixed-Tilt Solar Class:

"Fixed-Tilt Solar Class" shall mean an ELCC Class consisting of Variable Resources that produce electrical energy with solar panels that are primarily mounted in a fixed orientation.

Forecast Pool Requirement:

"Forecast Pool Requirement" or "FPR" shall mean the amount equal to one plus the unforced reserve margin (stated as a decimal number) for the PJM Region required pursuant to this Reliability Assurance Agreement, as approved by the PJM Board pursuant to Reliability Assurance Agreement, Schedule 4.1.

FRR Capacity Plan or FRR Plan:

"FRR Capacity Plan" or "FRR Plan" shall mean a long-term plan for the commitment of Capacity Resources and Price Responsive Demand to satisfy the capacity obligations of a Party that has elected the FRR Alternative, as more fully set forth in the Reliability Assurance Agreement, Schedule 8.1.

FRR Entity:

"FRR Entity" shall mean, for the duration of such election, a Party that has elected the FRR Alternative hereunder.

FRR Service Area:

"FRR Service Area" shall mean (a) the service territory of an IOU as recognized by state law, rule or order; (b) the service area of a Public Power Entity or Electric Cooperative as recognized by franchise or other state law, rule, or order; or (c) a separately identifiable geographic area that is: (i) bounded by wholesale metering, or similar appropriate multi-site aggregate metering, that is visible to, and regularly reported to, the Office of the Interconnection, or that is visible to, and regularly reported to an Electric Distributor and such Electric Distributor agrees to aggregate the load data from such meters for such FRR Service Area and regularly report such aggregated information, by FRR Service Area, to the Office of the Interconnection; and (ii) for which the FRR Entity has or assumes the obligation to provide capacity for all load (including load growth) within such area. In the event that the service obligations of an Electric Cooperative or Public Power Entity are not defined by geographic boundaries but by physical connections to a defined set of customers, the FRR Service Area in such circumstances shall be defined as all customers physically connected to transmission or distribution facilities of such Electric Cooperative or Public Power Entity within an area bounded by appropriate wholesale aggregate metering as described above.

Full Program Option:

"Full Program Option" shall mean participation in Emergency Load Response Program or Pre-Emergency Program which allows, pursuant to Tariff, Attachment DD and as applicable, (i) an energy payment for load reductions during a pre-emergency or emergency event, and (ii) a capacity payment for the ability to reduce load during a pre-emergency or emergency event.

Full Requirements Service:

"Full Requirements Service" shall mean wholesale service to supply all of the power needs of a Load Serving Entity to serve end-users within the PJM Region that are not satisfied by its own generating facilities.

Gas Combined Cycle Class:

"Gas Combined Cycle Class" shall mean an ELCC Class consisting of Unlimited Resources of the combined cycle technology type that is primarily fueled by natural gas, but does not meet the requirements to be included in the Gas Combined Cycle Dual Fuel Class.

Gas Combined Cycle Dual Fuel Class:

"Gas Combined Cycle Dual Fuel Class" shall mean an ELCC Class consisting of Unlimited Resources of the combined cycle technology type that is primarily fueled by natural gas, and that attests that it has the capability to start independently using onsite sources and operate independently on alternate onsite fuel source(s) up to its maximum capacity level during the winter season of the applicable Delivery Year in which it is providing capacity, and capable of operating on the alternate fuel for two 16-hour periods over two consecutive days at its maximum capacity level.

Gas Combustion Turbine Class:

"Gas Combustion Turbine Class" shall mean an ELCC Class consisting of Unlimited Resources of the combustion turbine technology type that is primarily fueled by natural gas, but does not meet the requirements to be included in the Gas Combustion Turbine Dual Fuel Class.

Gas Combustion Turbine Dual Fuel Class:

"Gas Combustion Turbine Dual Fuel Class" shall mean an ELCC Class consisting of Unlimited Resources of the combustion turbine technology type that is primarily fueled by natural gas, and attests that it has the capability to start independently using onsite sources and operate independently on alternate onsite fuel source(s) up to its maximum capacity level during the winter season of the applicable Delivery Year in which it is providing capacity, and capable of operating on the alternate fuel for two 16-hour periods over two consecutive days at its maximum capacity level.

Generation Capacity Resource:

"Generation Capacity Resource" shall mean a Generating Facility, or the contractual right to capacity from a specified Generating Facility, that meets the requirements of RAA, Schedule 9 and RAA, Schedule 10, and, for Generating Facilities that are committed to an FRR Capacity Plan, that meets the requirements of RAA, Schedule 8.1. A Generation Capacity Resource may be an Existing Generation Capacity Resource or a Planned Generation Capacity Resource.

Generation Capacity Resource Provider:

"Generation Capacity Resource Provider" shall mean a Member that owns, or has the contractual authority to control the output of, a Generation Capacity Resource, that has not transferred such authority to another entity.

Generation Owner:

"Generation Owner" shall mean a Member that owns or leases with rights equivalent to ownership, or otherwise controls and operates one or more operating generation resources located in the PJM Region. The foregoing notwithstanding, for a planned generation resource to qualify a Member as a Generation Owner, such resource shall have cleared an RPM auction, and for Energy Resources, the resource shall have a FERC-jurisdictional interconnection agreement or wholesale market participation agreement within PJM. Purchasing all or a portion of the output of a generation resource shall not be sufficient to qualify a Member as a Generation Owner. For purposes of Members Committee sector classification, a Member that is primarily a retail end-user of electricity that owns generation may qualify as a Generation Owner if: (1) the generation resource is the subject of a FERC-jurisdictional interconnection agreement or wholesale market participation agreement within PJM; (2) the average physical unforced capacity owned by the Member and its affiliates over the five Planning Periods immediately preceding the relevant Planning Period exceeds the average PJM capacity obligation of the Member and its affiliates over the same time period; and (3) the average energy produced by the Member and its affiliates within PJM over the five Planning Periods immediately preceding the relevant Planning Period exceeds the average energy consumed by the Member and its affiliates within PJM over the five Planning Periods immediately preceding the relevant Planning Period exceeds the average energy consumed by the Member and its affiliates within PJM over the same time period.

Generator Forced Outage:

"Generator Forced Outage" shall mean an immediate reduction in output or capacity or removal from service, in whole or in part, of a generating unit by reason of an Emergency or threatened Emergency, unanticipated failure, or other cause beyond the control of the owner or operator of the facility, as specified in the relevant portions of the PJM Manuals. A reduction in output or removal from service of a generating unit in response to changes in market conditions shall not constitute a Generator Forced Outage.

Generator Maintenance Outage:

"Generator Maintenance Outage" shall mean the scheduled removal from service, in whole or in part, of a generating unit in order to perform repairs on specific components of the facility, if removal of the facility qualifies as a maintenance outage pursuant to the PJM Manuals.

Generator Planned Outage:

"Generator Planned Outage" shall mean the scheduled removal from service, in whole or in part, of a generating unit for inspection, maintenance or repair with the approval of the Office of the Interconnection in accordance with the PJM Manuals.

Good Utility Practice:

"Good Utility Practice" shall mean any of the practices, methods and acts engaged in or approved by a significant portion of the electric utility industry during the relevant time period, or any of the practices, methods and acts which, in the exercise of reasonable judgment in light of the facts known at the time the decision was made, could have been expected to accomplish the desired result at a reasonable cost consistent with good business practices, reliability, safety and expedition. Good Utility Practice is not intended to be limited to the optimum practice, method, or act to the exclusion of all others, but rather is intended to include acceptable practices, methods, or acts generally accepted in the region; including those practices required by Federal Power Act Section 215(a)(4).

Hybrid Resource Class:

"Hybrid Resource Class" shall mean the ELCC Classes specified in RAA Schedules 9.1 and 9.2 Section B. Each Hybrid Resource Class has a specified combination of two components, whereby, absent being part of a Combination Resource, the individual components would be in a Capacity Storage Resource Class, a Variable Resource Class or would be an Unlimited Resource. A resource that is a member of a Hybrid Resource Class has a single Point Of Interconnection, unless the resource is controlled in an integrated fashion, is at a single site, and is approved by PJM to be considered a single resource in accordance with the PJM Manuals.

Hydropower With Non-Pumped Storage:

"Hydropower With Non-Pumped Storage" shall mean a hydropower facility that can capture and store incoming stream flow, without use of pumps, in pondage or a reservoir, and the Generation Owner has the ability, within the constraints available in the applicable operating license, to exert material control over the quantity of stored water and output of the facility throughout an Operating Day.

Hydropower With Non-Pumped Storage Class:

"Hydropower With Non-Pumped Storage Class" shall mean an ELCC Class consisting of Combination Resources that are Hydropower With Non-Pumped Storage resources.

Incremental Auction:

"Incremental Auction" shall mean any of several auctions conducted for a Delivery Year after the Base Residual Auction for such Delivery Year and before the first day of such Delivery Year, including the First Incremental Auction, Second Incremental Auction, Third Incremental Auction, or Conditional Incremental Auction. Incremental Auctions (other than the Conditional Incremental Auction), shall be held for the purposes of:

- (i) allowing Market Sellers that committed Capacity Resources in the Base Residual Auction for a Delivery Year, which subsequently are determined to be unavailable to deliver the committed Unforced Capacity in such Delivery Year (due to resource retirement, resource cancellation or construction delay, resource derating, EFORd increase, Accredited UCAP Factor decrease, a decrease in the Nominated Demand Resource Value of a Planned Demand Resource, delay or cancellation of a Qualifying Transmission Upgrade, or similar occurrences) to submit Buy Bids for replacement Capacity Resources; and
- (ii) allowing the Office of the Interconnection to reduce or increase the amount of committed capacity secured in prior auctions for such Delivery Year if, as a result of changed circumstances or expectations since the prior auction(s), there is, respectively, a significant excess or significant deficit of committed capacity for such Delivery Year, for the PJM Region or for an LDA.

Intermittent Hydropower Class:

"Intermittent Hydropower Class" shall mean an ELCC Class consisting of Variable Resources that are run-of-river hydropower generators that must generally pass incoming water and

therefore cannot appreciably store water to later increase the output of the facility. Resources in the Intermittent Hydropower Class are not Hydropower with Non-Pumped Storage resources.

IOU:

"IOU" shall mean an investor-owned utility with substantial business interest in owning and/or operating electric facilities in any two or more of the following three asset categories: generation, transmission, distribution.

Intermittent Landfill Gas Class:

"Intermittent Landfill Gas Class" shall mean an ELCC Class consisting of Variable Resources fueled by landfill gas that, because of fuel availability patterns, cannot run consistently at installed capacity levels for 24 or more hours.

Large Load Adjustment:

"Large Load Adjustment" shall mean any MW quantity of adjustments to summer peak load at the "zone/area" level and summed by Zone as further detailed in PJM Manuals. For purposes of this definition, a "zone/area" is an area within a Zone for which the relevant Electric Distributor specifies a separate Obligation Peak Load MW value. A zone/area is a service area of an Electric Distributor that is a separately identifiable, geographic area bounded by wholesale metering (e.g., the service territory of an operating company of a Transmission Owner).

Limited Demand Resource:

"Limited Demand Resource" shall mean, for Delivery Years through May 31, 2018, and for FRR Capacity Plans Delivery Years through May 31, 2019, a resource that is placed under the direction of the Office of the Interconnection and that will, at a minimum, be available for interruption for at least 10 Load Management Events during the summer period of June through September in the Delivery Year, and will be capable of maintaining each such interruption for at least a 6-hour duration. At a minimum, the Limited Demand Resource shall be available for such interruptions on weekdays, other than NERC holidays, from 12:00PM (noon) to 8:00PM Eastern Prevailing Time. The Limited Demand Resource must be available during the summer period of June through September in the corresponding Delivery Year to be offered for sale or Self-Supplied in an RPM Auction, or included as a Limited Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Limited Duration Resource:

"Limited Duration Resource" shall mean a Generation Capacity Resource that is not a Variable Resource, that is not a Combination Resource, and that is not capable of running continuously at Maximum Facility Output for 24 hours or longer. A Capacity Storage Resource is a Limited Duration Resource.

Load Serving Entity or LSE:

"Load Serving Entity" or "LSE" shall mean any entity (or the duly designated agent of such an entity), including a load aggregator or power marketer, (i) serving end-users within the PJM Region, and (ii) that has been granted the authority or has an obligation pursuant to state or local law, regulation or franchise to sell electric energy to end-users located within the PJM Region. Load Serving Entity shall include any end-use customer that qualifies under state rules or a utility retail tariff to manage directly its own supply of electric power and energy and use of transmission and ancillary services.

Locational Reliability Charge:

"Locational Reliability Charge" shall mean the charge determined pursuant to RAA, Article 7, section 2.

Markets and Reliability Committee:

"Markets and Reliability Committee" shall mean the committee established pursuant to the Operating Agreement as a Standing Committee of the Members Committee.

Maximum Emergency Service Level:

"Maximum Emergency Service Level" or "MESL" of Price Responsive Demand for the 2017/2018 through the 2021/2022 Delivery Years shall mean the level, determined at a PRD Substation level, to which Price Responsive Demand shall be reduced during the Delivery Year when a Maximum Generation Emergency is declared and the Locational Marginal Price exceeds the price associated with such Price Responsive Demand identified by the PRD Provider in its PRD Plan.

Member:

"Member" shall have the meaning provided in the Operating Agreement.

Members Committee:

"Members Committee" shall mean the committee specified in Operating Agreement, section 8 composed of the representatives of all the Members.

NERC:

"NERC" shall mean the North American Electric Reliability Corporation or any successor thereto.

Network External Designated Transmission Service:

"Network External Designated Transmission Service" shall mean the quantity of network transmission service confirmed by PJM for use by a market participant to import power and

energy from an identified Generation Capacity Resource located outside the PJM Region, upon demonstration by such market participant that it owns such Generation Capacity Resource, has an executed contract to purchase power and energy from such Generation Capacity Resource, or has a contract to purchase power and energy from such Generation Capacity Resource contingent upon securing firm transmission service from such resource.

Network Resources:

"Network Resources" shall have the meaning set forth in the PJM Tariff.

Network Transmission Service:

"Network Transmission Service" shall mean transmission service provided pursuant to the rates, terms and conditions set forth in Tariff, Part III or transmission service comparable to such service that is provided to a Load Serving Entity that is also a Transmission Owner.

Nominal PRD Value:

"Nominal PRD Value" shall mean, as to any PRD Provider, an adjustment, determined in accordance with Reliability Assurance Agreement, Schedule 6.1, to the peak-load forecast used to determine the quantity of capacity sought through an RPM Auction, reflecting the aggregate effect of Price Responsive Demand on peak load resulting from the Price Responsive Demand to be provided by such PRD Provider.

Nominated Demand Resource Value:

"Nominated Demand Resource Value" shall have the meaning specified in Tariff, Attachment DD.

Non-Retail Behind the Meter Generation:

"Non-Retail Behind the Meter Generation" shall mean Behind the Meter Generation that is used by municipal electric systems, electric cooperatives, and electric distribution companies to serve load.

Nuclear Class:

"Nuclear Class" shall mean an ELCC Class consisting of Unlimited Resources primarily fueled by nuclear fuel.

Obligation Peak Load:

"Obligation Peak Load" shall have the meaning specified in Reliability Assurance Agreement, Schedule 8.

Office of the Interconnection:

"Office of the Interconnection" shall mean the employees and agents of PJM Interconnection, L.L.C., subject to the supervision and oversight of the PJM Board, acting pursuant to the Operating Agreement.

Offshore Wind Class:

"Offshore Wind Class" shall mean an ELCC Class consisting of Variable Resources that produce electrical energy with offshore wind turbines located in the ocean.

Oil Fired Combustion Turbine Class:

"Oil Fired Combustion Turbine Class" shall mean an ELCC Class consisting of Unlimited Resources of the combustion turbine technology type that are primarily fueled by oil.

Onshore Wind Class:

"Onshore Wind Class" shall mean an ELCC Class consisting of Variable Resources that produce electrical energy using wind turbines and that are not in the Offshore Wind Class.

Operating Agreement of the PJM Interconnection, L.L.C., Operating Agreement or PJM Operating Agreement:

"Operating Agreement of the PJM Interconnection, L.L.C.," "Operating Agreement" or "PJM Operating Agreement" shall mean that agreement, dated as of April 1, 1997 and as amended and restated as of June 2, 1997, including all Schedules, Exhibits, Appendices, addenda or supplements hereto, as amended from time to time thereafter, among the Members of the PJM Interconnection, L.L.C, on file with the Commission.

Operating Day:

"Operating Day" shall have the same meaning as provided in the Operating Agreement.

Operating Reserve:

"Operating Reserve" shall mean the amount of generating capacity scheduled to be available for a specified period of an Operating Day to ensure the reliable operation of the PJM Region, as specified in the PJM Manuals.

Ordinary Water Storage:

"Ordinary Water Storage" shall mean water stored in the pondage or reservoir of a hydropower resource which is typically available during normal operating conditions pursuant to the FERC license governing the operation of the hydropower resource.

Other Limited Duration Class:

"Other Limited Duration Class" shall mean the ELCC Classes specified in RAA Schedules 9.1 and 9.2 section B of this Agreement, each of which has a specified characteristic duration and consists of Limited Duration Resources that are not Capacity Storage Resources. The characteristic duration of an Other Limited Duration Class is the maximum period of time represented in the ELCC model that the resources of the class can run at a stated capability.

Other Limited Duration Combination Class:

"Other Limited Duration Combination Class" shall mean the ELCC Classes specified in RAA Schedules 9.1 and 9.2 section B. Each Other Limited Duration Class has a specified combination of two components, whereby, absent being part of a Combination Resource, one component would be in an Other Limited Duration Class, and the other component would be in a Variable Resource Class or would be an Unlimited Resource. A resource that is a member of an Other Limited Duration Class has a single Point Of Interconnection, unless the resource is controlled in an integrated fashion, is at a single site, and is approved by PJM to be considered a single resource in accordance with the PJM Manuals.

Other Steam Class:

"Other Steam Class" shall mean an ELCC Class consisting of Unlimited Resources of the steam technology type and do not qualify for the Coal Class, Nuclear Class, or Waste to Energy Steam Class (beginning with the 2027/2028 Delivery Year).

Other Supplier:

"Other Supplier" shall mean a Member that: (i) is engaged in buying, selling or transmitting electric energy, capacity, ancillary services, Financial Transmission Rights or other services available under PJM's governing documents in or through the Interconnection or has a good faith intent to do so, and (ii) is not a Generation Owner, Electric Distributor, Transmission Owner or End-Use Customer.

Other Unlimited Resource Class:

"Other Unlimited Resource Class" shall mean an ELCC Class consisting of Unlimited Resources that do not qualify for any other ELCC Class specified in RAA Schedule 9.2, section D.

Other Variable Resource Class:

"Other Variable Resource Class" shall mean an ELCC Class consisting of Variable Resources that are not in any other Variable Resource class, including Variable Resources that are composed of multiple components, each of which would be a Variable Resource. A resource composed of both fixed-tilt solar panels and tracking solar panels is not in this class. A resource that is a member of a Other Variable Resource Class has a single Point Of Interconnection, unless the resource is controlled in an integrated fashion, is at a single site, and is approved by PJM to be considered a single resource in accordance with the PJM Manuals.

Partial Requirements Service:

"Partial Requirements Service" shall mean wholesale service to supply a specified portion, but not all, of the power needs of a Load Serving Entity to serve end-users within the PJM Region that are not satisfied by its own generating facilities.

Party:

"Party" shall mean an entity bound by the terms of the Operating Agreement.

Peak Shaving Adjustment:

"Peak Shaving Adjustment" shall mean a load forecast mechanism that allows load reductions by end-use customers to result in a downward adjustment of the summer load forecast for the associated Zone. Any End-Use Customer identified in an approved peak shaving plan shall not also participate in PJM Markets as Price Responsive Demand, Demand Resource, Base Capacity Demand Resource, Capacity Performance Demand Resource, or Economic Load Response Participant.

Percentage Internal Resources Required:

"Percentage Internal Resources Required" shall mean, for purposes of an FRR Capacity Plan, the percentage of the LDA Reliability Requirement for an LDA that must be satisfied with Capacity Resources located in such LDA.

Performance Assessment Interval:

"Performance Assessment Interval" shall have the meaning specified in Tariff, Attachment DD.

PJM:

"PJM" shall mean PJM Interconnection, L.L.C., including the Office of the Interconnection as referenced in the PJM Operating Agreement. When such term is being used in the RAA it shall also include the PJM Board.

PJM Board:

"PJM Board" shall mean the Board of Managers of the LLC, acting pursuant to the Operating Agreement, except when such term is being used in Tariff, Attachment M, in which case PJM Board shall mean the Board of Managers of PJM or its designated representative, exclusive of any members of PJM Management.

PJM Manuals:

"PJM Manuals" shall mean the instructions, rules, procedures and guidelines established by the Office of the Interconnection for the operation, planning and accounting requirements of the PJM Region.

PJM Region:

"PJM Region" shall have the same meaning as provided in the Operating Agreement.

PJM Region Installed Reserve Margin:

"PJM Region Installed Reserve Margin" shall mean the percent installed reserve margin for the PJM Region required pursuant to Reliability Assurance Agreement, Schedule 4.1, as approved by the PJM Board.

PJM Tariff, Tariff, O.A.T.T., OATT or PJM Open Access Transmission Tariff:

"PJM Tariff," "Tariff," "O.A.T.T., "OATT" or "PJM Open Access Transmission Tariff" shall mean that certain PJM Open Access Transmission Tariff, including any schedules, appendices, or exhibits attached thereto, on file with FERC and as amended from time to time thereafter.

Planned Demand Resource:

"Planned Demand Resource" shall mean any Demand Resource that does not currently have the capability to provide a reduction in demand or to otherwise control load, but that is scheduled to be capable of providing such reduction or control on or before the start of the Delivery Year for which such resource is to be committed, as determined in accordance with the requirements of Reliability Assurance Agreement, Schedule 6. As set forth in Reliability Assurance Agreement, Schedule 6 and Reliability Assurance Agreement, Schedule 8.1, a Demand Resource Provider submitting a DR Sell Offer Plan shall identify as Planned Demand Resources in such plan all Demand Resources in excess of those that qualify as Existing Demand Resources.

Planned External Generation Capacity Resource:

"Planned External Generation Capacity Resource" shall mean a proposed Generation Capacity Resource, or a proposed increase in the capability of a Generation Capacity Resource, that (a) is to be located outside the PJM Region, (b) participates in the generation interconnection process of a Control Area external to PJM, (c) is scheduled to be physically and electrically interconnected to the transmission facilities of such Control Area on or before the first day of the Delivery Year for which such resource is to be committed to satisfy the reliability requirements of the PJM Region, and (d) is in full commercial operation prior to the first day of such Delivery Year, such that it is sufficient to provide the Installed Capacity set forth in the Sell Offer forming the basis of such resource's commitment to the PJM Region. Prior to participation in any Base Residual Auction for such Delivery Year, the Capacity Market Seller must demonstrate that it has a fully executed system impact study agreement (or other documentation which is functionally equivalent to a System Impact Study Agreement under the PJM Tariff) or, for resources which are greater than 20MWs participating in a Base Residual Auction for the 2019/2020 Delivery Year and subsequent Delivery Years, an agreement or other documentation which is functionally equivalent to a Facilities Study Agreement under the PJM Tariff), with the transmission owner to whose transmission facilities or distribution facilities the resource is being directly connected, and, as applicable, the transmission provider. Prior to participating in any Incremental Auction for such Delivery Year, the Capacity Market Seller must demonstrate it has entered into an interconnection agreement, or such other documentation that is functionally equivalent to an Interconnection Service Agreement under the PJM Tariff, with the transmission owner to whose transmission facilities or distribution facilities the resource is being directly connected, and, as applicable, the transmission provider. A Planned External Generation Capacity Resource must provide evidence to PJM that it has been studied as a Network Resource, or such other similar interconnection product in such external Control Area, must provide contractual evidence that it has applied for or purchased transmission service to be deliverable to the PJM border, and must provide contractual evidence that it has applied for transmission service to be deliverable to the bus at which energy is to delivered, the agreements for which must have been executed prior to participation in any Reliability Pricing Model Auction for such Delivery Year. Any such resource shall cease to be considered a Planned External Generation Capacity Resource as of the earlier of (i) the date that interconnection service commences as to such resource; or (ii) the resource has cleared an RPM Auction, in which case it shall become an Existing Generation Capacity Resource for purposes of the mitigation of offers for any RPM Auction for all subsequent Delivery Years.

Planned Generation Capacity Resource:

"Planned Generation Capacity Resource" shall mean a Generation Capacity Resource, or additional megawatts to increase the size of a Generation Capacity Resource that is being or has been modified to increase the number of megawatts of available installed capacity thereof, participating in the generation interconnection process under Tariff, Part IV, Subpart A, as applicable, for which: (i) Interconnection Service is scheduled to commence on or before the first day of the Delivery Year for which such resource is to be committed to RPM or to an FRR Capacity Plan; (ii) for any such resource seeking to offer into a Base Residual Auction, or for any such resource of 20 MWs or less seeking to offer into a Base Residual Auction, a System Impact Study Agreement (or, for resources for which a System Impact Study Agreement is not required, has such other agreement or documentation that is functionally equivalent to a System Impact Study Agreement) has been executed prior to the Base Residual Auction for such Delivery Year; (iii) for any such resource of more than 20 MWs seeking to offer into a Base Residual Auction for the 2019/2020 Delivery Year and subsequent Delivery Years, a Facilities Study Agreement (or, for resources for which a Facilities Study Agreement is not required, has such other agreement or documentation that is functionally equivalent to a Facility Studies Agreement) has been executed prior to the Base Residual Auction for such Delivery Year; and (iv) an Interconnection Service Agreement has been executed prior to any Incremental Auction for such Delivery Year in which such resource plans to participate. For purposes of the mustoffer requirement and mitigation of offers for any RPM Auction for a Delivery Year, a Generation Capacity Resource shall cease to be considered a Planned Generation Capacity Resource as of the earlier of (i) the date that Interconnection Service commences as to such resource; or (ii) the resource has cleared an RPM Auction for any Delivery Year, in which case it

shall become an Existing Generation Capacity Resource for any RPM Auction for all subsequent Delivery Years.

Planning Period:

"Planning Period" shall mean the 12 months beginning June 1 and extending through May 31 of the following year, or such other period approved by the Members Committee.

Portfolio Expected Unserved Energy:

"Portfolio Expected Unserved Energy" shall mean the annual amount of expected unserved energy, in MWh, that is expected for the RTO when at the annual reliability criteria that provides an acceptable level of reliability consistent with the Reliability Principles and Standards.

PRD Curve:

"PRD Curve" shall mean a price-consumption curve at a PRD Substation level, if available, and otherwise at a Zonal (or sub-Zonal LDA, if applicable) level, that details the base consumption level of Price Responsive Demand and the decreasing consumption levels at increasing prices.

PRD Provider:

"PRD Provider" shall mean a PJM Member that has entered contractual arrangements with enduse customers that satisfy the eligibility criteria for and provides Price Responsive Demand.

PRD Provider's Zonal Expected Peak Load Value of PRD:

"PRD Provider's Zonal Expected Peak Load Value of PRD" shall mean the expected contribution to Delivery Year peak load of a PRD Provider's Price Responsive Demand, were such demand not to be reduced in response to price, based on the contribution of the end-use customers comprising such Price Responsive Demand to the most recent prior Delivery Year's peak demand, escalated to the Delivery Year in question, as determined in a manner consistent with the Office of the Interconnection's load forecasts used for purposes of the RPM Auctions.

PRD Reservation Price:

"PRD Reservation Price" shall mean an RPM Auction clearing price identified in a PRD Plan for Price Responsive Demand load below which the PRD Provider desires not to commit the identified load as Price Responsive Demand.

PRD Substation:

"PRD Substation" shall mean an electrical substation that is located in the same Zone or in the same sub-Zonal LDA as the end-use customers identified in a PRD Plan or PRD registration and that, in terms of the electrical topography of the Transmission Facilities comprising the PJM Region, is as close as practicable to such loads.
Price Responsive Demand:

"Price Responsive Demand" or "PRD" shall mean end-use customer load registered by a PRD Provider pursuant to Reliability Assurance Agreement, Schedule 6.1 that have, as set forth in more detail in the PJM Manuals, the metering capability to record electricity consumption at an interval of one hour or less, Supervisory Control capable of curtailing such load (consistent with applicable RERRA requirements) at each PRD Substation identified in the relevant PRD Plan or PRD registration in response to a Maximum Generation Emergency declared by the Office of the Interconnection (prior to 2022/2023Delivery Year) or a Performance Assessment Interval that triggers a PRD performance assessment (effective with 2022/2023 Delivery Year), and a retail rate structure, or equivalent contractual arrangement, capable of changing retail rates as frequently as an hourly basis, that is linked to or based upon changes in real-time Locational Marginal Prices at a PRD Substation level and that results in a predictable automated response to varying wholesale electricity prices.

Price Responsive Demand Credit:

"Price Responsive Demand Credit" shall mean a credit, based on committed Price Responsive Demand, as determined under Reliability Assurance Agreement, Schedule 6.1.

Price Responsive Demand Plan or PRD Plan:

"Price Responsive Demand Plan" or "PRD Plan" shall mean a plan, submitted by a PRD Provider and received by the Office of the Interconnection in accordance with Reliability Assurance Agreement, Schedule 6.1 and procedures specified in the PJM Manuals, claiming a peak demand limitation due to Price Responsive Demand to support the determination of such PRD Provider's Nominal PRD Value.

Public Power Entity:

"Public Power Entity" shall mean any agency, authority, or instrumentality of a state or of a political subdivision of a state, or any corporation wholly owned by any one or more of the foregoing, that is engaged in the generation, transmission, and/or distribution of electric energy.

Qualifying Transmission Upgrades:

"Qualifying Transmission Upgrades" shall have the meaning specified in Tariff, Attachment DD.

Relevant Electric Retail Regulatory Authority:

"Relevant Electric Retail Regulatory Authority" or "RERRA" shall have the meaning specified in the PJM Operating Agreement.

Reliability Principles and Standards:

"Reliability Principles and Standards" shall mean the principles and standards established by the Office of the Interconnection that define, among other things, an acceptable probabilistic of loss of load criteria due to inadequate generation or transmission capability, as amended from time to time.

Required Approvals:

"Required Approvals" shall mean all of the approvals required for the Operating Agreement to be modified or to be terminated, in whole or in part, including the acceptance for filing by FERC and every other regulatory authority with jurisdiction over all or any part of the Operating Agreement.

Self-Supply:

"Self-Supply" shall have the meaning provided in Tariff, Attachment DD.

Small Commercial Customer:

"Small Commercial Customer" shall have the same meaning as in the PJM Tariff.

State Consumer Advocate:

"State Consumer Advocate" shall mean a legislatively created office from any State, all or any part of the territory of which is within the PJM Region, and the District of Columbia established, inter alia, for the purpose of representing the interests of energy consumers before the utility regulatory commissions of such states and the District of Columbia and the FERC.

State Regulatory Structural Change:

"State Regulatory Structural Change" shall mean as to any Party, a state law, rule, or order that, after September 30, 2006, initiates a program that allows retail electric consumers served by such Party to choose from among alternative suppliers on a competitive basis, terminates such a program, expands such a program to include classes of customers or localities served by such Party that were not previously permitted to participate in such a program, or that modifies retail electric market structure or market design rules in a manner that materially increases the likelihood that a substantial proportion of the customers of such Party that are eligible for retail choice under such a program (a) that have not exercised such choice will exercise such choice; or (b) that have exercised such choice will no longer exercise such choice, including for example, without limitation, mandating divestiture of utility-owned generation or structural changes to such Party's default service rules that materially affect whether retail choice is economically viable.

Steam Class:

"Steam Class" shall mean an ELCC Class consisting of Unlimited Resources of the steam technology type and the primary fuel is not coal or nuclear.

Summer-Period Demand Resource:

Summer-Period Demand Resource shall mean, for the 2020/2021 Delivery Year and subsequent Delivery Years, a resource that is placed under the direction of the Office of the Interconnection, and will be available June through October and the following May of the Delivery Year, and will be available for an unlimited number of interruptions during such months by the Office of the Interconnection, and will be capable of maintaining each such interruption between the hours of 10:00AM to 10:00PM Eastern Prevailing Time. The Summer-Period Demand Resource must be available June through October and the following May in the corresponding Delivery Year to be offered for sale in an RPM Auction, or included as a Summer-Period Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Summer-Period Energy Efficiency Resource:

Summer-Period Energy Efficiency Resource shall mean, for the 2020/2021 Delivery Year and subsequent Delivery Years, a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, meeting the requirements of Reliability Assurance Agreement, Schedule 6 and exceeding then-current building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during the summer peak periods as described in Reliability Assurance Agreement, Schedule 6 and the PJM Manuals) reduction in electric energy consumption that is not reflected in the peak load forecast prepared for the Delivery Year for which the Summer-Period Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention.

Supervisory Control:

"Supervisory Control" shall mean the capability to curtail, in accordance with applicable RERRA requirements, load registered as Price Responsive Demand at each PRD Substation identified in the relevant PRD Plan or PRD registration in response to a Maximum Generation Emergency declared by the Office of the Interconnection. Except to the extent automation is not required by the provisions of the Operating Agreement, the curtailment shall be automated, meaning that load shall be reduced automatically in response to control signals sent by the PRD Provider or its designated agent directly to the control equipment where the load is located without the requirement for any action by the end-use customer.

Threshold Quantity:

"Threshold Quantity" shall mean, as to any FRR Entity for any Delivery Year, the sum of (a) the Unforced Capacity equivalent (determined using the Pool-Wide Average EFORD through the 2024/2025 Delivery Year, or pool-wide average Accredited UCAP Factor effective with the 2025/2026 Delivery Year) of the Installed Reserve Margin for such Delivery Year multiplied by the Preliminary Forecast Peak Load for which such FRR Entity is responsible under its FRR Capacity Plan for such Delivery Year, plus (b) the lesser of (i) 3% of the Unforced Capacity amount determined in (a) above or (ii) 450 MW. If the FRR Entity is not responsible for all load

within a Zone, the Preliminary Forecast Peak Load for such entity shall be determined in accordance with Reliability Assurance Agreement, Schedule 8.1, section D.2.

Tracking Solar Class:

"Tracking Solar Class" shall mean an ELCC Class consisting of Variable Resources that produce electrical energy with solar panels that are primarily mounted on trackers that align the panels with incoming sunlight over the course of the day.

Transmission Facilities:

"Transmission Facilities" shall mean facilities that: (i) are within the PJM Region; (ii) meet the definition of transmission facilities pursuant to FERC's Uniform System of Accounts or have been classified as transmission facilities in a ruling by FERC addressing such facilities; and (iii) have been demonstrated to the satisfaction of the Office of the Interconnection to be integrated with the PJM Region transmission system and integrated into the planning and operation of the PJM Region to serve all of the power and transmission customers within the PJM Region.

Transmission Owner:

"Transmission Owner" shall mean a Member that owns or leases with rights equivalent to ownership Transmission Facilities and is a signatory to the PJM Transmission Owners Agreement. Taking transmission service shall not be sufficient to qualify a Member as a Transmission Owner.

Unforced Capacity:

"Unforced Capacity" shall mean installed capacity rated at summer conditions that is not on average experiencing a forced outage or forced derating, calculated for each Capacity Resource on the 12-month period from October to September without regard to the ownership of or the contractual rights to the capacity of the unit.

Unlimited Resource:

"Unlimited Resource" shall mean a generating unit having the ability to maintain output at a stated capability continuously on a daily basis without interruption. Through the 2024/2025 Delivery Year, an Unlimited Resource is a Generation Capacity Resource that is not an ELCC Resource.

Variable Resource:

"Variable Resource" shall mean a Generation Capacity Resource with output that can vary as a function of its energy source, such as wind, solar, run of river hydroelectric power without storage, and landfill gas units without an alternate fuel source. All Intermittent Resources are Variable Resources, with the exception of Hydropower with Non-Pumped Storage.

Waste to Energy Steam Class:

"Waste to Energy Steam Class" shall mean an ELCC Class consisting of Unlimited Resources of the steam technology type whose primary fuel is municipal waste or wood waste.

Winter Peak Load (or WPL):

"Winter Peak Load" or "WPL" shall mean the average of the Demand Resource customer's specific peak hourly load between hours ending 7:00 EPT through 21:00 EPT on the PJM defined 5 coincident peak days from December through February two Delivery Years prior the Delivery Year for which the registration is submitted. Notwithstanding, if the average use between hours ending 7:00 EPT through 21:00 EPT on a winter 5 coincident peak day is below 35% of the average hours ending 7:00 EPT through 21:00 EPT over all five of such peak days, then up to two such days and corresponding peak demand values may be excluded from the calculation. Upon approval by the Office of the Interconnection, a Curtailment Service Provider may provide alternative data to calculate Winter Peak Load, as outlined in the PJM Manuals, when there is insufficient hourly load data for the two Delivery Years prior to the relevant Delivery Year or if more than two days meet the exclusion criteria described above.

Zonal Capacity Price:

"Zonal Capacity Price" shall mean the clearing price required in each Zone to meet the demand for Unforced Capacity and satisfy Locational Deliverability Requirements for the LDA or LDAs associated with such Zone. If the Zone contains multiple LDAs with different Capacity Resource Clearing Prices, the Zonal Capacity Price shall be a weighted average of the Capacity Resource Clearing Prices for such LDAs, weighted by the Unforced Capacity of Capacity Resources cleared in each such LDA.

Zone or Zonal:

"Zone" or "Zonal" shall refer to an area within the PJM Region, as set forth in Tariff, Attachment J and RAA, Schedule 15, or as such areas may be (i) combined as a result of mergers or acquisitions or (ii) added as a result of the expansion of the boundaries of the PJM Region. A Zone shall include any Non-Zone Network Load located outside the PJM Region that is served from such Zone under Tariff, Attachment H-A.

Zonal Winter Weather Adjustment Factor (ZWWAF):

"Zonal Winter Weather Adjustment Factor" or "ZWWAF" shall mean the PJM zonal winter weather normalized coincident peak divided by PJM zonal average of 5 coincident peak loads in December through February.

SCHEDULE 9.2:

EFFECTIVE LOAD CARRYING CAPABILITY ANALYSIS FOR THE 2025/2026 DELIVERY YEAR AND SUBSEQUENT DELIVERY YEARS

A. Overview of Effective Load Carrying Capability Analysis

The inputs of the effective load carrying capability analysis shall consider similar data and forecasts as that used in development of the FPR, as described in Schedule 4.C, and will include:

-Historical weather and load data;

-Historical output of existing Variable Resources;

-Estimates of putative historical output for planned Variable Resources;

-Forced outage patterns for Unlimited Resources, including consideration of correlated outage risks;

-Resource deployment forecast; and

-Modeling parameters for Limited Duration Resources, Combination Resources, and Demand Resources.

The outputs of the effective load carrying capability analysis include:

-ELCC Class Rating values, in percent.

B. ELCC Classes

- (1) (a) The following are the ELCC Classes for Variable Resources:
 - Tracking Solar Class
 - Fixed-Tilt Solar Class
 - Onshore Wind Class
 - Offshore Wind Class
 - Intermittent Landfill Gas Class
 - Intermittent Hydropower Class
 - Other Variable Resource Class

(b) The following are the types of ELCC Classes for Limited Duration Resources:

- The type of Capacity Storage Resource Classes
- The type of Other Limited Duration Resource Classes

Within those types, the following are the specific ELCC Classes for Limited Duration Resources:

- Capacity Storage Resource Class (4-Hour Duration)
- Capacity Storage Resource Class (6-Hour Duration)
- Capacity Storage Resource Class (8-Hour Duration)
- Capacity Storage Resource Class (10-Hour Duration)

- Other Limited Duration Class (4-Hour Duration)
- Other Limited Duration Class (6-Hour Duration)
- Other Limited Duration Class (8-Hour Duration)
- Other Limited Duration Class (10-Hour Duration)

(c) The following are the ELCC Classes for Combination Resources:

- The types of Hybrid Resource Classes, as further specified in subpart (2) below
- Hydropower With Non-Pumped Storage Class
- Complex Hybrid Class
- The types of Other Limited Duration Combination Classes, as further specified in subpart (3).
 - (d) The following are the ELCC Classes for Unlimited Resources
 - Nuclear Class
 - Coal Class
 - Gas Combined Cycle Class
 - Gas Combustion Turbine Class
 - Gas Combined Cycle Dual Fuel Class
 - Oil Fired Combustion Turbine Class (effective with the 2027/2028 Delivery Year)
 - Gas Combustion Turbine Dual Fuel Class
 - Diesel Utility Class
 - <u>Other</u> Steam Class
 - Waste to Energy Steam Class (effective with the 2027/2028 Delivery Year)
 - Other Unlimited Resource Class

(e) The following are the ELCC Classes for Demand Resources

- Demand Resource Class

(2) PJM shall establish Hybrid Resource Classes for all "open-loop" combinations of each Capacity Storage Resource class and each Variable Resource class or Unlimited Resource class, as well as all "closed-loop" combinations of each Capacity Storage Resource class and each Variable Resource class or Unlimited Resource class. An "open-loop" resource operates by charging the storage component from the grid, while a "closed-loop" resource does not.

(3) PJM shall establish "Other Limited Duration Combination Classes" for all combinations of each Variable Resource Class and each Other Limited Duration Resource Class, and for combinations of an Unlimited Resource with each Other Limited Duration Resource Class.

(4) For a given Delivery Year, ELCC Class Ratings will not be calculated for any ELCC Class to the extent that no member of the class is expected to provide, or offer to provide capacity, in the applicable Delivery Year. PJM will determine the ELCC Class Ratings for an ELCC Class when any one of the following criteria are met:

(a) An Existing Generation Capacity Resource is in such class; or

(b) A Planned Generation Capacity Resource has submitted timely and valid data through the ELCC data submission process and is in such class; or

(c) The resource deployment forecast contains a resource in such class.

(5) (a) For each ELCC Resource, except an ELCC Resource that is a Capacity Storage Resource or includes a Capacity Storage Resource component, PJM shall determine the ELCC Class of which such resource is a member by matching the physical characteristics of such resource with the definition of the ELCC Class.

(b) For each ELCC Resource that is a Capacity Storage Resource or includes a Capacity Storage Resource component, PJM shall determine, by matching the physical characteristics of such resource with the definition of the ELCC Class, the type of ELCC Class of which such resource is a member; provided however, the Generation Capacity Resource Provider shall choose the specific ELCC Class within the type ELCC Class identified by PJM that corresponds to the chosen characteristic duration.

If the Generation Capacity Resource Provider fails to choose, PJM will choose a specific ELCC Class to assign to such resource. The election of the specific ELCC Class corresponding to the chosen characteristic duration shall be for a term of five consecutive Delivery Years. After such five Delivery Year period, a Generation Capacity Resource Provider may request a change in the ELCC Class, based on choosing a different characteristic duration, by submitting to the Office of the Interconnection a written request to switch ELCC Classes and provide documentation supporting such change. A Generation Capacity Resource Provider must submit such a request, and supporting documentation, by August 1 prior to the calendar year for the RPM Auction in which the ELCC Resource intends to submit a Sell Offer or otherwise commit to provide capacity, except for 2025/2026 Delivery Year such required information must be provided to the Office of the Interconnection in accordance with the PJM Manuals. The Office of the Interconnection shall provide no later than following November 15 written notification to the Generation Capacity Resource Provider of its determination. If the request is granted, the ELCC Resource shall be considered in the new ELCC Class starting with the next Delivery Year for which no RPM Auction has been conducted and for subsequent Delivery Years. If the request is denied, the Office of the Interconnection shall include in the notice a written explanation for the denial.

(6) Mixed-technology resources are composed of components with different generation technologies, at least one of which would be an ELCC Resource, behind a single Point of Interconnection. For a mixed-technology resource composed of components that do not have significant interaction, the components are eligible to participate as separate resources. A mixed-technology resource composed of components that have significant interaction must participate as a single Combination Resource (or, if the components would all be Variable Resources, then as a single Variable Resource).

The Generation Capacity Resource Provider of a mixed-technology resource eligible to participate as either a single ELCC Resource or as multiple stand-alone resources shall elect, for a term of five consecutive Delivery Years, whether PJM is to model it as a single ELCC Resource or as multiple stand-alone resources. After such five Delivery Year period, a Generation Capacity Resource Provider may request a change in such modelling approach by submitting to the Office of the Interconnection a written request to change the modelling approach and provide documentation supporting such change. A Generation Capacity Resource Provider must submit such a request, and supporting documentation, by August 1 prior to the calendar year for the RPM Auction in which the ELCC Resource(s) intend(s) to submit a Sell Offer or otherwise commit to provide capacity, except for 2025/2026 Delivery Year such required information must be provided to the Office of the Interconnection in accordance with the PJM Manuals. The Office of the Interconnection shall provide no later than following November 15 written notification to the Generation Capacity Resource Provider of its determination. If the request is granted, the ELCC Resource(s) shall be modelled as requested starting with the next Delivery Year for which no RPM Auction has been conducted and for subsequent Delivery Years. If the request is denied, the Office of the Interconnection shall include in the notice a written explanation for the denial.

C. Calculation of ELCC Class Rating

ELCC Class Ratings for a Delivery Year are calculated by adding to the forecasted resource portfolio incremental quantities of resources belonging to the subject ELCC Class, depending on the resource type:

(1) The ELCC Class Rating of Variable Resources, Limited Duration Resources, Unlimited Resources (except Other Unlimited Resources), and Demand Resources shall be the ratio of the expected unserved energy improvement resulting from adding an incremental quantity of the subject ELCC Class to the expected unserved energy improvement resulting from adding an incremental quantity of an Unlimited Resource with no outages, where expected unserved energy improvement is calculated relative to the Portfolio EUE for the Delivery Year.

(2) No ELCC Class Rating is determined for Combination Resources and ELCC Resources in the Hydropower with Non-Pumped Storage Class, in the Complex Hybrid Class, in the Other Unlimited Resource Class, and in any ELCC Class whose members are so distinct from one another that a single ELCC Class Rating would fail to capture their physical characteristics.

D. Calculation of Accredited UCAP and ELCC Resource Performance Adjustment

(1) (a) For Variable Resources and Limited Duration Resources, Accredited UCAP values shall be equal to the lesser of the resource's Capacity Interconnection Right or the product of:

(i) the Effective Nameplate Capacity;

(ii) the applicable ELCC Class Rating; and

(iii) the ELCC Resource Performance Adjustment.

(b) For any resource in an ELCC Class for which no Class Rating has been calculated pursuant to C(2), the Accredited UCAP shall be based on a resource-specific effective load carrying capability analysis based on the resource's unique parameters.

(c) For Unlimited Resources that have an ELCC Class Rating determined pursuant to C(1), Accredited UCAP values shall be equal to the product of:

(i) the installed capacity;

(ii) the applicable ELCC Class Rating; and

(iii) the ELCC Resource Performance Adjustment.

(d) For Demand Resources, Accredited UCAP values shall be equal to the product of:

- (i) the Nominated Value of the Demand Resource; and
- (ii) the applicable ELCC Class Rating.

(2) The ELCC Resource Performance Adjustment shall be calculated according to the following methods, as further detailed in the PJM Manuals:

(a) For a Variable Resource, a Limited Duration Resource, and an Unlimited Resource: based on a metric consisting of the weighted average expected hourly output of the resource in the ELCC model during hours of loss of load risk where: (i) the weights correspond to the modeled probability of losing load in such hour and (ii) the expected hourly output is based on the resource's modeled output during the same hour on days since June 1st, 2012 identified as having similar weather from an RTO-perspective. For a given resource or component, the Performance Adjustment shall equal the ratio of such metric to the average (weighted by the Effective Nameplate Capacity) of such metrics for all units in the applicable Variable Resource ELCC Class or applicable Unlimited Resource ELCC Class.

In determining the ELCC Resource Performance Adjustment, the actual output of a Variable Resource shall be adjusted to reflect historical curtailments, and output in any hour shall be capped at: (i) the greater of the Variable Resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year, for hours in the months of June through October and the following May of the Delivery Year, and (ii) the Variable Resource's assessed deliverability, as defined in the PJM Manuals, for hours in the months of November through April of the Delivery Year. The output of an Unlimited Resource in any hour shall be capped at the greater of the resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year.

E. Calculation of Accredited UCAP Factor

For Generation Capacity Resources, PJM shall determine an Accredited UCAP Factor, which is the ratio of the resource's Accredited UCAP to the resource's installed capacity.

G. Installed Capacity of ELCC Resources

Rules and procedures for technically determining and demonstrating the installed capacity of ELCC Resources shall be developed by the Office of the Interconnection and maintained in the PJM Manuals. The installed capacity of a Limited Duration Resource is based on the sustained level of output that the unit can provide and maintain over a continuous period, whereby the duration of that period matches the characteristic duration of the corresponding ELCC Class, with consideration given to ambient conditions expected to exist at the time of PJM system peak load, as described in the PJM Manuals. The installed capacity of a Combination Resource (other than Hydropower With Non-Pumped Storage) is based on the lesser of the Maximum Facility

Output or the sum of the equivalent Effective Nameplate Capacity values of the resource's constituent components considered on a stand-alone basis. The installed capacity of an Unlimited Resource and Variable Resource shall be determined in accordance with the PJM Manuals. The installed capacity of Demand Resources, for purposes of the ELCC analysis, is based on the forecasted deployment level in the PJM Load Forecast.

H. Details of the Effective Load Carrying Capability Methodology

The effective load carrying capability analysis shall compare expected hourly load levels (based on historical weather) with the expected hourly output of the expected future resource mix in order to identify the relative marginal resource adequacy value of each individual ELCC Class compared to an Unlimited Resource with no outages. In performing this analysis, the model inputs shall be scaled to meet the annual reliability criteria of the Office of the Interconnection. The effective load carrying capability analysis shall compare hourly values for: (i) expected load based on historical weather; (ii) expected Variable Resource output; (iii) expected output of Limited Duration Resources and of Combination Resources as described below; (iv) expected Unlimited Resource output; and (v) expected Demand Resource output. These expected quantities are based on forecasted load and actual and putative values for Variable Resource output (standalone or as a component of Combination Resources) and Unlimited Resource output after June 1, 2012 (inclusive) through the most recent Delivery Year for which complete data exist. For resources that have not existed each year since June 1, 2012, putative output is an estimate of the hourly output that resource would have produced in a historical hour if that resource had existed in that hour. For Variable Resources, this putative output estimate is developed based on historical weather data consistent with the particular site conditions for each such resource in accordance with the PJM Manuals; for Unlimited Resources, the putative output is developed based on actual performance of similar units in accordance with the PJM Manuals.

Variable Resource actual output shall be adjusted in the ELCC analysis to reflect historical curtailments, and output shall be capped in any hour at: (i) the greater of the Variable Resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year, during the months of June through October and the following May of the Delivery Year, and (ii) the Variable Resource's assessed deliverability, as defined in the PJM Manuals, during the months of November through April of the Delivery Year. The output of Unlimited Resources shall not exceed the greater of the Unlimited Resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year.

The effective load carrying capability analysis shall simulate performance of Demand Resources, and shall simulate the output of Limited Duration Resources and Combination Resources based on their Office of the Interconnection-validated parameters, including the putative output of the Variable Resource component of Combination Resources, as described above.

The quantity of deployed resources studied in the analysis shall be based on resource deployment forecasts and, where applicable, on available information based on Sell Offers submitted in RPM Auctions or Fixed Resource Requirement plans for the applicable Delivery Year, and, where applicable, information provided to the Office of the Interconnection regarding intent to offer in an RPM Auction, pursuant to the requirements in the Tariff, Attachment DD, section 5.5.

The model inputs, specifically the load scenarios, shall be scaled to meet the annual reliability criteria of the Office of the Interconnection. The resulting expected unserved energy constitutes the Portfolio EUE for the Delivery Year. Energy Resources are not included in the effective load carrying capability analysis. Generating units that are expected to only offer or otherwise provide a portion of their Accredited UCAP for that Delivery Year are represented in the analysis in proportion to the expected quantity offered or delivered divided by the Accredited UCAP.

I. Methodology to Simulate Output of Certain Resources in the Effective Load Carrying Capability Model

The effective load carrying capability analysis shall simulate the output of Limited Duration Resources and Combination Resources based on their physical parameters, including limited storage capability, and shall simulate the deployment of Demand Resources. The analysis shall simulate output from the subject Limited Duration Resources, Combination Resources, and Demand Resources in hours in which all output from Unlimited Resources and available output from Variable Resources is insufficient to meet load. The analysis shall first simulate the output of Demand Resources. If the simulated output of Demand Resources is insufficient to meet load, then the output of the subject Limited Duration Resources and Combination Resources shall be simulated on an hour-by-hour basis based on their relative duration, starting from longer duration resources to shorter duration resources. The output of Combination Resources shall be capped in any hour at: (i) the greater of the Combination Resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year, during the months of June through October and the following May of the Delivery Year, and (ii) the Combination Resource's assessed deliverability, as defined in the PJM Manuals, during the months of November through April of the Delivery Year. Energy Storage Resource charging is during hours with sufficient margin, including between daily peaks if necessary.

J. Administration of Effective Load Carrying Capability Analysis

The Office of the Interconnection shall post final ELCC Class Rating values at least once per year in a report that also includes appropriate details regarding methodology and inputs. The Office of the Interconnection shall post this report and shall communicate ELCC Resource Performance Adjustment values to applicable Generation Capacity Resource Providers no later than five months prior to the start of the target Delivery Year, as described in the PJM Manuals. Accredited UCAP values for the applicable Delivery Year shall establish the maximum Unforced Capacity that an ELCC Resource can physically provide or offer to provide in the applicable Delivery Year.

The Office of the Interconnection shall also post preliminary ELCC Class Rating values for nine subsequent Delivery Years. For any Delivery Year for which a final ELCC Class Rating has not been posted and a preliminary ELCC Class Rating has been posted, the Accredited UCAP of an ELCC Resource for such Delivery Year shall be based on the most recent preliminary ELCC Class Rating value for that Delivery Year, together with the most recently calculated ELCC Resource Performance Adjustment value for that ELCC Resource. Except to the extent specified

above or otherwise specified, the preliminary ELCC Class Rating values for future years are non-binding and are only for indicative purposes. A Generation Capacity Resource Provider can offer or provide capacity from an ELCC Resource that is not subject to a capacity market must offer obligation (as specified in Tariff, Attachment DD, Section 6.6) at a level less than the Accredited UCAP for such resource.

In order to facilitate the effective load carrying capability analysis, the Generation Capacity Resource Provider of each ELCC Resource must submit to the Office of the Interconnection the required information as specified in the PJM Manuals by no later than August 1 prior to the calendar year for the RPM Auction in which the ELCC Resource intends to submit a Sell Offer or otherwise commit to provide capacity, except for 2025/2026 Delivery Years such required information must be provided to the Office of the Interconnection in accordance with the PJM Manuals. The required information may include relevant physical parameters, relevant historical data such as weather data and actual or estimated historical energy output, and documentation supporting such parameters and historical data. The relevant physical parameters are those that are incorporated into the effective load carrying capability analysis. The parameters required for Hydropower With Non-Pumped Storage shall include Ordinary Water Storage and any applicable Exigent Water Storage. Submitted parameters must indicate the expected duration for which any submitted physical parameters are valid.

The Office of the Interconnection shall evaluate, validate, and approve the foregoing information in accordance with the process set forth in the PJM Manuals. In evaluating the validity of submitted information, the Office of the Interconnection may assess the consistency of such information with observed conditions. If the Office of the Interconnection observes that the information provided by the Generation Capacity Resource Provider of the ELCC Resource is inconsistent with observed conditions, the Office of the Interconnection will coordinate with the Generation Capacity Resource Provider of the ELCC Resource to understand the information and observed conditions before making a determination regarding the validity of the applicable parameters. The Office of the Interconnection may engage the services of a consultant with technical expertise to evaluate the foregoing information.

After the Office of the Interconnection has completed its evaluation of the foregoing information, the Office of the Interconnection shall notify the Generation Capacity Resource Provider in writing whether the submitted information is considered invalid by no later than September 1 following the submission of the information. The Office of the Interconnection's determination on the validity of the foregoing information shall continue for the applicable Delivery Year and, if requested, for such longer period as the Office of the Interconnection may determine is supported by the data.

In the event that the Office of the Interconnection is unable to validate any of the required information, physical parameters, supporting documentation, or other related information submitted by the Generation Capacity Resource Provider of an ELCC Resource, then the Office of the Interconnection shall calculate Accredited UCAP values for that ELCC Resource based only on the validated information. Such ELCC Resource shall not be permitted to offer or otherwise provide capacity above such Accredited UCAP values until the Office of the Interconnection determines new Accredited UCAP values for such resource.

Generation Capacity Resource Providers of ELCC Resources that are hydropower plants with water storage must provide documentation to support the physical parameters provided for

expected load carrying capability analysis modeling, as specified in the PJM Manuals. This documentation must: (a) support the plant's physical capabilities; (b) demonstrate that the parameters do not violate any federal, state, river basin, or other applicable authority operating limitations of the plant; and (c) demonstrate full authorization from FERC, any river basin commissions, and any other applicable authorities to meet those capabilities.

Attachment B

Revisions to the PJM Reliability Assurance Agreement

(Clean Format)

ARTICLE 1 – DEFINITIONS

Unless the context otherwise specifies or requires, capitalized terms used herein shall have the respective meanings assigned herein or in the Schedules hereto, or in the PJM Tariff or PJM Operating Agreement if not otherwise defined in this Agreement, for all purposes of this Agreement (such definitions to be equally applicable to both the singular and the plural forms of the terms defined). Unless otherwise specified, all references herein to Articles, Sections or Schedules, are to Articles, Sections or Schedules of this Agreement. As used in this Agreement:

Accredited UCAP:

"Accredited UCAP" shall mean the quantity of Unforced Capacity, as denominated in Effective UCAP, that an ELCC Resource is capable of providing in a given Delivery Year.

Accredited UCAP Factor:

"Accredited UCAP Factor" shall mean, through the 2024/2025 Delivery Year, one minus EFORd, and for 2025/2026 Delivery Year and subsequent Delivery Years, the ratio of the Capacity Resource's Accredited UCAP to the Capacity Resource's installed capacity.

Agreement:

"Agreement" shall mean this Reliability Assurance Agreement, together with all Schedules hereto, as amended from time to time.

Annual Demand Resource:

"Annual Demand Resource" shall mean a resource that is placed under the direction of the Office of the Interconnection during the Delivery Year, and will be available for an unlimited number of interruptions during such Delivery Year by the Office of the Interconnection, and will be capable of maintaining each such interruption between the hours of 10:00AM to 10:00PM Eastern Prevailing Time for the months of June through October and the following May, and 6:00AM through 9:00PM Eastern Prevailing Time for the months of November through April unless there is an Office of the Interconnection approved maintenance outage during October through April. The Annual Demand Resource must be available in the corresponding Delivery year to be offered for sale or Self-Supplied in an RPM Auction, or included as an Annual Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Annual Energy Efficiency Resource:

"Annual Energy Efficiency Resource" shall mean a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, meeting the requirements of Reliability Assurance Agreement, Schedule 6 and exceeding thencurrent building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during the summer and winter periods described in such Schedule 6 and the PJM Manuals) reduction in electric energy consumption that is not reflected in the peak load forecast prepared for the Delivery Year for which the Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention.

Applicable Regional Entity:

"Applicable Regional Entity" shall have the same meaning as in the PJM Tariff.

Base Capacity Demand Resource:

"Base Capacity Demand Resource" shall mean, for the 2018/2019 and 2019/2020 Delivery Years, a resource that is placed under the direction of the Office of the Interconnection and that will be available June through September of a Delivery Year, and will be available to the Office of the Interconnection for an unlimited number of interruptions during such months, and will be capable of maintaining each such interruption for at least a 10-hour duration between the hours of 10:00AM to 10:00PM Eastern Prevailing Time. The Base Capacity Demand Resource must be available June through September in the corresponding Delivery Year to be offered for sale or self-supplied in an RPM Auction, or included as a Base Capacity Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Base Capacity Energy Efficiency Resource:

"Base Capacity Energy Efficiency Resource" shall mean, for the 2018/2019 and 2019/2020 Delivery Years, a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, meeting the requirements of RAA, Schedule 6 and exceeding then-current building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during the summer peak periods as described in Reliability Assurance Agreement, Schedule 6 and the PJM Manuals) reduction in electric energy consumption that is not reflected in the peak load forecast prepared for the Delivery Year for which the Base Capacity Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention.

Base Capacity Resource:

"Base Capacity Resource" shall have the same meaning as in Tariff, Attachment DD.

Base Residual Auction:

"Base Residual Auction" shall have the same meaning as in Tariff, Attachment DD.

Behind The Meter Generation:

"Behind The Meter Generation" shall refer to a generating unit that delivers energy to load without using the Transmission System or any distribution facilities (unless the entity that owns or leases the distribution facilities consented to such use of the distribution facilities and such consent has been demonstrated to the satisfaction of the Office of the Interconnection; provided, however, that Behind The Meter Generation does not include (i) at any time, any portion of such generating unit's capacity that is designated as a Capacity Resource or (ii) in any hour, any portion of the output of such generating unit that is sold to another entity for consumption at another electrical location or into the PJM Interchange Energy Market.

Black Start Capability:

"Black Start Capability" shall mean the ability of a generating unit or station to go from a shutdown condition to an operating condition and start delivering power without assistance from the power system.

Capacity Emergency Transfer Objective (CETO):

"Capacity Emergency Transfer Objective" or "CETO" shall mean, through the 2024/2025 Delivery Year, the amount of electric energy that a given area must be able to import in order to remain within a loss of load expectation of one event in 25 years when the area is experiencing a localized capacity emergency, as determined in accordance with the PJM Manuals. Without limiting the foregoing, CETO shall be, for Delivery Years through 2024/2025, calculated based in part on EFORD determined in accordance with Reliability Assurance Agreement, Schedule 5, Paragraph C. Beginning with the 2025/2026 Delivery Year, CETO shall mean the amount of electric energy that a given area must be able to import in order to satisfy a normalized expected unserved energy for the area that is equal to forty percent of the normalized expected unserved energy is the expected unserved energy (for the area or RTO, as appropriate) divided by the forecasted annual energy (for the area or RTO, as appropriate), when the area is experiencing a localized capacity emergency, as determined in accordance with the PJM Manuals.

Capacity Emergency Transfer Limit (CETL):

Capacity Emergency Transfer Limit" or "CETL" shall mean the capability of the transmission system to support deliveries of electric energy to a given area experiencing a localized capacity emergency as determined in accordance with the PJM Manuals.

Capacity Import Limit:

For any Delivery Year up to and including the 2019/2020 Delivery Year, "Capacity Import Limit" shall mean, (a) for the PJM Region, (1) the maximum megawatt quantity of external Generation Capacity Resources that PJM determines for each Delivery Year, through appropriate modeling and the application of engineering judgment, the transmission system can receive, in aggregate at the interface of the PJM Region with all external balancing authority areas and deliver to load in the PJM Region under capacity emergency conditions without violating applicable reliability criteria on any bulk electric system facility of 100kV or greater, internal or external to the PJM Region, that has an electrically significant response to transfers on such interface, minus (2) the then-applicable Capacity Benefit Margin; and (b) for certain source zones identified in the PJM manuals as groupings of one or more balancing authority areas, (1) the maximum megawatt quantity of external Generation Capacity Resources that PJM determines the transmission system can receive at the interface of the PJM Region with each such source zone and deliver to load in the PJM Region under capacity emergency conditions without violating applicable reliability criteria on any bulk electric system facility of 100kV or greater, internal or external to the PJM Region, that has an electrically significant response to transfers on such interface, minus the then-applicable Capacity Benefit Margin times (2) the ratio of the maximum import quantity from each such source zone divided by the PJM total maximum import quantity. As more fully set forth in the PJM Manuals, PJM shall make such determination based on the latest peak load forecast for the studied period, the same computer simulation model of loads, generation and transmission topography employed in the determination of Capacity Emergency Transfer Limit for such Delivery Year, including external facilities from an industry standard model of the loads, generation, and transmission topography of the Eastern Interconnection under peak conditions. PJM shall specify in the PJM Manuals the areas and minimum distribution factors for identifying monitored bulk electric system facilities that have an electrically significant response to such transfers on the PJM interface. Employing such tools, PJM shall model increased power transfers from external areas into PJM to determine the transfer level at which one or more reliability criteria is violated on any monitored bulk electric system facilities that have an electrically significant response to such transfers. For the PJM Region Capacity Import Limit, PJM shall optimize transfers from other source areas not experiencing any reliability criteria violations as appropriate to increase the Capacity Import Limit. The aggregate megawatt quantity of transfers into PJM at the point where any increase in transfers on the interface would violate reliability criteria will establish the Capacity Import Limit. Notwithstanding the foregoing, a Capacity Resource located outside the PJM Region shall not be subject to the Capacity Import Limit if the Capacity Market Seller seeks an exception thereto by demonstrating to PJM, by no later than five (5) business days prior to the commencement of the offer period for the relevant RPM Auction, that such resource meets all of the following requirements:

(i) it has, at the time such exception is requested, met all applicable requirements to be pseudo-tied into the PJM Region, or the Capacity Market Seller has committed in writing that it will meet such requirements, unless prevented from doing so by circumstances beyond the control of the Capacity Market Seller, prior to the relevant Delivery Year;

(ii) at the time such exception is requested, it has long-term firm transmission service confirmed on the complete transmission path from such resource into PJM; and

(iii) it is, by written commitment of the Capacity Market Seller, subject to the same obligations imposed on Generation Capacity Resources located in the PJM Region by Tariff, Attachment DD, section 6.6 to offer their capacity into RPM Auctions; provided, however, that (a) the total megawatt quantity of all exceptions granted hereunder for a Delivery Year, plus the Capacity Import Limit for the applicable interface determined for such Delivery Year, may not exceed the total megawatt quantity of Network External Designated Transmission Service on such interface that PJM has confirmed for such Delivery Year; and (b) if granting a qualified exception would result in a violation of the rule in clause (a), PJM shall grant the requested exception but reduce the Capacity Import Limit by the quantity necessary to ensure that the total quantity of Network External Designated Transmission Service is not exceeded.

Capacity Only Option:

"Capacity Only Option" shall mean participation in Emergency Load Response Program or Pre-Emergency Program which allows, pursuant to Tariff, Attachment DD and as applicable, a capacity payment for the ability to reduce load during a pre-emergency or emergency event.

Capacity Performance Resource:

"Capacity Performance Resource" shall have the same meaning as in Tariff, Attachment DD.

Capacity Resources:

"Capacity Resources" shall mean megawatts of (i) net capacity from Existing Generation Capacity Resources or Planned Generation Capacity Resources meeting the requirements of the Reliability Assurance Agreement, Schedules 9 and Reliability Assurance Agreement, Schedule 10 that are or will be owned by or contracted to a Party and that are or will be committed to satisfy that Party's obligations under the Reliability Assurance Agreement, or to satisfy the reliability requirements of the PJM Region, for a Delivery Year; (ii) net capacity from Existing Generation Capacity Resources or Planned Generation Capacity Resources not owned or contracted for by a Party which are accredited to the PJM Region pursuant to the procedures set forth in such Schedules 9 and 10; or (iii) load reduction capability provided by Demand Resources or Energy Efficiency Resources that are accredited to the PJM Region pursuant to the procedures set forth in the Reliability Assurance Agreement, Schedule 6.

Capacity Storage Resource Class:

"Capacity Storage Resource Class" shall mean the ELCC Classes specified in Schedules 9.1 and 9.2, section B of this Agreement, each of which is composed of Capacity Storage Resources with the same specified characteristic duration of 4, 6, 8, and 10 hours. The characteristic duration of an Energy Storage Resource Class is the ratio of the modeled MWh energy storage capability of members of the class to the modeled MW power capability of members of the class.

Capacity Transfer Right:

"Capacity Transfer Right" shall have the meaning specified in Tariff, Attachment DD.

Coal Class:

"Coal Class" shall mean an ELCC Class consisting of Unlimited Resources primarily fueled by coal.

Combination Resource:

"Combination Resource" shall mean a Generation Capacity Resource that has a component that has the characteristics of a Limited Duration Resource combined with (i) a component that has

the characteristics of an Unlimited Resource or (ii) a component that has the characteristics of a Variable Resource.

Compliance Aggregation Area (CAA):

"Compliance Aggregation Area" or "CAA" shall have the same meaning as in the Tariff.

Complex Hybrid Class:

"Complex Hybrid Class" shall mean an ELCC Class composed of Combination Resources that combine three or more components, whereby one component is a class of Limited Duration Resource, and the other components are different Variable Resource classes, and such Combination Resources cannot be included in any other Combination Resource class. A resource that is a member of a Complex Hybrid Class has a single Point Of Interconnection, unless the resource is controlled in an integrated fashion, is at a single site, and is approved by PJM to be considered a single resource in accordance with the PJM Manuals.

Consolidated Transmission Owners Agreement, PJM Transmission Owners Agreement or Transmission Owners Agreement:

"Consolidated Transmission Owners Agreement," "PJM Transmission Owners Agreement" or "Transmission Owners Agreement" shall mean that certain Consolidated Transmission Owners Agreement, dated as of December 15, 2005, by and among the Transmission Owners and by and between the Transmission Owners and PJM Interconnection, L.L.C. on file with the Commission, as amended from time to time.

Control Area:

"Control Area" shall mean an electric power system or combination of electric power systems bounded by interconnection metering and telemetry to which a common generation control scheme is applied in order to:

(a) match the power output of the generators within the electric power system(s) and energy purchased from entities outside the electric power system(s), with the load within the electric power system(s);

(b) maintain scheduled interchange with other Control Areas, within the limits of Good Utility Practice;

(c) maintain the frequency of the electric power system(s) within reasonable limits in accordance with Good Utility Practice and the criteria of NERC and each Applicable Regional Entity;

(d) maintain power flows on transmission facilities within appropriate limits to preserve reliability; and

(e) provide sufficient generating capacity to maintain operating reserves in accordance with Good Utility Practice.

Daily Unforced Capacity Obligation:

"Daily Unforced Capacity Obligation" shall mean the capacity obligation of a Load Serving Entity during the Delivery Year, determined in accordance with the Reliability Assurance Agreement, Schedule 8 or, as to an FRR Entity, in the Reliability Assurance Agreement, Schedule 8.1.

Delivery Year:

"Delivery Year" shall mean a Planning Period for which a Capacity Resource is committed pursuant to the auction procedures specified in Tariff, Attachment DD or pursuant to an FRR Capacity Plan under RAA, Schedule 8.1.

Demand Resource (DR):

"Demand Resource" or "DR" shall mean a Limited Demand Resource, Extended Summer Demand Resource, Annual Demand Resource, Base Capacity Demand Resource or Summer-Period Demand Resource with a demonstrated capability to provide a reduction in demand or otherwise control load in accordance with the requirements of RAA, Schedule 6 that offers and that clears load reduction capability in a Base Residual Auction or Incremental Auction or that is committed through an FRR Capacity Plan.

Demand Resource Factor or DR Factor:

"Demand Resource Factor" or "DR Factor" shall mean, for Delivery Years through May 31, 2018, that factor approved from time to time by the PJM Board used to determine the unforced capacity value of a Demand Resource in accordance with Reliability Assurance Agreement, Schedule 6

Demand Resource Officer Certification Form:

"Demand Resource Officer Certification Form" shall mean a certification as to an intended Demand Resource Sell Offer, in accordance with Reliability Assurance Agreement, Schedule 6 and Reliability Assurance Agreement, Schedule 8.1 and the PJM Manuals.

Demand Resource Registration:

"Demand Resource Registration" shall mean a registration in the Full Program Option or Capacity Only Option of the Emergency or Pre-Emergency Load Resource Program in accordance with Tariff, Attachment K-Appendix, section 8.

Demand Resource Sell Offer Plan:

"Demand Resource Sell Offer Plan" shall mean the plan required by Reliability Assurance Agreement, Schedule 6 and Reliability Assurance Agreement, Schedule 8.1 in support of an intended offer of Demand Resources in an RPM Auction, or an intended inclusion of Demand Resources in an FRR Capacity Plan.

Diesel Utility Class:

"Diesel Utility Class" shall mean an ELCC Class consisting of Unlimited Resources of the diesel technology type that is not primarily fueled by landfill gas.

Effective Nameplate Capacity:

"Effective Nameplate Capacity" shall mean (i) for each Variable Resource and Combination Resource, the resource's Maximum Facility Output (or, for a Co-Located Resource, the applicable share of the Mixed Technology Facility's Maximum Facility Output); (ii) for each Limited Duration Resource, the sustained level of output that the unit can provide and maintain over a continuous period, whereby the duration of that continuous period matches the characteristic duration of the corresponding ELCC Class, with consideration given to ambient conditions expected to exist at the time of PJM system peak load, to the extent that such conditions impact such resource's capability, not to exceed the Maximum Facility Output (or, for a Co-Located Resource, the applicable share of the Mixed Technology Facility's Maximum Facility Output). For the 2025/2026 Delivery Year and subsequent Delivery Years, the Effective Nameplate Capacity of each Limited Duration Resource shall not exceed the greater of the Capacity Interconnection Rights of such Limited Duration Resource, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year.

Effective UCAP:

"Effective UCAP" shall mean a unit of measure that represents the capacity product transacted in the Reliability Pricing Model and included in FRR Capacity Plans. One megawatt of Effective UCAP has the same capacity value of one megawatt of Unforced Capacity.

ELCC Class:

"ELCC Class" shall mean a defined group of ELCC Resources that share a common set of operational characteristics and for which effective load carrying capability analysis, as set forth in RAA, Schedules 9.1 and 9.2, will establish a unique ELCC Class UCAP and corresponding ELCC Class Rating(s). ELCC Classes shall be defined in the Schedules 9.1 and 9.2, section B of this Agreement. Members of an ELCC Class shall share a common method of calculating the ELCC Resource Performance Adjustment, provided that the individual ELCC Resource Performance Adjustment values will generally differ among ELCC Resources.

ELCC Class Rating:

"ELCC Class Rating" shall mean the rating factor, based on effective load carrying capability analysis, that applies to ELCC Resources that are members of an ELCC Class as part of the calculation of their Accredited UCAP.

ELCC Class UCAP:

"ELCC Class UCAP" shall mean the aggregate Effective UCAP all modeled ELCC Resources in a given ELCC Class are capable of providing in a given Delivery Year.

ELCC Portfolio UCAP:

"ELCC Portfolio UCAP" shall mean the aggregate Effective UCAP that all modeled ELCC Resources are capable of providing in a given Delivery Year.

ELCC Resource:

"ELCC Resource" shall mean, through the 2024/2025 Delivery Year, a Generation Capacity Resource that is a Variable Resource, a Limited Duration Resource, or a Combination Resource, and beginning with the 2025/2026 Delivery Year, a Generation Capacity Resource or a Demand Resource.

ELCC Resource Performance Adjustment:

"ELCC Resource Performance Adjustment" shall mean the performance of a specific ELCC Resource relative to the aggregate performance of the ELCC Class to which it belongs as further described in RAA, Schedule 9.1, section F and RAA, Schedule 9.2, section D.

Electric Cooperative:

"Electric Cooperative" shall mean an entity owned in cooperative form by its customers that is engaged in the generation, transmission, and/or distribution of electric energy.

Electric Distributor:

"Electric Distributor" shall mean a Member that 1) owns or leases with rights equivalent to ownership of electric distribution facilities that are used to provide electric distribution service to electric load within the PJM Region; or 2) is a generation and transmission cooperative or a joint municipal agency that has a member that owns electric distribution facilities used to provide electric distribution service to electric load within the PJM Region.

Emergency:

"Emergency" shall mean (i) an abnormal system condition requiring manual or automatic action to maintain system frequency, or to prevent loss of firm load, equipment damage, or tripping of system elements that could adversely affect the reliability of an electric system or the safety of persons or property; or (ii) a fuel shortage requiring departure from normal operating procedures in order to minimize the use of such scarce fuel; or (iii) a condition that requires implementation of emergency procedures as defined in the PJM Manuals.

End-Use Customer:

"End-Use Customer" shall mean a Member that is a retail end-user of electricity within the PJM Region. For purposes of Members Committee sector classification, a Member that is a retail end-user that owns generation may qualify as an End-Use customer if: (1) the average physical unforced capacity owned by the Member and its affiliates in the PJM region over the five Planning Periods immediately preceding the relevant Planning Period does not exceed the average PJM capacity obligation for the Member and its affiliates over the same time period; or (2) the average energy produced by the Member and its affiliates within the PJM region over the five Planning Periods immediately preceding the relevant Planning Period does not exceed the average energy consumed by that Member and its affiliates within the PJM region over the same time period. The foregoing notwithstanding, taking retail service may not be sufficient to qualify a Member as an End-Use Customer.

Energy Efficiency Resource:

"Energy Efficiency Resource" shall mean a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, meeting the requirements of RAA, Schedule 6 and exceeding then-current building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during the periods described in Reliability Assurance Agreement, Schedule 6 and the PJM Manuals) reduction in electric energy consumption that is not reflected in the peak load forecast prepared for the Delivery Year for which the Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention. Annual Energy Efficiency Resources, Base Capacity Energy Efficiency Resources and Summer-Period Energy Efficiency Resources are types of Energy Efficiency Resources.

Exigent Water Storage:

"Exigent Water Storage" shall mean water stored in the pondage or reservoir of a hydropower resource which is not typically available during normal operating conditions (as those conditions are described in the relevant FERC hydropower license), but which can be drawn upon during emergency conditions (as described in the FERC hydropower license), including in order to avoid a load shed. In an effective load carrying capability analysis, exigent storage capability from an upstream hydro facility can be considered relative to a downstream hydro facility by assessing cascading storage and flows.

Existing Demand Resource:

"Existing Demand Resource" shall mean a Demand Resource for which the Demand Resource Provider has identified existing end-use customer sites that are registered for the current Delivery Year with PJM (even if not registered by such Demand Resource Provider) and that the Demand Resource Provider reasonably expects to have under a contract to reduce load based on PJM dispatch instructions by the start of the Delivery Year for which such resource is offered.

Existing Generation Capacity Resource:

"Existing Generation Capacity Resource" shall mean, for purposes of the must-offer requirement and mitigation of offers for any RPM Auction for a Delivery Year, a Generation Capacity Resource that, as of the date on which bidding commences for such auction: (a) is in service; or (b) is not yet in service, but has cleared any RPM Auction for any prior Delivery Year. A Generation Capacity Resource shall be deemed to be in service if interconnection service has ever commenced (for resources located in the PJM Region), or if it is physically and electrically interconnected to an external Control Area and is in full commercial operation (for resources not located in the PJM Region). The additional megawatts of a Generation Capacity Resource that is being, or has been, modified to increase the number of megawatts of available installed capacity thereof shall not be deemed to be an Existing Generation Capacity Resource until such time as those megawatts (a) are in service; or (b) are not yet in service, but have cleared any RPM Auction for any prior Delivery Year.

Extended Summer Demand Resource:

"Extended Summer Demand Resource" shall mean, for Delivery Years through May 31, 2018, and for FRR Capacity Plans Delivery Years through May 31, 2019, a resource that is placed under the direction of the Office of the Interconnection and that will be available June through October and the following May, and will be available for an unlimited number of interruptions during such months by the Office of the Interconnection, and will be capable of maintaining each such interruption for at least a 10-hour duration between the hours of 10:00AM to 10:00PM Eastern Prevailing Time. The Extended Summer Demand Resource must be available June through October and the following May in the corresponding Delivery Year to be offered for sale or Self-Supplied in an RPM Auction, or included as an Extended Summer Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Facilities Study Agreement:

"Facilities Study Agreement" shall have the same meaning as in Tariff, Part VI, section 206.

FERC or Commission:

"FERC" or "Commission" shall mean the Federal Energy Regulatory Commission or any successor federal agency, commission or department exercising jurisdiction over the Tariff, Operating Agreement and Reliability Assurance Agreement.

Firm Point-To-Point Transmission Service:

"Firm Point-To-Point Transmission Service" shall have the meaning specified in the Tariff.

Firm Service Level:

"Firm Service Level" or "FSL" of Price Responsive Demand for the 2022/2023 Delivery Year and subsequent Delivery Years shall mean the level, determined at a PRD Substation level, to which Price Responsive Demand shall be reduced during the Delivery Year when an Emergency Action that triggers a Performance Assessment Interval is declared and the Locational Marginal Price exceeds the price associated with such Price Responsive Demand identified by the PRD Provider in its PRD Plan. "Firm Service Level" or "FSL" of Demand Resource shall mean the pre-determined level for which an end-use customer's load shall be reduced, upon notification from the Curtailment Service Provider's market operations center or its agent.

Firm Transmission Service:

"Firm Transmission Service" shall mean transmission service that is intended to be available at all times to the maximum extent practicable, subject to an Emergency, an unanticipated failure of a facility, or other event beyond the control of the owner or operator of the facility or the Office of the Interconnection.

Fixed Resource Requirement Alternative or FRR Alternative:

"Fixed Resource Requirement Alternative" or "FRR Alternative" shall mean an alternative method for a Party to satisfy its obligation to provide Unforced Capacity hereunder, as set forth in the Reliability Assurance Agreement, Schedule 8.1.

Fixed-Tilt Solar Class:

"Fixed-Tilt Solar Class" shall mean an ELCC Class consisting of Variable Resources that produce electrical energy with solar panels that are primarily mounted in a fixed orientation.

Forecast Pool Requirement:

"Forecast Pool Requirement" or "FPR" shall mean the amount equal to one plus the unforced reserve margin (stated as a decimal number) for the PJM Region required pursuant to this Reliability Assurance Agreement, as approved by the PJM Board pursuant to Reliability Assurance Agreement, Schedule 4.1.

FRR Capacity Plan or FRR Plan:

"FRR Capacity Plan" or "FRR Plan" shall mean a long-term plan for the commitment of Capacity Resources and Price Responsive Demand to satisfy the capacity obligations of a Party that has elected the FRR Alternative, as more fully set forth in the Reliability Assurance Agreement, Schedule 8.1.

FRR Entity:

"FRR Entity" shall mean, for the duration of such election, a Party that has elected the FRR Alternative hereunder.

FRR Service Area:

"FRR Service Area" shall mean (a) the service territory of an IOU as recognized by state law, rule or order; (b) the service area of a Public Power Entity or Electric Cooperative as recognized by franchise or other state law, rule, or order; or (c) a separately identifiable geographic area that is: (i) bounded by wholesale metering, or similar appropriate multi-site aggregate metering, that is visible to, and regularly reported to, the Office of the Interconnection, or that is visible to, and regularly reported to an Electric Distributor and such Electric Distributor agrees to aggregate the load data from such meters for such FRR Service Area and regularly report such aggregated information, by FRR Service Area, to the Office of the Interconnection; and (ii) for which the FRR Entity has or assumes the obligation to provide capacity for all load (including load growth) within such area. In the event that the service obligations of an Electric Cooperative or Public Power Entity are not defined by geographic boundaries but by physical connections to a defined set of customers, the FRR Service Area in such circumstances shall be defined as all customers physically connected to transmission or distribution facilities of such Electric Cooperative or Public Power Entity within an area bounded by appropriate wholesale aggregate metering as described above.

Full Program Option:

"Full Program Option" shall mean participation in Emergency Load Response Program or Pre-Emergency Program which allows, pursuant to Tariff, Attachment DD and as applicable, (i) an energy payment for load reductions during a pre-emergency or emergency event, and (ii) a capacity payment for the ability to reduce load during a pre-emergency or emergency event.

Full Requirements Service:

"Full Requirements Service" shall mean wholesale service to supply all of the power needs of a Load Serving Entity to serve end-users within the PJM Region that are not satisfied by its own generating facilities.

Gas Combined Cycle Class:

"Gas Combined Cycle Class" shall mean an ELCC Class consisting of Unlimited Resources of the combined cycle technology type that is primarily fueled by natural gas, but does not meet the requirements to be included in the Gas Combined Cycle Dual Fuel Class.

Gas Combined Cycle Dual Fuel Class:

"Gas Combined Cycle Dual Fuel Class" shall mean an ELCC Class consisting of Unlimited Resources of the combined cycle technology type that is primarily fueled by natural gas, and that attests that it has the capability to start independently using onsite sources and operate independently on alternate onsite fuel source(s) up to its maximum capacity level during the winter season of the applicable Delivery Year in which it is providing capacity, and capable of operating on the alternate fuel for two 16-hour periods over two consecutive days at its maximum capacity level.

Gas Combustion Turbine Class:

"Gas Combustion Turbine Class" shall mean an ELCC Class consisting of Unlimited Resources of the combustion turbine technology type that is primarily fueled by natural gas, but does not meet the requirements to be included in the Gas Combustion Turbine Dual Fuel Class.

Gas Combustion Turbine Dual Fuel Class:

"Gas Combustion Turbine Dual Fuel Class" shall mean an ELCC Class consisting of Unlimited Resources of the combustion turbine technology type that is primarily fueled by natural gas, and attests that it has the capability to start independently using onsite sources and operate independently on alternate onsite fuel source(s) up to its maximum capacity level during the winter season of the applicable Delivery Year in which it is providing capacity, and capable of operating on the alternate fuel for two 16-hour periods over two consecutive days at its maximum capacity level.

Generation Capacity Resource:

"Generation Capacity Resource" shall mean a Generating Facility, or the contractual right to capacity from a specified Generating Facility, that meets the requirements of RAA, Schedule 9 and RAA, Schedule 10, and, for Generating Facilities that are committed to an FRR Capacity Plan, that meets the requirements of RAA, Schedule 8.1. A Generation Capacity Resource may be an Existing Generation Capacity Resource or a Planned Generation Capacity Resource.

Generation Capacity Resource Provider:

"Generation Capacity Resource Provider" shall mean a Member that owns, or has the contractual authority to control the output of, a Generation Capacity Resource, that has not transferred such authority to another entity.

Generation Owner:

"Generation Owner" shall mean a Member that owns or leases with rights equivalent to ownership, or otherwise controls and operates one or more operating generation resources located in the PJM Region. The foregoing notwithstanding, for a planned generation resource to qualify a Member as a Generation Owner, such resource shall have cleared an RPM auction, and for Energy Resources, the resource shall have a FERC-jurisdictional interconnection agreement or wholesale market participation agreement within PJM. Purchasing all or a portion of the output of a generation resource shall not be sufficient to qualify a Member as a Generation Owner. For purposes of Members Committee sector classification, a Member that is primarily a retail end-user of electricity that owns generation may qualify as a Generation Owner if: (1) the generation resource is the subject of a FERC-jurisdictional interconnection agreement or wholesale market participation agreement within PJM; (2) the average physical unforced capacity owned by the Member and its affiliates over the five Planning Periods immediately preceding the relevant Planning Period exceeds the average PJM capacity obligation of the Member and its affiliates over the same time period; and (3) the average energy produced by the Member and its affiliates within PJM over the five Planning Periods immediately preceding the relevant Planning Period exceeds the average energy consumed by the Member and its affiliates within PJM over the five Planning Periods immediately preceding the relevant Planning Period exceeds the average energy consumed by the Member and its affiliates within PJM over the same time period.

Generator Forced Outage:

"Generator Forced Outage" shall mean an immediate reduction in output or capacity or removal from service, in whole or in part, of a generating unit by reason of an Emergency or threatened Emergency, unanticipated failure, or other cause beyond the control of the owner or operator of the facility, as specified in the relevant portions of the PJM Manuals. A reduction in output or removal from service of a generating unit in response to changes in market conditions shall not constitute a Generator Forced Outage.

Generator Maintenance Outage:

"Generator Maintenance Outage" shall mean the scheduled removal from service, in whole or in part, of a generating unit in order to perform repairs on specific components of the facility, if removal of the facility qualifies as a maintenance outage pursuant to the PJM Manuals.

Generator Planned Outage:

"Generator Planned Outage" shall mean the scheduled removal from service, in whole or in part, of a generating unit for inspection, maintenance or repair with the approval of the Office of the Interconnection in accordance with the PJM Manuals.

Good Utility Practice:

"Good Utility Practice" shall mean any of the practices, methods and acts engaged in or approved by a significant portion of the electric utility industry during the relevant time period, or any of the practices, methods and acts which, in the exercise of reasonable judgment in light of the facts known at the time the decision was made, could have been expected to accomplish the desired result at a reasonable cost consistent with good business practices, reliability, safety and expedition. Good Utility Practice is not intended to be limited to the optimum practice, method, or act to the exclusion of all others, but rather is intended to include acceptable practices, methods, or acts generally accepted in the region; including those practices required by Federal Power Act Section 215(a)(4).

Hybrid Resource Class:

"Hybrid Resource Class" shall mean the ELCC Classes specified in RAA Schedules 9.1 and 9.2 Section B. Each Hybrid Resource Class has a specified combination of two components, whereby, absent being part of a Combination Resource, the individual components would be in a Capacity Storage Resource Class, a Variable Resource Class or would be an Unlimited Resource. A resource that is a member of a Hybrid Resource Class has a single Point Of Interconnection, unless the resource is controlled in an integrated fashion, is at a single site, and is approved by PJM to be considered a single resource in accordance with the PJM Manuals.

Hydropower With Non-Pumped Storage:

"Hydropower With Non-Pumped Storage" shall mean a hydropower facility that can capture and store incoming stream flow, without use of pumps, in pondage or a reservoir, and the Generation Owner has the ability, within the constraints available in the applicable operating license, to exert material control over the quantity of stored water and output of the facility throughout an Operating Day.

Hydropower With Non-Pumped Storage Class:

"Hydropower With Non-Pumped Storage Class" shall mean an ELCC Class consisting of Combination Resources that are Hydropower With Non-Pumped Storage resources.

Incremental Auction:

"Incremental Auction" shall mean any of several auctions conducted for a Delivery Year after the Base Residual Auction for such Delivery Year and before the first day of such Delivery Year, including the First Incremental Auction, Second Incremental Auction, Third Incremental Auction, or Conditional Incremental Auction. Incremental Auctions (other than the Conditional Incremental Auction), shall be held for the purposes of:

- (i) allowing Market Sellers that committed Capacity Resources in the Base Residual Auction for a Delivery Year, which subsequently are determined to be unavailable to deliver the committed Unforced Capacity in such Delivery Year (due to resource retirement, resource cancellation or construction delay, resource derating, EFORd increase, Accredited UCAP Factor decrease, a decrease in the Nominated Demand Resource Value of a Planned Demand Resource, delay or cancellation of a Qualifying Transmission Upgrade, or similar occurrences) to submit Buy Bids for replacement Capacity Resources; and
- (ii) allowing the Office of the Interconnection to reduce or increase the amount of committed capacity secured in prior auctions for such Delivery Year if, as a result of changed circumstances or expectations since the prior auction(s), there is, respectively, a significant excess or significant deficit of committed capacity for such Delivery Year, for the PJM Region or for an LDA.

Intermittent Hydropower Class:

"Intermittent Hydropower Class" shall mean an ELCC Class consisting of Variable Resources that are run-of-river hydropower generators that must generally pass incoming water and

therefore cannot appreciably store water to later increase the output of the facility. Resources in the Intermittent Hydropower Class are not Hydropower with Non-Pumped Storage resources.

IOU:

"IOU" shall mean an investor-owned utility with substantial business interest in owning and/or operating electric facilities in any two or more of the following three asset categories: generation, transmission, distribution.

Intermittent Landfill Gas Class:

"Intermittent Landfill Gas Class" shall mean an ELCC Class consisting of Variable Resources fueled by landfill gas that, because of fuel availability patterns, cannot run consistently at installed capacity levels for 24 or more hours.

Large Load Adjustment:

"Large Load Adjustment" shall mean any MW quantity of adjustments to summer peak load at the "zone/area" level and summed by Zone as further detailed in PJM Manuals. For purposes of this definition, a "zone/area" is an area within a Zone for which the relevant Electric Distributor specifies a separate Obligation Peak Load MW value. A zone/area is a service area of an Electric Distributor that is a separately identifiable, geographic area bounded by wholesale metering (e.g., the service territory of an operating company of a Transmission Owner).

Limited Demand Resource:

"Limited Demand Resource" shall mean, for Delivery Years through May 31, 2018, and for FRR Capacity Plans Delivery Years through May 31, 2019, a resource that is placed under the direction of the Office of the Interconnection and that will, at a minimum, be available for interruption for at least 10 Load Management Events during the summer period of June through September in the Delivery Year, and will be capable of maintaining each such interruption for at least a 6-hour duration. At a minimum, the Limited Demand Resource shall be available for such interruptions on weekdays, other than NERC holidays, from 12:00PM (noon) to 8:00PM Eastern Prevailing Time. The Limited Demand Resource must be available during the summer period of June through September in the corresponding Delivery Year to be offered for sale or Self-Supplied in an RPM Auction, or included as a Limited Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Limited Duration Resource:

"Limited Duration Resource" shall mean a Generation Capacity Resource that is not a Variable Resource, that is not a Combination Resource, and that is not capable of running continuously at Maximum Facility Output for 24 hours or longer. A Capacity Storage Resource is a Limited Duration Resource.

Load Serving Entity or LSE:

"Load Serving Entity" or "LSE" shall mean any entity (or the duly designated agent of such an entity), including a load aggregator or power marketer, (i) serving end-users within the PJM Region, and (ii) that has been granted the authority or has an obligation pursuant to state or local law, regulation or franchise to sell electric energy to end-users located within the PJM Region. Load Serving Entity shall include any end-use customer that qualifies under state rules or a utility retail tariff to manage directly its own supply of electric power and energy and use of transmission and ancillary services.

Locational Reliability Charge:

"Locational Reliability Charge" shall mean the charge determined pursuant to RAA, Article 7, section 2.

Markets and Reliability Committee:

"Markets and Reliability Committee" shall mean the committee established pursuant to the Operating Agreement as a Standing Committee of the Members Committee.

Maximum Emergency Service Level:

"Maximum Emergency Service Level" or "MESL" of Price Responsive Demand for the 2017/2018 through the 2021/2022 Delivery Years shall mean the level, determined at a PRD Substation level, to which Price Responsive Demand shall be reduced during the Delivery Year when a Maximum Generation Emergency is declared and the Locational Marginal Price exceeds the price associated with such Price Responsive Demand identified by the PRD Provider in its PRD Plan.

Member:

"Member" shall have the meaning provided in the Operating Agreement.

Members Committee:

"Members Committee" shall mean the committee specified in Operating Agreement, section 8 composed of the representatives of all the Members.

NERC:

"NERC" shall mean the North American Electric Reliability Corporation or any successor thereto.

Network External Designated Transmission Service:

"Network External Designated Transmission Service" shall mean the quantity of network transmission service confirmed by PJM for use by a market participant to import power and

energy from an identified Generation Capacity Resource located outside the PJM Region, upon demonstration by such market participant that it owns such Generation Capacity Resource, has an executed contract to purchase power and energy from such Generation Capacity Resource, or has a contract to purchase power and energy from such Generation Capacity Resource contingent upon securing firm transmission service from such resource.

Network Resources:

"Network Resources" shall have the meaning set forth in the PJM Tariff.

Network Transmission Service:

"Network Transmission Service" shall mean transmission service provided pursuant to the rates, terms and conditions set forth in Tariff, Part III or transmission service comparable to such service that is provided to a Load Serving Entity that is also a Transmission Owner.

Nominal PRD Value:

"Nominal PRD Value" shall mean, as to any PRD Provider, an adjustment, determined in accordance with Reliability Assurance Agreement, Schedule 6.1, to the peak-load forecast used to determine the quantity of capacity sought through an RPM Auction, reflecting the aggregate effect of Price Responsive Demand on peak load resulting from the Price Responsive Demand to be provided by such PRD Provider.

Nominated Demand Resource Value:

"Nominated Demand Resource Value" shall have the meaning specified in Tariff, Attachment DD.

Non-Retail Behind the Meter Generation:

"Non-Retail Behind the Meter Generation" shall mean Behind the Meter Generation that is used by municipal electric systems, electric cooperatives, and electric distribution companies to serve load.

Nuclear Class:

"Nuclear Class" shall mean an ELCC Class consisting of Unlimited Resources primarily fueled by nuclear fuel.

Obligation Peak Load:

"Obligation Peak Load" shall have the meaning specified in Reliability Assurance Agreement, Schedule 8.

Office of the Interconnection:

"Office of the Interconnection" shall mean the employees and agents of PJM Interconnection, L.L.C., subject to the supervision and oversight of the PJM Board, acting pursuant to the Operating Agreement.

Offshore Wind Class:

"Offshore Wind Class" shall mean an ELCC Class consisting of Variable Resources that produce electrical energy with offshore wind turbines located in the ocean.

Oil Fired Combustion Turbine Class:

"Oil Fired Combustion Turbine Class" shall mean an ELCC Class consisting of Unlimited Resources of the combustion turbine technology type that are primarily fueled by oil.

Onshore Wind Class:

"Onshore Wind Class" shall mean an ELCC Class consisting of Variable Resources that produce electrical energy using wind turbines and that are not in the Offshore Wind Class.

Operating Agreement of the PJM Interconnection, L.L.C., Operating Agreement or PJM Operating Agreement:

"Operating Agreement of the PJM Interconnection, L.L.C.," "Operating Agreement" or "PJM Operating Agreement" shall mean that agreement, dated as of April 1, 1997 and as amended and restated as of June 2, 1997, including all Schedules, Exhibits, Appendices, addenda or supplements hereto, as amended from time to time thereafter, among the Members of the PJM Interconnection, L.L.C, on file with the Commission.

Operating Day:

"Operating Day" shall have the same meaning as provided in the Operating Agreement.

Operating Reserve:

"Operating Reserve" shall mean the amount of generating capacity scheduled to be available for a specified period of an Operating Day to ensure the reliable operation of the PJM Region, as specified in the PJM Manuals.

Ordinary Water Storage:

"Ordinary Water Storage" shall mean water stored in the pondage or reservoir of a hydropower resource which is typically available during normal operating conditions pursuant to the FERC license governing the operation of the hydropower resource.

Other Limited Duration Class:

"Other Limited Duration Class" shall mean the ELCC Classes specified in RAA Schedules 9.1 and 9.2 section B of this Agreement, each of which has a specified characteristic duration and consists of Limited Duration Resources that are not Capacity Storage Resources. The characteristic duration of an Other Limited Duration Class is the maximum period of time represented in the ELCC model that the resources of the class can run at a stated capability.

Other Limited Duration Combination Class:

"Other Limited Duration Combination Class" shall mean the ELCC Classes specified in RAA Schedules 9.1 and 9.2 section B. Each Other Limited Duration Class has a specified combination of two components, whereby, absent being part of a Combination Resource, one component would be in an Other Limited Duration Class, and the other component would be in a Variable Resource Class or would be an Unlimited Resource. A resource that is a member of an Other Limited Duration Class has a single Point Of Interconnection, unless the resource is controlled in an integrated fashion, is at a single site, and is approved by PJM to be considered a single resource in accordance with the PJM Manuals.

Other Steam Class:

"Other Steam Class" shall mean an ELCC Class consisting of Unlimited Resources of the steam technology type and do not qualify for the Coal Class, Nuclear Class, or Waste to Energy Steam Class (beginning with the 2027/2028 Delivery Year).

Other Supplier:

"Other Supplier" shall mean a Member that: (i) is engaged in buying, selling or transmitting electric energy, capacity, ancillary services, Financial Transmission Rights or other services available under PJM's governing documents in or through the Interconnection or has a good faith intent to do so, and (ii) is not a Generation Owner, Electric Distributor, Transmission Owner or End-Use Customer.

Other Unlimited Resource Class:

"Other Unlimited Resource Class" shall mean an ELCC Class consisting of Unlimited Resources that do not qualify for any other ELCC Class specified in RAA Schedule 9.2, section D.

Other Variable Resource Class:

"Other Variable Resource Class" shall mean an ELCC Class consisting of Variable Resources that are not in any other Variable Resource class, including Variable Resources that are composed of multiple components, each of which would be a Variable Resource. A resource composed of both fixed-tilt solar panels and tracking solar panels is not in this class. A resource that is a member of a Other Variable Resource Class has a single Point Of Interconnection, unless the resource is controlled in an integrated fashion, is at a single site, and is approved by PJM to be considered a single resource in accordance with the PJM Manuals.
Partial Requirements Service:

"Partial Requirements Service" shall mean wholesale service to supply a specified portion, but not all, of the power needs of a Load Serving Entity to serve end-users within the PJM Region that are not satisfied by its own generating facilities.

Party:

"Party" shall mean an entity bound by the terms of the Operating Agreement.

Peak Shaving Adjustment:

"Peak Shaving Adjustment" shall mean a load forecast mechanism that allows load reductions by end-use customers to result in a downward adjustment of the summer load forecast for the associated Zone. Any End-Use Customer identified in an approved peak shaving plan shall not also participate in PJM Markets as Price Responsive Demand, Demand Resource, Base Capacity Demand Resource, Capacity Performance Demand Resource, or Economic Load Response Participant.

Percentage Internal Resources Required:

"Percentage Internal Resources Required" shall mean, for purposes of an FRR Capacity Plan, the percentage of the LDA Reliability Requirement for an LDA that must be satisfied with Capacity Resources located in such LDA.

Performance Assessment Interval:

"Performance Assessment Interval" shall have the meaning specified in Tariff, Attachment DD.

PJM:

"PJM" shall mean PJM Interconnection, L.L.C., including the Office of the Interconnection as referenced in the PJM Operating Agreement. When such term is being used in the RAA it shall also include the PJM Board.

PJM Board:

"PJM Board" shall mean the Board of Managers of the LLC, acting pursuant to the Operating Agreement, except when such term is being used in Tariff, Attachment M, in which case PJM Board shall mean the Board of Managers of PJM or its designated representative, exclusive of any members of PJM Management.

PJM Manuals:

"PJM Manuals" shall mean the instructions, rules, procedures and guidelines established by the Office of the Interconnection for the operation, planning and accounting requirements of the PJM Region.

PJM Region:

"PJM Region" shall have the same meaning as provided in the Operating Agreement.

PJM Region Installed Reserve Margin:

"PJM Region Installed Reserve Margin" shall mean the percent installed reserve margin for the PJM Region required pursuant to Reliability Assurance Agreement, Schedule 4.1, as approved by the PJM Board.

PJM Tariff, Tariff, O.A.T.T., OATT or PJM Open Access Transmission Tariff:

"PJM Tariff," "Tariff," "O.A.T.T., "OATT" or "PJM Open Access Transmission Tariff" shall mean that certain PJM Open Access Transmission Tariff, including any schedules, appendices, or exhibits attached thereto, on file with FERC and as amended from time to time thereafter.

Planned Demand Resource:

"Planned Demand Resource" shall mean any Demand Resource that does not currently have the capability to provide a reduction in demand or to otherwise control load, but that is scheduled to be capable of providing such reduction or control on or before the start of the Delivery Year for which such resource is to be committed, as determined in accordance with the requirements of Reliability Assurance Agreement, Schedule 6. As set forth in Reliability Assurance Agreement, Schedule 6 and Reliability Assurance Agreement, Schedule 8.1, a Demand Resource Provider submitting a DR Sell Offer Plan shall identify as Planned Demand Resources in such plan all Demand Resources in excess of those that qualify as Existing Demand Resources.

Planned External Generation Capacity Resource:

"Planned External Generation Capacity Resource" shall mean a proposed Generation Capacity Resource, or a proposed increase in the capability of a Generation Capacity Resource, that (a) is to be located outside the PJM Region, (b) participates in the generation interconnection process of a Control Area external to PJM, (c) is scheduled to be physically and electrically interconnected to the transmission facilities of such Control Area on or before the first day of the Delivery Year for which such resource is to be committed to satisfy the reliability requirements of the PJM Region, and (d) is in full commercial operation prior to the first day of such Delivery Year, such that it is sufficient to provide the Installed Capacity set forth in the Sell Offer forming the basis of such resource's commitment to the PJM Region. Prior to participation in any Base Residual Auction for such Delivery Year, the Capacity Market Seller must demonstrate that it has a fully executed system impact study agreement (or other documentation which is functionally equivalent to a System Impact Study Agreement under the PJM Tariff) or, for resources which are greater than 20MWs participating in a Base Residual Auction for the 2019/2020 Delivery Year and subsequent Delivery Years, an agreement or other documentation which is functionally equivalent to a Facilities Study Agreement under the PJM Tariff), with the transmission owner to whose transmission facilities or distribution facilities the resource is being directly connected, and, as applicable, the transmission provider. Prior to participating in any Incremental Auction for such Delivery Year, the Capacity Market Seller must demonstrate it has entered into an interconnection agreement, or such other documentation that is functionally equivalent to an Interconnection Service Agreement under the PJM Tariff, with the transmission owner to whose transmission facilities or distribution facilities the resource is being directly connected, and, as applicable, the transmission provider. A Planned External Generation Capacity Resource must provide evidence to PJM that it has been studied as a Network Resource, or such other similar interconnection product in such external Control Area, must provide contractual evidence that it has applied for or purchased transmission service to be deliverable to the PJM border, and must provide contractual evidence that it has applied for transmission service to be deliverable to the bus at which energy is to delivered, the agreements for which must have been executed prior to participation in any Reliability Pricing Model Auction for such Delivery Year. Any such resource shall cease to be considered a Planned External Generation Capacity Resource as of the earlier of (i) the date that interconnection service commences as to such resource; or (ii) the resource has cleared an RPM Auction, in which case it shall become an Existing Generation Capacity Resource for purposes of the mitigation of offers for any RPM Auction for all subsequent Delivery Years.

Planned Generation Capacity Resource:

"Planned Generation Capacity Resource" shall mean a Generation Capacity Resource, or additional megawatts to increase the size of a Generation Capacity Resource that is being or has been modified to increase the number of megawatts of available installed capacity thereof, participating in the generation interconnection process under Tariff, Part IV, Subpart A, as applicable, for which: (i) Interconnection Service is scheduled to commence on or before the first day of the Delivery Year for which such resource is to be committed to RPM or to an FRR Capacity Plan; (ii) for any such resource seeking to offer into a Base Residual Auction, or for any such resource of 20 MWs or less seeking to offer into a Base Residual Auction, a System Impact Study Agreement (or, for resources for which a System Impact Study Agreement is not required, has such other agreement or documentation that is functionally equivalent to a System Impact Study Agreement) has been executed prior to the Base Residual Auction for such Delivery Year; (iii) for any such resource of more than 20 MWs seeking to offer into a Base Residual Auction for the 2019/2020 Delivery Year and subsequent Delivery Years, a Facilities Study Agreement (or, for resources for which a Facilities Study Agreement is not required, has such other agreement or documentation that is functionally equivalent to a Facility Studies Agreement) has been executed prior to the Base Residual Auction for such Delivery Year; and (iv) an Interconnection Service Agreement has been executed prior to any Incremental Auction for such Delivery Year in which such resource plans to participate. For purposes of the mustoffer requirement and mitigation of offers for any RPM Auction for a Delivery Year, a Generation Capacity Resource shall cease to be considered a Planned Generation Capacity Resource as of the earlier of (i) the date that Interconnection Service commences as to such resource; or (ii) the resource has cleared an RPM Auction for any Delivery Year, in which case it

shall become an Existing Generation Capacity Resource for any RPM Auction for all subsequent Delivery Years.

Planning Period:

"Planning Period" shall mean the 12 months beginning June 1 and extending through May 31 of the following year, or such other period approved by the Members Committee.

Portfolio Expected Unserved Energy:

"Portfolio Expected Unserved Energy" shall mean the annual amount of expected unserved energy, in MWh, that is expected for the RTO when at the annual reliability criteria that provides an acceptable level of reliability consistent with the Reliability Principles and Standards.

PRD Curve:

"PRD Curve" shall mean a price-consumption curve at a PRD Substation level, if available, and otherwise at a Zonal (or sub-Zonal LDA, if applicable) level, that details the base consumption level of Price Responsive Demand and the decreasing consumption levels at increasing prices.

PRD Provider:

"PRD Provider" shall mean a PJM Member that has entered contractual arrangements with enduse customers that satisfy the eligibility criteria for and provides Price Responsive Demand.

PRD Provider's Zonal Expected Peak Load Value of PRD:

"PRD Provider's Zonal Expected Peak Load Value of PRD" shall mean the expected contribution to Delivery Year peak load of a PRD Provider's Price Responsive Demand, were such demand not to be reduced in response to price, based on the contribution of the end-use customers comprising such Price Responsive Demand to the most recent prior Delivery Year's peak demand, escalated to the Delivery Year in question, as determined in a manner consistent with the Office of the Interconnection's load forecasts used for purposes of the RPM Auctions.

PRD Reservation Price:

"PRD Reservation Price" shall mean an RPM Auction clearing price identified in a PRD Plan for Price Responsive Demand load below which the PRD Provider desires not to commit the identified load as Price Responsive Demand.

PRD Substation:

"PRD Substation" shall mean an electrical substation that is located in the same Zone or in the same sub-Zonal LDA as the end-use customers identified in a PRD Plan or PRD registration and that, in terms of the electrical topography of the Transmission Facilities comprising the PJM Region, is as close as practicable to such loads.

Price Responsive Demand:

"Price Responsive Demand" or "PRD" shall mean end-use customer load registered by a PRD Provider pursuant to Reliability Assurance Agreement, Schedule 6.1 that have, as set forth in more detail in the PJM Manuals, the metering capability to record electricity consumption at an interval of one hour or less, Supervisory Control capable of curtailing such load (consistent with applicable RERRA requirements) at each PRD Substation identified in the relevant PRD Plan or PRD registration in response to a Maximum Generation Emergency declared by the Office of the Interconnection (prior to 2022/2023Delivery Year) or a Performance Assessment Interval that triggers a PRD performance assessment (effective with 2022/2023 Delivery Year), and a retail rate structure, or equivalent contractual arrangement, capable of changing retail rates as frequently as an hourly basis, that is linked to or based upon changes in real-time Locational Marginal Prices at a PRD Substation level and that results in a predictable automated response to varying wholesale electricity prices.

Price Responsive Demand Credit:

"Price Responsive Demand Credit" shall mean a credit, based on committed Price Responsive Demand, as determined under Reliability Assurance Agreement, Schedule 6.1.

Price Responsive Demand Plan or PRD Plan:

"Price Responsive Demand Plan" or "PRD Plan" shall mean a plan, submitted by a PRD Provider and received by the Office of the Interconnection in accordance with Reliability Assurance Agreement, Schedule 6.1 and procedures specified in the PJM Manuals, claiming a peak demand limitation due to Price Responsive Demand to support the determination of such PRD Provider's Nominal PRD Value.

Public Power Entity:

"Public Power Entity" shall mean any agency, authority, or instrumentality of a state or of a political subdivision of a state, or any corporation wholly owned by any one or more of the foregoing, that is engaged in the generation, transmission, and/or distribution of electric energy.

Qualifying Transmission Upgrades:

"Qualifying Transmission Upgrades" shall have the meaning specified in Tariff, Attachment DD.

Relevant Electric Retail Regulatory Authority:

"Relevant Electric Retail Regulatory Authority" or "RERRA" shall have the meaning specified in the PJM Operating Agreement.

Reliability Principles and Standards:

"Reliability Principles and Standards" shall mean the principles and standards established by the Office of the Interconnection that define, among other things, an acceptable probabilistic of loss of load criteria due to inadequate generation or transmission capability, as amended from time to time.

Required Approvals:

"Required Approvals" shall mean all of the approvals required for the Operating Agreement to be modified or to be terminated, in whole or in part, including the acceptance for filing by FERC and every other regulatory authority with jurisdiction over all or any part of the Operating Agreement.

Self-Supply:

"Self-Supply" shall have the meaning provided in Tariff, Attachment DD.

Small Commercial Customer:

"Small Commercial Customer" shall have the same meaning as in the PJM Tariff.

State Consumer Advocate:

"State Consumer Advocate" shall mean a legislatively created office from any State, all or any part of the territory of which is within the PJM Region, and the District of Columbia established, inter alia, for the purpose of representing the interests of energy consumers before the utility regulatory commissions of such states and the District of Columbia and the FERC.

State Regulatory Structural Change:

"State Regulatory Structural Change" shall mean as to any Party, a state law, rule, or order that, after September 30, 2006, initiates a program that allows retail electric consumers served by such Party to choose from among alternative suppliers on a competitive basis, terminates such a program, expands such a program to include classes of customers or localities served by such Party that were not previously permitted to participate in such a program, or that modifies retail electric market structure or market design rules in a manner that materially increases the likelihood that a substantial proportion of the customers of such Party that are eligible for retail choice under such a program (a) that have not exercised such choice will exercise such choice; or (b) that have exercised such choice will no longer exercise such choice, including for example, without limitation, mandating divestiture of utility-owned generation or structural changes to such Party's default service rules that materially affect whether retail choice is economically viable.

Summer-Period Demand Resource:

Summer-Period Demand Resource shall mean, for the 2020/2021 Delivery Year and subsequent Delivery Years, a resource that is placed under the direction of the Office of the Interconnection,

and will be available June through October and the following May of the Delivery Year, and will be available for an unlimited number of interruptions during such months by the Office of the Interconnection, and will be capable of maintaining each such interruption between the hours of 10:00AM to 10:00PM Eastern Prevailing Time. The Summer-Period Demand Resource must be available June through October and the following May in the corresponding Delivery Year to be offered for sale in an RPM Auction, or included as a Summer-Period Demand Resource in an FRR Capacity Plan for the corresponding Delivery Year.

Summer-Period Energy Efficiency Resource:

Summer-Period Energy Efficiency Resource shall mean, for the 2020/2021 Delivery Year and subsequent Delivery Years, a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, meeting the requirements of Reliability Assurance Agreement, Schedule 6 and exceeding then-current building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during the summer peak periods as described in Reliability Assurance Agreement, Schedule 6 and the PJM Manuals) reduction in electric energy consumption that is not reflected in the peak load forecast prepared for the Delivery Year for which the Summer-Period Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention.

Supervisory Control:

"Supervisory Control" shall mean the capability to curtail, in accordance with applicable RERRA requirements, load registered as Price Responsive Demand at each PRD Substation identified in the relevant PRD Plan or PRD registration in response to a Maximum Generation Emergency declared by the Office of the Interconnection. Except to the extent automation is not required by the provisions of the Operating Agreement, the curtailment shall be automated, meaning that load shall be reduced automatically in response to control signals sent by the PRD Provider or its designated agent directly to the control equipment where the load is located without the requirement for any action by the end-use customer.

Threshold Quantity:

"Threshold Quantity" shall mean, as to any FRR Entity for any Delivery Year, the sum of (a) the Unforced Capacity equivalent (determined using the Pool-Wide Average EFORD through the 2024/2025 Delivery Year, or pool-wide average Accredited UCAP Factor effective with the 2025/2026 Delivery Year) of the Installed Reserve Margin for such Delivery Year multiplied by the Preliminary Forecast Peak Load for which such FRR Entity is responsible under its FRR Capacity Plan for such Delivery Year, plus (b) the lesser of (i) 3% of the Unforced Capacity amount determined in (a) above or (ii) 450 MW. If the FRR Entity is not responsible for all load within a Zone, the Preliminary Forecast Peak Load for such entity shall be determined in accordance with Reliability Assurance Agreement, Schedule 8.1, section D.2.

Tracking Solar Class:

"Tracking Solar Class" shall mean an ELCC Class consisting of Variable Resources that produce electrical energy with solar panels that are primarily mounted on trackers that align the panels with incoming sunlight over the course of the day.

Transmission Facilities:

"Transmission Facilities" shall mean facilities that: (i) are within the PJM Region; (ii) meet the definition of transmission facilities pursuant to FERC's Uniform System of Accounts or have been classified as transmission facilities in a ruling by FERC addressing such facilities; and (iii) have been demonstrated to the satisfaction of the Office of the Interconnection to be integrated with the PJM Region transmission system and integrated into the planning and operation of the PJM Region to serve all of the power and transmission customers within the PJM Region.

Transmission Owner:

"Transmission Owner" shall mean a Member that owns or leases with rights equivalent to ownership Transmission Facilities and is a signatory to the PJM Transmission Owners Agreement. Taking transmission service shall not be sufficient to qualify a Member as a Transmission Owner.

Unforced Capacity:

"Unforced Capacity" shall mean installed capacity rated at summer conditions that is not on average experiencing a forced outage or forced derating, calculated for each Capacity Resource on the 12-month period from October to September without regard to the ownership of or the contractual rights to the capacity of the unit.

Unlimited Resource:

"Unlimited Resource" shall mean a generating unit having the ability to maintain output at a stated capability continuously on a daily basis without interruption. Through the 2024/2025 Delivery Year, an Unlimited Resource is a Generation Capacity Resource that is not an ELCC Resource.

Variable Resource:

"Variable Resource" shall mean a Generation Capacity Resource with output that can vary as a function of its energy source, such as wind, solar, run of river hydroelectric power without storage, and landfill gas units without an alternate fuel source. All Intermittent Resources are Variable Resources, with the exception of Hydropower with Non-Pumped Storage.

Waste to Energy Steam Class:

"Waste to Energy Steam Class" shall mean an ELCC Class consisting of Unlimited Resources of the steam technology type whose primary fuel is municipal waste or wood waste.

Winter Peak Load (or WPL):

"Winter Peak Load" or "WPL" shall mean the average of the Demand Resource customer's specific peak hourly load between hours ending 7:00 EPT through 21:00 EPT on the PJM defined 5 coincident peak days from December through February two Delivery Years prior the Delivery Year for which the registration is submitted. Notwithstanding, if the average use between hours ending 7:00 EPT through 21:00 EPT on a winter 5 coincident peak day is below 35% of the average hours ending 7:00 EPT through 21:00 EPT over all five of such peak days, then up to two such days and corresponding peak demand values may be excluded from the calculation. Upon approval by the Office of the Interconnection, a Curtailment Service Provider may provide alternative data to calculate Winter Peak Load, as outlined in the PJM Manuals, when there is insufficient hourly load data for the two Delivery Years prior to the relevant Delivery Year or if more than two days meet the exclusion criteria described above.

Zonal Capacity Price:

"Zonal Capacity Price" shall mean the clearing price required in each Zone to meet the demand for Unforced Capacity and satisfy Locational Deliverability Requirements for the LDA or LDAs associated with such Zone. If the Zone contains multiple LDAs with different Capacity Resource Clearing Prices, the Zonal Capacity Price shall be a weighted average of the Capacity Resource Clearing Prices for such LDAs, weighted by the Unforced Capacity of Capacity Resources cleared in each such LDA.

Zone or Zonal:

"Zone" or "Zonal" shall refer to an area within the PJM Region, as set forth in Tariff, Attachment J and RAA, Schedule 15, or as such areas may be (i) combined as a result of mergers or acquisitions or (ii) added as a result of the expansion of the boundaries of the PJM Region. A Zone shall include any Non-Zone Network Load located outside the PJM Region that is served from such Zone under Tariff, Attachment H-A.

Zonal Winter Weather Adjustment Factor (ZWWAF):

"Zonal Winter Weather Adjustment Factor" or "ZWWAF" shall mean the PJM zonal winter weather normalized coincident peak divided by PJM zonal average of 5 coincident peak loads in December through February.

SCHEDULE 9.2:

EFFECTIVE LOAD CARRYING CAPABILITY ANALYSIS FOR THE 2025/2026 DELIVERY YEAR AND SUBSEQUENT DELIVERY YEARS

A. Overview of Effective Load Carrying Capability Analysis

The inputs of the effective load carrying capability analysis shall consider similar data and forecasts as that used in development of the FPR, as described in Schedule 4.C, and will include:

-Historical weather and load data;

-Historical output of existing Variable Resources;

-Estimates of putative historical output for planned Variable Resources;

-Forced outage patterns for Unlimited Resources, including consideration of correlated outage risks;

-Resource deployment forecast; and

-Modeling parameters for Limited Duration Resources, Combination Resources, and Demand Resources.

The outputs of the effective load carrying capability analysis include:

-ELCC Class Rating values, in percent.

B. ELCC Classes

- (1) (a) The following are the ELCC Classes for Variable Resources:
 - Tracking Solar Class
 - Fixed-Tilt Solar Class
 - Onshore Wind Class
 - Offshore Wind Class
 - Intermittent Landfill Gas Class
 - Intermittent Hydropower Class
 - Other Variable Resource Class

(b) The following are the types of ELCC Classes for Limited Duration Resources:

- The type of Capacity Storage Resource Classes
- The type of Other Limited Duration Resource Classes

Within those types, the following are the specific ELCC Classes for Limited Duration Resources:

- Capacity Storage Resource Class (4-Hour Duration)
- Capacity Storage Resource Class (6-Hour Duration)
- Capacity Storage Resource Class (8-Hour Duration)
- Capacity Storage Resource Class (10-Hour Duration)

- Other Limited Duration Class (4-Hour Duration)
- Other Limited Duration Class (6-Hour Duration)
- Other Limited Duration Class (8-Hour Duration)
- Other Limited Duration Class (10-Hour Duration)

(c) The following are the ELCC Classes for Combination Resources:

- The types of Hybrid Resource Classes, as further specified in subpart (2) below
- Hydropower With Non-Pumped Storage Class
- Complex Hybrid Class
- The types of Other Limited Duration Combination Classes, as further specified in subpart (3).
 - (d) The following are the ELCC Classes for Unlimited Resources
 - Nuclear Class
 - Coal Class
 - Gas Combined Cycle Class
 - Gas Combustion Turbine Class
 - Gas Combined Cycle Dual Fuel Class
 - Oil Fired Combustion Turbine Class (effective with the 2027/2028 Delivery Year)
 - Gas Combustion Turbine Dual Fuel Class
 - Diesel Utility Class
 - Other Steam Class
 - Waste to Energy Steam Class (effective with the 2027/2028 Delivery Year)
 - Other Unlimited Resource Class

(e) The following are the ELCC Classes for Demand Resources

- Demand Resource Class

(2) PJM shall establish Hybrid Resource Classes for all "open-loop" combinations of each Capacity Storage Resource class and each Variable Resource class or Unlimited Resource class, as well as all "closed-loop" combinations of each Capacity Storage Resource class and each Variable Resource class or Unlimited Resource class. An "open-loop" resource operates by charging the storage component from the grid, while a "closed-loop" resource does not.

(3) PJM shall establish "Other Limited Duration Combination Classes" for all combinations of each Variable Resource Class and each Other Limited Duration Resource Class, and for combinations of an Unlimited Resource with each Other Limited Duration Resource Class.

(4) For a given Delivery Year, ELCC Class Ratings will not be calculated for any ELCC Class to the extent that no member of the class is expected to provide, or offer to provide capacity, in the applicable Delivery Year. PJM will determine the ELCC Class Ratings for an ELCC Class when any one of the following criteria are met:

(a) An Existing Generation Capacity Resource is in such class; or

(b) A Planned Generation Capacity Resource has submitted timely and valid data through the ELCC data submission process and is in such class; or

(c) The resource deployment forecast contains a resource in such class.

(5) (a) For each ELCC Resource, except an ELCC Resource that is a Capacity Storage Resource or includes a Capacity Storage Resource component, PJM shall determine the ELCC Class of which such resource is a member by matching the physical characteristics of such resource with the definition of the ELCC Class.

(b) For each ELCC Resource that is a Capacity Storage Resource or includes a Capacity Storage Resource component, PJM shall determine, by matching the physical characteristics of such resource with the definition of the ELCC Class, the type of ELCC Class of which such resource is a member; provided however, the Generation Capacity Resource Provider shall choose the specific ELCC Class within the type ELCC Class identified by PJM that corresponds to the chosen characteristic duration.

If the Generation Capacity Resource Provider fails to choose, PJM will choose a specific ELCC Class to assign to such resource. The election of the specific ELCC Class corresponding to the chosen characteristic duration shall be for a term of five consecutive Delivery Years. After such five Delivery Year period, a Generation Capacity Resource Provider may request a change in the ELCC Class, based on choosing a different characteristic duration, by submitting to the Office of the Interconnection a written request to switch ELCC Classes and provide documentation supporting such change. A Generation Capacity Resource Provider must submit such a request, and supporting documentation, by August 1 prior to the calendar year for the RPM Auction in which the ELCC Resource intends to submit a Sell Offer or otherwise commit to provide capacity, except for 2025/2026 Delivery Year such required information must be provided to the Office of the Interconnection in accordance with the PJM Manuals. The Office of the Interconnection shall provide no later than following November 15 written notification to the Generation Capacity Resource Provider of its determination. If the request is granted, the ELCC Resource shall be considered in the new ELCC Class starting with the next Delivery Year for which no RPM Auction has been conducted and for subsequent Delivery Years. If the request is denied, the Office of the Interconnection shall include in the notice a written explanation for the denial.

(6) Mixed-technology resources are composed of components with different generation technologies, at least one of which would be an ELCC Resource, behind a single Point of Interconnection. For a mixed-technology resource composed of components that do not have significant interaction, the components are eligible to participate as separate resources. A mixed-technology resource composed of components that have significant interaction must participate as a single Combination Resource (or, if the components would all be Variable Resources, then as a single Variable Resource).

The Generation Capacity Resource Provider of a mixed-technology resource eligible to participate as either a single ELCC Resource or as multiple stand-alone resources shall elect, for a term of five consecutive Delivery Years, whether PJM is to model it as a single ELCC Resource or as multiple stand-alone resources. After such five Delivery Year period, a Generation Capacity Resource Provider may request a change in such modelling approach by submitting to the Office of the Interconnection a written request to change the modelling approach and provide documentation supporting such change. A Generation Capacity Resource Provider must submit such a request, and supporting documentation, by August 1 prior to the calendar year for the RPM Auction in which the ELCC Resource(s) intend(s) to submit a Sell Offer or otherwise commit to provide capacity, except for 2025/2026 Delivery Year such required information must be provided to the Office of the Interconnection in accordance with the PJM Manuals. The Office of the Interconnection shall provide no later than following November 15 written notification to the Generation Capacity Resource Provider of its determination. If the request is granted, the ELCC Resource(s) shall be modelled as requested starting with the next Delivery Year for which no RPM Auction has been conducted and for subsequent Delivery Years. If the request is denied, the Office of the Interconnection shall include in the notice a written explanation for the denial.

C. Calculation of ELCC Class Rating

ELCC Class Ratings for a Delivery Year are calculated by adding to the forecasted resource portfolio incremental quantities of resources belonging to the subject ELCC Class, depending on the resource type:

(1) The ELCC Class Rating of Variable Resources, Limited Duration Resources, Unlimited Resources (except Other Unlimited Resources), and Demand Resources shall be the ratio of the expected unserved energy improvement resulting from adding an incremental quantity of the subject ELCC Class to the expected unserved energy improvement resulting from adding an incremental quantity of an Unlimited Resource with no outages, where expected unserved energy improvement is calculated relative to the Portfolio EUE for the Delivery Year.

(2) No ELCC Class Rating is determined for Combination Resources and ELCC Resources in the Hydropower with Non-Pumped Storage Class, in the Complex Hybrid Class, in the Other Unlimited Resource Class, and in any ELCC Class whose members are so distinct from one another that a single ELCC Class Rating would fail to capture their physical characteristics.

D. Calculation of Accredited UCAP and ELCC Resource Performance Adjustment

(1) (a) For Variable Resources and Limited Duration Resources, Accredited UCAP values shall be equal to the lesser of the resource's Capacity Interconnection Right or the product of:

(i) the Effective Nameplate Capacity;

(ii) the applicable ELCC Class Rating; and

(iii) the ELCC Resource Performance Adjustment.

(b) For any resource in an ELCC Class for which no Class Rating has been calculated pursuant to C(2), the Accredited UCAP shall be based on a resource-specific effective load carrying capability analysis based on the resource's unique parameters.

(c) For Unlimited Resources that have an ELCC Class Rating determined pursuant to C(1), Accredited UCAP values shall be equal to the product of:

(i) the installed capacity;

(ii) the applicable ELCC Class Rating; and

(iii) the ELCC Resource Performance Adjustment.

(d) For Demand Resources, Accredited UCAP values shall be equal to the product of:

(i) the Nominated Value of the Demand Resource; and

(ii) the applicable ELCC Class Rating.

(2) The ELCC Resource Performance Adjustment shall be calculated according to the following methods, as further detailed in the PJM Manuals:

(a) For a Variable Resource, a Limited Duration Resource, and an Unlimited Resource: based on a metric consisting of the weighted average expected hourly output of the resource in the ELCC model during hours of loss of load risk where: (i) the weights correspond to the modeled probability of losing load in such hour and (ii) the expected hourly output is based on the resource's modeled output during the same hour on days since June 1st, 2012 identified as having similar weather from an RTO-perspective. For a given resource or component, the Performance Adjustment shall equal the ratio of such metric to the average (weighted by the Effective Nameplate Capacity) of such metrics for all units in the applicable Variable Resource ELCC Class or applicable Unlimited Resource ELCC Class.

In determining the ELCC Resource Performance Adjustment, the actual output of a Variable Resource shall be adjusted to reflect historical curtailments, and output in any hour shall be capped at: (i) the greater of the Variable Resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year, for hours in the months of June through October and the following May of the Delivery Year, and (ii) the Variable Resource's assessed deliverability, as defined in the PJM Manuals, for hours in the months of November through April of the Delivery Year. The output of an Unlimited Resource in any hour shall be capped at the greater of the resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year.

E. Calculation of Accredited UCAP Factor

For Generation Capacity Resources, PJM shall determine an Accredited UCAP Factor, which is the ratio of the resource's Accredited UCAP to the resource's installed capacity.

G. Installed Capacity of ELCC Resources

Rules and procedures for technically determining and demonstrating the installed capacity of ELCC Resources shall be developed by the Office of the Interconnection and maintained in the PJM Manuals. The installed capacity of a Limited Duration Resource is based on the sustained level of output that the unit can provide and maintain over a continuous period, whereby the duration of that period matches the characteristic duration of the corresponding ELCC Class, with consideration given to ambient conditions expected to exist at the time of PJM system peak load, as described in the PJM Manuals. The installed capacity of a Combination Resource (other than Hydropower With Non-Pumped Storage) is based on the lesser of the Maximum Facility

Output or the sum of the equivalent Effective Nameplate Capacity values of the resource's constituent components considered on a stand-alone basis. The installed capacity of an Unlimited Resource and Variable Resource shall be determined in accordance with the PJM Manuals. The installed capacity of Demand Resources, for purposes of the ELCC analysis, is based on the forecasted deployment level in the PJM Load Forecast.

H. Details of the Effective Load Carrying Capability Methodology

The effective load carrying capability analysis shall compare expected hourly load levels (based on historical weather) with the expected hourly output of the expected future resource mix in order to identify the relative marginal resource adequacy value of each individual ELCC Class compared to an Unlimited Resource with no outages. In performing this analysis, the model inputs shall be scaled to meet the annual reliability criteria of the Office of the Interconnection. The effective load carrying capability analysis shall compare hourly values for: (i) expected load based on historical weather; (ii) expected Variable Resource output; (iii) expected output of Limited Duration Resources and of Combination Resources as described below; (iv) expected Unlimited Resource output; and (v) expected Demand Resource output. These expected quantities are based on forecasted load and actual and putative values for Variable Resource output (standalone or as a component of Combination Resources) and Unlimited Resource output after June 1, 2012 (inclusive) through the most recent Delivery Year for which complete data exist. For resources that have not existed each year since June 1, 2012, putative output is an estimate of the hourly output that resource would have produced in a historical hour if that resource had existed in that hour. For Variable Resources, this putative output estimate is developed based on historical weather data consistent with the particular site conditions for each such resource in accordance with the PJM Manuals; for Unlimited Resources, the putative output is developed based on actual performance of similar units in accordance with the PJM Manuals.

Variable Resource actual output shall be adjusted in the ELCC analysis to reflect historical curtailments, and output shall be capped in any hour at: (i) the greater of the Variable Resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year, during the months of June through October and the following May of the Delivery Year, and (ii) the Variable Resource's assessed deliverability, as defined in the PJM Manuals, during the months of November through April of the Delivery Year. The output of Unlimited Resources shall not exceed the greater of the Unlimited Resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year.

The effective load carrying capability analysis shall simulate performance of Demand Resources, and shall simulate the output of Limited Duration Resources and Combination Resources based on their Office of the Interconnection-validated parameters, including the putative output of the Variable Resource component of Combination Resources, as described above.

The quantity of deployed resources studied in the analysis shall be based on resource deployment forecasts and, where applicable, on available information based on Sell Offers submitted in RPM Auctions or Fixed Resource Requirement plans for the applicable Delivery Year, and, where applicable, information provided to the Office of the Interconnection regarding intent to offer in an RPM Auction, pursuant to the requirements in the Tariff, Attachment DD, section 5.5.

The model inputs, specifically the load scenarios, shall be scaled to meet the annual reliability criteria of the Office of the Interconnection. The resulting expected unserved energy constitutes the Portfolio EUE for the Delivery Year. Energy Resources are not included in the effective load carrying capability analysis. Generating units that are expected to only offer or otherwise provide a portion of their Accredited UCAP for that Delivery Year are represented in the analysis in proportion to the expected quantity offered or delivered divided by the Accredited UCAP.

I. Methodology to Simulate Output of Certain Resources in the Effective Load Carrying Capability Model

The effective load carrying capability analysis shall simulate the output of Limited Duration Resources and Combination Resources based on their physical parameters, including limited storage capability, and shall simulate the deployment of Demand Resources. The analysis shall simulate output from the subject Limited Duration Resources, Combination Resources, and Demand Resources in hours in which all output from Unlimited Resources and available output from Variable Resources is insufficient to meet load. The analysis shall first simulate the output of Demand Resources. If the simulated output of Demand Resources is insufficient to meet load, then the output of the subject Limited Duration Resources and Combination Resources shall be simulated on an hour-by-hour basis based on their relative duration, starting from longer duration resources to shorter duration resources. The output of Combination Resources shall be capped in any hour at: (i) the greater of the Combination Resource's Capacity Interconnection Rights, or the transitional system capability as limited by the transitional resource MW ceiling as defined in the PJM Manuals, awarded for the applicable Delivery Year, during the months of June through October and the following May of the Delivery Year, and (ii) the Combination Resource's assessed deliverability, as defined in the PJM Manuals, during the months of November through April of the Delivery Year. Energy Storage Resource charging is during hours with sufficient margin, including between daily peaks if necessary.

J. Administration of Effective Load Carrying Capability Analysis

The Office of the Interconnection shall post final ELCC Class Rating values at least once per year in a report that also includes appropriate details regarding methodology and inputs. The Office of the Interconnection shall post this report and shall communicate ELCC Resource Performance Adjustment values to applicable Generation Capacity Resource Providers no later than five months prior to the start of the target Delivery Year, as described in the PJM Manuals. Accredited UCAP values for the applicable Delivery Year shall establish the maximum Unforced Capacity that an ELCC Resource can physically provide or offer to provide in the applicable Delivery Year.

The Office of the Interconnection shall also post preliminary ELCC Class Rating values for nine subsequent Delivery Years. For any Delivery Year for which a final ELCC Class Rating has not been posted and a preliminary ELCC Class Rating has been posted, the Accredited UCAP of an ELCC Resource for such Delivery Year shall be based on the most recent preliminary ELCC Class Rating value for that Delivery Year, together with the most recently calculated ELCC Resource Performance Adjustment value for that ELCC Resource. Except to the extent specified

above or otherwise specified, the preliminary ELCC Class Rating values for future years are non-binding and are only for indicative purposes. A Generation Capacity Resource Provider can offer or provide capacity from an ELCC Resource that is not subject to a capacity market must offer obligation (as specified in Tariff, Attachment DD, Section 6.6) at a level less than the Accredited UCAP for such resource.

In order to facilitate the effective load carrying capability analysis, the Generation Capacity Resource Provider of each ELCC Resource must submit to the Office of the Interconnection the required information as specified in the PJM Manuals by no later than August 1 prior to the calendar year for the RPM Auction in which the ELCC Resource intends to submit a Sell Offer or otherwise commit to provide capacity, except for 2025/2026 Delivery Years such required information must be provided to the Office of the Interconnection in accordance with the PJM Manuals. The required information may include relevant physical parameters, relevant historical data such as weather data and actual or estimated historical energy output, and documentation supporting such parameters and historical data. The relevant physical parameters are those that are incorporated into the effective load carrying capability analysis. The parameters required for Hydropower With Non-Pumped Storage shall include Ordinary Water Storage and any applicable Exigent Water Storage. Submitted parameters must indicate the expected duration for which any submitted physical parameters are valid.

The Office of the Interconnection shall evaluate, validate, and approve the foregoing information in accordance with the process set forth in the PJM Manuals. In evaluating the validity of submitted information, the Office of the Interconnection may assess the consistency of such information with observed conditions. If the Office of the Interconnection observes that the information provided by the Generation Capacity Resource Provider of the ELCC Resource is inconsistent with observed conditions, the Office of the Interconnection will coordinate with the Generation Capacity Resource to understand the information and observed conditions before making a determination regarding the validity of the applicable parameters. The Office of the Interconnection may engage the services of a consultant with technical expertise to evaluate the foregoing information.

After the Office of the Interconnection has completed its evaluation of the foregoing information, the Office of the Interconnection shall notify the Generation Capacity Resource Provider in writing whether the submitted information is considered invalid by no later than September 1 following the submission of the information. The Office of the Interconnection's determination on the validity of the foregoing information shall continue for the applicable Delivery Year and, if requested, for such longer period as the Office of the Interconnection may determine is supported by the data.

In the event that the Office of the Interconnection is unable to validate any of the required information, physical parameters, supporting documentation, or other related information submitted by the Generation Capacity Resource Provider of an ELCC Resource, then the Office of the Interconnection shall calculate Accredited UCAP values for that ELCC Resource based only on the validated information. Such ELCC Resource shall not be permitted to offer or otherwise provide capacity above such Accredited UCAP values until the Office of the Interconnection determines new Accredited UCAP values for such resource.

Generation Capacity Resource Providers of ELCC Resources that are hydropower plants with water storage must provide documentation to support the physical parameters provided for

expected load carrying capability analysis modeling, as specified in the PJM Manuals. This documentation must: (a) support the plant's physical capabilities; (b) demonstrate that the parameters do not violate any federal, state, river basin, or other applicable authority operating limitations of the plant; and (c) demonstrate full authorization from FERC, any river basin commissions, and any other applicable authorities to meet those capabilities.